

UNITED STATES DEPARTMENT OF THE INTERIOR

J. A. Krug, Secretary

GEOLOGICAL SURVEY

W. E. Wrather, Director


Water-Supply Paper 998

SUSPENDED SEDIMENT IN  
THE COLORADO RIVER

1925-41

BY

C. S. HOWARD



UNITED STATES  
GOVERNMENT PRINTING OFFICE  
WASHINGTON : 1947



## CONTENTS

---

	Page
Abstract.....	1
Introduction.....	1
Collection of samples.....	2
Colorado River sampler.....	2
Types of samples collected.....	4
Individual samples.....	4
Integrated samples.....	4
Frequency of sampling.....	5
Size samples.....	5
Determination of suspended sediment.....	5
Determinations.....	5
Weighing the samples.....	5
Weighing the sediment.....	5
Computations.....	5
Concentrations.....	5
Loads.....	6
Daily loads.....	6
Monthly loads.....	6
Annual loads.....	6
Daily sediment records.....	6
Mean daily concentrations.....	6
Suspended sediment in individual samples.....	7
Annual, maximum, and minimum daily loads.....	8
Sources of loads measured at Grand Canyon station.....	10
Physical nature of suspended and deposited sediment.....	11
Methods of determination of particle size.....	11
Suspended sediment.....	13
Bank deposits.....	13
Reservoir deposits.....	13
Determined quantities of suspended sediment.....	14
Index.....	165

## ILLUSTRATIONS


---

PLATE 1. Geological Survey Colorado River sampler.....	10
2. Line of demarcation of inflow and water of Lake Mead approximately 90 miles above Boulder Dam.....	18
3. Deposit in slack-water area about 97 miles above Boulder Dam.....	18
FIGURE 1. Map of the Colorado River drainage basin showing sediment-sampling stations.....	3

## TABLES

	Page
TABLE 1. Maximum and minimum daily loads of suspended sediment at gaging stations on Colorado, Green, and San Juan Rivers, October 1, 1925, to September 30, 1941-----	8
2. Suspended sediment and runoff of Colorado River at gaging station near Yuma, Ariz., October 1, 1925, to September 30, 1941-----	10
3. Load of suspended sediment and runoff at Cisco, Green River, and Bluff gaging stations in comparison with Grand Canyon station-----	10
4. Kind of information and periods covered by the tables of data for 8 gaging stations-----	15
5. Mean daily concentration of suspended sediment in the Colorado River near Cisco, Utah, May 14, 1929, to September 30, 1939-----	15
6. Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River near Cisco, Utah, October 1, 1939, to September 30, 1941-----	16
7. Mean daily concentration of suspended sediment in the Colorado River at Lees Ferry, Ariz., October 1, 1928, to December 16, 1933-----	21
8. Mean daily concentration of suspended sediment in the Colorado River near Grand Canyon, Ariz., October 1, 1925, to September 30, 1929-----	25
9. Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River near Grand Canyon, Ariz., October 1, 1929, to September 30, 1941-----	30
10. Suspended-sediment concentration in individual samples collected from the Colorado River near Grand Canyon, Ariz., April 1, 1935, to September 30, 1936-----	54
11. Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River near Willow Beach, Ariz., October 1, 1934, to September 30, 1936-----	83
12. Mean daily concentration of suspended sediment in the Colorado River near Topock, Ariz., October 1, 1925, to September 30, 1934-----	87
13. Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River near Topock, Ariz., October 1, 1934, to March 31, 1939-----	92
14. Mean daily concentration of suspended sediment in the Green River near Green River, Utah, May 1, 1929, to September 30, 1939-----	101
15. Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Green River near Green River, Utah, October 1, 1939, to September 30, 1941-----	106
16. Suspended-sediment concentration at different sampling times, mean daily discharge, mean daily concentration, and daily load of suspended sediment in San Juan River near Bluff, Utah, August 13 to September 21, 1928-----	110

	Page
TABLE 17. Suspended-sediment concentration at different sampling times, mean daily discharge, mean daily concentration, and daily load of suspended sediment in the San Juan River near Bluff, Utah, July 1 to September 30, 1929-----	113
18. Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the San Juan River near Bluff, Utah, October 1, 1929, to September 30, 1941-----	117
19. Suspended-sediment concentration in individual samples collected from the San Juan River near Bluff, Utah, in September and October 1937, September 1939, July to October 1940, and March, April, and September 1941-----	141
20. Suspended-sediment concentration at different sampling times, mean daily discharge, mean daily concentration, and daily load of suspended sediment in Little Colorado River at Grand Falls, Ariz., July 6 to September 26, 1931-----	144
21. Velocity and suspended-sediment concentration of water in the Colorado River near Grand Canyon, Ariz., April 6 to July 24, 1935-----	146
22. Velocity and suspended-sediment concentration of water in the Colorado River near Topock, Ariz., April 3 to June 29, 1935-----	148
23. Mechanical analyses of suspended sediment in samples collected in the Colorado River near Grand Canyon, Ariz., April 5, 1935, to September 30, 1941-----	150
24. Mechanical analyses of suspended sediment in samples collected in the Colorado River near Willow Beach, Ariz., April 2, 1935, to September 27, 1936-----	159
25. Mechanical analyses of suspended sediment in samples collected in the San Juan River near Bluff, Utah, May 3, 1935, to September 30, 1936-----	161



# SUSPENDED SEDIMENT IN THE COLORADO RIVER

1925-41

By C. S. HOWARD

## ABSTRACT

This report gives the results of sediment-sampling studies of the Geological Survey in the Colorado River basin for the period from October 1, 1925, to September 30, 1941. Records are given for the entire period for the Grand Canyon gaging station and for shorter periods at other stations in the basin. The results reported consist of the records of the mean daily concentrations of sediment for all stations, and in addition, the mean daily discharge and daily load of sediment for many of the stations.

The available records indicate that the runoff of the Colorado near Cisco, Utah, plus the runoff of the Green at Green River, Utah, plus the runoff of the San Juan near Bluff, Utah, amount to about 90 percent of the runoff at the Grand Canyon gaging station, but the sediment loads at the three upper stations amount to only about 60 percent of the sediment load at Grand Canyon. The Little Colorado River and two or three other unsampled tributaries probably are the major sources of the unmeasured sediment.

Information is given concerning the sizes of the particles of the sediment at the Grand Canyon, Willow Beach, and Bluff stations during periods of this investigation.

The annual load at Grand Canyon during the 16 years ranged from 50,080,000 tons in 1933-34 to 480,000,000 tons in 1928-29, and the mean annual load at that station for the 16-year period was 200,200,000 tons. The mean annual runoff for the Grand Canyon station during the period was 12,640,000 acre-feet

## INTRODUCTION

For the 16-year period, October 1, 1925, to September 30, 1941, sampling programs were carried on at the gaging station on the Colorado River near Grand Canyon, Ariz., and for shorter periods at other stations on the main river and its principal tributaries. The sampling points were at gaging stations for which records of discharge were being obtained and at which engineers were available for the collection of samples and the determination of the quantity of sediment in the individual samples.

Records of discharge were made available by A. B. Purton, Salt Lake City, Utah, and W. E. Dickinson and John H. Gardiner, Tuc-

son, Ariz., district engineers of the Geological Survey. The samples were collected by members of the staffs of those district offices. The computations of daily and annual loads were made by the personnel of the Water Resources Laboratory of the Geological Survey.

The field work and preparation of this report were under the supervision of W. D. Collins, Chemist in Charge, Quality of Water Division, Water Resources Branch of the Geological Survey.

The data presented in this report cover the entire period for which a comprehensive sediment-sampling program was carried on in the Colorado River Basin. The results obtained in the continuation of this program are prepared annually for presentation in the series of reports entitled "Quality of surface waters of the United States."

### COLLECTION OF SAMPLES

Sediment samples were collected as a continuing project during the periods indicated at the following stations:

Colorado River near Cisco, Utah, May 14, 1929, to September 30, 1941.

Colorado River at Lees Ferry, Ariz., October 1, 1929, to December 16, 1933.

Colorado River near Grand Canyon, Ariz., October 1, 1925, to September 30, 1941.

Colorado River near Willow Beach, Ariz., October 1, 1934 to September 30, 1939.

Colorado River near Topock, Ariz., October 1, 1925, to March 31, 1939.

Green River at Green River, Utah, May 1, 1929, to September 30, 1941.

San Juan River near Bluff, Utah, August 13 to September 21, 1928; July 1 to September 30, 1941.

Little Colorado River at Grand Falls, Ariz., July 6 to September 26, 1931.

The locations of these stations are shown on the map of the Colorado River drainage basin, figure 1.

### COLORADO RIVER SAMPLER

The samples were collected by means of the sampler shown in plate 1. This sampler, designed by Carl H. Au, hydraulic engineer of the Geological Survey and described in a previous publication,<sup>1</sup> was designed to be attached to the cable in place of the current meter used for discharge measurements and was made so that suitable weights could be added to the bottom of the sampler.

The first samplers were made to puncture a paper covering a  $\frac{5}{8}$ -inch hole in an ordinary milk-bottle cap, but the samplers were modified so that a stopper could be pulled out of a rubber cap that had been fitted to a regular pint milk bottle in place of the ordinary milk-bottle cap.

<sup>1</sup> Howard, C. S., Suspended matter in the Colorado River in 1925-28: U. S. Geol. Survey Water Supply Paper 635, pp. 18-19, 1930.




FIGURE 1.—Map of the Colorado River drainage basin showing sediment-sampling stations.

**TYPES OF SAMPLES COLLECTED****INDIVIDUAL SAMPLES**

During the early part of the investigation "bottom," "surface," and "average" ("integrated") samples were collected. The bottom samples were collected by lowering the bottle to the bottom, opening the bottle, and allowing it to stay there for a time long enough to be filled, after which it was raised rapidly. The average, or integrated, samples were obtained by allowing the bottle to become nearly full as it was being lowered and raised, or, under some conditions, only during the raising. The detailed results obtained on the different types of samples are given in an earlier paper.<sup>2</sup>

**INTEGRATED SAMPLES**

The method of collecting average, or integrated, samples used in this study is the "depth-integration method" described in a report of the United States Engineers.<sup>3</sup>

Throughout this investigation average samples were used for the computation of the mean concentration for each day. During the first 3 years the average sample was collected by lowering the empty bottle to the bottom, opening the bottle, and raising it at such a rate that the bottle was full when it reached the surface. During the remainder of the investigation the average sample was taken by lowering to the bottom a bottle with an open hole in the cap and raising it at such a rate that it would not be quite full when it returned to the surface. At some river stages it was not possible to lower and raise the bottle fast enough to get a partially filled bottle and it was necessary to use the bottle-opening device. At times when the river was carrying fine drift, such as grass, needles, and the like, it was not possible to operate the bottle-opening device and integrated samples were obtained by lowering the bottle with the open hole in the cap to such a depth that it could be lowered and raised before the bottle became full. It has been shown<sup>4</sup> that there is an initial inrush of water into the bottle when it is opened at the bottom, and an undue proportion of the sample comes from the greatest depth. As a result of this inrush the samples collected in this manner are not representative for the entire depth, but no data are available to show the magnitude of the error in samples collected from the Colorado River by this method.

<sup>2</sup> Howard, C. S., op. cit., pp. 29-40.

<sup>3</sup> U. S. Engineer Office, St. Paul, Minn., A study of methods used in measurement and analysis of sediment loads in streams, Report 1, Field practice and equipment used in sampling suspended sediment, pp. 72-74, 1940.

<sup>4</sup> U. S. Engineer Office, St. Paul, Minn., A study of methods used in measurement and analysis of sediment loads in streams: Report 1, Field practice and equipment used in sampling suspended sediment, pp. 72-74, 1940; Report 3, Analytical study of methods of sampling suspended sediment loads in streams, pp. 57-60, 1941; Report 5, Laboratory investigation of suspended sediment samplers, pp. 88-91, 1941.

**FREQUENCY OF SAMPLING**

At each gaging station a set of integrated samples was collected at three points in the cross section. It was planned to have one set of samples collected each day during periods of normal stage and two or more sets each day during periods of flood stage. It was not possible to carry out this daily sampling program at all stations, and for several periods the records are incomplete.

**SIZE SAMPLES**

Additional samples for the determinations of the sizes of the particles of the suspended sediment were collected approximately twice each week at the Grand Canyon station during the period from April 1, 1935, to September 30, 1941. For part of this period similar samples were collected at the Willow Beach and Bluff gaging stations.

**DETERMINATION OF SUSPENDED SEDIMENT****DETERMINATIONS**

Most of the determinations of the quantities of suspended sediment were made at the field stations. The original records were sent to the laboratory in Washington for review and further computations.

**WEIGHING THE SAMPLES**

For the period October 1, 1925, to March 31, 1930, the weight of each sample was considered to be 473 grams, but after March 31, 1930, each sample was weighed and that weight used in computing the concentration of sediment.

**WEIGHING THE SEDIMENT**

The weight of sediment in most of the samples was determined by filtering the samples through weighed filter papers, which were then dried and reweighed. Corrections for the moisture content of the filter papers were made by weighing a check paper at the time of the original and the final weighings.

The sediment in samples collected at Grand Canyon after October 1, 1940, was determined by transferring the sediment with as little of the original water as possible to a weighed evaporating dish and weighing the dried sediment.

**COMPUTATIONS****CONCENTRATIONS**

The sediment concentrations were computed for each sample and reported in percent by weight of the samples as collected. The mean concentration was computed from the individual results, usually as the average of the individual determinations, but sometimes one or

more of the individual determinations were obviously not representative for the day and therefore were not considered in computing the mean concentration for the day. During flood periods when sufficient samples had been collected, the mean concentration for the day was computed by considering the mean concentration for each set of samples and the rate of discharge for the part of the day for which those samples were considered representative.

#### LOADS

Loads of suspended sediment were reported as tons per day, tons per year, and for some stations for which sufficient records were available as tons per month. No effort was made to compute the volume of the sediment carried in any period.

*Daily loads.*—The daily loads of sediment were computed from the mean concentration for the day and the mean daily discharge by the following equation:

$$\text{Daily load (in tons)} = \text{mean concentration (percent by weight} \times \text{mean daily discharge (in second-feet)} \times 27.$$

The mean concentration of sediment was estimated for some of the days for which records were not available and the daily loads computed from these estimated values.

*Monthly loads.*—Monthly loads were computed as the sum of the daily loads for months for which data were available for all the days. These loads, where computed, are listed in the tables giving the daily loads of sediment.

*Annual loads.*—The annual loads of suspended sediment were computed as the sum of the monthly loads for those stations for which there were sufficient data for the computation of the monthly loads. If monthly loads were not computed the annual load was computed from the weighted-average concentration of all the samples collected during the year and the total discharge for the year. The weighted-average concentration was computed by multiplying the mean daily concentration by the mean daily discharge for each day for which samples were available and dividing the sum of those products by the sum of the mean discharge values for the same days.

The annual loads at stations for which sufficient records are available for computation of such loads are given in table 1.

#### DAILY SEDIMENT RECORDS

##### MEAN DAILY CONCENTRATIONS

The mean daily concentrations of sediment are given in tables 5 to 18 for all days for which sufficient records were available. For some days on which samples were not collected a concentration value was

estimated. In addition to the mean daily concentration values, the mean daily discharge and daily load of sediment are given for certain periods for most of the stations.

These tables show the variation in concentration and load of sediment from day to day. The highest concentrations in the main river occurred at the Grand Canyon station, and the highest concentrations in the tributaries occurred at the Bluff station on the San Juan River.

The records for the Willow Beach, Topock, and Yuma stations from 1935 to 1939 are of interest in showing the changes in concentration and load that occurred at those stations after the closing of Boulder Dam on February 1, 1935. After that date water released at Boulder Dam was clear, except for periods of density flows,<sup>5</sup> and the suspended sediment represented sediment picked up in the 10-mile stretch between Boulder Dam and the Willow Beach station and in the 105-mile stretch between the Willow Beach and Topock stations. After the closing of the dam the sediment concentration at Willow Beach and Topock showed a decrease, and at the end of the sampling periods at those stations the water was practically clear.

#### SUSPENDED SEDIMENT IN INDIVIDUAL SAMPLES

Records for the Grand Canyon and Topock gaging stations for the period 1925–28<sup>6</sup> showed the concentrations for the individual samples. Similar records are given in the present report for the Grand Canyon station for the period April 1, 1935, to September 30, 1936, and for the Bluff station during periods in 1937, 1939, 1940, and 1941. The records obtained during the 16 years of observations show considerable variation in sediment concentration throughout the cross section and at certain times throughout the day. The greatest variations in concentration were found during the periods of rapid rise that usually occurred after heavy rains on the desert part of the watershed.

Results of some observations of sediment concentration and corresponding water velocity at the Grand Canyon and Topock stations are given in tables 21 to 22. The data show no conclusive relationship between sediment concentration and velocity.

A study of the available records shows no direct relation between concentration and discharge. As a rule, the concentration of sediment increased with an increase in discharge, but the concentration of sediment carried seemed to depend more on the source of the increase in flow than on the quantity of the increase.

<sup>5</sup> Grover, N. C., and Howard, C. S., The passage of turbid water through Lake Mead: Am. Soc. Civil Eng. Trans., vol. 103, pp. 722–723, 1938.

<sup>6</sup> Howard, C. S., U. S. Geol. Survey Water Supply Paper 636, pp. 29–40, 1930.

## ANNUAL, MAXIMUM, AND MINIMUM DAILY LOADS

The annual, maximum, and minimum daily loads computed from the data for 1925-41 are given in table 1 for the Cisco, Lees Ferry, Grand Canyon, Willow Beach, and Topock stations on the main river; for the Green River, Utah, station on the Green River; and for the Bluff station on the San Juan. The data in this table indicate that the highest daily loads in the main stream occurred at the Grand Canyon station and that the highest daily loads in the tributaries occurred at the Bluff station on the San Juan.

TABLE 1.—*Maximum and minimum daily loads of suspended sediment at the Cisco, Lees Ferry, Grand Canyon, Willow Beach, Topock, Green River, and Bluff stations for the period Oct. 1, 1925, to Sept. 30, 1941*

## Colorado River near Cisco, Utah

Water year ended Sept. 30	Annual runoff (acre-feet)	Annual load of suspended sediment (tons)	Day of maximum load			Day of minimum load		
			Mean discharge (second- feet)	Suspended sedi- ment		Mean discharge (second- feet)	Suspended sedi- ment	
				Per- cent <sup>1</sup>	Load (tons)		Per- cent <sup>1</sup>	Load (tons)
1930 <sup>2</sup> .....	6,090,000	18,600,000	11,700	3.00	947,000	.....	.....	.....
1931 <sup>2</sup> .....	2,860,000	9,910,000	11,200	5.03	1,520,000	.....	.....	.....
1932.....	6,680,000	26,400,000	28,440	.72	767,000	1,740	0.03	1,400
1933.....	4,640,000	8,190,000	28,600	.42	324,000	.....	.00	.....
1934.....	2,220,000	2,720,000	15,500	.33	138,000	787	.01	216
1935.....	4,681,000	17,840,000	9,360	1.86	470,000	1,720	.01	459
1936.....	5,765,000	17,180,000	9,070	3.75	918,000	2,300	.004	243
1937.....	4,621,000	23,560,000	12,910	4.67	1,630,000	1,180	.02	637
1938.....	7,422,000	35,700,000	37,400	.87	879,000	1,930	.02	1,040
1939.....	4,252,000	14,470,000	5,320	2.85	409,000	960	.02	518
1940.....	3,463,000	9,900,000	9,430	2.91	741,000	1,670	.01	451
1941.....	6,576,000	32,200,000	40,500	1.12	1,225,000	2,010	.01	543

## Colorado River near Lees Ferry, Ariz.

1929.....	19,200,000	352,000,000	65,500	5.35	9,450,000	3,770	0.09	8,980
1930.....	13,100,000	195,000,000	41,600	8.02	9,000,000	4,700	.15	19,000
1931.....	6,380,000	57,200,000	9,810	5.51	1,460,000	2,780	.13	9,740
1932.....	15,300,000	214,000,000	49,500	6.27	8,370,000	4,000	.17	18,300
1933.....	9,730,000	112,000,000	79,900	1.09	2,350,000	4,500	.08	9,710

## Colorado River near Grand Canyon, Ariz.

1926 <sup>3</sup> .....	14,400,000	225,000,000	64,700	3.02	5,260,000	5,320	0.05	7,170
1927.....	17,300,000	398,000,000	74,000	13.1	27,600,000	3,530	.04	3,800
1928.....	15,600,000	172,000,000	65,400	2.58	4,550,000	4,610	.03	3,720
1929.....	19,400,000	480,000,000	59,300	10.9	17,400,000	3,190	.01	863
1930.....	13,400,000	235,400,000	54,800	10.7	16,800,000	5,610	.03	4,530
1931.....	6,720,000	68,810,000	31,300	1.83	1,540,000	4,400	.03	3,560
1932.....	16,000,000	261,400,000	49,800	7.49	10,100,000	2,160	.05	2,910
1933.....	10,000,000	178,100,000	15,200	9.06	3,710,000	3,240	.03	2,600
1934.....	4,656,000	50,080,000	8,570	11.5	2,660,000	4,370	.07	8,260
1935.....	10,216,000	122,300,000	101,400	1.01	2,770,000	2,830	.09	6,890
1936.....	12,322,000	157,600,000	21,500	7.74	4,490,000	3,280	.05	4,430
1937.....	12,410,000	191,300,000	43,700	2.95	3,480,000	2,520	.03	2,040
1938.....	15,630,000	232,400,000	39,100	8.76	9,250,000	4,580	.07	8,660
1939.....	9,618,000	86,320,000	28,000	2.12	1,600,000	3,550	.01	958
1940.....	7,435,100	75,410,000	13,300	4.96	1,781,000	2,660	.04	2,870
1941.....	16,940,000	270,100,000	76,800	2.92	6,050,000	9,380	.07	17,730

See footnotes at end of table.

## DETERMINATION OF SUSPENDED SEDIMENT

9

TABLE 1.—Maximum and minimum daily loads of suspended sediment at the Cisco, Lees Ferry, Grand Canyon, Willow Beach, Topock, Green River, and Bluff stations for the period Oct. 1, 1925, to Sept. 30, 1941—Continued

## Colorado River near Willow Beach, Ariz.

Water year ended Sept. 30	Annual runoff (acre-feet)	Annual load of suspended sediment (tons)	Day of maximum load			Day of minimum load		
			Mean discharge (second- feet)	Suspended sedi- ment		Mean discharge (second- feet)	Suspended sedi- ment	
				Per- cent <sup>1</sup>	Load (tons)		Per- cent <sup>1</sup>	Load (tons)
1935-----	5,556,000	13,890,000	6,760	2.12	387,000	152	0.02	81
1936-----	6,282,000	6,830,000	9,680	2.16	565,000	9,500	.001	256
1937-----	5,826,000	358,000	11,000	.02	5,940	-----	-----	-----
1938-----	6,168,000	451,000	6,160	.23	38,300	-----	-----	-----
1939-----	8,473,000	-----	26,000	.07	49,100	-----	-----	-----

## Colorado River near Topock, Ariz.

1926 <sup>4</sup> -----	14,300,000	140,000,000	17,900	3.56	1,720,000	6,490	0.19	20,800
1927-----	17,000,000	345,000,000	96,500	7.91	20,600,000	4,200	.15	17,000
1928-----	15,400,000	209,000,000	66,100	3.01	5,370,000	5,490	.26	38,500
1929-----	18,900,000	437,000,000	52,700	5.46	7,760,000	8,080	1.08	23,500
1930-----	13,200,000	245,000,000	42,200	6.71	7,640,000	4,220	.26	29,600
1931-----	6,770,000	64,700,000	28,500	.94	723,000	3,820	.28	28,900
1932-----	16,100,000	272,000,000	32,600	6.50	5,710,000	3,150	.36	30,600
1933-----	10,200,000	121,400,000	68,200	1.18	2,170,000	3,590	.22	21,300
1934-----	4,870,000	61,000,000	9,750	4.27	1,124,000	1,750	.06	2,840
1935-----	5,225,000	27,800,000	6,100	2.64	435,000	422	.02	227
1936-----	6,025,000	20,100,000	9,320	2.34	589,000	4,700	.11	13,960
1937-----	5,577,000	10,700,000	9,080	.25	61,300	8,520	.06	13,800
1938-----	5,967,000	9,710,000	12,700	.24	82,300	5,560	.08	12,000
1939 <sup>5</sup> -----	8,188,400	-----	26,600	.31	222,600	5,600	.001	151

See footnotes at end of table.

## Green River at Green River, Utah

1930 <sup>2</sup> -----	4,560,000	34,500,000	17,800	3.10	1,490,000	2,580	0.08	5,570
1931 <sup>2</sup> -----	2,390,000	7,450,000	12,300	.76	252,000	978	.01	270
1932-----	4,810,000	36,100,000	31,000	.81	677,000	580	.01	162
1933-----	3,530,000	15,360,000	7,720	2.26	471,000	1,140	.01	297
1934-----	1,306,000	1,780,000	1,480	3.42	136,700	520	.01	140
1935-----	2,850,000	14,350,000	17,800	.83	399,000	752	.01	216
1936-----	4,147,000	33,800,000	13,000	6.36	2,230,000	969	.005	135
1937-----	4,134,000	43,400,000	18,400	3.29	1,630,000	1,040	.02	562
1938-----	4,747,000	38,200,000	9,140	5.68	1,400,000	830	.03	672
1939-----	3,420,000	22,800,000	15,800	2.02	862,000	1,450	.01	392
1940-----	2,376,000	8,880,000	2,660	4.38	315,000	-----	-----	-----
1941-----	4,242,000	31,900,000	25,500	2.01	1,384,000	664	.02	359

## San Juan River near Bluff, Utah

1928 <sup>6</sup> -----	1,730,000	1,490,000	669	8.73	158,000	411	0.24	2,660
1928 <sup>7</sup> -----	3,110,000	100,500,000	20,000	21.2	11,450,000	1,680	.54	2,449
1930-----	1,720,000	58,300,000	13,900	23.0	8,620,000	229	.11	679
1931-----	887,000	15,290,000	3,480	9.64	905,000	113	.01	27
1932-----	2,950,000	75,300,000	9,160	11.3	2,790,000	145	.09	351
1933-----	1,240,000	23,610,000	5,960	13.2	2,120,000	26	.04	27
1934-----	661,900	21,170,000	4,920	20.3	2,700,000	-----	-----	-----
1935-----	2,183,000	42,700,000	12,500	8.72	2,940,000	150	.003	11
1936-----	1,631,000	32,600,000	3,950	21.4	2,282,000	469	.06	756
1937-----	2,336,000	52,200,000	10,290	13.3	2,840,000	400	.02	216
1938-----	2,466,000	52,100,000	14,000	14.2	5,370,000	204	.09	496
1939-----	1,239,000	21,410,000	11,000	20.9	6,207,000	-----	-----	-----
1940-----	996,300	26,300,000	12,130	12.1	3,960,000	118	.03	96
1941-----	4,242,000	112,700,000	25,200	2.02	3,370,000	664	.09	1,614

<sup>1</sup> Percent by weight. Value reported is usually the average of three or more integrated samples.<sup>2</sup> Incomplete records.<sup>3</sup> Oct. 1, 1938, to Apr. 7, 1939.<sup>4</sup> Oct. 12, 1925, to Sept. 27, 1926.<sup>5</sup> Aug. 13, to Sept. 21, 1928.<sup>6</sup> Oct. 3, 1925, to Sept. 30, 1926.<sup>7</sup> July 1, to Sept. 30, 1929.

The annual loads of sediment at the Yuma gaging station for the same period have been computed from the records of the Bureau of Reclamation and are given in table 2.

TABLE 2.—*Suspended sediment and runoff of the Colorado River at gaging station near Yuma, Ariz., Oct. 1, 1925, to Sept. 30, 1941*

Water year ended Sept. 30	Suspended sediment (tons) <sup>1</sup>	Runoff (acre-feet)
1926-----	152,000,000	13,300,000
1927-----	241,000,000	16,000,000
1928-----	128,000,000	13,900,000
1929-----	262,000,000	17,800,000
1930-----	180,000,000	12,500,000
1931-----	42,300,000	4,920,000
1932-----	198,200,000	14,300,000
1933-----	89,000,000	8,070,000
1934-----	27,400,000	2,916,000
1935-----	16,860,000	3,259,000
1936-----	17,600,000	3,803,000
1937-----	15,090,000	3,823,000
1938-----	13,870,000	4,076,000
1939-----	11,100,000	5,828,000
1940-----	5,067,000	5,323,000
1941-----	14,740,000	9,030,000

<sup>1</sup> Records furnished by Bureau of Reclamation.

The mean annual load of suspended sediment at the Grand Canyon station during the years 1925-41 was 200,200,000 tons and the mean annual runoff at the station during the same period was 12,640,000 acre-feet.

#### SOURCES OF LOADS MEASURED AT GRAND CANYON STATION


Records for the Grand Canyon gaging station represent the flow and sediment load of the Colorado River above Boulder Dam and Lake Mead, the reservoir behind Boulder Dam.

Approximately 90 percent of the runoff measured at the Grand Canyon station can be accounted for by the runoff measured at the Cisco, Green River, and Bluff gaging stations. The combined annual sediment load for those three stations, however, is less than two-thirds of the annual load carried past the Grand Canyon station. (See table 3.)

TABLE 3.—*Load of suspended sediment and runoff at Cisco, Green River, and Bluff gaging stations in comparison with Grand Canyon station*

[Expressed in percent of load and runoff at Grand Canyon gaging station]

	Cisco		Green River		Bluff		Unmeasured		Grand Canyon	
	Sus- pen- ded sediment	Run- off								
1932-----	10	42	14	30	29	18	47	10	100	100
1935-----	15	46	12	28	35	21	38	5	100	100
1938-----	15	47	16	30	22	16	47	7	100	100
1941-----	12	39	12	25	42	25	34	11	100	100



GEOLOGICAL SURVEY COLORADO RIVER SAMPLER.



For the four yearly periods covered by the data in table 3 the ratio of sediment to runoff was much higher for the Bluff station than for the Green River and Cisco stations. The data in this table also show that a large part of the suspended load at Grand Canyon came from sources from which samples were not collected. It seems, therefore, that an appreciable part of the suspended load carried past the Grand Canyon station was brought into the Colorado River by relatively small flows of very muddy water. It is likely that considerable quantities of sediment were brought into the Colorado River from the San Rafael and Fremont Rivers, and it is known that large quantities of sediment were brought in by the Little Colorado River.

An indication of the quantities brought in by the Little Colorado River during the 5 years ended September 30, 1934, can be obtained by comparing the records in table 1 for the Lees Ferry and Grand Canyon stations for those years, as the Little Colorado flows into the Colorado between those stations. In those 5 years the average annual increase in load of suspended sediment between the Lees Ferry and Grand Canyon stations was more than 59,000,000 tons. Paria River flows into the Colorado just below the Lees Ferry station and at times brings in considerable quantities of sediment. It should also be pointed out that during 3 of those years the annual loads for the Grand Canyon station were higher than the average load for the 16 years of observations.

## PHYSICAL NATURE OF THE SUSPENDED AND DEPOSITED SEDIMENT

The physical nature of the suspended sediment, particularly the particle size, is the determining factor as to where the various particles will be deposited along the banks in eddies and quiet water and in reservoirs. For the determination of the particle size of suspended and deposited sediments, samples were collected at different places in the basin. A few samples were collected to determine the weight per unit volume of the deposited material, but the records are not complete enough for a statement of the average weight per unit volume of sediment.

### METHODS OF DETERMINATION OF PARTICLE SIZE

The size of the particles was determined by a method adapted from the usual methods for such determinations<sup>7</sup> and consisted of a combination of sieving and decantation methods. The procedure

<sup>7</sup> U. S. Engineer Office, St. Paul, Minn. A study of methods used in measurement and analysis of sediment loads in streams, Report 4, Methods of analyzing sediment samples, pp. 175-179, 1941.

used with most of the samples provided for no dispersion of the suspended sediment and complete dispersion of samples of deposited sediment. The degree of dispersion in the suspended-sediment samples varied with the concentration and character of the dissolved solids in the water in which the sediment was being carried, and an attempt was made to use in the determinations water similar in character and concentration to the original water.

The procedure for suspended-sediment samples consisted in pouring the sample through a 100-mesh sieve and then through a 200-mesh sieve to get the quantities of particles with diameters of 0.149 and 0.074 millimeter, respectively. If the quantity on the 100-mesh sieve was large the material was transferred to a 50-mesh sieve, and the quantity held on that sieve (0.297 millimeter in diameter) was determined. The material that passed the 200-mesh sieve was washed into a cylinder and the quantities of small particles determined by settling. It was customary to determine the quantities of material with settling velocities corresponding to 0.050, 0.020, and in some cases 0.005 millimeter. For the determinations by settling, the temperature of the suspension in the cylinder was observed and the suspension well shaken. The cylinder was then set upright for a time sufficient for all the material of a given size to have fallen from the top of the liquid to the bottom of the cylinder under the existing temperature conditions. At the end of the correct settling time the liquid was decanted, leaving the size group at the bottom of the cylinder. The suspension was again shaken and allowed to stand the necessary time for the settling of the next size group. After decantation of the suspension, determinations of other size groups were made as desired by settling and subsequent decantations. This method of decantation gave results that represent all the material of the maximum size and quantities of the smaller sizes that were near enough the bottom to settle there in the required time. It seems likely, however, that the results of these determinations will be of value in estimating the rates of settling of the material carried in suspension.

Samples of deposited sediment were usually dry at the time the analysis was made, and it was necessary to disperse them before the analysis was started. A part of the sample was weighed out and placed in a conical vessel together with a small volume (4 milliliters) of 1.5 percent sodium-oxalate solution and about 150 milliliters of water. Air was bubbled through the liquid for about 3 hours with the orifice of the air tube at the bottom of the vessel. The sizes of the particles were then determined by the sieving-decantation method, except that distilled water was used for washing the material on the sieves and as additional water for the settling medium.

**SUSPENDED SEDIMENT**

The results of the determinations of the size of the particles of the suspended sediment samples are given in tables 23 to 25. As a rule most of the material in those samples was found to consist of particles with settling diameters of greater than 0.020 millimeter, but in only a few samples was there as much as 10 percent of the material coarse enough to be held on the 100-mesh sieve (0.149 millimeter in diameter). After the closing of Boulder Dam some of the suspended sediment at the Willow Beach station apparently was carried through the entire length of Lake Mead,<sup>8</sup> and that material consisted of particles whose diameters were less than 0.020 millimeter.

**BANK DEPOSITS**

Throughout the entire basin, deposits of sediment may be found along the banks of the river and its tributaries. These deposits usually represent the material that is first dropped out of suspension and that consists of the larger particles of the suspended sediment. Samples have been collected from some of these bank deposits and determinations made of the weight-volume relation of the material in the deposits and also of the size of the particles in the deposits. These deposits usually had a weight of more than 80 pounds per cubic foot of dry deposit, and the particles have effective settling diameters of greater than 0.020 millimeter. Considerable quantities of the material carried by the Colorado River, particularly during periods of summer floods, consist of particles whose settling diameters are less than 0.020 millimeter, and considerable quantities of the material had settling diameters of less than 0.002 millimeter. A weight greater than 80 pounds per cubic foot of deposit probably is not representative for all of the suspended material carried in the Colorado River Basin.

**RESERVOIR DEPOSITS**

Little has been reported on the extent and nature of the deposits of sediment in reservoirs in the Colorado River Basin. Studies by the Bureau of Reclamation on Lake Mead have included observations both on the nature of the inflow at the head of the lake and on the formation of deposits along the edge and at the bottom of the reservoir.

On a number of occasions it has been observed that the incoming water was very turbid and that there was a sharp line of demarcation between the incoming water and the lake water. Plate 2 shows such an inflow approximately 90 miles above Boulder Dam in January 1939. Observations taken just below the line of demarcation show

<sup>8</sup> Grover, N. C. and Howard, C. S., op. cit., pp. 727-728.

that the incoming water, because of its greater density, dips under the surface of the lake water and travels beneath the surface for considerable distances without complete mixing. This stratified flow in Lake Mead has been discussed by Bell.<sup>9</sup>

Observations on Lake Mead made from time to time by the Bureau of Reclamation have shown large deposits of material in places of slack water such as or the inside of curves and across inlets of side washes and streams. One of the deposits found on March 17, 1939, at mile 257, approximately 97 miles above Boulder Dam, in an area where there was slack water at a sharp bend is shown in plate 3. In addition, observations have shown considerable deposits at points throughout the upper end of the lake. In 1941, the deposits in Virgin Canyon, 50 miles above Boulder Dam, were more than 30 feet deep, and at the intake towers, just above the dam, it was possible to sink a 10-pound weight a vertical distance of about 80 feet into the deposits of unconsolidated material at the bottom of the reservoir.<sup>10</sup>

### DETERMINED QUANTITIES OF SUSPENDED SEDIMENT

The quantities of sediment in samples collected in the Colorado River Basin by the Geological Survey during the period 1925-41 are presented in this report. For selected periods the quantities in the individual samples collected at the Grand Canyon and Bluff gaging stations are given; for other periods only the mean daily concentrations are tabulated; for some periods the mean daily discharge and mean concentration of sediment and the daily load of sediment are given. These data are presented in tables 5 to 20. A key to these tables is given in table 4.

<sup>9</sup> Bell, H. S. Stratified flow in reservoirs and its use in prevention of silting. U. S. Dept. Agr. Misc. Pub. 491, 1942.

<sup>10</sup> Records of the Bureau of Reclamation, U. S. Dept. of the Interior.

TABLE 4.—*Kind of information and periods covered by the tables of data for 8 gaging stations*

Gaging station	Mean daily concentration of suspended sediment		Mean daily discharge, mean daily concentration, and daily load of suspended sediment	
	Period	Table No.	Period	Table No.
Colorado River: Near Cisco, Utah-----	May 14, 1929, to Sept. 30, 1930.	5	Oct. 1, 1939, to Sept. 30, 1941	6
At Lees Ferry, Ariz-----	Oct. 1, 1928, to Dec. 16, 1933	7	Oct. 1, 1929, to Sept. 30, 1941	9
Near Grand Canyon, Ariz-----	Oct. 1, 1925, to Sept. 30, 1929	8	Oct. 1, 1934, to Sept. 30, 1936	11
Near Willow Beach, Ariz-----	-----	-----	Oct. 1, 1934, to Mar. 31, 1939	13
Near Topock, Ariz-----	Oct. 1, 1925, to Sept. 30, 1934	12	Oct. 1, 1939, to Sept. 30, 1941	15
Green River at Green River, Utah-----	May 1, 1929, to Sept. 30, 1939	14	Oct. 1, 1929, to Sept. 30, 1941	18
San Juan River near Bluff, Utah-----	-----	-----	-----	-----
Suspended-sediment concentration in individual samples				
Gaging station	Period		Period	
	Apr. 1, 1935, to Sept. 30, 1936	10	-----	-----
Colorado River near Grand Canyon, Ariz-----	Nonconsecutive periods in 1937, 1939, 1940, and 1941	19	Aug 13 to Sept. 21, 1928-----	16
San Juan River near Bluff, Utah-----	-----	-----	July 1 to Sept. 30, 1922-----	17
Little Colorado River at Grand Falls, Ariz-----	-----	-----	July 6 to Sept. 26, 1931-----	20

Results of special studies at the Grand Canyon and Topock stations showing the velocity at the time of sampling are given in tables 21 and 22. Data on the size of the particles carried are presented as follows: Colorado River at Grand Canyon station, April 5, 1935, to September 30, 1941, in table 23; Colorado River near Willow Beach, April 2, 1935, to September 27, 1936, in table 24; and San Juan River near Bluff, May 3, 1935, to September 30, 1936, in table 25.

TABLE 5.—*Mean daily concentration of suspended sediment in the Colorado River at gaging station near Cisco, Utah, May 14, 1929, to Sept. 30, 1939*

1929-30

Day	Octo- ber	No- vember	De- cem- ber	Janu- ary	Febru- ary	March *	April	May	June	July	Aug- ust	Sep- tem- ber
1									.18	.03	.62	
2									.17	.03	.52	.05
3									.12	.03		.05
4									.16		.50	.04
5									.14	.02	.53	.06
6									.09	.04	.42	.51
7									.09	.06	.50	
8									.14	.04	.44	
9									.10	.02	.30	
10									.06	.03	.69	
11									.06	.15	.60	
12									.05	.15	.40	.05
13									.20	.24	.91	.04
14									.14	.42	.31	.03
15							0.06	.08	1.24	1.06		.03
16									.13	.21	.96	.03
17									.12	.13	.54	.03
18									.05	.35	.32	.03
19									.12	.04	.32	.02
20									.13	.10	.37	.19
21									.10	.07	.45	.13
22									.19	.04	.39	.12
23									.19	.04	.20	.14
24									.14	.04	.20	.08
25									.06	.05	.08	.06
26									.16	.08	.06	.08
27									.17	.05	.06	.05
28									.22	.03	.07	.16
29									.34	.03	.16	.05
30									.32	.02	.26	.04
31									.22		.28	.04

1930-31

1	1.38					0.03	0.03	0.24	0.15	0.31	3.57	0.70
2	1.60					.02	.03	.18	.22	.10	.86	.18
3	1.45					.03	.03	.21	.23	.10	1.56	.15
4	.42					.02	.02	.22	.30	.10	.39	.09
5	.18					.03	.04	.44	.29	.10	.15	.05
6	.11					.03	.04	.38	.19	.09	.38	.05
7	.10					.03	.01	.26	.23	.06	.34	.03
8	.14					.01	.02	.23	.27	.06	.31	.03
9	.12					.01	.02	.20	.28	.04	.11	.03
10	.08					.02	.06	.26	.18	.04	.06	.03
11	.08					.03	.10	.18	.14	.04	.07	.03
12	.09					.03	.08	.12	.12	.03	.05	.02
13	.08					.02	.11	.13	.14	.02	.04	.02
14	.07					.02	.20	.08	.10	.02	.04	.03
15	.08					.05	.26	.10	.10	.02	.06	.74
16	.06					.04	.30	.40	.09	.02	.02	.07
17	.04					.06	.16	.50	.10	.01	.24	.29
18	.05					.06	.12	.96	.11	.01	.02	.23
19	.03				0.12	.06	.10	.90	.09	.01	.06	1.69
20	.06				.10	.08	.20	.50	.09	.02	.04	.63
21	.04					.09	.06	.26	.29	.10	.04	.77
22	.04					.10	.05	.24	.20	.10	.04	.44
23	.03					.12	.05	.12	.17	.08	.04	.26
24	.03					.08	.06	.10	.15	.08	.03	5.03
25	.02					.03	.05	.83	.26	.07	.02	3.96
26	.02					.04	.06	.54	.20	.06	.01	.83
27	.01					.05	.06	.61	.35	.07	.01	.86
28	.02					.04	.04	.36	.32	.08	.01	.64
27	.01					.02	.20	.25	.08	1.30	.02	.49
30	.02					.04	.20	.21	.58	.1.89	.01	.26
31	.01					.03		.16		1.66	.01	

## QUANTITIES OF SUSPENDED SEDIMENT

TABLE 5.—*Mean daily concentration of suspended sediment in the Colorado River at gaging station near Cisco, Utah, May 14, 1929, to Sept. 30, 1939—Continued*

1931-32

Day	Octo- ber	No- vember	De- cem- ber	Janu- ary	Febru- ary	March	April	May	June	July	Aug- ust	Sep- tem- ber
1	0.18		0.05			0.43	0.19			0.08		
2											0.31	0.19
3	3.03	0.04				.29		0.54	0.13			
4			.04								.11	
5							.98					
6	.71	.03								.09		.06
7	.32							.49	.10			
8						.28	.50			.10		
9	.15							.38	.12			.03
10		.56										.04
11			.08			.11						
12	.10						.44					.03
13		.63								.29		.04
14	.09							.72	.11			
15						.04	.84			.13		
16												.03
17		.07							.14			
18						.06						
19					.14			.30		.16		.15
20		.04										.03
21	.10						.57	.26	.09			
22				0.13		.48				.06		
23							.54				1.06	.03
24	.13							.26	.11			
25						.42	.16					
26							.39				.15	
27	.08	.04		.08				.24		.04		.16
28				.06					.10			
29						.16	.48			.03		
30	.06										.99	.10
31								.14				

1932-33


TABLE 5.—*Mean daily concentration of suspended sediment in the Colorado River at gaging station near Cisco, Utah, May 14, 1929, to Sept. 30, 1939—Continued*

1933-34


1934-35

GEOLOGICAL SURVEY

WATER-SUPPLY PAPER 998 PLATE 2



LINE OF DEMARCACTION OF INFLOW AND WATER OF LAKE MEAD APPROXIMATELY 90 MILES ABOVE BOULDER DAM.



DEPOSIT IN SLACK-WATER AREA ABOUT 97 MILES ABOVE  
BOULDER DAM.

TABLE 5.—*Mean daily concentration of suspended sediment in the Colorado River at gaging station near Cisco, Utah, May 14, 1929, to Sept. 30, 1939—Continued*

1935-36

Day	Octo- ber	No- vember	De- cem- ber	Janu- ary	Febru- ary	March	April	May	June	July	Aug- ust	Sep- tem- ber
1	0.23							0.13		0.13	0.64	1.71
2						0.01	0.04	.11	0.06	.04	.31	1.40
3						.03			.06			.84
4			0.03									.24
5	.04				0.04	.03	.04	.28				
6		0.02						.34			.30	
7			.03	.00			.03		.06	.02	1.52	.13
8	.03					.04		.18			.81	.06
9		.03	.03				.04		.08	.03		
10				.01		.03				.41	.48	
11	.02		.01			.03	.67	.13		3.75		.36
12		.02				.05	2.05	.12	.05		.52	.26
13						.06		.08		.40		
14		.02					1.05	.14	.06	.35		.17
15	.01					.07						.06
16				.03			.75	.14		.11	.10	
17			.02			.06	.70			.06		.04
18	.01					.08	.09		.16	.04		
19		.01					.60	.10	.04	.46		
20			.03			.07	.06				.09	.03
21								.41	.08	.04	.42	.44
22		.02			.05			.44	.09		.26	1.00
23	.01							.39		.05		.38
24			.03			.05						.02
25	.02							.27	.07	.05	.16	
26							.05		.07	.04		.02
27								.20		.13		
28								.19		.04		
29	.02						.04		.05		.14	.05
30		.01							.10		.17	.02
31	.02			.06	.02				.07		.66	1.49

1936-37

1						0.22	0.04	0.26	0.10	0.12		2.37
2		0.22				.18	.04	.31	.13		0.10	4.74
3			0.02			.28	.08		.09			.25
4	0.03				0.04				.49			
5	.06											
6		.05				.35	.12		.09	.07	.06	.20
7								.52		.11		.16
8	.02		.02			.30	.12		.07		.64	
9		.04			.04			.42		.70		.17
10						.20			.08	.91		.10
11						.18	.68	.47			.15	.06
12	.02					.03	1.30	.41	.10	1.50	.05	
13		.02	.05			.20	1.45	.36		4.67		.04
14								.24	.09		.05	.04
15		.04					.23	1.18		.10	.84	
16	.02		.10				.26		.33		.04	.02
17							.26	.82		.07		.05
18							.20		.25			
19		.04						.68			.19	.04
20	.81						.34	.45		.10	.20	
21	.31						.22			.03		.06
22			.03					.47			.09	
23	.40	.04					.09			.06		.08
24							.12	.60	.14		.05	.04
25										.02		
26	.06						.18	.08	.36		.14	
27			.02				.38			.15		.02
28								.37	.10			.58
29	.10	.01					.06		.09	.03		.08
30								.25	.12	.14	.45	1.43
31	.48		.02						.16		.39	1.82

TABLE 5.—*Mean daily concentration of suspended sediment in Colorado River at gaging station near Cisco, Utah, May 14, 1929, to Sept. 30, 1939—Continued*

1937-38

Day	Octo- ber	No- vember	De- cem- ber	Janu- ary	Febru- ary	March	April	May	June	July	Aug- ust	Sep- tem- ber
1					0.03			0.53	0.15		0.06	0.80
2	0.07		0.02		.03	0.48		.54		0.16	.04	
3	.14		.02	0.03			0.05		.17			1.28
4		0.03		.03		3.28	.04		.11		.05	2.16
5	.06			.04	.04	3.23					.03	
6	.06	.03	.02					.51	.42	.17	.13	1.48
7			.02							.08		
8	.04	.18	.02	.02	.04	.21	.36		.09		.03	.31
9		.38				.20	.30	.35			.47	2.44
10	.03	.26	.04		.03			.16	.15	.12	.42	
11				.02		.07	.71				.25	
12	.02	.05	.02		.26			.17	.09	.10		1.94
13		.98	.03		.62		1.43				.10	
14	.02	.02			.36	.40	.96	.24	.16			
15	1.27		.35	.02	.26	.45			.10	.42	1.32	.67
16		.02	.56				1.19	.47		.35	.13	.25
17	1.36	.12	.02			.39		.41	.14			
18	.82	.02	.08		.08	.26				.16		.27
19	.55	.02	.06				1.22	.27			.08	.15
20				.06		.14		.22		.14		
21		.02	.04				1.29		.10		.04	.07
22	.20			.04	.04				.22	.08		
23				.04				.87	.20		.04	
24		.03				.19	.88	.16		.05		
25	.05		.02		.04					.06	.04	.06
26	.04			.02				.87	.16	.11		.06
27		.02				.68			.17			
28	.04		.04		.04	.40		.61	.30	.14	.09	.04
29		.02		.02				.17		.06		.03
30	.03		.02					.16	.27		.06	
31												

1938-39

1		0.03	0.04	0.04	0.02	0.04	0.23	0.68	0.15	0.03	0.03	
2		.08	.03	.06	.03			.52	.22			
3							.04	.48		.03		0.09
4								.64			.03	
5	.05	.03						.60	.40	.12	.03	4.55
6			.05		.03			.53	.38		.02	.73
7	.07	.03				.03		.33	.20	.14	.84	1.79
8	2.85		.05									
9						.04			.23		.01	
10			.04	.02					.16	.07	.01	
11	.43						.14	.20	.22		.10	.54
12			.02		.02				.15	.12	.01	
13	.16		.01					.28		.17		
14		.04				.03	.39		.14		.02	1.62
15	.08	.02	.01					.16	.09	.10		
16			.02					.38	.12	.07	.01	.34
17	.08				.04			.10	.17	.06	.01	
18		.02							.23			.15
19	.07		.01						.11	.04	.03	.07
20	.05	.03			.04	.36			.13			
21				.03				.13	.25	.07	.03	.05
22		.02					.57	.11	.24	.08		
23	.03	.02			.04					.08		.03
24			.02				.94	.46	.16		.03	
25	.02	.02		.02			.79		.16	.04		.02
26			.02						.09	.03	.02	
27	.03	.03			.05	.82	.20		.11	.04		.02
28			.02						.32	.08	.03	
29	.02	.04		.02			.45					1.24
30			.01								.02	2.14
31								.26			.02	.66

## QUANTITIES OF SUSPENDED SEDIMENT

21

TABLE 6.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Cisco, Utah, Oct. 1, 1939, to Sept. 30, 1941*

1939

Day	October		November		December				
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	2,590	0.04	2,800	2,270	0.02	1,230	2,420	0.02	1,310
2				2,500	.02	1,350	2,230	.01	602
3	2,590	.04	2,800				2,220	.02	1,200
4				2,590	.02	1,400	2,270	.01	613
5				2,680	.02	1,450	2,270	.01	613
6	2,680	.03	2,170	2,760	.06	4,470	2,200	.01	594
7				2,590	.01	699	2,320	.01	626
8	2,420	.02	1,300	2,590	.01	699	2,120	.01	572
9							1,920	.01	518
10	2,500	.14	9,450	2,590	.01	699	1,800	.01	486
11	2,590	.03	3,000	2,680	.05	3,620	2,140	.02	1,160
12							1,670	.01	451
13	2,500	.03	2,000	2,320	.04	2,500	1,860	.01	502
14				2,390	.02	1,290			
15	2,590	.02	1,400	2,320	.02	1,250	1,980	.02	1,070
16				2,500	.02	1,350			
17	2,500	.01	675	2,590	.01	699	1,710	.01	462
18							1,460	.02	788
19	2,270	.01	613						
20									
21	2,190	.01	591						
22									
23	2,120	.01	572						
24									
25	2,040	.01	551						
26									
27	2,190	.26	15,400						
28	2,370	.07	4,480	2,500	.01	675			
29	2,350	.04	2,540						
30				2,590	.02	1,400			
31	2,270	.04	2,450						

1940

	January			February			March		
	1	2	3	4	5	6	7	8	9
1	1,840	0.01	497	2,420	0.02	1,310	2,850	0.24	18,500
2	2,060	.01	556	2,590	.05	3,500	2,680	.11	7,960
3				2,760	.10	7,450	2,590	.12	8,390
4	2,420	.02	1,310	2,760	.08	5,960	2,500	.08	5,400
5							2,370	.03	1,920
6	2,420	.01	653	2,370	.05	3,200	2,350	.03	1,900
7							2,280	.04	2,460
8	2,250	.01	608				2,110	.02	1,140
9							2,140	.01	578
10	2,110	.01	570				2,150	.01	580
11	2,190	.01	591				2,140	.02	1,160
12							2,150	.01	580
13	2,590	.04	2,800				2,140	.02	1,310
14							2,140	.02	1,300
15	2,120	.02	1,140				2,140	.02	1,180
16							2,150	.01	580
17	1,710	.01	462				2,140	.02	1,200
18							2,140	.01	594
19	1,840	.02	994				1,920	.01	518
20							2,390	.02	1,290
21	1,780	.01	481				2,060	.01	556
22							2,070	.01	559
23	1,960	.02	1,060				2,760	.08	5,960
24							3,400	.50	45,900
25	1,900	.03	1,540				3,300	.20	17,800
26									
27	2,200	.04	2,380				4,370	.17	20,100
28									
29	2,500	.04	2,700						
30									
31	2,390	.03	1,940						

TABLE 6.—Mean daily discharge, mean daily concentration, and daily load of suspended sediment for the Colorado River at gaging station near Cisco, Utah, Oct. 1, 1939, to Sept. 30, 1941—Continued

1940								
Day	April			May			June	
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent
1	3,680	0.23	22,800	10,300	0.22	61,200		
2							21,700	0.15
3	3,970	.22	23,600	9,360	.16	40,400	22,500	.14
4								85,000
5	3,400	.18	16,500	11,900	.29	93,200	20,500	.11
6								60,900
7	3,400	.15	13,800	15,100	.38	155,000	17,300	.07
8				16,200	.34	149,000		32,700
9	3,680	.18	17,900				14,000	.07
10				17,300	.25	117,000		26,500
11	3,490	.16	15,100					
12				22,100	.37	221,000	10,800	.06
13	3,210	.16	13,900	23,300	.36	226,000	9,960	.06
14				25,000	.25	169,000		16,100
15	3,580	.42	40,600				11,600	.09
16				22,500	.18	109,000		
17	5,320	.43	61,800	21,300	.14	80,500	11,900	.08
18								25,700
19	5,320	.31	44,500	21,300	.15	86,300	11,200	.05
20							10,600	.04
21	7,430	.78	156,000	16,600	.10	44,800	9,360	.04
22								10,100
23	10,900	.67	197,000	15,100	.08	32,600	8,780	.04
24								9,450
25	11,600	.50	157,000	14,300	.07	27,000		
26							7,180	.03
27	11,900	.39	125,000	15,400	.10	41,600	8,880	.07
28								11,100
29	12,200	.38	125,000	17,700	.10	47,800		
30	10,600	.26	74,400				5,000	.04
31				18,500	.09	45,000		5,400

1945

## QUANTITIES OF SUSPENDED SEDIMENT

TABLE 6.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment for the Colorado River at gaging station near Cisco, Utah, Oct. 1, 1939, to Sept. 30, 1941—Continued*

1940

1941

	January		February			March			
1.	2,760	0.03	2,240	2,590	0.03	2,100	2,500	0.12	8,100
2.				2,590	.03	2,100			
3.	2,420	.02	1,310				2,940	.17	13,500
4.	2,190	.02	1,180	2,220	.03	1,800			
5.							2,940	.12	9,530
6.							2,760	.14	10,400
7.	1,840	.02	994	2,110	.02	1,140			
8.	2,010	.02	1,080	2,280	.02	1,230	2,590	.08	5,590
9.									
10.	2,060	.02	1,110	2,400	.03	1,940	2,500	.05	3,380
11.									
12.	2,270	.02	1,230	2,850	.16	12,310	2,370	.37	23,700
13.									
14.	2,400	.02	1,300	3,490	.20	18,850	2,680	.06	4,340
15.									
16.	2,420	.02	1,310	2,500	.10	6,750	2,850	.08	6,160
17.									
18.	2,250	.02	1,220	2,940	.14	11,110	2,760	.11	8,200
19.									
20.	2,010	.01	543	2,940	.10	7,940	3,030	.11	9,000
21.	2,270	.02	1,230						
22.				3,120	.20	16,800	3,780	.30	30,600
23.	2,420	.02	1,310	3,030	.17	18,900	4,070	.32	35,200
24.									
25.	2,420	.02	1,310				5,540	.52	77,800
26.									
27.				3,400	.20	18,400	4,680	.30	37,900
28.	2,250	.01	608	2,680	.18	13,000			
29.							4,270	.26	30,000
30.	2,370	.02	1,280						
31.							5,210	.46	64,700

TABLE 6.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment for the Colorado River at gaging station near Cisco, Utah, Oct. 1, 1939, to Sept. 30, 1941—Continued*

1941

Day	April		May		June				
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1				22,900	0.78	482,000	26,200	0.09	63,700
2	7,180	0.78	151,000						
3	6,690	.57	103,000	27,900	.76	573,000	26,200	.09	63,700
4				40,500	1.12	1,220,000			
5	6,000	.30	48,600	40,500	.80	875,000	27,100	.10	73,200
6				37,000	.66	659,000			
7	5,650	.30	45,800	34,400	.49	455,000			
8				34,800	.50	470,000			
9	5,540	.31	46,400	38,300	.57	589,000			
10									
11	6,810	.62	114,000				27,100	.13	95,100
12	6,450	.44	76,600	47,700	.60	773,000	24,100	.12	78,100
13	6,340	.34	58,200				21,300	.12	69,000
14									
15	6,280	.28	47,500	63,400	.38	650,000			
16	6,340	.31	53,100	57,400	.31	480,000	20,100	.09	48,800
17				48,200	.32	416,000			
18	5,990	.24	38,800	46,400	.24	301,000	22,900	.11	68,000
19				45,000	.19	231,000	28,400	.14	107,000
20	5,800	.25	37,800				31,300	.15	127,000
21							31,300	.17	144,000
22	5,200	.16	22,500	28,800	.22	171,000			
23	5,000	.22	29,700				30,500	.10	82,400
24				31,300	.18	152,000	30,900	.43	359,000
25	5,990	.31	50,100						
26	7,950	.50	107,000	35,700	.20	193,000	27,900	.11	82,900
27	11,200	.67	203,000	36,100	.17	166,000			
28	15,800	.94	401,000						
29	19,700	1.02	543,000	34,400	.12	112,000	21,700	.08	46,900
30	19,700	.83	441,000	27,900	.11	82,900			
31									

1941

	July		August		September	
	Mean discharge (second-feet)	Suspended sediment	Mean discharge (second-feet)	Suspended sediment	Mean discharge (second-feet)	Suspended sediment
1	16,900	0.07	31,900	3,800	0.02	2,050
2				3,800	.02	2,050
3	14,300	.06	23,200			
4				2,760	.02	1,490
5	13,300	.07	25,100			
6				2,500	.05	3,380
7	11,900	.05	18,100			
8				4,370	.78	92,000
9	11,200	.06	18,100	8,690	3.91	917,000
10				6,690	.85	154,000
11	10,900	.07	20,600			
12				5,320	.29	41,700
13	10,300	.05	13,900	5,000	.14	18,900
14				4,580	.10	12,400
15	9,660	.14	36,500			
16					4,170	.16
17	8,500	.04	9,180	5,880	1.13	179,000
18					3,870	.07
19	7,430	.17	34,100	5,650	1.30	198,000
20	7,390	.07	14,500	4,890	.20	26,400
21	7,950	.05	10,700			
22				4,270	.14	16,100
23					12,600	1.57
24	6,690	.04	7,220	3,300	.08	7,130
25	6,450	.21	36,600			
26				2,760	.03	2,240
27	5,650	.08	12,200			
28				2,220	.03	1,800
29	5,100	.04	5,510			
30	4,580	.03	3,710	2,100	.03	1,700
31					5,400	.17
					5,210	.10
						14,100

## QUANTITIES OF SUSPENDED SEDIMENT

25

TABLE 7.—Mean daily concentration of suspended sediment in the Colorado River at gaging station at Lees Ferry, Ariz., Oct. 1, 1928, to Dec. 16, 1933

1928-29

Day	Octo- ber	No- vem- ber	De- cem- ber	Janu- ary	Fe- bru- ary	March	April	May	June	July	August	Sep- tem- ber
1	0.17					0.37	0.79					
2		1.56					1.01	0.50	0.86	0.41	3.80	1.68
3			0.24							.33	5.24	
4				0.23				1.00	.66	.69		2.19
5	.33	.92				.24					3.68	
6												
7		.77	.21	.12	0.35				.72	.68	.31	5.67
8	.50					.58	1.93	.58	.58	.30	5.35	3.57
9						1.16	1.43	.70			4.50	
10						1.69	1.13	.70	.81	1.41	4.12	3.36
11						1.93	1.08	.94				2.60
12	1.12					2.34		1.06	.67	.65	2.28	
13		.38	.20			4.32		1.22				
14		.35		.12	0.22	2.13			1.25	.51		5.65
15							.74			.31	3.48	1.38
16		.38							.63		1.77	1.30
17			.16				.85	1.14		.33		
18				.16	.15			.90	.55		.81	.79
19							1.03	1.19		.28	.57	
20								1.02	.76			.66
21		.35		.29		.81	1.38	.87	.50		.53	
22					.38		1.12		.32	.36		2.26
23		.33						1.06	1.03		.51	
24	.97		.14					1.16	1.06	.40	.34	.39
25			.16									6.07
26	.62	.28		.30	.30		1.10	.99	.40		.46	
27					.33		1.14	.89		2.18		3.31
28			.09			.87	.95	.77	.37		.87	
29	.44								.86	.37	2.88	1.65
30		.31		.17	.19			.64	.84		4.20	1.31
31									.84		3.79	

1929-30

TABLE 7.—*Mean daily concentration of suspended sediment in the Colorado River at gaging station at Lees Ferry, Ariz., Oct. 1, 1928, to Dec. 16, 1935—Continued*

1930-31

Day	Octo- ber	Novem- ber	De- cem- ber	Janu- ary	Febru- ary	March	April	May	June	July	August	Sep- tem- ber
1	0.80	0.35	0.28	0.27	0.40	0.29	0.47	0.67	0.59	0.25	1.69	0.27
2	.60	.35	.32	.26	.41	.27	.44	.65	.50	.23	1.04	.25
3	.60	.35	.24	.60	.45	.29	.41	.65	.65	.31	1.32	.23
4	1.10	.35	.24	.40	.45	.28	.35	.65	.69	.40	2.92	.22
5	1.05	.35	.24	.75	.50	.27	.30	.63	.49	.50	3.11	.22
6	1.05	.37	.28	.40	.45	.26	.27	.59	.57	.62	2.22	.22
7	1.15	.35	.27	.25	.35	.26	.28	.55	.40	.70	1.77	.22
8	.90	.35	.25	.25	.38	.27	.29	.60	.54	.60	1.27	.23
9	.75	.32	.23	.23	.41	.28	.29	.63	.51	.40	.94	.25
10	.85	.31	.22	.22	.38	.30	.30	.65	.58	.35	1.59	.25
11	.60	.30	.24	.22	.37	.35	.30	.67	.60	.30	1.24	.30
12	.60	.30	.25	.23	.37	.32	.32	.75	.56	.25	1.45	.25
13	.68	.35	.24	.24	.37	.30	.34	.60	.54	.23	1.03	.22
14	.55	.41	.24	.25	.39	.30	.36	.58	.52	.20	.77	.18
15	.48	.37	.23	.25	.41	.30	.38	.52	.50	.18	.83	.15
16	.50	.35	.25	.26	.44	.31	.32	.47	.48	.17	.83	.51
17	.58	.33	.27	.27	.48	.36	.40	.47	.47	.17	.79	.51
18	.52	.80	.25	.32	.75	.43	.38	.49	.47	.17	.60	2.87
19	.52	.70	.24	.37	.58	.35	.55	.60	.47	.20	.82	1.82
20	.49	.68	.20	.30	.56	.29	.55	.91	.44	.28	.47	2.61
21	.40	.55	.18	.27	.52	.32	.56	1.50	.43	.20	.44	2.46
22	.49	.53	.16	.30	.48	.35	.56	1.24	.42	.18	.65	2.12
23	.45	.50	.15	.30	.45	.39	.56	.98	.37	.15	.59	1.97
24	.43	.48	.15	.33	.38	.42	.65	.97	.32	.13	.75	2.92
25	.40	.45	.15	.30	.37	.46	.57	.85	.32	.15	.77	5.51
26	.35	.41	.15	.30	.37	.47	.56	.66	.32	.20	.61	3.22
27	.33	.32	.24	.35	.36	.49	.56	.65	.30	.14	.61	2.29
28	.30	.26	.30	.38	.32	.51	.58	.65	.27	.13	.35	2.58
29	.40	.25	.35	.40	-----	.53	.61	.73	.24	.13	.20	2.22
30	.38	.24	.40	.40	-----	.55	.61	.59	.22	1.25	.16	2.42
31	.36	-----	.44	.40	-----	.52	-----	.59	-----	1.72	.28	-----

1931-32

1		0.38	-----	0.45	0.26	-----	1.07	-----	0.82	0.83	1.52	4.40
2	2.01	-----	-----	-----	-----	-----	1.07	-----	.74	.68	-----	3.62
3		-----	-----	-----	45	-----	-----	0.86	.61	.52	-----	-----
4		-----	-----	-----	-----	-----	1.39	-----	.99	.62	-----	1.87
5		-----	-----	-----	-----	-----	-----	-----	.57	.75	-----	-----
6		.35	-----	-----	.88	-----	1.65	-----	1.07	.59	-----	1.27
7	2.90	-----	-----	-----	-----	-----	1.65	-----	1.03	.50	.66	-----
8		-----	-----	-----	-----	-----	2.00	-----	1.04	.52	.66	1.02
9	1.76	.41	-----	.35	-----	0.75	2.08	-----	.99	.48	-----	-----
10		-----	-----	-----	-----	-----	-----	1.09	-----	.56	.61	.74
11		.55	0.27	-----	.81	1.82	-----	1.82	-----	.48	.53	-----
12	1.08	-----	.50	-----	1.02	1.82	-----	1.82	-----	.30	.45	.39
13		.71	-----	.44	-----	1.7	-----	-----	-----	-----	-----	-----
14	1.25	-----	.45	-----	-----	-----	1.18	1.13	1.40	1.56	.29	.49
15		-----	.47	-----	-----	-----	-----	1.19	-----	.60	1.40	-----
16	.84	1.36	.44	.43	-----	.78	1.31	1.13	-----	1.36	.19	.35
17		-----	-----	-----	-----	-----	1.71	1.12	-----	.51	-----	-----
18		.81	-----	-----	-----	-----	1.37	1.49	-----	.87	.15	-----
19	.49	-----	-----	-----	-----	-----	1.32	1.36	1.63	.60	-----	-----
20		.82	-----	-----	.86	-----	-----	1.11	1.57	.60	.54	-----
21	1.82	-----	-----	-----	-----	-----	1.53	1.06	.43	-----	.58	-----
22		-----	-----	1.05	-----	-----	1.24	.97	-----	.64	1.07	-----
23	2.26	.48	-----	-----	.35	.91	1.79	1.26	.98	.47	.49	3.97
24		-----	-----	-----	-----	1.44	1.17	.96	.45	-----	4.11	-----
25		.45	-----	-----	-----	-----	-----	.96	.48	.34	2.44	-----
26	1.29	-----	.56	.34	.99	-----	1.11	.88	-----	.28	1.74	-----
27		.38	-----	.43	.17	-----	1.29	.95	.83	.48	.27	1.57
28	.78	-----	.43	.17	-----	1.17	1.26	1.05	.81	.49	.26	2.38
29		-----	-----	-----	-----	-----	-----	.93	.69	.26	5.81	1.42
30	.60	.29	.54	.26	-----	-----	1.21	-----	.84	.70	.80	6.27
31		-----	-----	-----	-----	-----	-----	-----	.78	-----	.63	5.57

## QUANTITIES OF SUSPENDED SEDIMENT

27

TABLE 7.—*Mean daily concentration of suspended sediment in the Colorado River at gaging station at Lees Ferry, Ariz., Oct. 1, 1928, to Dec. 16, 1933—Continued*

1932-33

Day	Octo- ber	No- vem- ber	De- cem- ber	Janu- ary	Febr- uary	March	April	May	June	July	August	Sep- tem- ber
1		0.42	0.31	0.21	0.25			0.60	0.92	0.38	0.61	0.23
2	0.71							.77	1.09	.36		.22
3	.52							.93	1.11			
4								1.19	1.09			
5										1.16		
6								1.14	1.02	.29	.96	.16
7								1.13	.88	.30	.93	.18
8							0.52	.93		.56	1.02	
9						0.41		.87	.73	1.35		2.29
10		.35	.28				.51		.74	2.27	2.54	
11				.22	.23	.41	.43	.84	.73	1.69	2.12	2.18
12	.37	.37	.35	.23	.21	.52	.36	.85	.76	3.33	2.37	7.31
13									.75	2.46	1.45	6.23
14	.34	.30	.26	.08	.23	.55	.40	.73	.58	1.62		4.19
15							.40	.63	.61	.97	.93	2.90
16	.30	.34	.19	.19	.19			.53	.68	.97	.98	2.22
17	.29							.37	.55	.49	.68	
18								.34		.54	.90	
19									.47	.47		
20							.37	.42	.45			
21						.54	.34	.69	.56			
22								.30	.93	.47		
23								.33	1.38	.51		
24						.54	.33	1.55	.59			
25		.34				.44	.36	1.64	.51		.95	2.01 2.25
26	.41	.34	.18	.36	.21	.32	.34	1.24	.71		1.05	
27						.33	.42	.48	1.05	.57	.39	.98
28	.52		.21	.26		.35	.46	1.01	.46	.48	.49	.72
29		.34	.19				.40	1.07	.52	1.06		
30	.40	.26	.27	.19		.34		1.03	.45		.39	
31								.72		.78		

1933

1	0.58	0.39	1.26									
2		.35										
3												
4												
5		.45										
6	3.46											
7	3.24											
8	4.04			.49								
9	3.71	.40	.50									
10												
11	2.03	.52	.32									
12	1.23											
13	.99	.45	.40									
14	1.58	.49										
15		.40	.59									
16	.99	.38	.44									
17												
18												
19												
20			.43									
21												
22			.41									
23												
24	.45	.39										
25	.46	.41										
26												
27	.45	.44										
28	.34											
29		.49										
30	.38											
31												

TABLE 8.—Mean daily concentration of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1925, to Sept. 30, 1929

1925-26

Day	Octo- ber	No- vem- ber	Decem- ber	Janu- ary	Febru- ary	March	April	May	June	July	August •	Septem- ber
1	.							1.65				
2		0.38								0.21		
3												0.11
4			0.16	0.09	0.07	0.14		1.72			0.50	
5							0.86		1.28			
6		.43				.18				.15		
7					.10						.24	
8				.12				3.02	1.04			.07
9		.37				.32	3.15				.44	
10			.23		.11							
11						.44						.77
12	2.86		.14	.08			2.17		1.16	.48		
13		.34			.11			1.35				
14												
15			.16	.07			1.87				.89	1.83
16		.27				.16	.54					
17								.71		.64	1.09	
18		.28	.11		.06	.22	.68	1.94	.67	.80	1.25	
19												1.03
20											.62	
21										.39		
22			.10	.05		1.27		1.23			.72	
23		.25				.18						.27
24							3.55			.37		
25				.05							.60	1.25
26			.16			1.13		2.11			.34	
27			.09		.14							1.08
28							2.55			.24		.55
29		.50			.06						.20	
30		.15	.13			1.09						
31		.37						2.38				

1926-27

## QUANTITIES OF SUSPENDED SEDIMENT

29

TABLE 8.—*Mean daily concentration of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1925, to Sept. 30, 1929—Continued*

1927-28

Day	Octo- ber	No- vem- ber	Decem- ber	Janu- ary	Febru- ary	March	April	May	June	July	August	Sep- tem- ber
1				0.05								1.18
2				.09								1.75
3								2.11	1.28		0.72	1.02
4					0.06		1.22	2.92	1.10			.71
5	0.86	0.77	0.19	.07					.89	.41	.65	.93
6			.17		.12	0.36			1.02	.50		.76
7				.05		.56	.98	2.58		.29	1.13	.70
8	.49	1.19	.16		.38			.92	2.26	.85		.69
9					.07		.53	.67	1.99		.48	.45
10					.13		.75	.64	1.74	.77		.34
11							.60	.68	1.49		.17	.38
12	.42	.62	.08	.07	.49		.62	.52		.63		.24
13							.47			.77	.15	.20
14					.07	.23			1.72		.40	.18
15	.32	.38	.08				.78		1.45	.67	.17	.44
16						.19		.35	1.93	.45	.17	.26
17			.24	.11			.79	.31	1.24		.50	.62
18	.25				.10			.30	1.52	.57		.16
19				.09		.14	.67	.31	1.28		.57	.10
20			.27		.21			.24	1.13	.41	.14	.41
21	.21				.09			.28	1.12	.56		.32
22		.28	.04	.11			.55	.36	.97	.48	.63	.09
23					.12			.41		.41		.35
24		.22	.03	.09			.49		.97		.53	.06
25	.16							.56			.67	.07
26			.17					.60		.32		.57
27			.05	.05			.72			.38	.70	.50
28	.16	.16			.14			.72	1.03			.05
29			.08	.05				.90	.88	.48	.40	1.90
30			.16				1.57			.54		1.88
31	.17			.05							1.40	

1928-29

1	0.07	0.65	0.16	0.07	0.04	0.12	0.95	0.75	1.30	0.27	8.85	0.98
2	.19							.62	.88	.30	5.17	2.02
3	.16		.18					.61	1.04	.39	7.53	
4		2.28		.06	.05	.13	1.74	.68	.82	.30	5.70	2.80
5	.12		.13					.74	.88	.40	7.94	3.86
6		1.02		.05	.18	.09	4.20	.77	1.01	.23		5.64
7			.14					3.26	.87	1.08	.20	6.89
8	.55	.81		.04	.14	.22		3.31	.96	.92	.21	4.59
9			.12					2.72	1.09	.99	.22	4.87
10	.62	.61		.04	.15			2.07	1.18	1.15	.20	4.38
11			.11			2.94	1.70	1.68	1.03	1.28	3.82	3.81
12	.21	.32		.02	.11		1.50	1.53	.91	.41	4.40	3.34
13			.10			3.28	1.30			.87	.60	5.30
14	1.86	.28		.06	.05		1.26		.69	.23	9.28	1.62
15			.09			3.66	.96	1.27	.84	.18	5.66	1.66
16	5.76	.27		.03	.06		.80	1.48	.73	.20	3.21	1.32
17			.07			1.75	.79	1.46	.68	.19	1.91	1.39
18	3.01	.25		.04	.07			.77	1.38	.64	.24	1.23
19			.06			1.26	.89	1.88	.62	.30	.88	.65
20	1.96	.27		.06	.07		1.37	1.69	.77		.64	.61
21			.05			.92	2.05	1.26	.68	.29	.69	1.09
22	1.58	.23		.08	.12		1.98	1.98	.86	.36	.49	6.35
23						.61	1.88	1.45	.57	.31	.48	8.07
24	1.12	.23		.07				1.77	1.95	.40	2.52	4.81
25			.02			.11	.80	1.65	1.98	.52	.64	8.90
26	.83	.17		.08				1.61	1.40	.56	.50	6.87
27			.01		.08	1.19	1.30	1.30		.46	.73	4.24
28	.52	.14		.06				1.20		.40	7.49	3.99
29			.02			.95	.96	2.12	.52	3.12	.40	
30	.44			.05				.83	1.34	.29	10.9	4.22
31			.04			.62		1.33		8.03	.51	2.03

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941*

Day	1929							
	October			November			December	
	Mean discharge (second-feet)	Suspended sediment	Mean percent	Mean discharge (second-feet)	Suspended sediment	Mean percent	Mean discharge (second-feet)	Suspended sediment
1	22,900	1.57	970,000	10,800	0.20	58,000	7,230	0.07
2	21,600	1.06	618,000	10,800	.19	55,000	7,410	.07
3	20,200	—	539,000	10,800	—	46,600	7,780	14,700
4	18,900	1.00	510,000	10,800	.16	46,600	8,020	.08
5	17,700	.68	325,000	10,800	.17	49,500	8,340	.11
6	16,500	.58	258,000	10,700	.16	46,200	8,680	.11
7	15,800	.51	217,000	10,400	.19	53,300	8,840	.14
8	15,200	.45	184,000	10,300	.16	44,400	8,740	.13
9	15,100	.42	171,000	10,600	.18	51,500	8,360	.12
10	14,800	.36	144,000	10,700	—	48,600	8,280	.08
11	14,500	.37	145,000	10,600	.17	48,600	8,130	.12
12	14,400	.31	120,000	10,800	—	37,900	8,130	.15
13	14,900	.34	137,000	10,800	.13	37,900	8,120	.12
14	16,100	.34	148,000	10,700	—	37,500	8,170	.08
15	16,700	.41	185,000	10,500	.14	39,600	8,150	.14
16	16,300	.39	171,000	10,200	—	35,800	8,390	—
17	15,800	.43	181,000	10,000	.13	35,100	8,450	.04
18	16,800	.40	181,000	9,760	—	34,200	8,550	.12
19	16,900	1.37	624,000	9,320	.16	40,200	8,470	—
20	16,900	1.02	485,000	9,930	—	26,500	8,330	—
21	15,400	.73	303,000	8,950	.11	26,500	8,180	—
22	14,600	.70	276,000	9,220	.10	24,900	7,890	—
23	14,000	.58	219,000	9,350	.13	32,800	7,590	—
24	13,300	.69	248,000	9,320	—	32,000	7,160	—
25	12,700	.38	130,000	9,120	.13	32,000	6,450	—
26	12,400	.39	130,000	8,890	.11	26,400	5,960	—
27	11,900	—	83,400	8,330	.06	13,500	5,580	—
28	11,600	.26	81,300	7,890	—	12,800	4,890	—
29	11,300	.22	67,000	7,480	.06	12,100	4,540	—
30	11,200	.20	60,400	7,300	.07	13,800	4,370	—
31	10,900	.17	50,000	—	—	—	4,660	—
Monthly load (tons)		7,941,000	1,100,000					

## 1930

	January			February			March		
	Mean discharge (second-feet)	Suspended sediment	Mean percent	Mean discharge (second-feet)	Suspended sediment	Mean percent	Mean discharge (second-feet)	Suspended sediment	Mean percent
1	4,900	—	—	4,710	—	5,400	13,400	—	216,000
2	5,080	—	6,200	5,390	0.05	7,280	12,300	0.25	82,900
3	4,930	—	—	6,480	—	10,800	11,500	.19	58,900
4	4,880	0.04	5,260	7,200	.09	17,500	10,800	—	53,900
5	4,920	—	—	7,200	—	13,500	10,100	.20	54,500
6	5,340	—	6,500	6,600	.07	12,500	9,540	—	48,500
7	5,930	.04	6,390	6,380	—	13,500	9,200	.20	49,600
8	6,240	—	6,700	6,380	.10	17,290	9,030	.22	53,600
9	6,360	—	6,850	6,580	—	27,000	8,760	—	48,500
10	6,440	—	6,700	6,810	—	14,000	8,710	.21	49,300
11	6,700	.04	7,230	7,000	.07	13,200	8,950	.21	50,700
12	6,440	—	6,700	7,120	—	13,500	9,030	.22	53,600
13	6,090	—	6,580	7,280	.11	21,600	8,810	.20	47,500
14	5,780	—	5,400	7,580	—	21,500	8,490	.20	45,800
15	5,610	.03	4,530	7,890	.10	21,300	8,250	.16	35,600
16	5,550	—	—	8,440	—	27,000	8,170	.17	37,500
17	5,690	—	—	9,150	.17	42,000	8,280	.16	35,700
18	5,850	—	—	9,440	—	40,500	8,290	.20	44,700
19	6,030	—	—	9,300	.15	37,600	8,550	.20	46,100
20	5,640	—	—	9,280	—	40,500	8,890	.42	101,000
21	5,340	—	—	9,280	.25	62,600	9,810	.38	101,000
22	4,860	—	—	9,540	—	64,700	10,100	.40	109,000
23	4,160	—	—	10,200	—	65,000	10,100	—	113,000
24	3,860	—	—	10,700	.24	69,300	10,300	.46	125,000
25	3,260	—	—	11,500	—	80,900	11,400	.58	177,000
26	3,250	—	—	16,500	.64	285,000	11,400	.73	224,000
27	3,200	—	—	14,600	—	324,000	11,500	.68	211,000
28	4,430	—	—	13,800	1.33	495,000	11,500	.62	192,000
29	4,600	—	—	—	—	—	11,400	.68	209,000
30	4,420	—	—	—	—	—	11,300	.68	207,000
31	4,360	—	—	—	—	—	11,200	.62	187,000
Monthly load (tons)		—	—	1,864,000	—	—	3,069,000	—	—

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1930

Day	April			May			June		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	10,900	0.55	162,000	44,100	1.10	1,310,000	54,800	1.09	1,610,000
2	10,600	.49	140,000	42,200	1.07	1,220,000	65,900	1.28	2,280,000
3	9,910	.46	123,000	39,300	.80	848,000	69,000	1.21	2,250,000
4	9,500		80,000	36,900	.85	846,000	67,400	1.17	2,130,000
5	9,500		97,400	37,500	.75	759,000	60,500	1.20	1,960,000
6	9,540	.29	74,600	40,900	.86	949,000	54,800	.84	1,240,000
7	9,440	.32	81,500	41,400	.79	882,000	49,800	.87	1,170,000
8	10,300	.49	136,000	38,500	.64	665,000	46,200	.67	835,000
9	11,300	.68	207,000	36,000	.58	563,000	46,200		809,000
10	13,800	.74	275,000	33,700	.50	454,000	49,800	.61	819,000
11	21,000	1.97	1,120,000	31,300	.47	397,000	53,600	.84	1,210,000
12	30,100	1.99	1,620,000	29,600	.40	319,000	55,600	.66	990,000
13	39,100	2.94	3,100,000	27,600	.37	275,000	55,500	.54	808,000
14	40,200	2.63	2,850,000	25,800	.44	306,000	55,200	.74	1,100,000
15	39,100	2.78	2,930,000	24,200	.43	281,000	57,900	.69	1,080,000
16	40,100	3.38	3,660,000	22,800	.42	258,000	61,600	.68	1,130,000
17	40,300	1.71	1,860,000	21,500	.30	174,000	61,400	.65	1,080,000
18	41,100	1.47	1,630,000	20,600	.30	167,000	58,500	.57	899,000
19	39,600	1.86	1,990,000	21,400	.29	167,000	55,700	.64	961,000
20	36,900	2.09	2,080,000	24,400	.54	355,000	53,800	.45	653,000
21	33,100	.84	750,000	25,800	.62	431,000	51,600	.46	640,000
22	30,100	.89	723,000	25,400	.58	397,000	50,600	.54	737,000
23	28,600	1.08	833,000	24,900	.50	336,000	47,500	.53	679,000
24	29,300	.69	545,000	25,400	.45	308,000	44,700	.81	976,000
25	34,400	1.06	983,000	32,100	.74	641,000	43,400	.48	562,000
26	39,200	1.22	1,290,000	37,000	.89	888,000	42,500	.44	504,000
27	42,100	1.04	1,180,000	34,300	.78	722,000	40,000	.47	507,000
28	44,400	1.27	1,520,000	34,200	.78	719,000	36,000	.43	417,000
29	44,600	1.26	1,520,000	38,000	.63	646,000	32,200	.39	339,000
30	44,000	.87	1,030,000	42,600	.67	770,000	29,200	.30	236,000
31				48,300	1.03	1,340,000			
Monthly load (tons)			34,590,000			18,390,000			30,610,000

1930

	July			August			September		
1	26,600	0.32	230,000	17,500	2.01	963,000	10,200	0.46	127,000
2	24,900	.23	154,000	18,100	3.03	1,480,000	9,680		113,000
3	23,200	.32	200,000	17,800	2.41	1,160,000	9,350	.42	106,000
4	21,500	.20	116,000	19,000	2.83	1,450,000	9,370	.36	91,000
5	19,860	.20	106,000	23,000	4.47	2,770,000	10,200	.31	85,300
6	18,000	.22	107,000	24,100	3.40	2,210,000	9,830	.29	76,900
7	16,500	.18	80,100	28,100	3.36	2,550,000	10,000	.29	78,200
8	15,300	.20	82,500	21,400	3.10	1,790,000	13,500	.88	320,000
9	14,600	.20	78,800	27,300	6.64	4,890,000	14,500	1.83	716,000
10	14,100	.19	72,300	30,000	8.45	6,840,000	14,000	1.88	710,000
11	14,000	.27	102,000	44,400	10.3	12,300,000	13,300	1.48	531,000
12	13,200	.25	89,000	54,800	10.7	15,800,000	11,200	2.55	770,000
13	15,700	2.25	953,000	47,900	6.89	8,910,000	9,860	1.19	316,000
14	24,400	5.33	3,510,000	43,300	6.41	7,490,000	9,050	.93	227,000
15	19,500	4.19	2,200,000	35,900	8.64	8,360,000	8,470	1.08	247,000
16	16,700	3.28	1,480,000	34,700	5.46	5,110,000	8,090	.71	155,000
17	16,900	2.20	1,000,000	29,300	3.98	3,150,000	7,760	.68	142,000
18	15,400	2.32	964,000	27,600	3.31	2,460,000	7,400	.44	87,800
19	16,900	1.81	825,000	29,500	3.48	2,770,000	7,120	.46	88,300
20	25,200	2.76	1,880,000	32,900	3.09	2,740,000	6,980	.39	73,400
21	22,800		1,620,000	30,000	2.72	2,200,000	6,840	.29	53,500
22	21,100	2.93	1,670,000	25,400	2.36	1,620,000	6,550	.22	38,900
23	19,600	2.38	1,260,000	22,200	2.33	1,400,000	6,320	.17	29,000
24	21,600	3.36	1,960,000	20,100	1.77	960,000	6,170	.16	26,600
25	21,900	2.81	1,660,000	18,200	1.49	731,000	6,070	.14	22,900
26	19,700	2.34	1,240,000	16,400	1.21	535,000	6,160	.13	21,600
27	17,900	2.16	1,040,000	14,600	1.03	406,000	6,830	.15	27,600
28	16,500	1.42	632,000	13,500	.91	331,000	6,860	.15	27,800
29	15,600	1.18	496,000	12,500	.60	202,000	6,720	.14	25,400
30	15,400	1.12	465,000	12,100	.60	196,000	9,030	.33	80,400
31	18,100	1.38	674,000	11,200	.45	136,000			
Monthly load (tons)			26,950,000			103,900,000			5,415,000

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1930

Day	October			November			December		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	9,830	.53	141,000	8,210	.22	48,700	4,910	1.09	11,900
2	9,540	1.31	337,000	8,040	.24	52,100	5,140	.10	13,900
3	8,920	.89	214,000	8,060	.19	41,300	5,840	1.15	23,600
4	10,600	.66	189,000	7,950	.18	38,600	5,930	.40	64,000
5	10,300	.88	244,000	7,770	.16	33,500	5,950	.28	44,900
6	10,800	.94	274,000	7,580	.16	32,700	5,900	1.22	35,000
7	10,000	.80	216,000	7,530	.15	30,500	5,730	1.18	27,800
8	9,710	.91	238,000	7,410	.16	32,000	5,510	.19	28,200
9	9,220	.79	196,000	7,420	.14	28,000	5,560	1.13	19,500
10	8,850	.73	174,000	7,470	.19	38,300	5,600	.11	16,600
11	8,550	.75	173,000	7,420	.15	30,000	5,550	1.10	15,000
12	8,530	.66	152,000	7,300	.16	31,500	5,590	1.10	15,100
13	8,550	.49	113,000	7,180	.15	29,000	5,690	.09	13,800
14	8,810	.48	114,000	7,160	.12	23,200	5,690	1.10	15,300
15	8,820	.44	105,000	7,020	.27	51,100	5,680	.11	16,900
16	8,730	.35	82,400	6,990	.10	18,900	5,650	1.09	13,700
17	9,030	.30	73,100	7,100	.10	19,100	5,700	.08	12,300
18	9,340	.38	95,700	7,280	.14	27,500	5,610	1.08	12,100
19	9,120	.36	88,500	9,690	.43	112,000	5,570	1.08	12,000
20	9,060	.30	73,300	8,830	.68	162,000	5,470	.09	13,300
21	9,100	.33	81,000	8,190	.45	99,400	5,310	1.08	11,500
22	9,330	.32	80,500	8,430	.37	84,100	5,200	.07	9,820
23	9,480	.32	81,800	8,190	1.20	44,200	4,850	1.06	7,850
24	9,530	.32	82,300	8,010	.25	54,000	4,510	.06	7,310
25	9,380	.30	75,900	7,880	.28	59,500	3,980	1.06	6,450
26	9,160	.32	79,000	7,520	1.20	40,600	3,680	.05	4,960
27	8,970	.28	67,700	6,820	1.17	31,300	3,780	1.05	5,100
28	8,730	.23	54,200	5,950	.17	27,300	3,580	1.04	3,860
29	8,570	.21	48,500	5,390	1.10	14,500	3,480	.04	3,750
30	8,430	.18	40,900	4,990	.09	12,100	3,450	1.04	3,720
31	8,300	.18	40,300				3,600	.04	3,880
Monthly load (tons)		4,025,000				1,347,000			493,100

1931

	January			February			March		
	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day
1	3,580	1.04	3,860	5,420	1.10	14,600	6,230	1.14	23,500
2	3,550	.04	3,830	5,600	.10	15,100	6,160	.13	21,600
3	3,660	1.04	3,940	5,840	1.15	23,600	6,050	.11	18,000
4	3,860	1.04	4,150	6,770	.22	40,200	6,050	1.10	16,300
5	4,070	.04	4,400	6,780	.20	36,600	6,110	.11	18,100
6	4,080	1.05	5,500	6,890	.19	35,300	6,160	1.12	19,900
7	4,200	.07	7,930	6,840	.20	36,900	6,190	.12	20,000
8	4,210	1.06	6,820	6,790	1.19	34,800	6,160	1.10	18,600
9	4,420	.06	7,150	6,960	.18	33,800	6,250	.10	16,900
10	4,620	1.05	6,230	6,980	.19	35,800	6,500	1.12	21,000
11	4,670	.05	6,150	6,790	.15	27,500	6,740	.24	43,600
12	4,530	1.04	4,880	6,700	.16	28,900	6,810	1.22	40,400
13	4,500	1.04	4,850	6,920	.16	29,900	6,650	.20	35,900
14	4,490	.03	3,560	6,990	.20	37,700	6,470	1.17	29,700
15	4,560	1.03	3,690	7,080	.28	53,500	6,130	1.14	23,200
16	4,790	1.04	5,180	7,500	1.25	50,600	6,150	.13	21,600
17	4,870	.04	5,260	8,100	.26	56,800	6,530	.16	28,200
18	4,980	1.04	5,370	9,020	1.26	307,000	6,950	.24	45,000
19	4,900	.04	5,290	8,700	1.03	242,000	7,650	.36	74,300
20	4,830	1.03	3,910	8,070	.74	161,000	7,900	.39	83,100
21	4,860	.03	3,940	7,560	.67	137,000	8,120	.52	114,000
22	4,740	1.03	3,830	7,020	.54	102,000	8,380	.68	154,000
23	4,690	1.03	3,800	6,750	.38	69,200	8,380	.62	140,000
24	4,760	.03	3,860	6,570	.26	46,100	8,460	.52	119,000
25	4,980	1.03	4,020	6,530	1.20	35,200	8,540	.48	111,000
26	4,880	.07	9,220	6,540	.19	33,500	8,690	.64	127,000
27	4,920	1.07	9,280	6,330	.19	32,400	8,970	.57	138,000
28	4,950	.08	10,700	6,260	.17	28,700	9,360	.60	151,000
29	4,920	1.08	10,600				9,740	.66	173,000
30	5,080	.10	13,700				9,760	.60	158,000
31	5,220	1.10	14,100				9,550	.65	167,000
Monthly load (tons)		189,000				1,786,000			2,169,000

<sup>1</sup> Estimated.

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1931

Day	April			May			June		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	9,160	0.65	161,000	13,300	0.85	305,000	26,200	0.95	671,000
2	8,640	1.50	117,000	13,500	.80	291,000	25,100	.80	542,000
3	7,960	1.40	85,900	13,000	.95	333,000	24,400	.85	559,000
4	7,520	.38	77,100	12,600	.77	262,000	24,900	.68	457,000
5	7,000	1.33	62,300	12,800	.82	283,000	26,800	.97	701,000
6	6,650	.31	55,600	13,000	.88	309,000	28,700	.94	728,000
7	6,910	1.30	55,900	13,400	.72	260,000	29,800	.84	675,000
8	7,050	.31	59,000	14,300	.96	370,000	30,100	.86	698,000
9	7,170	1.30	58,000	15,900	.99	425,000	29,300	.68	537,000
10	7,200	1.29	56,300	16,000	.93	401,000	30,500	.64	444,000
11	7,100	.27	51,700	15,800	.83	354,000	31,900	.86	740,000
12	7,440	1.28	56,200	17,700	.96	458,000	31,600	.90	767,000
13	7,830	.30	63,400	18,300	.89	439,000	29,800	.70	563,000
14	7,840	1.30	63,400	17,100	.93	429,000	27,500	.71	527,000
15	7,860	.36	76,300	16,000	.76	328,000	25,400	.62	425,000
16	7,920	1.43	91,900	15,600	.72	303,000	24,000	.64	414,000
17	8,510	1.50	115,000	14,900	.77	309,000	23,500	.67	425,000
18	9,640	.51	133,000	14,700	.71	281,000	23,100	.50	312,000
19	10,500	.73	207,000	15,900	.76	326,000	23,100	.56	349,000
20	10,900	.75	220,000	21,400	1.16	670,000	23,600	.70	446,000
21	11,600	.74	232,000	29,000	1.51	1,180,000	23,600	.54	344,000
22	11,400	.86	264,000	33,800	1.68	1,530,000	22,000	.47	279,000
23	11,200	.72	217,000	31,300	1.83	1,540,000	20,200	.32	174,000
24	11,900	.66	212,000	27,800	1.45	1,000,000	18,600	.38	191,000
25	12,800	.81	280,000	24,400	1.14	750,000	17,300	.34	159,000
26	13,000	.70	245,000	21,000	1.07	606,000	15,900	.34	146,000
27	13,600	.70	257,000	19,000	.87	446,000	14,500	.29	113,000
28	13,800	.74	275,000	19,100	.90	464,000	13,700	.24	88,700
29	14,800	.92	367,000	23,200	1.03	644,000	13,300	.29	104,000
30	15,100	.80	326,000	26,700	1.01	727,000	12,900	.24	83,500
31				26,900	.98	711,000			
Monthly load (tons)			4,541,000			16,820,000			12,660,000

1931

	July			August			September		
	July	August	September	July	August	September	July	August	September
1	12,600	10.10	34,000	5,640	6.35	966,000	3,220	10.65	56,400
2	12,900	.23	80,000	8,400	3.14	711,000	3,110	.47	39,400
3	13,100	.24	84,800	7,830	5.06	1,070,000	3,200	.36	31,100
4	13,600	.27	99,000	7,860	3.88	823,000	2,930	.67	52,900
5	14,900	.42	169,000	8,860	3.48	832,000	2,720	.67	49,100
6	17,700	.88	420,000	7,470	4.75	957,000	2,780	.40	30,000
7	15,900	.93	399,000	6,930	3.40	635,000	3,120	.28	23,600
8	14,500	1.12	438,000	8,090	5.39	1,180,000	2,930	.20	15,300
9	12,700	.90	308,000	7,380	4.54	904,000	2,680	.22	15,900
10	11,600	.63	197,000	6,180	3.30	551,000	2,580	.15	10,400
11	10,400	.40	112,000	6,500	2.06	361,000	2,870	.21	16,300
12	9,290	.37	92,700	7,290	3.58	704,000	2,700	1.24	90,300
13	8,340	.31	69,700	5,980	2.50	403,000	2,560	.73	50,400
14	7,460	.22	44,300	5,380	2.02	293,000	2,630	.53	37,600
15	6,760	.16	29,200	5,570	1.28	192,000	2,840	.39	29,900
16	6,180	.13	21,700	5,270	1.00	142,000	3,140	.87	73,700
17	5,770	.11	17,100	4,960	.88	118,000	2,750	1.83	136,000
18	5,290	.09	12,800	4,720	1.67	213,000	3,440	.77	71,400
19	4,910	.11	14,600	4,140	1.95	218,000	4,610	1.08	134,000
20	5,200	.13	18,200	3,880	1.14	119,000	3,290	1.69	150,000
21	4,750	.61	78,200	3,640	.83	81,500	4,920	2.61	346,000
22	5,040	1.23	167,000	3,350	.78	70,500	5,460	2.25	331,000
23	4,690	2.86	362,000	3,180	.62	53,200	5,630	2.85	433,000
24	3,980	1.22	131,000	3,070	.46	38,100	5,810	3.58	561,000
25	3,600	.70	68,000	3,460	.86	80,300	8,710	2.70	634,000
26	3,480	1.42	39,400	3,400	1.87	171,000	12,400	4.01	1,340,000
27	3,620	.32	31,200	3,190	1.42	122,000	15,400	3.54	1,470,000
28	3,600	.27	26,200	2,940	.83	65,800	12,600	3.32	1,130,000
29	3,680	.75	74,400	2,900	.59	46,100	10,900	2.34	688,000
30	3,350	2.25	203,000	2,940	.55	43,600	8,850	2.48	592,000
31	5,160	.70	97,400	3,240	.32	28,000			
Monthly load (tons)			3,939,000			12,190,000			8,639,000

<sup>1</sup> Estimated.

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1931

Day	October			November			December		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	7,910	2.27	484,000	5,880	1.40	63,400	3,710	1.10	10,000
2	7,470	1.25	504,000	5,760	.36	55,900	4,160	1.12	13,500
3	7,730	1.24	500,000	5,820	.35	54,900	4,740	1.15	19,200
4	15,300	2.90	1,200,000	6,090	.31	50,900	4,600	.22	27,300
5	15,900	6.17	2,650,000	6,010	.28	45,400	4,610	1.16	19,900
6	18,200	5.24	2,570,000	5,810	.25	39,200	4,430	1.12	14,300
7	13,900	2.98	1,120,000	5,810	.22	34,500	4,010	.12	13,000
8	10,800	2.88	839,000	5,740	1.21	32,500	3,530	1.10	9,520
9	9,230	1.23	573,000	5,690	.21	32,200	3,720	.08	8,040
10	8,390	1.79	405,000	6,030	1.23	37,400	3,910	1.08	8,440
11	7,670	1.54	319,000	6,160	.26	43,200	4,130	1.08	8,900
12	7,340	1.17	232,000	6,520	.35	61,500	4,000	.09	9,710
13	7,970	1.12	241,000	7,960	.35	75,100	5,550	1.15	22,400
14	7,440	1.11	223,000	9,050	3.25	872,000	5,620	.23	34,900
15	6,860	.81	150,000	10,500	2.01	569,000	5,170	1.27	37,700
16	6,410	1.07	185,000	10,300	2.28	633,000	4,950	.17	22,700
17	6,290	.85	144,000	8,670	1.68	393,000	4,560	1.12	14,800
18	6,010	.60	97,300	7,310	1.30	256,000	4,080	1.11	12,100
19	5,800	.36	56,300	6,830	.98	181,000	3,150	.06	5,100
20	6,010	.46	74,600	6,650	.77	138,000	2,520	1.05	3,400
21	7,500	.39	78,900	6,500	.81	142,000	2,160	1.05	2,910
22	13,300	1.78	638,000	6,680	1.75	135,000	2,560	.07	4,830
23	11,200	2.38	719,000	6,440	.50	86,800	2,850	.06	4,610
24	9,230	2.14	533,000	6,310	.30	51,100	3,430	.06	5,560
25	7,800	1.71	360,000	6,290	1.28	47,500	4,740	1.07	8,950
26	6,820	1.79	329,000	6,100	1.26	42,800	4,900	.18	23,800
27	6,550	1.20	212,000	5,600	1.25	37,800	5,330	1.21	30,200
28	6,480	1.19	208,000	4,860	.24	31,400	6,200	1.24	40,100
29	6,170	1.03	171,000	4,390	1.18	21,300	6,550	.26	45,900
30	6,030	.61	99,200	4,020	.12	13,000	6,900	1.28	51,900
31	5,920	.62	99,000				7,010	.30	56,700
Monthly load (tons)			16,010,000				4,277,000		590,400

1932

	January			February			March		
	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day
1	7,160	1.24	46,300	4,170	0.10	11,200	12,100	1.28	418,000
2	6,170	1.26	43,300	4,190	1.08	9,040	13,300	1.30	466,000
3	5,680	1.22	33,700	4,380	1.10	11,800	15,200	2.18	894,000
4	5,410	.18	26,300	4,830	1.14	18,200	16,100	2.20	955,000
5	5,230	1.12	16,900	5,810	1.30	47,000	16,300	2.36	1,040,000
6	5,190	.15	21,000	6,450	.57	99,100	14,400	2.04	792,000
7	4,970	1.10	13,400	7,120	.61	117,000	12,200	1.72	566,000
8	4,620	1.08	9,980	6,720	1.00	181,000	10,600	1.24	354,000
9	4,450	.12	14,400	9,310	1.44	362,000	9,670	.98	256,000
10	4,770	1.11	14,200	23,600	4.47	2,850,000	9,580	.95	245,000
11	4,730	.11	14,000	45,900	8.12	10,100,000	10,900	.99	291,000
12	5,040	1.13	17,700	33,000	5.68	5,060,000	12,500	1.13	381,000
13	5,130	.15	20,800	23,800	4.95	3,180,000	13,300	1.23	441,000
14	5,410	1.13	19,000	22,700	3.48	2,130,000	12,800	1.04	359,000
15	5,450	1.14	20,600	17,300	2.35	1,100,000	11,500	1.06	329,000
16	5,380	.14	20,300	14,200	1.82	697,000	10,700	.87	251,000
17	5,270	1.13	18,500	12,100	1.44	470,000	10,200	.71	195,000
18	5,010	.15	21,900	11,200	1.07	323,000	10,100	.69	188,000
19	4,910	1.13	17,200	10,900	1.00	294,000	10,700	.71	205,000
20	4,900	.10	13,200	10,600	.94	269,000	11,000	.80	237,000
21	4,830	1.10	13,000	9,700	.81	212,000	12,500	1.03	347,000
22	4,610	1.10	12,400	10,700	.91	263,000	14,400	1.46	567,000
23	4,600	.10	12,400	10,300	.78	217,000	15,900	1.50	643,000
24	4,680	1.10	12,600	10,200	.93	256,000	17,300	1.78	831,000
25	4,450	.10	12,000	9,800	.76	201,000	19,200	2.42	1,250,000
26	4,220	1.08	9,120	9,650	.85	221,000	18,600	1.85	928,000
27	4,320	.08	9,330	9,670	.85	222,000	17,700	1.55	740,000
28	4,470	1.10	12,100	9,650	1.84	219,000	18,400	1.76	873,000
29	4,490	1.10	12,100	10,600	.92	263,000	17,900	1.90	917,000
30	4,700	.18	22,800				16,700	1.49	671,000
31	4,360	1.08	9,410				15,800	1.49	635,000
Monthly load (tons)			559,000				29,400,000		17,260,000

<sup>1</sup> Estimated.

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1932

Day	April			May			June		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	15,700	1.37	580,000	29,700	1.04	833,000	66,900	0.89	1,610,000
2	15,300	1.16	479,000	27,000	.83	604,000	66,800	.79	1,420,000
3	14,300	1.10	424,000	27,200	.92	675,000	62,700	.75	1,270,000
4	15,900	1.10	472,000	29,300	.80	632,000	58,600	.80	1,260,000
5	18,500	1.41	704,000	32,000	.98	846,000	57,200	.64	987,000
6	20,400	1.75	963,000	37,100	1.14	1,140,000	56,100	.56	847,000
7	23,300	2.26	1,420,000	43,500	1.48	1,740,000	55,200	.57	849,000
8	29,200	2.63	2,070,000	45,900	1.19	1,470,000	54,300	.63	923,000
9	31,400	1.20	1,690,000	46,100	1.30	1,620,000	52,100	.62	871,000
10	29,100	2.52	1,980,000	44,300	1.24	1,480,000	49,900	.51	686,000
11	26,700	1.97	1,420,000	44,000	1.04	1,230,000	50,200	.53	718,000
12	26,300	1.94	1,380,000	45,200	1.21	1,480,000	51,800	.46	643,000
13	24,800	1.73	1,160,000	47,700	1.02	1,310,000	53,600	1.40	578,000
14	23,800	1.72	1,100,000	52,100	1.21	1,700,000	54,000	.51	743,000
15	24,800	1.77	1,180,000	58,800	1.08	1,710,000	54,900	.46	681,000
16	27,600	1.53	1,140,000	68,000	1.16	2,130,000	57,700	.43	669,000
17	32,100	1.56	1,350,000	74,400	1.27	2,550,000	62,700	.54	913,000
18	32,400	1.82	1,600,000	79,700	1.66	3,570,000	64,000	.56	967,000
19	34,500	1.28	1,190,000	83,500	1.42	3,200,000	67,000	.61	1,100,000
20	38,200	1.71	1,760,000	85,900	1.49	3,450,000	67,900	.43	787,000
21	39,200	1.65	1,740,000	91,800	1.35	3,340,000	66,500	.74	1,330,000
22	38,600	1.66	1,730,000	94,000	1.45	3,680,000	63,000	.55	935,000
23	40,100	1.64	1,770,000	91,600	1.26	3,110,000	62,100	.62	1,040,000
24	40,500	1.45	1,580,000	90,300	1.28	3,120,000	63,100	.48	817,000
25	39,400	1.69	1,800,000	97,500	1.41	3,710,000	63,400	.39	667,000
26	36,700	1.38	1,370,000	101,000	.76	2,070,000	65,900	.55	978,000
27	33,900	1.70	1,550,000	99,100	1.13	3,020,000	67,800	.43	786,000
28	32,000	1.04	898,000	95,900	1.13	2,920,000	69,700	.41	771,000
29	32,300	1.12	976,000	89,400	1.04	2,510,000	71,200	.45	864,000
30	32,100	.98	848,000	78,400	.95	2,010,000	68,600	.50	926,000
31				70,700	1.90	1,720,000			
	Monthly load (tons)			38,320,000		64,580,000			27,640,000

1932

	July			August			September		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	65,300	0.39	687,000	18,600	0.96	482,000	31,200	5.82	4,900,000
2	62,200	.49	822,000	16,200	.99	433,000	20,600	1.40	2,220,000
3	59,700	.43	692,000	18,100	1.80	879,000	17,300	3.37	1,570,000
4	57,200	.42	643,000	20,100	1.32	716,000	14,800	2.70	1,080,000
5	54,500	.41	603,000	19,300	1.00	521,000	12,800	2.17	749,000
6	50,500	.54	735,000	17,400	.72	338,000	11,500	1.31	406,000
7	47,200	.35	446,000	16,500	1.64	285,000	10,800	.92	268,000
8	44,800	.41	495,000	15,000	.59	239,000	10,000	.91	245,000
9	41,200	.33	367,000	13,500	.39	142,000	9,380	1.07	270,000
10	36,900	.29	289,000	13,000	.42	147,000	8,920	.80	192,000
11	33,900	.28	256,000	11,800	.52	165,000	8,380	1.80	181,000
12	31,100	.27	226,000	10,700	1.40	115,000	7,870	.60	127,000
13	31,000	.28	234,000	9,940	.29	77,800	7,360	1.44	90,000
14	39,000	1.67	1,760,000	9,100	1.35	85,900	6,790	.29	53,100
15	34,100	1.55	1,420,000	8,440	.36	81,900	6,480	1.23	40,200
16	33,400	1.40	1,260,000	7,940	1.23	49,200	6,170	.20	33,300
17	30,800	1.20	997,000	7,500	.16	32,400	5,940	.23	36,800
18	27,900	.97	730,000	7,150	1.11	21,200	5,630	1.22	33,400
19	25,500	.79	543,000	6,750	.10	18,200	5,430	.24	35,100
20	24,500	.64	423,000	7,000	1.08	15,100	5,200	1.18	25,200
21	24,000	.56	362,000	7,620	.09	18,500	5,090	.16	22,000
22	23,900	.44	284,000	8,650	.35	81,700	4,960	1.12	16,000
23	23,300	.44	276,000	16,100	.99	430,000	4,810	1.12	15,600
24	21,600	.47	274,000	17,200	2.69	1,250,000	4,690	.18	22,800
25	19,500	.26	137,000	13,600	4.94	1,810,000	5,120	1.15	20,700
26	17,900	.28	135,000	11,400	3.76	1,160,000	6,240	.15	25,200
27	16,700	.27	122,000	11,500	2.15	667,000	9,000	.62	150,000
28	15,500	.22	92,000	18,600	2.13	1,070,000	6,970	.69	130,000
29	14,800	.16	63,900	32,100	5.95	5,150,000	6,280	1.02	173,000
30	15,700	.20	84,700	49,800	7.49	10,100,000	6,870	1.63	302,000
31	18,300	1.55	271,000	43,900	5.93	7,020,000			
	Monthly load (tons)			15,730,000		33,600,000			13,430,000

<sup>1</sup> Estimated.

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1932

Day	October			November			December		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	6,660	1.24	223,000	6,900	1.18	33,500	6,310	1.15	25,500
2	5,960	1.11	178,000	6,810	.17	31,200	6,250	.19	32,000
3	5,830	1.03	162,000	6,900	1.17	31,600	6,300	.17	28,900
4	5,540	.73	109,000	6,970	.17	32,000	6,460	1.17	29,600
5	5,320	.58	86,400	7,020	.15	28,400	6,560	.17	30,100
6	5,410	.39	56,900	7,010	1.14	26,500	6,730	.14	25,400
7	5,180	.34	47,500	6,860	.13	24,100	6,550	.17	30,000
8	5,140	.26	36,000	6,650	.13	23,300	6,440	.11	19,100
9	5,080	.22	30,200	6,670	.13	23,400	6,390	.11	19,000
10	5,050	.17	23,100	6,770	.11	20,100	6,170	.11	18,300
11	4,970	.14	18,800	6,810	.10	18,400	6,250	1.11	18,600
12	5,040	.14	19,000	6,730	.10	18,200	6,090	.11	18,100
13	5,150	.13	18,000	6,590	.10	17,800	5,700	.10	15,400
14	5,010	.23	31,100	6,550	.10	17,700	5,430	.10	14,600
15	5,080	.26	35,600	6,490	.10	17,500	6,060	.09	12,300
16	5,090	.20	27,500	6,510	.10	17,600	4,460	1.08	9,630
17	5,210	.17	23,900	6,550	.10	17,700	3,760	.07	7,090
18	5,220	.18	25,400	6,370	.10	17,200	3,400	1.06	5,500
19	5,230	.17	24,000	6,180	.09	16,000	3,180	.05	4,290
20	5,540	1.16	23,900	6,240	.09	15,200	2,790	.05	3,780
21	5,610	.14	21,200	6,490	.09	15,800	3,030	.05	4,100
22	5,990	.29	46,800	6,670	.10	18,000	3,370	.06	5,450
23	5,920	.50	79,800	6,520	.09	15,800	3,900	.04	4,210
24	6,180	.23	38,300	6,670	1.10	18,000	4,080	.04	4,400
25	6,340	1.05	180,000	6,660	.10	18,000	4,140	1.04	4,480
26	7,070	.52	99,100	6,670	.09	16,200	3,930	.04	4,230
27	6,770	.33	60,300	6,530	1.08	14,100	3,730	.04	4,020
28	7,110	.27	51,800	6,660	.08	14,400	3,660	.04	3,940
29	6,970	1.27	50,800	6,630	.12	21,500	3,700	.04	3,990
30	6,910	.27	50,300	6,460	.11	19,200	3,610	.04	3,880
31	6,950	.21	39,400				3,300	.04	3,560
Monthly load (tons)						617,400			413,400

1933

	January			February			March		
	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day
1	2,880	1.04	3,100	5,470	0.05	7,390	8,390	1.69	382,000
2	3,990	.03	3,240	5,480	.05	7,390	8,310	.94	211,000
3	3,340	1.03	2,700	5,450	1.05	7,340	8,250	.71	158,000
4	3,240	.03	2,600	5,140	.05	6,930	8,600	1.68	158,000
5	3,340	.04	3,610	5,060	1.05	6,820	8,570	.65	150,000
6	4,090	1.04	4,420	5,020	.05	6,770	8,410	.51	116,000
7	3,480	.03	2,800	4,930	.04	5,310	8,240	.42	93,300
8	3,690	1.03	2,990	4,710	.04	5,070	7,950	.31	66,500
9	3,340	1.02	1,810	4,320	.03	3,510	7,920	.32	63,300
10	3,490	.02	1,890	3,980	.03	3,210	7,840	.36	76,100
11	3,730	1.02	2,020	2,720	.02	1,460	7,780	.36	75,500
12	4,280	.02	2,320	2,910	.02	1,560	7,720	.38	79,100
13	4,890	1.06	7,900	4,510	.04	4,850	8,340	.43	96,700
14	5,180	.07	9,790	4,090	.03	3,320	8,520	.44	101,000
15	4,760	1.08	10,300	4,530	.03	3,670	9,390	.49	124,000
16	4,820	.09	11,700	4,610	.03	3,720	10,100	.90	245,000
17	4,980	1.11	14,800	4,650	.03	3,780	9,960	.69	185,000
18	5,210	.14	19,700	4,950	.03	3,990	9,550	.53	137,000
19	5,190	.04	5,610	5,130	1.04	5,530	9,870	1.49	130,000
20	5,000	1.04	5,390	5,220	.04	5,640	10,400	.45	126,000
21	5,120	.05	6,900	5,490	.05	7,390	9,700	.42	110,000
22	5,150	1.05	6,960	5,740	.06	9,280	9,290	.42	105,000
23	5,240	.05	7,070	5,830	.07	11,000	9,110	.38	93,400
24	5,470	1.06	8,850	5,910	.07	11,200	8,870	.40	95,700
25	5,610	.07	10,600	5,830	.07	11,000	9,210	.39	96,900
26	5,560	1.07	10,500	5,760	1.07	10,900	8,780	.36	85,300
27	5,640	.07	10,700	5,880	.07	11,100	8,240	.31	68,900
28	5,650	1.07	10,700	6,180	.08	13,300	7,860	.34	72,100
29	5,620	1.07	10,600				7,480	.32	64,600
30	5,480	.07	10,400				7,070	.33	62,900
31	5,490	1.06	8,870				7,120	.33	63,400
Monthly load (tons)						182,400			3,697,000

<sup>1</sup> Estimated.

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1933

Day	April			May			June		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	7,360	0.41	81,400	9,220	0.35	87,000	54,700	1.58	2,330,000
2	7,830	.39	82,400	11,600	.88	275,000	62,700	1.51	2,550,000
3	8,000	.39	84,100	12,900	.75	261,000	69,500	1.35	2,530,000
4	8,280	1.39	87,100	15,600	1.75	736,000	75,800	1.42	2,900,000
5	8,460	.39	89,000	18,000	1.48	718,000	80,000	1.10	2,370,000
6	8,940	.35	84,400	18,800	1.40	710,000	78,800	1.02	2,170,000
7	9,320	.51	128,000	18,000	1.40	680,000	76,400	1.14	2,350,000
8	9,940	.56	150,000	17,000	1.36	624,000	78,600	1.22	2,590,000
9	10,400	.56	157,000	17,100	1.19	549,000	77,400	1.00	2,090,000
10	10,600	.62	177,000	17,000	1.06	486,000	73,700	1.03	2,050,000
11	10,300	.44	122,000	17,400	1.00	469,000	67,500	.75	1,365,000
12	10,200	1.50	138,000	17,700	.86	411,000	64,900	.84	1,470,000
13	9,940	.47	126,060	17,800	.94	451,000	68,500	.74	1,370,000
14	9,890	.36	96,000	17,200	.91	422,000	75,300	.80	1,620,000
15	9,550	.38	97,900	15,800	.63	268,000	77,000	.83	1,700,000
16	9,060	.35	85,500	14,700	.64	254,000	76,600	.71	1,470,000
17	8,500	.36	82,500	13,800	.50	186,000	73,700	.62	1,230,000
18	8,070	.35	76,200	12,900	.42	146,000	72,600	.75	1,470,000
19	7,710	.30	62,400	12,200	.39	128,000	72,400	.78	1,520,000
20	7,360	.29	57,600	11,400	.33	101,000	71,400	.52	1,000,000
21	6,910	.25	46,600	11,000	.37	110,000	69,700	.46	865,000
22	6,870	.23	42,600	18,500	.97	484,000	69,000	.52	968,000
23	6,830	.22	40,500	28,500	1.72	1,320,000	67,200	.53	961,000
24	7,360	.22	43,700	37,500	2.53	2,560,000	63,000	.57	968,000
25	7,950	.25	53,600	44,600	2.94	3,540,000	59,400	.69	1,110,000
26	8,160	.31	68,200	44,500	2.50	3,000,000	54,500	.59	867,000
27	9,340	.34	85,700	41,100	1.76	1,950,000	49,600	.58	776,000
28	10,300	.41	114,000	39,400	1.62	1,720,000	44,700	.59	711,000
29	9,730	.42	110,000	39,100	1.47	1,550,000	40,800	.44	484,000
30	9,310	.33	82,900	42,500	1.31	1,500,000	37,600	.44	446,000
31				48,100	1.32	1,710,000			
Monthly load (tons)		2,752,000			27,410,000				46,300,000

1933

	July			August			September		
	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day
1	34,100	0.47	432,000	7,000	0.48	90,600	3,240	0.36	31,400
2	30,900	.35	292,000	6,470	.47	82,000	3,160	.28	23,900
3	28,800	.32	249,000	6,020	.44	71,400	3,080	.22	18,300
4	26,500	.28	200,000	7,070	.47	89,600	3,090	.18	15,000
5	24,600	.24	155,000	6,630	.41	73,300	3,160	.17	14,500
6	22,300	.16	96,200	8,300	.45	101,000	3,090	.14	11,700
7	20,900	.24	135,000	7,840	1.05	222,000	3,090	.11	9,170
8	23,200	.84	526,000	8,090	.77	168,000	3,150	.13	11,100
9	29,200	.65	512,000	11,300	2.40	731,000	3,200	.13	11,200
10	30,700	3.08	2,550,000	11,800	2.11	671,000	4,600	.25	31,000
11	26,400	2.53	1,800,000	10,500	1.53	433,000	6,040	.43	70,000
12	29,400	1.68	1,330,000	9,080	1.87	458,000	14,600	4.21	1,660,000
13	24,400	3.47	2,280,000	7,660	2.54	525,000	15,200	9.06	3,710,000
14	22,000	2.40	1,420,000	7,170	2.03	393,000	9,890	6.29	1,680,000
15	19,900	1.95	1,050,000	6,880	1.65	305,000	8,580	4.74	1,100,000
16	19,900	1.78	955,000	6,360	1.16	199,000	7,930	3.97	849,000
17	18,300	1.07	528,000	5,960	.80	129,000	7,880	2.89	614,000
18	17,300	.89	415,000	5,380	.86	125,000	8,050	2.26	491,000
19	15,500	1.15	481,000	4,990	.75	101,000	8,000	1.55	334,000
20	14,500	.93	364,000	4,820	.66	85,800	7,150	1.56	301,000
21	15,400	.86	357,000	4,930	.54	71,800	6,700	1.47	266,000
22	13,500	.66	240,000	4,730	.66	84,200	10,400	1.75	491,000
23	12,100	.72	235,000	4,970	.99	133,000	13,500	2.40	874,000
24	11,100	.72	216,000	4,920	.91	121,000	11,200	3.06	924,000
25	9,920	.65	174,000	4,530	.98	120,000	8,000	2.8	606,000
26	9,370	.62	157,000	4,040	.95	104,000	7,150	1.75	337,000
27	10,200	3.12	838,000	3,840	.81	83,900	7,420	.94	188,000
28	9,810	1.89	500,000	3,560	.87	83,500	7,300	.61	120,000
29	9,920	1.95	522,000	3,410	.72	66,200	6,800	1.51	93,500
30	8,130	1.51	331,000	3,360	.50	45,300	6,400	.41	70,800
31	7,600	1.12	230,000	3,300	.43	38,300			
Monthly load (tons)		15,990,000			60,050,000				14,960,000

1 Estimate

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1933

Day	October			November			December		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	6,000	0.38	61,600	4,500	1.018	21,900	7,720	0.48	100,000
2	5,600	.36	55,300	4,450	.18	21,600	7,300	.47	92,600
3	5,530	.36	53,800	4,520	1.17	20,700	7,210	1.55	107,000
4	6,930	.78	146,000	4,530	1.17	20,800	6,740	.70	127,000
5	8,110	1.19	261,000	4,600	.16	19,900	6,230	1.60	101,000
6	8,930	1.57	379,000	5,140	.17	23,600	6,230	.47	79,100
7	10,500	3.67	1,040,000	5,140	1.17	23,600	6,080	1.42	68,900
8	14,500	5.77	2,260,000	5,010	.17	23,000	5,920	.37	59,100
9	12,100	4.76	1,560,000	5,080	.17	23,300	5,820	1.35	55,000
10	10,200	3.40	936,000	5,240	1.18	25,500	5,700	1.30	46,200
11	9,430	2.58	657,000	5,420	.18	26,300	5,500	.27	40,100
12	8,750	2.43	574,000	5,470	.21	31,000	5,360	1.22	31,800
13	7,820	2.22	469,000	5,380	1.21	30,500	5,210	.16	22,500
14	8,020	2.12	459,000	5,390	.21	30,600	5,070	1.20	27,400
15	8,060	1.53	333,000	5,400	1.20	29,200	5,770	.22	34,300
16	6,670	1.45	261,000	5,300	1.18	25,800	5,660	1.21	32,100
17	6,260	1.09	184,000	5,310	.17	24,400	5,290	1.21	30,000
18	6,990	.91	172,000	5,440	1.16	23,500	5,430	.20	29,300
19	6,810	.80	147,000	5,480	1.16	23,700	5,850	1.18	28,400
20	5,880	.82	130,000	5,380	1.16	23,200	5,830	1.16	25,200
21	5,460	.89	131,000	5,350	.15	21,700	5,610	1.14	21,200
22	5,240	.61	86,300	5,360	1.15	21,700	5,350	.13	18,800
23	5,170	.63	87,900	5,400	.15	21,900	5,010	1.13	17,600
24	5,080	.33	45,300	5,430	1.14	20,500	4,520	.12	14,600
25	4,950	.37	49,500	5,380	.13	18,900	4,400	1.11	13,100
26	4,920	.32	42,500	5,470	1.18	26,600	4,180	.10	11,300
27	4,920	.27	35,900	5,420	.15	22,000	4,030	1.10	10,900
28	4,910	.23	30,500	5,390	1.15	21,800	4,100	1.10	11,100
29	4,840	.22	28,700	5,290	.14	20,000	4,350	.07	8,220
30	4,700	.22	27,900	5,330	1.20	28,800	4,650	1.10	12,600
31	4,570	.18	22,200				5,080	.11	15,100
Monthly load (tons)			10,730,000			716,000			1,292,000

1934

	January			February			March		
1	5,590	1.15	22,600	5,270	0.12	17,100	6,360	0.28	48,100
2	5,900	1.20	31,900	5,160	.13	18,100	6,250	1.28	47,200
3	6,440	.25	43,500	5,050	.12	16,400	6,160	.28	46,600
4	6,470	1.27	47,200	5,050	.11	15,000	5,940	1.28	44,900
5	6,280	.29	49,200	4,980	.12	16,100	5,660	.29	44,300
6	6,320	1.28	47,800	4,990	.11	14,800	5,570	1.25	37,600
7	6,510	1.27	47,500	5,130	.13	18,000	5,550	.21	31,500
8	6,500	.26	45,600	5,140	1.15	20,800	5,430	1.20	29,300
9	6,220	1.25	42,000	5,290	.18	25,700	5,400	.19	27,700
10	6,110	.23	37,900	5,380	1.18	26,100	5,300	1.20	28,600
11	5,940	1.21	33,700	5,610	.17	25,700	5,250	1.19	26,900
12	5,530	1.18	26,900	6,000	1.20	32,400	5,180	.19	26,600
13	5,260	.16	22,700	6,150	1.25	41,500	5,360	1.19	27,500
14	4,820	1.14	18,200	6,390	.29	50,000	5,420	.19	27,800
15	4,520	.12	14,600	6,460	1.32	55,800	5,530	1.20	29,900
16	4,380	1.10	11,800	6,370	.33	56,800	5,590	1.25	37,700
17	4,270	.08	9,220	6,230	1.28	47,100	5,520	.25	37,300
18	4,330	1.08	9,350	5,980	.24	38,800	5,570	1.23	34,600
19	4,360	1.09	10,600	5,740	1.24	37,200	5,690	.21	32,300
20	4,440	.09	10,800	5,650	.24	36,600	5,780	1.22	34,300
21	4,730	1.09	11,500	5,550	1.22	33,000	5,690	.23	35,300
22	4,910	.09	11,900	5,460	.21	31,000	5,920	1.28	44,800
23	5,030	1.10	13,600	5,770	1.23	35,800	5,980	.32	51,700
24	4,940	.11	14,700	6,070	.24	39,300	5,920	1.30	48,000
25	4,950	1.10	13,400	6,420	1.26	45,100	5,790	1.28	43,800
26	5,130	.10	13,900	6,090	1.26	42,800	5,690	.24	36,900
27	5,180	1.11	15,400	6,190	.30	50,100	5,690	1.24	36,900
28	5,160	.12	16,700	6,190	1.30	50,100	5,720	.24	37,100
29	5,130	1.12	16,600				5,590	1.26	39,200
30	5,290	1.13	18,600				5,690	1.26	39,900
31	5,380	.13	18,900				5,730	.33	51,100
Monthly load (tons)			748,300			937,200			1,165,000

<sup>1</sup> Estimated.

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1934

Day	April		May		June	
	Mean discharge (second- feet)	Suspended sediment	Mean discharge (second- feet)	Suspended sediment	Mean discharge (second- feet)	Suspended sediment
		Mean percent		Tons per day		Mean percent
1	5,380	1.25	36,300	14,200	0.98	376,000
2	5,250	.17	24,100	14,500	.88	342,000
3	5,070	.17	23,300	14,300	.80	309,000
4	5,440	.18	26,400	13,700	.75	277,000
5	5,730	.20	30,900	15,000	.94	381,000
6	5,910	.22	35,100	15,600	.90	379,000
7	5,980	.21	33,900	14,900	.68	274,000
8	5,920	.25	40,000	14,000	.70	265,000
9	5,830	.28	44,100	13,300	.59	212,000
10	5,810	.24	37,600	13,400	.63	228,000
11	5,850	.24	37,900	14,900	.75	302,000
12	5,680	.20	30,700	18,200	1.02	501,000
13	5,460	.19	28,000	21,300	1.29	742,000
14	5,240	.15	21,200	24,100	1.30	846,000
15	5,210	.14	19,700	24,600	1.40	930,000
16	5,420	.18	26,300	24,900	1.36	914,000
17	6,680	.38	68,500	24,700	1.01	674,000
18	7,820	.87	184,000	22,900	.99	612,000
19	8,710	.85	200,000	20,600	.84	467,000
20	9,650	.91	237,000	19,500	.70	369,000
21	9,380	.76	192,000	19,800	.77	412,000
22	9,260	.65	163,000	19,600	.63	333,000
23	8,850	.57	136,000	19,300	.70	365,000
24	8,930	.64	154,000	18,700	.50	252,000
25	9,740	.69	181,000	18,200	.57	280,000
26	10,600	.83	238,000	17,700	.49	234,000
27	11,400	.82	252,000	16,800	.47	213,000
28	11,900	.95	305,000	15,500	.37	155,000
29	12,500	.86	290,000	16,600	.63	282,000
30	13,500	1.03	375,000	17,400	1.87	879,000
31				17,800	1.39	668,000
Monthly load (tons)			3,471,000		13,470,000	4,095,000

1934

	July		August		September		
	1	3,090	0.04	3,340	2,810	1.68	127,000
2	3,040	.04	3,280	2,440	.90	59,300	5,250
3	3,100	.03	2,510	2,120	1.70	40,100	4,430
4	3,190	.02	1,720	1,980	1.00	53,500	3,300
5	3,180	.02	1,720	1,970	1.64	87,200	2,650
6	3,040	.03	2,460	2,030	1.26	69,100	2,600
7	2,910	.02	1,570	1,890	.93	47,500	2,740
8	2,800	.03	2,270	1,750	.65	30,700	2,540
9	2,610	.03	2,110	1,590	.44	18,900	2,440
10	2,480	.03	2,010	1,620	.26	11,400	2,130
11	2,370	.04	2,560	1,490	.33	13,300	2,190
12	2,310	.04	2,490	1,750	.48	22,700	2,210
13	2,270	.03	1,840	1,750	.37	17,500	2,160
14	2,170	.02	1,170	1,780	.51	24,500	2,030
15	2,120	.02	1,140	2,030	2.25	123,000	1,950
16	2,030	.02	1,100	2,010	1.71	92,800	1,850
17	1,980	.02	1,070	2,000	.92	49,700	1,950
18	1,970	.04	2,130	2,000	2.33	126,000	2,310
19	1,920	.05	2,590	2,130	2.26	130,000	2,430
20	1,840	.02	994	3,300	1.48	132,000	2,540
21	1,880	.02	1,020	2,860	1.34	103,000	2,570
22	1,840	.01	497	3,010	1.76	143,000	2,340
23	2,070	.02	1,120	2,880	1.39	108,000	2,170
24	2,050	.58	32,100	2,600	2.42	170,000	1,960
25	1,950	2.02	106,000	2,590	1.78	124,000	1,860
26	2,040	1.76	96,900	2,650	1.20	85,900	1,810
27	2,070	.80	44,700	2,640	1.20	85,500	1,770
28	2,650	.55	39,400	3,410	1.31	121,000	4,210
29	2,150	.94	54,600	6,110	9.10	1,500,000	4,050
30	2,050	.51	28,200	5,930	4.84	775,000	3,500
31	2,620	1.68	119,000	8,560	11.5	2,660,000	4.07
Monthly load (tons)			563,600		7,152,000	5,746,000	

1 Estimated.

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1934

Day	October			November			December		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	3,080	3.20	266,000	2,810	0.13	9,860	3,920	0.17	18,000
2	3,070	2.24	185,000	2,820	.13	9,910	3,870	.18	18,800
3	3,500	1.50	142,000	2,760	.13	9,690	4,000	.18	19,400
4	3,460	.94	87,800	2,720	.12	8,800	4,040	.20	21,800
5	3,220	.62	53,900	2,720	.12	8,800	3,970	.18	19,300
6	3,060	.42	34,700	2,760	.12	8,940	3,800	.15	15,400
7	2,930	.37	29,300	2,800	.10	7,560	3,740	.12	12,100
8	2,910	.30	23,600	2,740	.12	8,580	3,570	.11	10,600
9	2,990	.25	20,200	2,720	.12	8,800	3,300	.14	12,500
10	2,930	.25	19,800	2,810	.12	9,100	3,080	.10	8,320
11	2,830	.22	16,800	2,910	.11	8,640	2,950	.11	8,750
12	2,740	.16	11,800	3,000	.14	11,300	2,830	.09	6,890
13	2,670	.18	13,000	2,990	.14	11,300	2,880	.09	6,990
14	2,610	.17	12,000	3,030	.16	13,100	3,120	.09	7,590
15	2,580	.17	11,900	3,170	.15	12,900	3,500	.11	10,400
16	2,590	.16	11,200	3,330	.16	14,400	3,860	.16	16,700
17	2,460	.14	9,290	3,470	.18	16,000	3,980	.16	17,200
18	2,430	.14	9,180	3,460	.18	16,800	4,420	.36	43,000
19	2,530	.14	9,560	3,440	.16	14,800	4,630	.30	37,500
20	2,520	.13	8,860	3,470	.15	14,000	4,480	.30	36,300
21	2,490	.12	8,070	3,560	.18	17,300	4,460	.29	34,900
22	2,590	.11	7,700	3,830	.19	19,700	4,660	.28	35,200
23	2,690	.10	7,260	3,780	.24	24,500	4,780	.29	37,400
24	2,670	.15	10,800	3,850	.22	22,900	4,540	.24	29,400
25	2,690	.12	8,720	3,830	.25	25,900	4,340	.21	24,600
26	2,690	.12	8,720	3,990	.24	25,900	4,160	.18	20,200
27	2,680	.12	8,690	3,930	.21	22,300	4,200	.18	20,400
28	2,680	.12	8,690	4,000	.21	22,700	4,280	.18	20,800
29	2,750	.13	9,670	4,030	.20	21,800	4,410	.20	23,800
30	2,840	.12	9,210	3,990	.20	21,500	4,470	.19	22,900
31	2,810	.14	10,600				4,400	.18	21,400
Monthly load (tons)				449,000				638,500	

1935

	January			February			March		
	Mean	discharge	(second-feet)	Mean	discharge	(second-feet)	Mean	discharge	(second-feet)
1	4,400	0.14	16,600	5,300	0.38	54,400	5,680	0.46	70,600
2	4,420	.22	26,200	5,320	.34	48,800	5,540	.44	65,800
3	4,360	.17	20,000	5,310	.31	44,400	5,460	.48	70,800
4	4,410	.18	21,400	5,330	1.35	50,400	5,230	1.35	49,400
5	4,340	.19	22,300	5,560	1.35	52,500	5,040	.30	40,800
6	4,210	.18	20,500	5,560	.40	60,100	4,780	.28	36,100
7	4,200	.18	20,400	5,560	.44	66,000	5,060	.32	43,700
8	3,990	.76	81,900	5,370	.40	58,000	5,770	.44	68,600
9	4,210	.28	31,800	5,240	.38	53,800	5,920	.46	73,500
10	4,460	1.90	229,000	5,650	.36	54,900	5,890	.54	85,900
11	4,160	1.13	127,000	6,300	1.03	175,000	5,890	.44	70,000
12	5,220	1.10	155,000	6,000	.90	146,000	5,620	.41	62,200
13	5,650	1.19	182,000	5,880	.71	113,000	5,530	.35	52,300
14	7,980	3.47	748,000	6,340	.75	128,000	5,480	.38	56,200
15	6,380	2.35	405,000	6,020	.92	150,000	5,360	.36	52,100
16	5,690	1.02	157,000	5,580	.62	93,400	5,090	.43	59,100
17	5,950	.98	157,000	5,560	.47	70,600	5,090	.44	60,500
18	6,350	1.05	180,000	5,520	.40	59,600	7,420	1.72	345,000
19	5,970	.72	116,000	5,580	.51	76,800	8,080	1.55	338,000
20	5,800	.81	127,000	5,400	.36	52,500	7,380	1.16	231,000
21	5,130	.67	92,800	5,270	.32	45,500	6,920	.94	176,000
22	4,970	.48	64,400	4,970	.29	38,900	6,790	.89	163,000
23	4,580	.32	39,600	4,710	.28	35,600	6,730	.79	144,000
24	4,050	.22	24,100	4,580	.24	29,700	6,590	.70	125,000
25	3,360	.16	14,500	4,800	.22	28,500	6,730	.61	111,000
26	2,940	.10	7,940	5,570	.61	91,800	6,940	.60	112,000
27	3,000	.12	9,720	6,100	.59	97,200	6,940	.64	120,000
28	3,040	.22	18,100	5,990	.57	92,200	6,650	.61	110,000
29	3,300	.19	16,900				6,700	.56	101,000
30	3,910	.21	22,200				6,940	.59	111,000
31	4,520	.32	41,600				7,440	.72	145,000
Monthly load (tons)				2,068,000				3,350,000	

<sup>1</sup> Estimated.

## QUANTITIES OF SUSPENDED SEDIMENT

41

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1935

Day	April			May			June		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	7,970	0.93	200,000	13,700	0.85	314,000	48,100	1.70	2,210,000
2	8,260	1.06	236,000	14,300	.90	348,000	48,600	1.90	2,490,000
3	8,890	1.26	302,000	15,600	1.04	438,000	49,400	1.58	2,110,000
4	9,480	1.24	317,000	16,700	1.22	550,000	48,700	1.45	1,910,000
5	9,330	1.31	330,000	17,400	1.28	601,000	46,200	1.31	1,630,000
6	9,630	1.38	359,000	16,400	1.04	461,000	45,400	1.12	1,370,000
7	10,900	1.40	412,000	15,300	.99	409,000	47,100	1.08	1,370,000
8	11,600	1.48	464,000	14,100	1.06	404,000	50,700	1.10	1,510,000
9	11,600	1.42	445,000	13,600	.88	323,000	54,200	1.28	1,870,000
10	12,300	1.60	531,000	13,400	.73	264,000	57,800	1.28	2,000,000
11	15,600	3.16	1,330,000	13,100	.68	241,000	63,600	1.25	2,150,000
12	14,400	2.16	840,000	13,300	.68	244,000	69,800	1.26	2,370,000
13	13,200	1.58	563,000	14,300	.77	297,000	72,600	1.14	2,230,000
14	11,300	1.31	400,000	16,200	.80	350,000	84,300	1.22	2,780,000
15	10,800	1.12	327,000	18,500	.97	490,000	86,400	1.06	2,470,000
16	10,200	.89	245,000	20,900	1.13	638,000	87,200	1.09	2,570,000
17	10,000	.81	219,000	24,100	1.45	944,000	91,900	1.03	2,560,000
18	10,900	.84	247,000	24,000	1.52	985,000	101,400	1.01	2,770,000
19	12,300	1.11	369,000	23,300	1.36	856,000	103,100	.82	2,280,000
20	13,500	1.46	532,000	24,000	1.32	855,000	89,000	.79	1,900,000
21	14,100	1.38	525,000	25,200	1.26	857,000	80,900	.72	1,570,000
22	14,700	1.38	548,000	26,300	1.22	866,000	77,000	.55	1,140,000
23	14,400	1.23	478,000	29,700	1.38	1,110,000	73,800	.54	1,080,000
24	13,900	1.20	450,000	31,000	1.48	1,240,000	73,400	.58	1,150,000
25	13,600	1.10	404,000	26,800	1.48	1,070,000	70,300	.36	1,060,000
26	14,000	1.06	401,000	26,000	1.08	758,000	65,400	.44	777,000
27	15,800	1.26	538,000	27,300	1.01	744,000	63,500	.48	823,000
28	16,900	1.40	639,000	31,100	1.01	848,000	58,800	.44	699,000
29	15,200	1.08	443,000	36,200	1.26	1,230,000	53,700	.37	537,000
30	14,000	.92	348,000	40,000	1.38	1,490,000	50,300	.36	489,000
31				44,500	1.54	1,850,000			
Monthly load (tons)		13,440,000			22,080,000			51,880,000	

1935

	July			August			September		
1	47,600	0.36	463,000	10,800	0.16	46,700	9,140	1.43	353,000
2	43,800	.35	414,000	11,000	.25	74,300	10,500	1.83	519,000
3	41,200	.33	367,000	10,600	.17	48,700	11,700	2.80	885,000
4	39,200	.28	296,000	10,000	.23	62,100	12,300	5.02	1,670,000
5	36,800	.28	278,000	10,500	.36	102,000	10,100	2.54	693,000
6	35,000	.30	284,000	12,700	1.82	624,000	8,630	1.94	452,000
7	33,400	.22	198,000	11,100	1.54	462,000	7,670	2.00	414,000
8	31,800	.23	197,000	10,700	.72	208,000	6,880	1.64	305,000
9	29,700	.23	184,000	10,300	.44	122,000	6,450	1.12	195,000
10	27,700	.20	150,000	9,950	.46	124,000	6,250	.97	164,000
11	26,500	.17	122,000	10,200	1.72	474,000	6,270	.72	122,000
12	25,300	.19	130,000	10,200	1.13	311,000	5,820	.64	101,000
13	24,300	.16	105,000	9,330	.97	244,000	5,950	.56	90,000
14	23,800	.16	103,000	8,720	1.11	261,000	6,490	.65	114,000
15	23,200	.16	100,000	8,880	1.16	278,000	6,410	.64	93,500
16	22,400	.15	90,800	9,040	.98	239,000	6,870	.56	104,000
17	21,900	.13	76,900	9,680	.76	199,000	7,190	.49	77,700
18	20,900	.13	73,400	8,120	1.35	296,000	6,370	.38	56,800
19	19,500	.14	73,700	8,400	.53	120,000	5,740	.41	63,500
20	18,900	.30	153,000	7,560	.40	81,700	5,450	.31	45,600
21	20,800	.39	219,000	8,040	.44	95,500	5,480	.21	31,100
22	17,200	.62	288,000	8,140	.54	119,000	5,100	.16	22,000
23	18,000	.60	292,000	7,600	.48	98,500	4,740	.15	19,200
24	17,100	.35	162,000	7,660	.50	103,000	4,500	.14	17,000
25	16,000	.24	104,000	7,380	.52	104,000	4,360	.12	14,100
26	15,700	.27	114,000	9,640	4.81	1,250,000	4,440	.15	18,000
27	14,800	.54	216,000	8,470	2.56	585,900	7,420	.24	48,100
28	14,100	.46	175,000	10,600	2.74	784,000	13,000	.90	316,000
29	13,000	.23	80,700	9,950	1.86	500,000	9,630	2.14	556,000
30	12,100	.22	71,900	8,980	1.69	410,000	18,100	4.14	2,020,000
31	11,400	.19	58,500	8,240	2.14	467,000			9,580,000
Monthly load (tons)		5,640,000			8,902,000				

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1935

Day	October		November		December				
	Mean discharge (second- feet)	Suspended sediment	Mean discharge (second- feet)	Suspended sediment	Mean discharge (second- feet)	Suspended sediment			
		Mean percent		Tons per day		Mean percent	Tons per day		
1	15,800	5.09	2,170,000	5,190	0.23	32,200	5,750	0.14	21,700
2	10,500	4.65	1,320,000	5,230	.20	28,200	5,790	.11	17,200
3	9,250	3.44	859,000	5,080	.15	20,600	5,820	.10	15,700
4	8,800	1.98	470,000	5,250	.15	21,300	5,820	.10	15,700
5	8,020	1.28	277,000	5,260	.13	18,500	5,760	.09	14,000
6	7,490	.88	178,000	5,260	.13	18,500	6,870	.11	20,400
7	7,240	.69	135,000	5,380	.12	17,400	6,230	.22	37,000
8	6,830	.54	99,600	5,570	.13	19,600	5,480	.19	28,100
9	6,550	.45	79,600	5,680	.13	19,900	5,040	.13	17,700
10	6,300	.42	71,400	5,680	.12	18,400	4,970	.11	14,800
11	6,020	.31	50,400	5,710	.13	20,000	4,970	.08	10,700
12	5,820	.26	40,900	5,650	.13	19,800	4,910	.08	10,600
13	5,600	.22	33,300	5,560	.12	18,000	4,960	.09	12,100
14	5,380	.19	27,600	5,790	.12	18,800	5,010	.10	13,500
15	5,140	.16	22,200	5,960	.12	19,300	5,060	.09	12,300
16	5,010	.14	18,900	6,020	.11	17,900	4,970	.09	12,100
17	4,950	.13	17,400	5,970	.11	17,700	4,790	.09	11,600
18	4,820	.12	15,600	5,830	.10	15,700	4,600	.09	11,200
19	4,660	.11	13,800	5,690	.10	15,400	4,620	.09	11,200
20	4,670	.11	13,900	5,610	.09	13,600	4,670	.08	10,100
21	4,650	.12	15,100	5,540	.10	15,000	4,600	.08	9,940
22	4,730	.12	15,300	5,610	.09	13,600	4,230	.07	7,990
23	4,570	.11	13,600	5,790	.09	14,100	3,630	.07	6,860
24	5,440	.12	17,600	5,760	.11	17,100	3,350	.06	5,430
25	5,560	.14	21,000	5,920	.11	17,600	3,280	.05	4,430
26	5,430	.15	22,000	5,930	.11	17,600	3,140	.06	5,090
27	5,100	.16	22,000	5,900	.10	15,900	3,170	.06	5,140
28	4,960	.20	26,800	5,920	.12	19,200	3,330	.06	5,390
29	5,050	.49	66,800	5,710	.11	17,000	3,560	.07	6,730
30	5,000	.44	59,400	5,650	.15	22,900	3,760	.08	8,120
31	5,040	.26	35,400				4,000	.06	6,480
Monthly load (tons)		6,229,000			560,800			389,300	

1936

	January		February		March				
	Mean discharge (second- feet)	Suspended sediment	Mean discharge (second- feet)	Suspended sediment	Mean discharge (second- feet)	Suspended sediment			
1	3,750	0.08	8,100	5,390	0.08	11,600	7,370	0.47	93,500
2	3,820	.08	8,250	5,560	.15	22,500	6,740	.38	69,200
3	4,100	.06	6,640	5,440	.16	23,500	6,340	.36	61,600
4	4,310	.06	6,980	5,650	.16	24,400	5,970	.30	48,400
5	4,180	.07	7,900	5,580	.17	25,600	6,020	.24	39,000
6	4,220	.07	7,980	5,610	.27	40,900	7,340	.25	49,500
7	4,280	.07	8,090	5,160	.17	23,700	8,770	.42	99,500
8	4,220	.07	7,980	4,910	.17	22,500	9,010	.66	161,000
9	4,180	.06	6,770	5,190	.17	23,800	8,790	1.17	178,000
10	3,900	.06	6,320	5,350	.14	20,200	8,500	1.28	294,000
11	4,310	.05	5,820	5,050	.09	12,300	8,270	1.10	246,000
12	4,580	.06	7,420	4,650	.10	12,600	8,480	1.03	236,000
13	4,520	.07	8,540	4,540	.08	9,810	8,740	.86	203,000
14	4,410	.07	8,330	4,910	.07	9,280	9,140	.77	190,000
15	4,400	.06	7,130	4,970	.07	9,390	8,980	.81	196,000
16	4,610	.06	7,470	5,190	.14	19,600	8,750	.74	175,000
17	4,730	.06	7,660	5,450	.10	14,700	9,010	.65	158,000
18	5,040	.06	8,160	6,160	.13	21,600	9,250	.62	155,000
19	5,250	.06	8,500	6,510	.16	28,100	9,330	.64	161,000
20	5,260	.06	8,520	6,530	.16	28,200	9,270	.51	128,000
21	5,100	.08	11,000	6,390	.16	27,600	8,800	.49	116,000
22	5,040	.07	9,530	6,480	.16	28,000	8,630	.45	105,000
23	4,870	.06	7,890	6,560	.18	31,900	8,420	.39	88,700
24	4,780	.05	6,450	6,300	.19	32,300	8,470	.37	84,600
25	4,560	.07	8,620	6,630	.19	34,000	8,470	.34	77,800
26	4,450	.06	7,210	6,730	.32	58,100	8,430	.35	79,700
27	4,390	.06	7,110	6,070	.18	29,500	8,500	.37	84,900
28	4,410	.04	4,760	6,510	.28	49,200	7,850	.37	78,400
29	4,670	.06	7,570	7,780	.35	73,500	7,490	.40	80,900
30	4,930	.06	7,990				7,660	.34	70,300
31	5,210	.07	9,850				7,220	.37	72,100
Monthly load (tons)		240,500			768,400			3,980,000	

## QUANTITIES OF SUSPENDED SEDIMENT

43

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1936

Day	April		May		June	
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day
1	6,740	0.35	63,700	51,200	1.16	1,600,000
2	7,000	.27	51,000	51,100	1.01	1,390,000
3	7,670	.30	62,100	49,900	.95	1,280,000
4	7,840	.44	93,100	47,100	.80	1,020,000
5	7,920	.39	83,400	44,400	.79	947,000
6	7,310	.39	77,000	45,900	.67	830,000
7	7,640	.38	78,400	50,700	.74	1,010,000
8	7,820	.38	80,200	58,700	.94	1,490,000
9	7,180	.39	75,600	66,400	1.06	1,900,000
10	6,810	.28	51,500	64,400	.90	1,560,000
11	6,720	.26	47,200	58,600	.74	1,170,000
12	7,340	.22	43,600	52,700	.61	868,000
13	9,810	.71	188,000	46,200	.54	674,000
14	10,200	.89	245,000	42,300	.51	582,000
15	11,500	1.09	338,000	40,500	.42	459,000
16	14,300	1.18	456,000	44,000	.44	523,000
17	17,600	1.46	694,000	49,100	.51	676,000
18	21,600	1.68	980,000	55,200	.55	820,000
19	23,700	1.64	1,050,000	62,600	.53	896,000
20	27,600	1.62	1,210,000	67,700	.64	1,170,000
21	32,700	1.65	1,460,000	71,800	.59	1,140,000
22	35,400	1.57	1,500,000	70,600	.59	1,120,000
23	36,800	1.57	1,560,000	74,600	.58	1,170,000
24	39,400	1.32	1,400,000	75,100	.58	1,180,000
25	43,100	1.43	1,660,000	70,600	.44	839,000
26	47,700	1.58	2,030,000	67,900	.51	935,000
27	49,600	1.39	1,860,000	66,100	.54	964,000
28	49,900	1.59	2,140,000	65,600	.47	832,000
29	51,100	1.32	1,820,000	65,600	.45	797,000
30	51,700	1.26	1,760,000	65,400	.50	883,000
31				64,600	.46	802,000
Monthly load (tons)			23,160,000	31,530,000		13,610,000

1936

	July		August		September	
1	25,600	0.18	124,000	9,800	1.13	299,000
2	24,100	.17	111,000	9,390	.94	238,000
3	23,100	.17	106,000	9,450	.92	235,000
4	22,400	.16	96,800	11,200	1.48	448,000
5	21,200	.15	85,900	15,300	3.14	1,300,000
6	19,300	.17	88,600	19,700	4.22	2,240,000
7	17,900	.18	87,000	20,700	5.35	4,290,000
8	16,600	.12	53,800	24,700	6.54	4,360,000
9	15,700	.13	55,100	27,200	5.31	3,900,000
10	14,400	.13	50,500	27,200	3.99	2,930,000
11	15,500	.12	50,200	23,200	3.18	1,990,000
12	15,900	2.22	953,000	21,000	2.73	1,550,000
13	29,800	.82	660,000	18,600	2.53	1,270,000
14	29,200	4.72	3,720,000	16,900	2.12	967,000
15	20,500	1.72	952,000	15,200	2.22	911,000
16	17,800	3.13	1,500,000	13,300	1.68	603,000
17	16,900	3.62	1,650,000	12,800	1.49	515,000
18	16,300	2.40	1,060,000	12,800	1.15	397,000
19	14,700	1.84	730,000	12,200	1.42	468,000
20	13,700	1.02	377,000	12,400	1.22	408,000
21	14,300	.89	344,000	11,900	1.40	450,000
22	15,200	.91	373,000	11,100	1.60	480,000
23	14,300	.76	293,000	13,300	1.75	628,000
24	14,100	.62	236,000	14,900	2.13	857,000
25	12,900	.74	258,000	12,300	2.08	691,000
26	12,100	.56	183,000	11,000	2.19	650,000
27	11,800	.66	210,000	10,500	2.07	587,000
28	10,800	1.11	324,000	9,720	1.34	352,000
29	11,400	1.24	382,000	9,010	.98	238,000
30	10,600	1.31	375,000	9,300	1.15	289,000
31	8,810	.99	235,000	10,800	5.50	1,600,000
Monthly load (tons)			15,720,000	36,140,000		25,230,000

<sup>1</sup>Estimated.

## SEDIMENT IN COLORADO RIVER, 1925-41

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

Day	October			November			December		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	5,180	0.64	89,500	7,250	0.45	88,100	6,600	0.13	23,200
2	5,300	.50	71,600	10,700	1.78	514,000	6,480	.15	26,200
3	5,120	.42	58,100	9,560	1.70	439,000	6,270	.14	23,700
4	5,150	.40	55,600	9,670	1.91	499,000	6,200	.13	21,800
5	5,240	.37	52,300	9,100	1.58	388,000	5,960	.16	25,700
6	5,240	.41	58,000	9,130	.96	237,000	5,800	.12	18,800
7	5,390	.36	52,400	8,710	.95	223,000	5,740	.40	15,500
8	5,580	.31	46,700	8,310	.90	202,000	5,560	.11	16,500
9	5,540	.32	47,900	7,940	.84	180,000	5,420	.10	14,600
10	5,520	.26	38,800	7,570	.69	141,000	5,230	.10	14,100
11	5,700	.22	33,900	7,260	.44	86,200	5,110	.09	12,400
12	5,780	.24	37,500	7,310	.40	78,900	4,880	.11	14,500
13	5,740	.24	37,200	7,480	.47	94,900	4,620	.10	12,500
14	5,680	.22	33,700	7,510	.36	73,000	4,370	.10	11,800
15	5,690	.21	32,300	7,290	.34	66,900	4,210	.08	9,090
16	5,660	.23	35,100	7,220	.36	70,200	4,130	.07	7,810
17	5,650	.21	32,000	7,120	.33	63,400	4,110	.07	7,770
18	5,560	.19	28,500	7,050	.20	38,100	4,220	.06	6,840
19	5,430	.18	26,400	7,090	.20	38,300	4,580	.08	9,890
20	5,380	.18	26,100	7,160	.30	58,000	5,160	.08	11,100
21	5,870	.24	38,000	7,070	.19	36,300	5,390	.12	17,500
22	5,790	.70	109,000	7,100	.16	30,700	5,700	.08	12,300
23	5,900	.35	55,800	7,200	.28	54,400	5,820	.11	17,300
24	6,520	.55	96,800	7,180	.20	38,800	5,860	.11	17,400
25	7,050	.46	87,600	7,200	.21	40,800	6,030	.11	17,900
26	7,410	.55	110,000	7,170	.16	31,000	6,020	.12	19,500
27	7,120	.59	113,000	7,040	.26	49,400	5,820	.10	15,700
28	6,980	.49	92,300	6,990	.16	30,200	5,900	.19	30,300
29	6,960	.48	90,200	6,960	.17	31,900	6,410	.11	19,000
30	6,820	.54	99,400	6,830	.22	40,600	6,830	.24	44,300
31	6,830	.40	73,800				6,070	.16	26,200
Monthly load (tons)		1,860,000			3,963,000				541,200

1937

	January			February			March		
	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day
1	5,970	0.12	19,300	4,130	0.05	5,580	8,550	0.54	125,000
2	6,010	.12	19,500	4,590	.06	7,440	8,270	.51	114,000
3	5,760	.10	15,600	4,740	.05	6,400	8,200	.50	111,000
4	5,270	.10	14,200	4,800	.05	6,480	8,090	.43	93,900
5	4,960	.12	16,100	4,950	.07	9,360	8,030	.41	88,900
6	4,430	.10	12,000	5,110	.08	11,000	8,000	.42	90,700
7	3,810	.07	7,200	5,820	.13	20,400	8,310	.49	110,000
8	3,560	.07	6,730	8,910	.34	81,800	8,320	.46	103,000
9	3,460	.06	5,610	10,000	.46	124,000	8,340	.54	122,000
10	2,960	.07	5,590	17,100	4.32	1,990,000	8,640	.57	133,000
11	2,860	.06	4,630	12,100	1.36	440,000	9,190	.65	161,000
12	2,750	.05	3,710	9,670	1.28	334,000	10,200	.78	215,000
13	2,020	.04	2,180	8,720	.95	224,000	10,800	.95	277,000
14	2,200	.04	2,380	9,090	.60	147,000	11,900	1.01	325,000
15	3,270	.07	6,180	9,140	.55	136,000	12,900	1.32	460,000
16	3,010	.05	4,060	8,930	.44	106,000	14,600	1.75	690,000
17	2,520	.05	3,400	18,200	2.34	1,150,000	17,700	2.79	1,330,000
18	2,810	.05	3,790	17,000	2.76	1,270,000	16,100	2.32	1,010,000
19	3,450	.04	3,730	16,800	2.29	1,040,000	19,600	2.87	1,520,000
20	3,840	.05	5,180	13,400	1.88	680,000	22,000	2.87	1,700,000
21	3,840	.04	4,150	12,000	1.56	505,000	22,300	2.76	1,660,000
22	3,810	.04	4,110	11,500	1.34	416,000	19,700	2.37	1,260,000
23	3,590	.03	2,910	9,890	1.03	275,000	20,100	2.26	1,230,000
24	2,980	.04	3,220	8,820	.77	183,000	18,000	1.97	957,000
25	2,820	.04	3,050	8,240	.68	151,000	17,300	1.91	892,000
26	2,560	.04	2,760	7,930	.53	113,000	18,000	1.74	846,000
27	2,520	.03	2,040	7,890	.45	95,900	16,300	1.53	673,000
28	2,880	.03	2,330	8,280	.70	156,000	14,900	1.39	559,000
29	3,050	.03	2,470				14,000	1.26	476,000
30	3,150	.03	2,550				13,100	.99	350,000
31	3,580	.04	3,870				12,700	.89	305,000
Monthly load (tons)		194,500			9,688,000				17,990,000

<sup>1</sup> Estimated.

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1937

Day	April			May			June		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	12,200	0.70	231,000	36,000	1.46	1,420,000	51,500	0.71	987,000
2	11,600	.79	219,000	32,700	1.00	883,000	60,300	.88	1,430,000
3	10,800	.62	181,000	28,500	.88	677,000	64,900	.78	1,370,000
4	11,200	.68	206,000	25,600	.76	525,000	60,100	.85	1,386,000
5	13,800	1.16	432,000	25,800	.78	543,000	55,900	.75	1,130,000
6	15,300	1.45	599,000	30,200	.92	750,000	55,500	.60	899,000
7	13,900	1.23	462,000	35,700	1.00	964,000	54,700	.60	886,000
8	13,100	1.10	389,000	41,400	1.28	1,430,000	51,300	.56	776,000
9	13,900	1.00	375,000	43,600	1.28	1,519,000	47,200	.56	714,000
10	15,000	1.18	478,000	43,200	1.26	1,470,000	43,300	.56	655,000
11	15,000	1.02	413,000	50,400	1.40	1,910,000	39,100	.48	507,000
12	17,300	1.37	640,000	57,200	1.56	2,410,000	36,300	.43	421,000
13	19,200	1.80	939,000	65,400	1.92	3,390,000	34,800	.44	413,000
14	20,400	1.75	964,000	71,400	1.64	3,160,000	33,100	.40	357,000
15	22,700	2.04	1,250,000	67,900	1.40	2,570,000	33,900	.41	365,000
16	24,900	2.03	1,360,000	69,400	1.38	2,590,000	33,800	.36	329,000
17	28,800	2.32	1,800,000	72,100	1.43	2,780,000	34,900	.46	433,000
18	34,200	2.24	2,070,000	78,500	1.24	2,630,000	32,900	.44	391,000
19	43,700	2.95	3,480,000	82,100	1.19	2,640,000	31,600	.34	290,000
20	44,600	2.78	3,350,000	81,500	1.04	2,290,000	30,400	.31	254,000
21	42,100	2.48	2,820,000	83,600	1.12	2,530,000	31,400	.45	382,000
22	43,700	2.19	2,580,000	77,000	1.00	2,080,000	34,000	.36	330,000
23	42,700	2.25	2,590,000	72,500	.98	1,920,000	34,100	.41	377,000
24	40,500	2.37	2,599,000	70,800	.90	1,720,000	33,600	.34	308,000
25	42,500	2.07	2,380,000	69,100	.88	1,640,000	33,500	.40	362,000
26	41,800	2.06	2,320,000	66,600	.82	1,470,000	34,200	.38	351,000
27	36,500	1.65	1,630,000	63,100	.86	1,470,000	32,600	.62	546,000
28	32,000	1.40	1,210,000	58,400	.70	1,100,000	32,400	.44	385,000
29	31,300	1.37	1,160,000	53,600	.62	897,000	29,300	.38	301,000
30	34,500	1.43	1,330,000	48,500	.66	864,000	31,100	.40	336,000
31				48,100	.66	857,000			
Monthly load (tons)				40,440,000	53,090,000				117,600,000

1937

	July			August			September		
1	30,800	0.40	333,000	13,300	1.61	578,000	9,760	2.49	656,000
2	28,800	1.00	778,000	12,100	1.92	627,000	12,200	1.72	567,000
3	27,400	.51	377,000	11,100	2.14	641,000	14,700	4.77	1,390,000
4	25,600	.36	249,000	10,300	2.08	578,000	15,100	3.14	1,280,000
5	24,700	.21	140,000	10,100	1.60	436,000	13,800	3.03	1,130,000
6	22,500	.25	152,000	10,300	.79	220,000	12,800	2.70	933,000
7	20,900	.28	158,000	9,420	.69	175,000	11,100	2.98	893,000
8	19,500	.33	174,000	9,340	.72	182,000	10,100	2.72	742,000
9	18,700	.38	192,000	8,400	.62	141,000	8,660	2.69	629,000
10	18,800	1.15	584,000	7,620	.94	193,000	8,200	2.48	549,000
11	19,100	1.23	634,000	7,300	.78	154,000	7,600	2.43	499,000
12	21,600	.67	391,000	7,300	.67	132,000	7,160	2.41	466,000
13	27,100	2.47	1,810,000	7,340	.93	184,000	7,110	2.28	438,000
14	27,200	2.52	1,550,000	7,040	1.16	220,000	7,340	1.41	279,000
15	30,200	2.55	2,080,000	6,350	.79	135,000	6,690	1.33	240,000
16	31,200	2.87	2,420,000	5,820	.54	84,900	5,980	1.25	202,000
17	30,900	2.73	2,280,000	5,460	.48	70,800	5,580	1.00	151,000
18	32,000	3.26	2,820,000	5,180	.30	42,000	5,300	.76	109,000
19	31,300	2.56	2,160,000	4,950	.23	30,700	5,050	.76	104,000
20	28,200	2.40	1,830,000	4,870	.28	36,800	4,800	.68	88,100
21	25,000	2.20	1,480,000	4,510	.22	26,800	4,470	.57	68,800
22	21,900	1.91	1,130,000	4,220	.19	21,600	4,380	.48	56,800
23	19,200	1.64	850,000	4,110	.24	26,600	4,290	.61	70,700
24	16,900	1.36	621,000	5,180	.26	36,400	4,630	1.12	140,000
25	14,900	1.24	499,000	4,830	1.24	162,000	4,200	.52	59,000
26	13,600	1.14	419,000	4,510	.32	39,000	4,370	.91	107,000
27	12,400	.98	328,000	4,490	.34	41,200	4,200	.78	88,500
28	11,300	.71	217,000	4,450	.34	40,900	3,960	.31	33,100
29	11,200	.52	157,000	4,310	.26	30,300	4,220	.40	45,600
30	11,800	.40	127,000	4,690	.19	24,100	10,400	1.13	317,000
31	14,500	1.32	517,000	4,290	.52	60,200			
Monthly load (tons)				27,760,000	5,370,000				12,740,000

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1937

Monthly load (tons) 16,870,000

1,398,000

1,497,000

1938

	January		February		March	
1	5,090	0.11	15,100	5,110	0.09	12,400
2	5,090	.11	15,100	5,490	.11	16,300
3	4,930	.10	13,300	5,620	.15	22,800
4	4,750	.10	12,800	5,490	.12	17,800
5	4,630	.10	12,500	5,620	.14	21,200
6	4,820	.11	14,300	5,750	.15	23,300
7	5,330	.09	13,000	6,010	.24	38,900
8	5,540	.11	16,500	6,010	.16	26,000
9	5,820	.13	20,400	6,140	.20	33,200
10	5,890	.13	20,700	6,280	.18	30,500
11	5,750	.14	21,700	6,140	.20	33,200
12	5,320	.12	17,200	6,010	.17	27,600
13	4,850	.09	11,800	5,880	.16	25,400
14	4,580	.08	9,890	6,280	.18	30,500
15	4,580	.07	8,660	7,570	.42	85,800
16	4,680	.07	8,850	7,720	.36	75,000
17	4,970	.08	10,700	8,340	.81	182,000
18	5,230	.10	14,100	8,340	.69	155,000
19	5,540	.12	17,900	8,020	.63	136,000
20	5,910	.15	23,900	7,720	.57	119,000
21	6,660	.16	28,800	7,420	.45	90,200
22	7,180	.24	46,500	7,120	.50	96,100
23	6,950	.28	52,500	6,700	.35	63,300
24	6,700	.23	41,600	6,280	.27	45,800
25	6,620	.19	34,000	6,010	.23	37,300
26	6,360	.17	29,200	5,750	.21	32,600
27	5,970	.14	22,600	5,750	.20	31,000
28	5,660	.14	21,400	6,010	.20	32,500
29	5,390	.13	18,900	-----	-----	13,800
30	4,990	.12	16,200	-----	-----	16,400
31	4,700	.10	12,700	-----	-----	15,700
Monthly load (tons)		622,800		1,541,000		29,590,000

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1938

Day	April			May			June		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1.	14,600	1.08	426,000	58,600	2.00	3,160,000	85,400	0.92	2,120,000
2.	13,400	.90	326,000	63,700	2.00	3,440,000	94,900	.90	2,310,000
3.	12,200	.68	224,000	65,500	1.52	2,690,000	96,600	1.10	2,840,000
4.	11,200	.65	197,000	69,200	1.48	2,770,000	94,100	.88	2,240,000
5.	10,300	.60	167,000	62,600	1.46	2,470,000	93,400	.84	2,120,000
6.	9,490	.51	131,000	56,900	1.46	2,240,000	95,600	.72	1,860,000
7.	9,150	.44	109,000	53,100	1.32	1,890,000	99,400	.74	1,990,000
8.	9,830	.53	141,000	46,900	1.16	1,470,000	98,700	.71	1,890,000
9.	10,300	.55	153,000	41,100	1.00	1,110,000	98,700	.68	1,810,000
10.	10,500	.59	167,000	37,000	.95	949,000	94,100	.79	2,010,000
11.	11,200	.64	194,000	33,600	.80	726,000	87,500	.66	1,560,000
12.	11,200	.57	172,000	30,500	.70	576,000	84,000	.50	1,130,000
13.	10,700	.47	136,000	28,300	.51	390,000	79,200	.68	1,450,000
14.	10,900	.49	144,000	26,900	.44	320,000	76,400	.64	1,320,000
15.	13,200	.55	196,000	26,300	.44	312,000	73,100	.69	1,360,000
16.	17,900	1.18	570,000	28,300	.54	413,000	77,100	.66	1,370,000
17.	20,700	1.46	816,000	36,600	.78	771,000	79,200	.54	1,150,000
18.	21,000	1.58	896,000	51,500	1.31	1,820,000	71,200	.64	1,230,000
19.	18,700	1.30	656,000	63,700	1.45	2,490,000	66,700	.56	1,010,000
20.	18,200	1.06	521,000	68,600	1.43	2,650,000	63,700	.52	894,000
21.	23,400	1.72	1,090,000	68,600	1.20	2,220,000	63,100	.51	869,000
22.	36,600	2.38	2,350,000	70,500	1.27	2,420,000	61,400	.62	1,030,000
23.	43,400	2.94	3,450,000	68,600	1.22	2,260,000	58,600	.52	823,000
24.	47,400	2.92	3,740,000	67,400	1.04	1,890,000	62,000	.63	1,050,000
25.	53,100	2.44	3,500,000	66,100	1.04	1,860,000	73,100	.60	1,180,000
26.	56,400	2.57	3,910,000	59,100	.90	1,440,000	73,800	.84	1,670,000
27.	62,000	2.81	4,700,000	55,300	.88	1,310,000	68,600	.56	1,040,000
28.	66,100	2.51	4,480,000	54,700	.82	1,210,000	63,100	.48	818,000
29.	65,500	2.20	3,890,000	58,000	.82	1,280,000	62,600	.40	676,000
30.	57,400	2.22	3,440,000	66,100	.86	1,530,000	64,900	.73	1,280,000
31.				74,400	1.11	2,230,000			
	Monthly load (tons)			40,890,000		52,310,000			44,100,000

1938

	July			August			September		
	1.	2.	3.	4.	5.	6.	7.	8.	9.
1.	60,200	0.74	1,200,000	11,300	0.12	36,600	5,570	0.13	19,600
2.	60,200	.96	1,560,000	10,900	.17	50,000	6,230	.14	23,500
3.	63,100	1.00	1,700,000	11,300	.17	51,900	8,400	.62	141,000
4.	56,400	.76	1,160,000	10,900	.16	47,100	15,000	3.72	1,510,000
5.	50,500	.46	627,000	10,200	1.14	38,600	19,300	3.04	1,580,000
6.	45,900	.43	533,000	9,680	.12	31,400	22,500	4.34	2,640,000
7.	43,000	.40	464,000	9,030	.11	26,800	25,400	3.97	2,720,000
8.	40,100	.32	346,000	8,870	.09	21,600	21,000	2.94	1,670,000
9.	36,600	.29	287,000	10,400	.15	42,100	21,300	2.65	1,520,000
10.	33,200	.32	287,000	10,200	1.24	341,000	21,000	2.59	1,470,000
11.	30,200	.26	212,000	10,000	1.78	481,000	22,200	2.28	1,370,000
12.	28,000	.22	166,000	9,030	.84	205,000	22,500	3.01	1,880,000
13.	25,900	.20	140,000	9,350	.55	139,000	21,000	3.56	2,020,000
14.	24,600	.18	120,000	12,200	.38	125,000	20,100	2.82	1,530,000
15.	22,700	.16	98,100	10,700	.76	220,000	22,200	2.80	1,680,000
16.	20,900	.16	90,300	10,000	.86	232,000	23,400	2.68	1,690,000
17.	19,800	.13	69,500	9,680	.81	212,000	19,600	2.20	1,160,000
18.	20,400	.14	77,100	11,600	.60	188,000	17,300	1.58	738,000
19.	20,400	.15	82,600	10,700	1.64	474,000	16,800	1.67	758,000
20.	19,500	.18	94,800	9,510	1.92	493,000	15,000	1.46	591,000
21.	18,700	.24	121,000	8,550	1.26	291,000	13,800	1.18	440,000
22.	17,300	.35	163,000	7,800	.95	200,000	12,800	1.33	460,000
23.	16,300	.31	136,000	7,070	.64	122,000	12,000	.86	279,000
24.	16,100	.23	100,000	6,650	1.04	187,000	11,300	.78	238,000
25.	15,300	.18	74,400	6,230	.82	138,000	10,700	.67	194,000
26.	14,600	.19	74,900	5,960	.56	90,100	10,000	.44	119,000
27.	14,200	.19	72,800	5,570	.34	51,100	9,510	.34	87,300
28.	13,300	.19	68,200	5,440	.26	38,200	9,200	.27	67,100
29.	12,600	.16	54,400	5,180	.34	47,600	9,030	.24	58,500
30.	12,000	.14	45,400	5,050	.20	27,300	8,550	.20	46,200
31.	12,000	.13	42,100	4,790	.19	24,600			
	Monthly load (tons)			10,270,000		4,673,000			28,650,000

Estimated.

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1938

Day	October			November			December		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	8,070	0.18	39,200	9,000	0.20	48,600	5,900	0.04	6,370
2	7,830	.19	40,200	8,790	.19	45,100	5,300	.03	4,290
3	7,660	.17	35,200	8,740	.22	51,900	5,120	.02	2,760
4	7,770	.15	31,500	8,820	.17	40,500	5,350	.03	4,330
5	7,140	.19	36,600	8,520	.16	36,800	5,880	.03	4,760
6	7,040	.16	30,400	8,440	.15	34,200	6,340	.04	6,850
7	6,870	.29	53,800	8,690	.13	30,500	6,620	.05	8,940
8	6,890	.17	31,600	9,010	.14	34,100	6,870	.05	9,270
9	6,620	.15	26,800	9,270	.14	35,000	7,150	.06	11,600
10	6,580	.16	28,400	9,140	.13	32,100	7,220	.07	13,600
11	8,760	.20	47,300	9,050	.13	31,800	7,650	.07	14,500
12	12,400	.39	131,000	9,010	.12	29,200	8,370	.09	20,300
13	11,800	.67	213,000	8,970	.12	29,100	8,430	.10	22,800
14	12,500	.70	236,000	8,650	.12	28,000	8,260	.08	17,800
15	12,100	.52	170,000	8,840	.14	33,400	8,200	.08	17,700
16	11,300	.61	186,000	9,010	.14	34,100	8,280	.08	17,900
17	12,100	.76	248,000	9,140	.14	34,500	8,380	.09	20,400
18	12,000	.67	217,000	8,970	.12	29,100	8,130	.08	17,600
19	11,000	.45	134,000	8,680	.10	23,400	7,640	.07	14,400
20	10,500	.62	176,000	8,100	.09	19,700	7,250	.06	11,700
21	10,200	.51	140,000	7,950	.08	17,200	6,800	.06	11,000
22	10,300	.40	111,000	8,130	.07	15,400	7,080	.04	7,650
23	10,600	.50	143,000	8,100	.07	15,300	7,520	.07	14,200
24	11,100	.42	126,000	7,980	.07	15,100	7,620	.10	20,600
25	10,800	.48	140,000	7,680	.07	14,500	7,350	.08	15,900
26	10,400	.46	129,000	7,540	.06	12,200	7,320	.08	15,800
27	10,100	.35	95,400	7,400	.06	12,000	7,270	.09	17,700
28	9,820	.32	84,800	7,100	.06	11,500	7,040	.06	11,400
29	9,870	.34	90,600	6,680	.05	9,020	6,610	.05	8,920
30	9,530	.28	72,000	6,160	.05	8,320	5,910	.05	7,980
31	9,220	.34	84,600	-----	-----	-----	5,010	.04	5,410
Monthly load (tons)			3,328,000	-----			811,600	-----	
384,400									

1939

	January			February			March		
	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day
1	4,750	0.04	5,130	5,920	0.04	6,390	6,040	0.08	13,000
2	4,740	.03	3,840	5,820	.04	6,290	6,050	.06	9,800
3	4,610	.03	3,730	5,950	.03	4,820	6,020	.06	9,750
4	4,450	.03	3,600	5,920	.04	6,390	6,050	.07	11,400
5	4,410	.03	3,570	5,790	.04	6,250	6,040	.06	9,780
6	4,800	.03	3,890	5,690	.04	6,150	6,150	.05	8,300
7	5,360	.02	2,890	5,400	.04	5,830	6,240	.05	8,420
8	5,600	.03	4,540	5,090	.03	4,120	6,160	.06	10,000
9	5,610	.04	6,060	5,060	.03	4,100	6,130	.06	9,930
10	5,790	.04	6,250	5,060	.03	4,100	6,080	.06	9,850
11	6,050	.04	6,530	5,410	.02	2,920	5,980	.06	9,690
12	6,260	.04	6,760	5,880	.03	4,760	6,100	.06	9,880
13	6,270	.04	6,770	5,910	.04	4,380	6,650	.07	12,600
14	6,310	.04	6,810	5,610	.03	4,540	7,540	.10	20,400
15	6,120	.05	8,260	5,340	.03	4,330	8,460	.17	38,800
16	6,060	.05	8,180	5,230	.03	4,240	9,240	.28	69,900
17	6,090	.04	6,580	5,350	.02	2,990	10,000	.34	91,800
18	6,130	.04	6,620	5,740	.02	3,100	10,400	.54	152,000
19	6,050	.04	6,530	6,040	.04	6,520	10,600	.60	172,000
20	6,120	.04	6,610	6,050	.04	6,530	10,900	.68	200,000
21	5,930	.04	6,400	5,930	.04	6,400	11,200	.89	269,000
22	6,170	.03	5,000	6,050	.04	6,530	12,000	1.07	347,000
23	6,020	.03	4,880	6,160	.04	6,650	21,100	1.82	1,040,000
24	6,170	.04	6,660	6,060	.06	9,820	27,400	1.84	1,360,000
25	6,690	.04	7,230	6,080	.09	14,800	27,200	1.92	1,420,000
26	6,760	.07	12,800	5,910	.08	12,800	28,500	2.06	1,590,000
27	6,610	.06	10,700	5,870	.06	9,440	28,000	2.12	1,300,000
28	6,480	.05	8,750	5,870	.07	11,100	27,000	1.83	1,330,000
29	6,450	.05	8,710	-----	-----	-----	27,500	1.66	1,230,000
30	6,580	.04	7,110	-----	-----	-----	28,000	1.50	1,130,000
31	6,430	.05	8,680	-----	-----	-----	27,800	1.45	1,090,000
Monthly load (tons)			200,100	-----			178,200	-----	
13,250,000									

<sup>1</sup> Estimated.

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grana Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1939

Day	April			May			June		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	25,500	1.24	854,000	22,500	0.53	322,000	32,800	0.40	354,000
2	23,700	1.10	704,000	24,200	.67	438,000	34,600	.41	383,000
3	22,000	1.05	624,000	29,600	.84	671,000	37,900	.44	450,000
4	20,300	.98	537,000	33,400	.94	848,000	39,300	.47	499,000
5	19,500	.88	463,000	37,000	1.04	1,040,000	40,300	.52	566,000
6	21,900	1.60	946,000	39,800	1.13	1,210,000	37,500	.54	547,000
7	23,800	1.68	1,080,000	40,600	1.12	1,230,000	37,400	.53	535,000
8	25,400	1.36	933,000	42,600	1.14	1,310,000	39,900	.57	614,000
9	24,800	1.28	857,000	45,300	1.17	1,430,000	41,200	.52	578,000
10	24,000	.90	553,000	44,400	.95	1,140,000	39,000	.47	495,000
11	22,600	.83	506,000	40,800	.94	1,040,000	36,500	.37	365,000
12	21,800	.64	377,000	39,500	.90	960,000	34,400	.34	316,000
13	22,000	.64	380,000	40,100	.77	834,000	31,900	.32	276,000
14	21,500	.58	337,000	41,100	.77	854,000	29,400	.27	214,000
15	20,200	.58	316,000	42,600	.79	909,000	28,000	.25	189,000
16	18,700	.47	237,000	41,500	.67	751,000	27,100	.27	198,000
17	18,100	.47	230,000	38,400	.66	684,000	26,800	.30	217,000
18	18,500	.43	215,000	38,000	.73	749,000	27,000	.31	226,000
19	18,200	.38	187,000	39,300	.63	668,000	26,600	.26	187,000
20	17,200	.36	167,000	39,400	.61	649,000	24,600	.24	159,000
21	16,300	.30	132,000	38,100	.58	597,000	23,500	.20	127,000
22	15,800	.24	102,000	37,500	.55	557,000	21,900	.20	118,000
23	15,300	.30	124,000	40,700	.69	758,000	20,100	.20	109,000
24	15,500	.26	109,000	44,400	.80	959,000	18,500	.13	64,900
25	16,100	.26	113,000	46,600	.75	944,000	16,300	.14	61,600
26	16,800	.32	145,000	48,100	.67	870,000	14,900	.10	40,200
27	20,300	.58	318,000	46,600	.69	868,000	14,100	.08	30,500
28	21,800	.54	318,000	42,600	.63	725,000	13,900	.09	33,800
29	21,000	.42	238,000	39,600	.54	577,000	13,900	.10	37,500
30	21,900	.56	331,000	36,000	.44	428,000	13,600	.10	36,700
31				33,700	.43	391,000			
Monthly load (tons)		12,460,000		25,410,000				8,027,000	

1939

	July			August			September		
	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day
1	13,400	0.09	32,600	3,980	0.01	1,070	2,890	0.07	5,460
2	13,000	.07	24,600	3,920	.01	1,060	3,670	.36	35,700
3	12,400	.06	20,100	3,580	.01	967	3,880	.35	36,700
4	11,700	.06	19,000	3,550	.01	958	3,860	.15	15,600
5	11,200	.04	12,100	3,490	.05	4,710	5,140	.68	94,400
6	10,600	.05	14,300	3,730	.08	8,060	7,640	.52	107,000
7	10,200	.04	11,000	4,570	.02	2,470	8,540	1.65	380,000
8	9,820	.04	10,600	4,930	.01	1,330	10,300	1.84	512,000
9	9,370	.04	10,100	4,930	.29	38,600	12,200	4.76	1,570,000
10	9,130	.04	9,860	4,930	.53	70,500	11,100	2.30	689,000
11	8,680	.04	9,370	4,690	.16	20,300	13,200	1.58	563,000
12	8,270	.03	6,700	4,620	.14	17,500	13,800	4.33	1,610,000
13	7,880	.03	6,380	5,400	.23	33,500	17,300	4.66	2,180,000
14	7,650	.02	4,130	5,010	.11	14,900	25,200	6.37	4,330,000
15	7,400	.02	4,000	5,230	.12	16,900	18,100	5.70	2,790,000
16	7,050	.03	5,710	5,380	.28	40,700	14,800	3.82	1,530,000
17	6,990	.02	3,770	4,920	.11	14,600	15,600	3.75	1,580,000
18	6,720	.03	5,440	4,570	.20	24,700	12,600	2.36	803,000
19	6,410	.02	3,460	4,270	.25	28,800	11,600	1.44	451,000
20	6,040	.02	3,260	3,900	.21	22,100	10,700	1.39	402,000
21	5,690	.02	3,070	3,580	.15	14,500	9,970	1.58	425,000
22	5,430	.03	4,400	3,400	.14	12,900	9,130	1.44	355,000
23	5,190	.02	2,800	3,240	.10	8,750	8,250	1.36	303,000
24	5,040	.02	2,720	3,100	.07	5,860	7,720	.99	206,000
25	4,820	.02	2,600	3,020	.07	5,710	7,080	.61	117,000
26	4,720	.02	2,550	2,910	.07	5,500	6,720	.60	109,000
27	4,520	.02	2,440	2,830	.05	3,820	6,300	.49	83,300
28	4,350	.01	1,170	2,880	.05	3,890	6,640	.42	73,300
29	4,240	.01	1,140	2,890	.09	7,020	8,630	.45	105,000
30	4,040	.01	1,090	2,790	.16	12,100	7,380	.39	77,700
31	4,000	.01	1,080	2,850	.05	3,850			
Monthly load (tons)		241,500		447,600				21,540,000	

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1939

Day	October			November			December		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	5,870	0.42	66,600	5,100	0.08	11,000	5,280	0.06	8,550
2	5,750	.84	130,000	5,470	.08	11,800	5,320	.06	8,620
3	5,950	.50	80,300	5,450	.10	14,700	5,320	.06	8,620
4	5,820	.30	47,100	5,340	.09	13,000	5,310	.06	8,600
5	5,930	.27	47,100	5,390	.09	13,100	5,450	.05	7,360
6	5,870	.32	50,700	5,340	.09	13,000	5,480	.06	8,880
7	5,830	.29	45,600	5,310	.09	12,900	5,360	.05	7,240
8	5,750	.22	34,200	5,340	.10	14,400	5,340	.06	8,650
9	5,650	.17	25,900	5,470	.10	14,800	5,300	.06	8,960
10	5,690	.14	21,500	5,560	.09	13,500	5,230	.06	8,470
11	5,700	.15	23,100	5,710	.09	13,900	5,130	.06	8,310
12	5,870	.14	22,200	5,900	.10	15,900	5,150	.06	8,340
13	5,970	.12	19,300	5,990	.10	16,200	5,170	.06	8,380
14	6,330	.12	20,500	6,060	.10	16,400	5,170	.06	8,380
15	6,470	.16	28,000	6,220	.12	20,200	5,180	.07	9,790
16	6,300	.15	25,500	6,090	.10	16,400	5,190	.05	7,010
17	6,500	.16	28,100	6,020	.10	16,200	5,220	.06	8,460
18	6,480	.17	29,700	5,920	.09	14,400	5,240	.06	8,490
19	6,190	.17	28,400	5,710	.08	12,300	5,140	.06	8,330
20	6,040	.26	42,400	5,730	.08	12,400	5,060	.07	9,560
21	5,950	.20	32,100	5,710	.07	10,800	5,020	.08	10,800
22	5,870	.16	25,400	5,690	.08	12,300	4,890	.08	10,600
23	5,660	.12	18,300	5,650	.07	10,700	4,870	.07	9,200
24	5,440	.24	35,300	5,540	.07	10,500	4,840	.06	7,840
25	5,380	.18	26,100	5,340	.06	8,630	4,930	.06	7,990
26	5,220	.18	25,400	5,340	.06	8,650	4,860	.06	7,870
27	5,080	.12	16,500	5,190	.06	8,410	4,570	.06	7,400
28	5,020	.10	13,600	5,190	.06	8,410	4,170	.08	9,010
29	4,980	.09	12,100	5,240	.06	8,490	4,160	.09	10,100
30	4,980	.08	10,800	5,260	.07	9,940	4,320	.11	12,800
31	4,840	.08	10,400				4,340	.10	11,700
Monthly load (tons)			1,042,000	383,400			273,900		

1940

	January			February			March		
	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day
1	3,980	0.04	4,300	4,720	0.10	12,700	5,650	0.14	21,400
2	3,610	.04	3,900	5,000	.08	10,800	7,820	.24	50,700
3	3,360	.04	3,630	5,410	.08	11,700	8,790	.36	85,400
4	3,430	.04	3,700	5,800	.08	12,500	8,610	.95	221,000
5	3,560	.04	3,840	6,870	.18	33,400	8,000	.87	188,000
6	3,740	.04	4,040	7,350	.19	37,700	7,520	.68	138,000
7	4,220	.04	4,560	7,400	.57	114,000	6,990	.57	108,000
8	5,130	.07	9,700	7,030	.53	101,000	8,320	.56	126,000
9	5,350	.07	10,100	6,750	.41	74,700	9,000	.55	134,000
10	5,390	.09	13,100	6,410	.34	58,800	8,580	.41	98,000
11	5,620	.09	13,700	6,090	.29	47,700	8,930	.44	106,000
12	5,820	.10	15,700	5,750	.21	32,600	8,520	.45	104,000
13	5,880	.10	15,900	5,600	.20	30,200	8,120	.36	78,900
14	6,360	.13	22,300	5,520	.18	26,800	7,920	.32	68,400
15	7,170	.63	122,000	5,470	.16	23,600	8,260	.30	66,900
16	6,580	.18	32,000	5,310	.14	20,100	7,820	.45	95,000
17	6,010	.21	34,100	5,320	.12	17,200	7,460	.35	70,500
18	5,870	.21	33,300	5,390	.11	16,000	7,200	.28	54,400
19	5,580	.16	24,100	5,270	.10	14,200	6,990	.24	45,300
20	5,050	.12	16,400	5,150	.10	13,900	6,650	.21	37,700
21	4,460	.11	13,200	5,120	.08	11,100	6,290	.18	30,600
22	4,000	.10	10,800	5,150	.07	9,730	6,270	.16	27,100
23	3,560	.10	9,610	5,180	.07	9,790	6,450	.16	27,900
24	2,870	.07	5,420	5,010	.07	9,470	6,500	.17	29,800
25	2,660	.04	2,870	4,880	.06	7,910	6,640	.17	30,500
26	3,130	.04	3,380	4,980	.08	10,800	6,710	.20	36,200
27	3,440	.04	3,720	5,180	.07	9,790	6,940	.18	33,700
28	3,510	.06	5,690	5,390	.07	10,200	7,280	.18	35,400
29	3,870	.06	6,270	5,360	.09	13,000	8,020	.30	65,000
30	4,360	.07	8,240				8,460	.32	73,100
31	4,670	.07	8,830				9,050	.38	92,900
Monthly load (tons)			468,400	801,400			2,377,000		

## QUANTITIES OF SUSPENDED SEDIMENT

51

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1940

Day	April			May			June		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1.....	9,250	0.38	94,900	23,100	1.00	624,000	34,500	0.69	643,000
2.....	10,200	.48	132,000	22,900	.99	612,000	34,500	.65	605,000
3.....	10,300	.46	128,000	22,900	.77	476,000	36,500	.58	572,000
4.....	9,800	.44	116,000	21,400	.79	456,000	39,500	.59	629,000
5.....	9,530	.36	92,600	20,000	.69	373,000	41,600	.70	786,000
6.....	9,580	.35	90,500	18,900	.66	337,000	41,200	.65	723,000
7.....	9,870	.42	112,000	19,100	.67	346,000	39,900	.54	582,000
8.....	9,920	.41	110,000	22,800	.68	419,000	37,400	.62	626,000
9.....	9,210	.42	104,000	16,300	1.02	724,000	34,600	.54	504,000
10....	8,810	.30	71,400	7,200	.86	632,000	32,200	.53	461,000
11....	9,220	.43	107,000	11,400	1.09	924,000	30,700	.42	348,000
12....	9,240	.43	107,000	11,800	1.19	1,020,000	28,400	.36	276,000
13....	9,400	.48	122,000	12,900	1.10	977,000	25,900	.26	182,000
14....	9,130	.38	93,700	16,700	1.26	1,250,000	23,300	.23	145,000
15....	8,580	.35	81,100	4,400	1.20	1,120,000	21,600	.20	117,000
16....	8,480	.33	75,600	12,100	1.19	1,350,000	20,400	.18	99,100
17....	8,520	.29	66,700	4,400	1.13	1,360,000	19,900	.15	80,600
18....	8,710	.26	61,100	5,500	1.28	1,570,000	20,200	.19	104,000
19....	9,300	.28	70,300	4,400	1.17	1,400,000	20,700	.21	117,000
20....	9,830	.38	101,000	4,600	1.22	1,470,000	20,400	.18	99,100
21....	10,600	.42	120,000	3,900	.96	1,140,000	19,100	.20	103,000
22....	10,900	.50	147,000	6,600	.88	965,000	18,800	.15	76,100
23....	10,600	.42	120,000	17,800	.80	816,000	18,000	.14	68,000
24....	11,200	.50	151,000	6,900	.78	777,000	16,900	.13	59,300
25....	16,100	.99	430,000	4,800	.64	601,000	16,200	.12	52,500
26....	19,100	1.17	603,000	3,300	.57	512,000	15,700	.09	38,200
27....	19,600	1.14	603,000	3,200	.60	520,000	15,400	.10	41,600
28....	20,700	1.25	699,000	1,700	.52	445,000	14,700	.11	43,700
29....	21,500	1.05	610,000	3,200	.55	477,000	14,100	.08	30,500
30....	22,000	.97	576,000	3,200	.56	496,000	13,400	.08	28,900
31....				3,100	.48	429,000			
Monthly load (tons)			5,996,000			24,620,000			8,241,000

1940

	July			August			September		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1.....	12,500	0.08	27,000	6,440	0.40	67,600	5,430	2.76	405,000
2.....	11,600	.07	21,900	5,320	.68	97,700	5,260	2.21	314,000
3.....	11,200	.06	18,100	4,260	1.94	223,000	5,530	1.58	236,000
4.....	12,000	.10	32,400	3,630	2.26	222,000	5,480	1.30	192,000
5.....	10,500	.08	22,700	3,310	2.14	191,000	5,430	1.02	150,000
6.....	9,610	.07	18,200	3,130	1.70	144,000	5,210	1.25	176,000
7.....	9,430	.06	15,300	2,980	1.28	103,000	6,030	1.14	186,000
8.....	8,660	.22	51,400	2,850	.84	64,600	5,020	.92	125,000
9.....	7,980	.32	68,900	2,740	.49	36,300	4,400	4.70	558,000
10....	7,580	.40	81,900	2,600	.23	16,200	4,600	1.55	192,000
11....	7,380	.14	27,900	2,460	.22	14,600	4,110	.60	66,600
12....	7,060	.10	19,100	2,390	.18	11,600	3,760	1.02	104,000
13....	6,620	.08	14,300	2,320	.12	7,520	3,680	.54	53,700
14....	6,240	.07	11,800	2,350	.09	5,710	7,270	.87	171,000
15....	6,080	.06	9,850	2,570	.06	4,160	8,980	4.83	1,170,000
16....	5,800	.05	7,830	3,220	.05	4,350	6,200	5.24	877,000
17....	5,500	.04	5,940	5,060	2.26	309,000	5,530	3.12	466,000
18....	5,190	.05	7,530	3,330	4.94	444,000	8,690	1.90	446,000
19....	4,840	.05	6,530	2,990	3.06	247,000	11,300	4.97	1,520,000
20....	4,660	.04	5,030	2,700	2.64	183,000	11,400	4.57	1,400,000
21....	4,920	.03	3,990	2,410	1.14	74,200	12,700	4.25	1,460,000
22....	5,470	.02	2,950	2,380	.68	43,700	13,200	3.44	1,230,000
23....	6,120	.03	4,960	3,100	1.32	110,000	13,300	4.96	1,780,000
24....	4,980	.04	5,380	4,940	4.93	658,000	14,200	3.56	1,360,000
25....	4,480	.10	12,100	7,890	5.12	1,090,000	14,100	3.96	1,510,000
26....	4,430	.09	10,800	6,990	5.87	1,110,000	11,200	3.28	992,000
27....	4,660	.10	12,600	7,730	5.48	1,140,000	9,650	3.42	891,000
28....	7,070	.23	43,900	9,230	3.98	992,000	9,030	2.88	702,000
29....	5,740	2.93	454,000	7,130	4.65	895,000	8,900	2.10	505,000
30....	4,600	2.01	250,000	5,390	4.57	665,000	11,900	2.78	893,000
31....	5,340	1.24	179,000	4,830	3.77	492,000			
Monthly load(tons)			1,453,000			9,666,000			20,130,000

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1940

Day	October			November			December		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	22,300	8.06	4,850,000	8,750	0.65	154,000	6,590	0.28	49,800
2	26,200	7.05	4,990,000	8,310	.60	135,000	6,410	.23	39,800
3	19,200	4.61	2,390,000	7,360	.59	117,000	6,200	.24	40,200
4	17,200	4.14	1,920,000	6,970	.54	102,000	6,020	.18	29,300
5	16,900	2.86	1,300,000	6,860	.56	104,000	6,020	.15	24,400
6	18,800	4.17	2,120,000	6,750	.54	98,400	6,090	.16	26,300
7	23,100	4.33	2,700,000	6,490	.47	82,400	6,080	.18	29,500
8	17,700	3.62	1,730,000	6,440	.40	69,600	6,130	.16	26,500
9	17,300	3.29	1,570,000	6,760	.34	62,100	6,270	.16	27,100
10	17,000	2.82	1,290,000	6,830	.28	51,600	6,440	.16	27,800
11	14,400	1.67	649,000	6,770	.26	47,500	6,420	.20	34,700
12	13,000	1.44	505,000	6,550	.24	42,400	6,410	.28	48,500
13	12,000	1.38	447,000	6,410	.20	34,600	7,030	.20	38,000
14	11,400	1.08	332,000	6,450	.25	43,500	7,540	.32	65,100
15	10,600	1.03	295,000	6,520	.20	35,200	7,770	.25	52,400
16	9,850	1.80	213,000	6,610	.22	39,300	8,250	.69	154,000
17	9,300	.75	188,000	6,660	.21	35,100	7,580	.62	127,000
18	8,920	.70	169,000	6,360	.17	29,200	6,910	.37	69,000
19	8,520	.66	152,000	6,140	.16	26,500	5,910	.32	51,100
20	8,070	.58	126,000	6,220	.15	25,200	4,830	.32	41,700
21	7,680	.66	137,000	9,810	.50	132,000	4,300	.24	27,900
22	7,440	.48	96,400	10,500	.55	241,000	5,940	.34	54,500
23	7,300	.34	67,000	8,770	.99	284,000	5,320	.54	77,600
24	7,110	.34	65,300	7,700	.83	173,000	5,320	.50	71,800
25	6,890	.31	57,700	7,860	.88	187,000	7,520	.94	191,000
26	6,800	.26	47,700	7,650	.76	157,000	6,720	.94	171,000
27	6,870	.24	63,100	7,350	.52	103,000	9,140	2.09	516,000
28	6,680	.25	45,100	7,200	.43	83,600	8,740	1.56	368,000
29	7,070	.84	160,000	7,070	.38	72,500	7,560	1.41	288,000
30	7,920	.48	103,000	6,770	.31	56,700	7,110	1.55	298,000
31	8,190	.51	113,000	-----	-----	-----	7,140	.84	162,000
Monthly load (tons)		28,900,000	-----	2,774,000			3,227,000		

1941

	January			February			March		
	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day
1	7,940	0.85	182,000	6,490	0.38	66,600	13,600	1.58	580,000
2	10,600	1.95	558,000	6,590	.43	76,500	13,400	1.48	535,000
3	11,300	2.66	812,000	6,580	.38	67,500	13,300	1.42	510,000
4	9,700	1.92	503,000	6,440	.34	59,100	12,600	1.27	432,000
5	8,170	1.12	247,000	6,410	.35	60,600	12,600	1.24	422,000
6	7,340	.95	188,000	6,410	.34	58,800	14,000	1.29	488,000
7	6,690	.80	144,000	6,280	.35	59,300	12,800	1.05	363,000
8	6,330	.66	113,000	6,020	.27	43,900	12,100	.90	294,000
9	5,930	.50	80,100	5,800	.27	42,300	11,700	.82	259,000
10	5,610	.36	54,500	6,370	.27	46,400	11,100	.72	216,000
11	5,340	.30	43,300	7,040	.78	148,000	10,100	.79	215,000
12	5,540	.22	32,900	6,760	.65	119,000	9,540	.66	170,000
13	13,500	9.87	3,600,000	6,730	.60	109,000	9,050	.56	137,000
14	7,590	3.44	705,000	6,870	.74	137,000	8,720	.59	139,000
15	6,630	1.63	292,000	7,920	.89	190,000	8,410	.48	109,000
16	6,730	1.10	200,000	7,890	.90	192,000	22,100	6.28	3,750,000
17	6,790	.78	143,000	8,090	.74	162,000	19,100	3.40	1,750,000
18	6,910	.88	164,000	9,060	.68	166,000	15,100	2.83	1,150,000
19	6,490	.64	112,000	11,300	1.64	500,000	14,000	2.44	922,000
20	6,220	.64	108,000	10,800	1.45	423,000	13,500	2.04	744,000
21	5,880	.52	82,600	11,300	1.33	406,000	13,100	1.85	654,000
22	5,540	.39	58,300	11,600	1.35	423,000	13,100	1.76	623,000
23	5,320	.30	43,100	14,800	2.19	875,000	13,200	1.70	606,000
24	5,310	.26	37,300	16,900	2.65	1,210,000	13,100	1.64	580,000
25	5,520	.28	41,700	16,100	2.17	943,000	15,000	1.70	688,000
26	6,200	.38	64,500	14,900	2.02	813,000	14,900	1.70	684,000
27	6,380	.35	60,300	14,300	1.88	726,000	16,000	1.94	838,000
28	6,980	.38	71,600	13,700	1.97	729,000	17,100	2.29	1,060,000
29	7,010	.49	92,700	-----	-----	-----	18,000	1.86	904,000
30	6,650	.45	80,800	-----	-----	-----	16,500	1.61	717,000
31	6,410	.43	74,400	-----	-----	-----	15,600	1.35	569,000
Monthly load (tons)		5,499,000	-----	8,851,000			21,110,000		

\* Estimated.

TABLE 9.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Grand Canyon, Ariz., Oct. 1, 1929, to Sept. 30, 1941—Continued*

1941

Day	April			May			June		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	15,800	1.33	567,000	39,900	1.94	2,090,000	78,700	0.78	1,660,000
2	15,700	1.24	526,000	40,100	2.64	2,860,000	75,100	.64	1,300,000
3	16,300	1.36	599,000	41,300	1.20	2,230,000	72,200	.70	1,360,000
4	18,100	1.54	753,000	44,600	1.57	1,890,000	70,700	.62	1,180,000
5	20,000	2.17	1,170,000	50,900	1.59	2,180,000	69,000	.63	1,170,000
6	19,300	1.92	1,000,000	56,900	1.79	2,750,000	67,400	.62	1,130,000
7	18,500	2.00	999,000	76,800	2.92	6,050,000	66,800	.68	1,230,000
8	18,000	1.46	710,000	73,600	1.99	3,950,000	67,700	.61	1,120,000
9	18,600	1.50	753,000	73,300	1.68	3,320,000	72,300	.72	1,410,000
10	19,600	1.54	815,000	76,400	1.43	2,950,000	81,700	1.06	2,340,000
11	19,700	1.36	723,000	79,200	1.68	3,590,000	83,500	1.32	2,980,000
12	19,800	1.24	663,000	82,700	1.87	4,180,000	77,700	1.46	3,060,000
13	21,700	1.32	773,000	86,800	1.55	3,630,000	70,200	.88	1,670,000
14	22,900	1.60	989,000	92,300	1.38	3,440,000	63,000	.93	1,580,000
15	23,400	1.79	1,130,000	101,600	1.34	3,680,000	58,600	.72	1,140,000
16	22,200	1.33	797,000	112,500	1.47	4,470,000	56,700	.60	919,000
17	21,400	1.45	838,000	119,200	1.45	4,670,000	56,300	.62	942,000
18	20,900	1.34	756,000	114,500	1.17	3,620,000	56,000	.48	726,000
19	20,200	1.10	600,000	103,700	1.06	2,970,000	57,200	.60	927,000
20	20,000	.95	513,000	99,100	1.18	3,160,000	59,800	.56	904,000
21	19,400	.88	461,000	99,200	.98	2,570,000	64,700	.62	1,080,000
22	19,100	.69	356,000	94,800	.83	2,120,000	72,400	1.65	1,270,000
23	18,300	.72	356,000	83,500	.70	1,580,000	75,100	.70	1,420,000
24	17,100	.66	305,000	76,600	.78	1,570,000	74,700	.58	1,170,000
25	18,500	.59	295,000	80,100	.92	1,990,000	74,000	.73	1,460,000
26	20,500	.87	482,000	83,100	1.28	2,870,000	73,700	.67	1,330,000
27	20,600	1.90	501,000	82,700	1.88	4,150,000	74,900	.62	1,250,000
28	21,800	1.00	589,000	84,900	1.42	3,260,000	70,100	.72	1,360,000
29	29,300	2.18	1,720,000	86,700	1.18	2,760,000	66,100	.58	1,040,000
30	33,000	2.44	2,170,000	87,500	.91	2,150,000	60,600	.55	900,000
31				84,200	.90	2,050,000			
Monthly load (tons)		22,910,000			94,760,000			41,020,000	

1941

	July			August			September		
1	56,200	1.05	759,000	14,200	0.30	115,000	7,740	0.71	148,000
2	50,400	.38	517,000	13,400	.28	94,100	7,140	.86	166,000
3	45,700	.36	444,000	12,400	.14	46,900	6,730	.84	153,000
4	42,600	.35	403,000	11,500	.11	34,200	6,790	.60	110,000
5	40,200	1.35	380,000	10,700	1.10	28,900	7,520	.39	79,200
6	37,800	.33	337,000	10,100	.08	21,800	7,650	1.30	62,000
7	36,400	.27	265,000	10,000	.07	18,900	7,180	1.30	58,200
8	36,100	.33	322,000	9,380	.07	17,700	6,790	.22	49,300
9	34,500	1.30	279,000	9,780	.12	31,700	6,610	.22	39,300
10	32,200	.24	209,000	9,610	.40	104,000	6,120	.38	59,500
11	30,100	.25	203,000	11,400	1.00	308,000	5,760	.35	54,400
12	29,400	.24	190,000	23,500	2.89	1,830,000	5,540	.28	41,900
13	28,400	.22	169,000	23,500	1.20	1,780,000	5,350	.39	56,300
14	27,900	.23	173,000	18,900	2.84	1,450,000	7,150	1.98	382,000
15	26,800	.20	145,000	17,300	1.20	934,000	8,460	2.02	461,000
16	25,700	1.20	139,000	17,800	1.39	668,000	10,100	1.68	458,000
17	24,100	.22	143,000	19,100	5.44	2,810,000	11,000	1.93	573,000
18	23,000	.21	130,000	18,400	3.41	1,690,000	12,400	1.65	552,000
19	22,400	1.20	121,000	17,100	1.30	1,380,000	12,700	3.03	1,040,000
20	21,600	1.20	117,000	17,500	2.07	978,000	11,600	1.25	783,000
21	20,700	.16	89,400	18,100	1.84	899,000	12,400	1.20	670,000
22	21,900	.28	166,000	16,900	1.69	771,000	10,700	1.40	404,000
23	21,300	1.28	161,000	14,900	1.20	483,000	12,200	1.35	445,000
24	22,300	.27	163,000	13,400	1.08	391,000	13,600	1.80	661,000
25	20,400	1.30	165,000	13,700	.99	366,000	23,300	2.09	1,320,000
26	20,300	.49	269,000	12,600	1.00	340,000	25,700	1.25	1,740,000
27	19,100	.53	273,000	11,500	1.00	310,000	19,300	2.71	1,410,000
28	18,600	.68	341,000	10,500	1.09	303,000	16,800	1.58	717,000
29	17,200	1.68	316,000	9,450	.98	250,000	16,500	1.45	646,000
30	15,600	.67	282,000	8,890	.82	197,000	21,200	1.88	1,080,000
31	14,800	.36	144,000	8,430	.69	157,000			
Monthly load (tons)		7,814,000			18,810,000			14,410,000	

<sup>1</sup> Estimated.

TABLE 10.—*Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936*

Sampling points: Except as otherwise indicated, samples were taken at points A to D at distances of 120, 180, 240, and 300 feet, respectively, from zero mark on cable at north bank; the letter x denotes sampling points A to D at distances of 100, 160, 280, and 360 feet from zero mark on cable; y denotes sampling points at 140, 200, 260, and 330 feet from zero mark; z denotes sampling points at 150, 210, 270, and 350 feet from zero mark.

Type of sample: I, Integrated; S, surface.

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1935</i>							
Apr. 1.....	10:10 a. m.....	4.87	0.88	0.90	0.98	0.96	I
Apr. 2.....	9:15 a. m.....	5.15	1.03	.93	.93	.92	I
	4:40 p. m.....	5.42	1.19	1.11	1.21	1.14	I
Apr. 3.....	9:05 a. m.....	5.71	1.25	1.24	1.32	1.22	I
	4:30 p. m.....	5.75	1.29	1.27	1.22	1.25	I
	4:30 p. m.....	5.75	.99	.95	.88	.85	S
Apr. 4.....	10:40 a. m.....	6.12	1.26	1.35	1.32	1.23	I
			1.26	1.16	1.20	.99	I z
				.87	.86	.83	S z
	4:30 p. m.....	5.91	1.29	1.28	1.16	1.32	I
			1.26	1.34	1.35	1.00	I z
				.95	.87	.93	S z
Apr. 5.....	9:15 a. m.....	6.00	1.43	1.18	1.40	1.23	I
	2:15 p. m.....	5.89	1.30	1.36	1.36	1.44	I
			1.12	1.05	.94	.93	S
	4:35 p. m.....	5.80	1.42	1.24	1.33	1.26	I
	7:05 p. m.....	5.75	1.33	1.24	1.26	1.24	I
			1.13	1.08	.94	.96	S
Apr. 6.....	9:30 a. m.....	6.16	1.43	1.34	1.42	1.32	I
	4:20 p. m.....	6.04	1.34	1.36	1.35	1.48	I
		6.04	1.20	1.20	1.00	.98	S
Apr. 7.....	9:45 a. m.....	6.74	1.53	1.40	1.38	1.36	I
		6.74	1.18	1.02	.89	.84	S
	4:45 p. m.....	6.72	1.40	1.38	1.44	1.28	I
Apr. 8.....	9:30 a. m.....	7.25	1.48	1.40	1.60	1.52	I
		7.25	1.29	1.17	1.18	1.22	S
	3:15 p. m.....	7.10	1.42	1.40	1.57	1.46	I
		7.10	1.29	.96	.84	.99	S
Apr. 9.....	9:40 a. m.....	7.22	1.41	1.46	1.57	1.57	I
		1.63	1.45	1.50	1.49	I x	
		1.38	1.13	.91	1.28	S x	
	4:35 p. m.....	7.04	1.30	1.29	1.45	1.29	I
		1.39	1.41	1.24	1.29	I x	
		1.29	.96	.91	1.26	S x	
Apr. 10.....	7:00 a. m.....	7.37	1.51	1.52	1.56	1.43	I
		1.22	.80	.78	.82	S	
	9:35 a. m.....	7.33	1.30	1.21	1.44	1.42	I
	2:55 p. m.....	7.38	1.46	1.51	1.46	1.39	S
				1.00	.95	1.00	
	5:00 p. m.....	7.48	1.72	1.66	1.82	1.79	I
	7:15 p. m.....	7.50	2.01	1.85	1.96	2.07	I
		1.72	1.45	1.38	1.29	S	
Apr. 11.....	9:30 a. m.....	9.47	2.57	2.99	2.78	2.54	I
		2.50	2.72	2.87	2.24	I y	
		2.12	1.11	.88	1.02	S y	
	5:35 p. m.....	9.47	3.55	3.47	3.78	4.43	I
		3.51	3.39	4.16	3.82	I y	
		3.15	2.39	2.37	2.41	S y	
Apr. 12.....	6:55 a. m.....	8.30	2.20	2.60	2.61	2.18	I
		2.00	1.49	1.42	1.54	S	
	10:15 a. m.....	8.32	1.99	2.20	2.78	1.96	I
	4:05 p. m.....	8.59	1.91	1.95	2.27	2.20	I
		1.67	1.16	1.21	1.13	S	
	7:15 a. m.....	8.59	1.94	2.01	1.90	1.86	I
		1.54	1.16	1.21	1.14	S	

TABLE 10.—*Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued*

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1935</i>							
Apr. 13	10:15 a. m.	7.96	1.57	1.68	1.69	1.48	I
	4:15 p. m.	7.73	1.42	1.50	1.78	1.42	I
Apr. 14	9:15 a. m.	6.99	1.24	1.50	1.47	1.20	I
	4:08 p. m.	6.91	1.19	1.39	1.37	1.08	I
Apr. 15	10:15 a. m.	6.87	1.15	1.15	1.12	1.03	I
			1.12	1.11	1.00		I x
			1.04	.87	.87		S x
	4:30 p. m.	6.70	1.21	1.08	1.23	1.08	I
			1.19	1.04	1.19		I x
			1.11	.91	.81		S x
Apr. 16	7:15 a. m.	6.30	0.96	0.84	0.94	0.78	I
			.82	.57	.63	.71	S
	10:45 a. m.	6.45	.98	1.01	.89	.79	I
	3:05 p. m.	6.46	.92	1.01	.99	.80	I
			.78	.64	.64	.73	S
	4:55 p. m.	6.43	.89	.90	.98	.77	I
	7:25 p. m.	6.47	.86	.92	.93	.75	I
			.71	.57	.55	.72	S
Apr. 17	9:20 a. m.	6.23	.75	.83	.91	.69	I
	4:25 p. m.	6.38	.85	.93	.88	.64	S
			.77	.58	.59	.68	
Apr. 18	9:30 a. m.	6.70	.78	.88	.92	.67	I
			.77	.78	.76		I y
			.51	.49	.54	.56	S y
	4:45 p. m.	6.90	.82	1.05	.82	.65	I
			.84	.95	1.17		I y
			.68	.55	.45	.65	S y
Apr. 19	6:45 a. m.	7.38	1.07	1.21	1.24	1.00	I
			.96	.66	.73	.79	S
	10:00 a. m.	7.39	.97	.96	1.09	.95	I
	1:10 p. m.	7.43	1.02	1.10	1.09	.86	I
			.95	.90	.74	.77	S
	4:10 p. m.	7.59	1.07	1.20	1.25	.91	I
	7:10 p. m.	7.72	1.33	1.35	1.37	1.10	I
			1.09	.67	.75	.73	S
Apr. 20	9:00 a. m.	7.94	1.23	1.33	1.28	1.21	I
	5:10 p. m.	8.19	1.56	1.64	2.05	1.34	I
Apr. 21	9:20 a. m.	8.28	1.45	1.48	1.46	1.48	I
			1.25	1.17	1.10	.92	S
	6:55 p. m.	8.30	1.24	1.38	1.35	1.17	I
Apr. 22	10:40 a. m.	8.49	1.30	1.40	1.45	1.20	I
			1.51	1.36	1.22	1.34	I x
			1.30	.77	.78	1.35	S x
	4:25 p. m.	8.80	1.28	1.46	1.58	1.33	I
			1.40	1.47	1.50	1.26	I x
			.99	1.01	.79	1.17	S x
Apr. 23	7:00 a. m.	8.37	1.14	1.23	1.14	1.15	I
			.98	.87	.63	.90	S
	11:55 a. m.	8.30	1.32	1.19	1.28	1.12	I
	3:05 p. m.	8.43	1.27	1.22	1.31	1.13	I
			1.18	.72	.81	1.09	S
	5:15 p. m.	8.43	1.29	1.20	1.41	1.23	I
	7:15 p. m.	8.46	1.24	1.06	1.36	1.25	I
			1.09	.84	.68	.81	S
Apr. 24	9:35 a. m.	8.04	1.23	1.22	1.30	1.15	I
			1.03	.85	.78	.72	S
	4:55 p. m.	8.24	1.14	1.13	1.29	1.28	I
Apr. 25	10:50 a. m.	8.11	1.05	1.15	1.20	.97	I
			1.15	1.10	1.18	.88	I y
			.84	.78	.65	.72	S y

TABLE 10.—Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1935</i>							
Apr. 25	4:18 p. m.	8.14	1.08 1.05 .96	1.13 1.19 .70	1.13 1.19 .74	1.04 1.08 .74	I I y S y
Apr. 26	7:00 a. m.	8.21	1.06 .90	.98 .66	1.21 .60	.85 .64	I S
	10:15 a. m.	8.29	.95	1.19	1.09	.81	I
	1:15 p. m.	8.30	.93	1.14	1.18	.78	I
	4:45 p. m.	8.41	1.06	1.13	1.36	.92	I
	7:15 p. m.	8.50	1.17	1.16	1.18	1.17	I
	7:15 p. m.	8.50	.90	.62	.52	.52	S
Apr. 27	9:10 a. m.	8.95	1.02	1.11	1.12	1.28	I
	3:40 p. m.	9.15	1.33	1.52	1.48	1.25	I
Apr. 28	9:10 a. m.	9.65	1.24	1.31	1.53	1.30	I
	4:05 p. m.	9.46	1.33	1.32	1.80	1.44	I
			1.10	.98	.72	.66	S
Apr. 29	8:55 a. m.	8.88	.99 1.22 1.03	1.20 1.30 .79	1.25 .92 .60	.94 1.12	I I x S x
	4:40 p. m.	8.60	1.00 1.16 1.00	.97 1.09 .76	1.24 .98 .62	.90 .92 .94	I I x S x
Apr. 30	9:22 a. m.	8.25	.90	.98	1.01	.82	I
	1:25 p. m.	8.21	.92	.90	.85	.82	I
			.71	.44	.54	.48	S
	4:35 p. m.	8.22	.84	.98	.96	.90	I
	7:10 p. m.	8.18	.93	.92	.94	.95	I
			.81	.65	.44	.51	S
May 1	10:10 a. m.	8.19	.91 .73	.79 .41	1.25 .46	.73 .40	I I
	4:35 p. m.	8.18	.78	.40	.85	.70	I
May 2	9:10 a. m.	8.33	.86 .86 .67	.93 .66 .44	.98 .95 .40	.77 .72 .45	I I y S y
	4:10 p. m.	8.42	1.01	1.04	1.13	.84	I
			.93	1.00	.99	.72	I
			.71	.44	.40	.41	S y
May 3	6:50 a. m.	8.70	.89	1.01	1.02	.84	I
	10:20 a. m.	8.84	.92	1.01	1.23	.94	I
	1:35 p. m.	8.96	1.01 .79				I
	2:35 p. m.	8.97	1.06 .78	1.18 .67	1.15 .55	.99 .42	I
	4:40 p. m.	9.09	.88	1.11	1.20	1.05	I
	7:35 p. m.	9.10	1.15	.92	1.26	1.05	I
			.99	.49	.56	.49	S
May 4	8:45 a. m.	9.37	1.15	1.03	1.53	1.04	I
	4:35 p. m.	9.56	1.06	1.07	1.62	1.31	I
May 5	12:00 n.	9.80	1.30 1.03	1.49 1.70	1.54 .71	1.15 .53	I S
	4:15 p. m.	9.95	1.15	1.19	1.35	1.04	I
May 6	10:10 a. m.	9.29	1.09 1.05	.90 .81	.88 .83	.85 .96	I I x
	4:55 p. m.	9.11	1.13 1.26	1.12 1.13	1.11 1.13	1.12 1.17	I I x
			1.10	.88	.61	1.01	S x

## QUANTITIES OF SUSPENDED SEDIMENT

57

TABLE 10.—Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
May 7 1935	6:55 a. m.	8.79	0.98	0.89	1.14	0.93	I
			.86	.67	.63	.58	S
	8:55 a. m.	8.70	.95	1.04	1.09	.99	I
	2:30 p. m.	8.78	.95	.84	.98	1.05	I
May 8			.78	.65	.60	.69	S
	5:00 p. m.	8.67	.94	.95	1.06	1.17	I
	12:15 p. m.	8.24	1.01	1.17	1.19	1.02	I
	5:00 p. m.	8.17	1.04	.97	1.06	1.01	S
May 9			.94		.70	.65	
	12:30 p. m.	8.13	.93	.97	.97	.93	I
			.88	.98	.97	.73	I y
			.72	.54	.59	.58	S y
May 10	4:45 p. m.	8.12	.86	.80	.86	.75	I
			.85	.91	.85	.75	I y
			.70	.53	.53	.54	S y
	6:55 a. m.	7.97	.68	.76	.77	.66	I
May 11	10:30 a. m.	7.94	.89	.68	.83	.63	I
	1:45 p. m.	7.99	.71	.71	.77	.63	I
			.57	.48	.40	.42	S
	5:04 p. m.	7.93	.72	.77	.78	.68	I
May 12	7:10 p. m.	7.91	.71	.70	.80	.70	I
			.57	.47	.45	.43	S
	9:30 a. m.	7.78	.71	.71	.76	.81	I
	4:48 p. m.	7.89	.64	.62	.64	.59	I
May 13	9:00 a. m.	7.90	.57	.59	.73	.55	I
	4:10 p. m.	8.01	.66	.75	.87	.67	I
			.56	.34	.32	.27	S
	9:15 a. m.	8.35	1.41	.67	.79	.63	I
May 14	5:05 p. m.	8.55	.87	.90	.93	.68	I
	7:03 a. m.	9.02	.75	.78	.87	.68	I
			.63	.44	.32	.32	S
	11:00 a. m.	9.17	.72	.82	.88	.71	I
May 15	4:30 p. m.	9.36	.73	.72	.87	.71	I
	7:20 p. m.	9.41	.88	.94	.91	.87	I
			.63	.49	.38	.34	S
	9:05 a. m.	9.91	.90	.91	.90	.82	I
May 16	4:20 p. m.	10.15	1.02	.85	1.25	1.22	I
			.95	.62	.60	.50	S
May 17	9:05 a. m.	10.70	1.14	1.22	1.04	1.08	I
			1.29	1.08	1.10	1.11	I y
			.89	.68	.53	.57	S y
	5:00 p. m.	10.88	.90	1.28	1.26	1.10	I
May 18			1.06	1.23	1.28	.95	I y
			.74	.77	.68	.66	S y
	7:05 a. m.	11.86	1.31	1.60	1.60	1.44	I
			1.19	1.12	1.14	.66	S
May 19	11:55 a. m.	11.90	1.65	1.40	1.72	1.48	I
			1.28	.95	.88	.75	S
	4:05 p. m.	11.95	1.15	1.34	1.46	1.30	I
May 20	8:55 a. m.	12.03	1.53	1.50	1.77	1.60	I
	4:40 p. m.	11.70	1.34	1.32	1.70	1.42	I
May 21	9:20 a. m.	11.55	1.39	1.23	1.54	2.17	I
			1.16	.97	.90	.63	S
	4:35 p. m.	11.66	.92	1.49	1.34	1.36	I
May 22	9:22 a. m.	11.70	1.38	1.53	1.68	1.14	I
			1.49	1.22	1.26	1.25	I x
			1.22	.95	.74	.82	S x
	4:17 p. m.	11.92	1.38	1.09	2.20	1.48	I
May 23			1.45	1.16	1.32	.98	I x
			1.09	1.05	.78	.62	S x

TABLE 10.—Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
1935							
May 21	7:05 a. m.	12.15	1.25	1.32	1.57	1.36	I
			1.17	1.03	1.10	.87	S
	10:40 a. m.	12.15	1.05	1.17	1.19	1.26	I
	2:15 p. m.	12.25	1.11	1.18	1.26	1.07	I
			.88	.85	.84	.57	S
	4:48 p. m.	12.23	1.30	1.33	1.32	1.36	I
May 22	9:00 a. m.	12.47	1.17	1.17	1.29	1.28	I
	4:35 p. m.	12.53	1.26	1.05	1.24	1.35	I
			1.04	.91	.83	.78	S
May 23	9:08 a. m.	13.18	1.55	1.28	1.34	1.68	I
			1.26	1.25	1.28	1.46	Iy
			1.08	.97	1.00	.68	Sy
	4:35 p. m.	13.88	1.58	1.20	2.39	1.52	I
			1.29	1.18	1.51	1.37	Iy
			1.18	.93	.98	.67	Sy
May 24	7:00 a. m.	14.04	1.45	1.52	1.17	1.74	I
			1.24	1.12	.90	.97	S
	10:20 a. m.	13.92	1.20	1.65	1.80	1.90	I
	4:35 p. m.	13.61	1.28	1.44	1.34	1.89	I
	7:10 p. m.	13.41	1.44	1.22	1.27	1.37	I
			1.24	1.06	.99	.82	S
May 25	9:00 a. m.	12.70	1.50	1.39	1.54	1.46	I
	4:13 p. m.	12.49	1.33	1.42	1.78	1.40	I
May 26	9:50 a. m.	12.30	1.04	.96	1.23	1.32	I
	4:20 p. m.	12.38		.76	.76	.70	S
				.93	.92	1.25	I
May 27	9:05 a. m.	12.71	.99	.92	.86	1.05	I
			1.01	.96	1.02	1.15	Ix
			.88	.78	.64	.77	Sx
	4:23 p. m.	12.96	1.15	.78	1.05	1.05	I
			1.18	1.10	.96	.92	Ix
			.79	.83		.71	Sx
May 28	6:50 a. m.	13.45	1.00	1.09	1.00	1.25	I
			1.10		1.43	.99	S
	10:45 a. m.	13.70	1.12	1.13	1.31	1.14	I
	2:05 p. m.	14.00	.84	.98	.50	.59	S
	4:25 p. m.	14.17	.84	.75	.76	.64	I
			1.13	.89	1.04	1.13	I
May 29	8:40 a. m.	14.95	1.25	1.04	1.18	1.19	I
	3:55 p. m.	15.38	1.13	2.23	1.31	1.66	I
			1.07	.86	1.06	1.00	S
May 30	8:43 a. m.	15.90	1.40	1.35	1.67	1.39	I
	12:15 p. m.	15.97	1.15	1.13	1.69	1.39	I
			1.30	1.56	1.28	1.53	Iy
			1.06	.92	.83	.74	Sy
	4:35 p. m.	16.14	1.28	1.38	1.14	1.25	I
			1.23	1.32	1.40	1.48	Iy
			1.26	1.08	1.00	.63	Sy
May 31	7:00 a. m.	16.78	1.54	1.82	1.75	1.73	I
			1.38	.82	.64	1.00	S
	12:55 p. m.	17.12	1.20	1.45	2.43	1.47	I
	4:40 p. m.	17.15	1.29	1.21	1.46	1.18	I
	7:30 p. m.	17.30	1.92	1.58	1.60	2.08	I
			1.73	1.17	1.23	2.49	S
June 1	9:35 a. m.	17.65	1.89	3.78	1.56	1.91	I
	4:25 p. m.	17.72	1.63	1.44	1.63	1.76	I
June 2	8:35 a. m.	17.76	1.76	1.34	1.96	2.34	I
	4:00 p. m.	17.85	1.94	1.67	1.73	2.51	I

## QUANTITIES OF SUSPENDED SEDIMENT

59

TABLE 10.—*Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1936, to Sept. 30, 1936—Continued*

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1936</i>							
June 3	9:20 a. m.	17.82	1.80 1.17	1.37 .91	1.42 1.05	1.72 1.21	I S
	4:40 p. m.	17.85	1.16 1.17	.96 1.17	2.63 1.22	.69	S x
June 4	9:05 a. m.	17.90	1.62 1.16	1.66 .90	1.41 .88	1.33 .84	I S
	4:30 p. m.	17.80	1.25 1.11	1.09 .97	1.74 .90	1.54 .78	I S
June 5	10:15 a. m.	17.30	1.28	1.28	1.49	2.04	I
	7:50 p. m.	17.15	1.16	.94	.99	1.31	I
June 6	12:00 n.	17.20	1.35 1.20 .90	.99 1.25 .75	1.54 1.04 .82	.98 1.40 1.08	I I y S y
	7:35 p. m.	17.18	1.15 .88	1.04 1.07	.79 1.04	1.17 .97	I I y
			.64	.67	.77	.65	S y
June 7	7:00 a. m.	17.34	1.16 .82	.71 .77	.92 .72	1.13 .77	I S
	11:40 a. m.	17.44	1.07	.86	.99	1.27	I
	4:25 p. m.	17.57	1.19	1.16	1.19	1.13	I
	7:15 p. m.	17.66	.99 .86	1.29 .70	1.17 .80	1.11 .80	I S
June 8	8:55 a. m.	18.12	1.08	1.02	1.00	1.34	I
	3:50 p. m.	18.30	1.20	.93	1.04	1.21	I
June 9	8:50 a. m.	18.96	1.26	1.17	1.22	1.49	I
	4:10 p. m.	19.20	1.11	1.10	1.50	1.38	I
June 10	9:20 a. m.	20.00	1.07	.81	1.69	2.53	I
	12:45 p. m.	20.10	1.19	1.09	1.37	1.28	I x
			.85	.84	.89	.86	S x
	4:40 p. m.	20.20	1.50 1.14	1.76 1.32	1.50 1.47	1.57 1.13	I I x
			.98	.86	.86	.74	S x
June 11	7:15 a. m.	20.75	1.26 .85	1.11 .85	1.23 .88	1.60 1.22	I S
	12:45 p. m.	20.85	1.97	2.82	3.15	1.23	I
			.90	1.21	.81	1.02	S
	5:05 p. m.	20.90	1.19	1.16	1.39	1.39	I
June 12	7:25 p. m.	21.00	1.45	1.05	.96	1.35	I
			.99	.76	.91	.97	S
June 13	8:50 a. m.	21.53	1.32	1.10	1.13	1.21	I
	4:40 p. m.	21.70	1.39	1.18	1.47	1.25	I
June 14			1.09	.82	.80	.95	S
	8:50 a. m.	22.44	1.21	.93	1.09	1.17	I
	1:50 p. m.	22.58	1.20	.93	1.40	1.28	I y
			1.05	.83	.88	.94	S y
June 15	7:15 p. m.	22.80	1.15	1.16	.89	1.42	I
			1.04	.96	1.18	1.26	I y
			.94	1.11	.95	.92	S y
June 14	6:45 a. m.	23.43	1.36	1.32	1.09	1.36	I
			1.00	.99	.87	1.19	S
	1:20 p. m.	23.75	1.26	1.05	1.24	1.20	I
			1.16	.67	.88	.92	S
	4:30 p. m.	23.65	1.33	1.11	1.20	1.39	I
June 15	7:25 p. m.	23.82	1.01	1.24	1.20	1.24	I
			1.32	.91	.82	.89	S
June 15	8:55 a. m.	24.15	1.05	1.04	1.03	1.15	I
	4:25 p. m.	24.33	1.08	.83	1.05	1.21	I

TABLE 10.—*Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued*

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
1935							
June 16	8:25 a. m.	24.55	1.04	0.98	0.91	1.39	I
	4:55 p. m.	24.72	1.02	1.15	1.11	1.11	S
June 17	8:55 a. m.	25.30	1.06	.87	.65	.96	I
			1.02	1.00	1.15	1.26	I x
	4:30 p. m.	25.55	.71	.52	.62	1.41	S x
			1.13	.94	1.19	1.17	I
			.86	.96	.94	1.29	I x
			.78	.77	.72	1.51	S x
June 18	6:50 a. m.	26.20	1.12	.99	.97	1.06	I
			.71	.54	.65	.96	S
	12:50 p. m.	26.20	.99	.83	.89	1.05	I
			.65	.63	.64	.75	S
	4:20 p. m.	26.30	1.04	.98	.94	1.45	I
	7:25 p. m.	26.35	1.05	.81	.83	1.11	I
			.78	.64	.60	.90	S
June 19	8:25 a. m.	26.75	.64	.77	.73	.82	I
	4:40 p. m.	26.40	1.04	.82	.88	.87	I
June 20	8:50 a. m.	25.30	.93	.69	.73	.96	I
			.88	.76	.75	1.03	I y
	3:55 p. m.	24.78	.55	.55	.47	.65	S y
			.81	.66	.83	.76	I
			.67	.69	.68	.80	I y
			.51	.46	.47	.57	S y
June 21	6:50 a. m.	23.90	.74	.75	.64	.89	I
			.65	.52	.45	.48	S
	12:05 p. m.	23.60	.69	.75	.79	.73	I
			.45	.36	.46	.52	S
	3:55 p. m.	23.60	.64	.64	.63	.68	I
	7:40 p. m.	23.30	.73	.63	.70	.79*	I
			.60	.67	.50	.60	S
June 22	8:40 a. m.	23.27	.65	.60	.55	.53	I
	4:50 p. m.	23.00	.52	.50	.55	.53	I
			.48	.55	.56	.49	S
June 23	8:50 a. m.	22.79	.57	.55	.53	.53	I
	3:45 p. m.	22.70	.54	.52	.56	.50	I
June 24	8:45 a. m.	22.87	.58	.52	.52	.55	I
			.57	.52	.58	.64	I x
	4:25 p. m.	22.68	.39	.40	.39	.67	S x
			.57	.65	.52	.61	I
			.56	.63	.53	.76	I x
			.46	.43	.33	.77	S x
June 25	6:40 a. m.	22.36	.60	.63	.60	.63	I
			.45	.36	.39	.40	S
	10:10 a. m.	22.30	.57	.53	.50	.45	I
	3:40 p. m.	22.06	.54	.51	.51	.58	I
	7:15 p. m.	21.90	.55	.54	.55	.60	I
			.44	.43	.44	.37	S
June 26	8:45 a. m.	21.48	.48	.52	.46	.49	I
	4:00 p. m.	21.07	.42	.37	.38	.44	I
			.37	.30	.36	.35	S
June 27	8:40 a. m.	21.20	.55	.48	.40	.59	I
			.48	.46	.55	.56	I y
			.31	.32	.34	.37	S y
	4:25 p. m.	20.93	.47	.45	.43	.46	I
			.47	.44	.41	.46	I y
			.34	.38	.32	.37	S y
June 28	8:55 a. m.	20.46	.40	.44	.53	.42	I
	12:30 p. m.	20.18	.43	.48	.49	.44	I
			.36	.27	.29	.37	S
	4:10 p. m.	20.08	.44	.42	.43	.45	I
	7:10 p. m.	19.92	.38	.42	.46	.39	I
			.33	.28	.29	.31	S

TABLE 10.—Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
1935							
June 29	8:35 a. m.	19.48	.40	.41	.37	.44	I
	4:20 p. m.	19.08	.34	.35	.34	.32	I
			.35	.37	.28	.34	S
June 30	8:40 a. m.	18.78	.37	.35	.33	.38	I
	3:55 p. m.	18.56	.39	.31	.36	.35	I
July 1	8:45 a. m.	18.16	.35	.33	.36	.37	I
			.39	.34	.36	.47	I x
	4:10 p. m.	18.00	.33	.34	.34	.34	S x
			.37	.32	.34	.50	I
			.26	.29	.24	.57	S x
July 2	6:55 a. m.	17.43	.39	.34	.32	.31	I
			.29	.30	.25	.32	S
	10:35 a. m.	17.38	.36	.35	.36	.33	I
	1:35 p. m.	17.33	.34	.36	.33	.35	S
			.29	.26	.28	.27	I
	4:25 p. m.	17.23	.33	.36	.35	.31	I
	7:00 p. m.	17.09	.38	.35	.37	.38	I
			.34	.28	.31	.30	S
July 3	9:20 a. m.	16.80	.27	.30	.28	.27	I
	3:30 p. m.	16.80	.42	.36	.39	.36	I
July 4	9:30 a. m.	16.32	.32	.28	.27	.27	I
	4:55 p. m.	16.21	.29	.27	.28	.28	I y
			.27	.25	.27	.26	S y
			.22	.24	.21	.22	
July 5	9:05 a. m.	15.76	.30	.28	.27	.27	I
	12:55 p. m.	15.66	.25	.26	.22	.28	I
			.23	.19	.19	.19	S
	4:35 p. m.	15.74	.26	.28	.25	.25	I
	7:25 p. m.	15.60	.32	.32	.34	.32	I
			.27	.26	.29	.25	S
July 6	9:55 a. m.	15.35	.31	.30	.38	.38	I
			.28	.30	.36	.27	S
	4:00 p. m.	15.19	.25	.24	.28	.28	I
July 7	9:00 a. m.	14.86	.22	.22	.25	.23	I
	4:30 p. m.	14.81	.21	.22	.22	.23	I
July 8	8:55 a. m.	14.50	.23	.24	.23	.19	I x
			.22	.22	.20	.30	S x
	3:55 p. m.	14.40	.17	.18	.17	.27	I
			.24	.24	.20	.25	S
			.23	.21	.25	.28	I x
			.19	.17	.28	.24	S x
July 9	6:45 a. m.	13.98	.24	.23	.24	.23	I
			.19	.18	.21	.16	S
	12:05 p. m.	13.77	.24	.24	.22	.24	I
			.18	.20	.18	.15	S
	4:00 p. m.	13.72	.22	.26	.22	.28	I
	7:05 p. m.	13.70	.24	.20	.20	.20	I
			.16	.16	.17	.14	S
July 10	8:50 a. m.	13.31	.19	.19	.21	.20	I
	4:15 p. m.	13.21	.19	.18	.22	.18	I
July 11	9:00 a. m.	12.93	.19	.21	.23	.16	I y
			.20	.19	.19	.20	
	4:10 p. m.	12.93	.17	.17	.14	.12	S y
			.16	.18	.14	.18	I
			.15	.14	.12	.14	S
	5:15 p. m.	12.93	.15	.15	.14	.18	I y
			.14	.13	.14	.13	S y

TABLE 10.—*Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued*

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
July 12, 1935	6:45 a. m.	12.64	.18 .16	.20 .14	.19 .16	.16 .13	I S
	12:40 p. m.	12.55	.18 .13	.17 .14	.17 .16	.16 .16	I S
	4:20 p. m.	12.45	.25	.23	.21	.22	I
	7:10 p. m.	12.59	.18 .17	.19 .19	.18 .15	.18 .13	I S
July 13	10:05 a. m.	12.54	.15 .13	.17 .12	.14 .12	.14 .13	I S
	3:50 p. m.	12.22	.16	.18	.16	.18	I
July 14	6:55 a. m.	12.12	.17	.16	.17	.18	I
	7:30 p. m.	12.09	.17	.17	.17	.14	I
July 15	9:15 a. m.	11.96	.17 .17	.15 .17	.17 .18	.15 .18	I Ix
	4:25 p. m.	11.88	.15 .17	.16 .15	.17 .17	.15 .18	Sx I
	9:55 a. m.	11.79	.17 .14	.15 .12	.15 .12	.14 .11	I S
	10:15 a. m.	11.76	.12	.14	.17	.16	I
July 16	3:40 p. m.	11.60	.15	.15	.16	.17	I
	7:15 p. m.	11.62	.14 .12	.13 .11	.15 .11	.12 .10	I S
	11:25 a. m.	11.50	.13 .11	.14 .08	.14 .10	.12 .08	I S
	4:25 p. m.	11.49	.14	.11	.13	.13	I
July 17	9:10 a. m.	11.29	.13	.14	.14	.13	I
	4:10 p. m.	11.04	.12	.15	.10	.11	I
July 18	9:00 a. m.	10.83	.15	.15	.13	.14	I
	4:00 p. m.	10.64	.14	.13	.13	.14	I
July 19	9:35 a. m.	10.43	.27	.23	.23	.21	I S
	3:55 p. m.	10.50	.25 .36	.21 .36	.20 .34	.17 .36	I I
July 21	6:55 a. m.	12.04	.33	.39	.31	.42	I
	12:55 p. m.	11.23	.33	.33	.31	.33	I
	7:25 p. m.	10.48	.50	.48	.48	.49	I
July 22	9:00 a. m.	10.05	.62	.62	.61	.61	I
	1:00 p. m.	9.84	.67	.69	.68	.68	I
	7:10 p. m.	9.67	.55	.55	.57	.56	I
July 23	6:55 a. m.	10.14	.59	.58	.58	.59	I
	12:00 noon	10.32	.71	.70	.69	.68	I
	7:20 p. m.	10.19	.52	.53	.52	.52	I
July 24	9:30 a. m.	9.97	.35 .34	.35 .33	.36 .33	.37 .33	I S
	4:35 p. m.	9.78	.41	.31	.34	.28	I
July 25	8:35 a. m.	9.44	.24	.23	.24	.23	I
	4:35 p. m.	9.46	.23	.23	.23	.22	I
July 26	12:30 p. m.	9.40	.25 .23	.26 .24	.25 .24	.25	I
	4:25 p. m.	9.24	.26	.28	.27	.26	S
	7:40 p. m.	9.15	.30 .29	.28	.29	.25 .29	I S
July 27	9:00 a. m.	8.80	.57 .55	.56 .56	.56 .55	.56	I
	3:40 p. m.	8.90	.55 .52	.56 .52	.56 .52	.54 .52	Sy I
			.62	.51	.51	.51	Sy

TABLE 10.—Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1935</i>							
July 28	8:55 a. m.	8.48	0.50	0.51	0.50	0.49	I
	4:25 p. m.	8.53	.43	.42	.43	.44	I
July 29	9:10 a. m.	8.15	.24	.24	.24	.24	I
			.25	.24	.24	.25	I x
	4:15 p. m.	8.00	.23	.23	.23	.22	S x
			.22	.22	.21	.22	I
July 30	8:55 a. m.	7.75	.23	.22	.22	.22	I
	12:25 p. m.	7.62	.21	.21	.21	.21	I
			.21	.20	.20	.20	S
	4:20 p. m.	7.52	.21	.21	.21	.21	I
	7:25 p. m.	7.53	.22	.21	.22	.21	S
July 31	8:25 a. m.	7.31	.19	.20	.19	.20	I
	4:15 p. m.	7.12	.18	.18	.18	.18	I
Aug. 1	9:35 a. m.	7.03	.16	.16	.17	.16	I
			.16	.16	.16	.16	I y
	4:50 p. m.	6.83	.16	.15	.16	.15	S y
			.16	.16	.17	.16	I
Aug. 2	7:00 a. m.	7.12	.19	.19	.18	.18	I
	7:00 a. m.	7.12	.18	.19	.18	.18	S
	11:10 a. m.	7.18	.33	.33	.32	.32	I
	2:55 p. m.	7.07	.30	.30	.31	.31	I
	7:10 p. m.	7.07	.19	.20	.20	.20	I
	7:10 p. m.	7.07	.19	.19	.19	.19	S
Aug. 3	8:45 a. m.	6.79	.17	.17	.21	.17	I
	4:30 p. m.	6.76	.17	.16	.16	.16	I
Aug. 4	9:00 a. m.	6.47	.18	.18	.18	.18	I
	4:10 p. m.	6.40	.24	.29	.29	.29	I
Aug. 5	9:55 a. m.	6.55	.32	.32	.32	.31	I
			.32	.32	.32	.32	I x
	4:55 p. m.	7.10	.41	.41	.41	.41	S x
			.40	.40	.41	.40	I x
Aug. 6	6:40 a. m.	7.39	2.33	2.36	2.39	2.41	I
			2.31	2.32	2.34	2.35	S
	12:30 p. m.	8.98	1.47	1.47	1.49	1.51	I
	4:30 p. m.	8.35	1.65	1.63	1.57	1.55	I
Aug. 7	9:30 a. m.	6.70	1.77	1.79	1.78	1.80	I
	4:10 p. m.	6.71	1.31	1.31	1.30	1.32	I
Aug. 8	9:30 a. m.	6.70	1.01	.75	.74	.76	I
			.73	.74	.74	.74	S
	5:00 p. m.	6.52	.55	.75	.75	.74	I y
			.54	.64	.66	.65	I y
Aug. 9	6:30 a. m.	6.78	.53	.51	.52	.51	S
				.52	.52	.37	I
	9:20 a. m.	6.68	.47	.48	.46	.47	I
	5:40 p. m.	6.51	.41	.41	.42	.41	I
Aug. 10	7:00 p. m.	6.54	.41	.42	.41	.41	S
			.41	.39	.40	.40	I
	8:40 a. m.	6.45	.50	.48	.48	.48	I
	4:45 p. m.	6.13	.48	.23	.60	.48	I

TABLE 10.—Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1935</i>							
Aug. 11.....	9:40 a. m.....	6.55	1.68	1.65	1.62	1.63	I
	5:00 p. m.....	6.51	1.78	1.80	1.81	1.81	I
Aug. 12.....	9:00 a. m.....	6.63	1.18	1.18	1.19	1.17	I
			1.18	1.17	1.16	1.19	Ix
			1.17	1.19	1.19	1.19	Sx
	5:00 p. m.....	6.71	1.09	1.08	1.09	1.09	Ix
			1.08	1.07	1.07	1.08	Sx
			1.07	1.07	1.07	1.07	I
Aug. 13.....	6:45 a. m.....	6.35	1.03	1.02	1.01	1.02	I
			1.00		1.00	.99	S
	11:45 a. m.....	6.11	1.01	1.01	1.03	1.02	I
	3:40 p. m.....	5.91	.97	.97	.96	.96	I
	7:15 p. m.....	5.79	.87	.86	.88	.86	S
			.88	.88	.88	.89	I
Aug. 14.....	8:40 a. m.....	5.73	1.07	1.07	1.06	1.05	I
	4:30 p. m.....	5.57	1.18	1.06	1.20	1.19	I
Aug. 15.....	8:40 a. m.....	5.85	1.04	1.02	1.01	1.00	Iy
			1.07	1.02	1.00	.99	Sy
			1.04	1.03	1.01	.99	I
	5:00 p. m.....	5.62	1.30	1.31	1.31	1.31	I
			1.28	1.31	1.30	1.27	Sy
			1.30	1.31	1.31	1.31	Iy
Aug. 16.....	7:00 a. m.....	5.64	1.08	1.06	1.07	1.08	S
			1.08	1.08	1.07	1.06	I
	9:10 a. m.....	5.66	1.10	1.10	1.10	1.09	I
	3:45 p. m.....	6.08	.88	.88	.88	.88	I
	7:00 p. m.....	6.29	.85	.84	.84	.85	S
			.85	.85	.84	.85	I
Aug. 17.....	8:40 a. m.....	6.20	.77	.76	.77	.78	I
	4:30 p. m.....	6.46	.74	.74	.74	.73	I
Aug. 18.....	9:00 a. m.....	5.43	1.15	1.13	1.14	1.15	I
	3:50 p. m.....	5.17	1.57	1.56	1.56	1.56	I
Aug. 19.....	6:50 a. m.....	5.54	.61	.61	.62	.62	I
			.60	.60	.60	.61	S
	10:20 a. m.....	5.77	.54	.54	.54	.53	I
	3:00 p. m.....	5.71	.48	.48	.48	.47	I
	7:00 p. m.....	5.57	.48	.49	.48	.47	S
			.49	.50	.49	.48	I
Aug. 20.....	8:45 a. m.....	5.13	.42	.42	.43	.42	I
			.42	.41	.40	.42	S
			.43	.42	.42	.42	Ix
	4:30 p. m.....	4.74	.39	.38	.38	.38	I
			.38	.37	.37	.38	Sx
			.39	.38	.38	.39	Ix
Aug. 21.....	9:30 a. m.....	5.10	.44	.42	.42	.36	I
	4:15 p. m.....	5.79	.46	.46	.45	.45	I
Aug. 22.....	11:45 a. m.....	5.34	.53	.54	.55	.54	Sy
			.56	.55	.55	.55	Iy
			.55	.55	.55	.55	I
	6:10 p. m.....	5.00	.54	.54	.54	.53	I
			.54	.54	.54	.52	Iy
			.52	.52	.52	.53	Sy
Aug. 23.....	6:50 a. m.....	4.80	.47	.48	.48	.47	S
			.48	.53	.57	.48	I
	12:00 noon.....	4.80	.44	.44	.44	.44	I
	3:50 p. m.....	5.01	.43	.69	.44	.44	I
	7:10 p. m.....	5.25	.44	.44	.43	.44	I
			.43	.42	.42	.42	S
Aug. 24.....	9:00 a. m.....	5.03	.51	.51	.50	.50	I
	4:30 p. m.....	4.92	.50	.50	.50	.49	I

## QUANTITIES OF SUSPENDED SEDIMENT

65

TABLE 10.—*Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued*

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1935</i>							
Aug. 25	9:20 a. m.	4.73	0.53	0.54	0.53	0.53	I
	4:10 p. m.	4.84	.52	.52	.52	.52	I
Aug. 26	8:45 a. m.	7.42	2.38	2.35	2.24	2.15	I
	12:10 p. m.	6.90	2.92	2.94	2.92	2.89	I
	4:30 p. m.	6.13	6.86	6.78	6.69	6.70	I
	7:30 p. m.	5.72	6.98	6.77	6.63	6.64	I x
Aug. 27	6:30 a. m.	5.33	2.96	3.01	3.03	3.03	I
	12:15 p. m.	5.30	2.50	2.53	2.52	2.55	I
	4:30 p. m.	5.50	2.31	2.32	2.30	2.30	I
	7:10 p. m.	5.61	2.42	2.41	2.39	2.37	I
			2.38	2.41	2.37	2.35	S
Aug. 28	8:45 a. m.	7.01	2.88	2.91	2.92	2.93	I
	4:40 p. m.	6.72	2.59	2.56	2.57	2.55	I
Aug. 29	8:45 a. m.	6.49	2.01	2.02	1.99	2.03	I
			2.00	2.04	2.04	2.01	I y
	4:40 p. m.	6.40	1.98	1.98	1.98	1.96	S y
			1.71	1.71	1.72	1.75	I
			1.72	1.74	1.74	1.73	I y
			1.68	1.68	1.70	1.70	S y
Aug. 30	6:40 a. m.	6.11	1.68	1.69	1.68	1.69	I
	11:00 a. m.	5.92	1.58	1.58	1.58	1.58	S
	3:30 p. m.	5.78	1.65	1.64	1.65	1.64	I
	7:15 p. m.	5.65	1.89	1.86	1.85	1.83	I
			1.85	1.85	1.83	1.78	S
Aug. 31	8:45 a. m.	5.39	2.14	2.12	2.14	2.13	I
	4:30 p. m.	5.28	2.15	2.15	2.16	2.15	I
Sept. 1	9:30 a. m.	5.94	1.45	1.46	1.46	1.46	I
	5:00 p. m.	6.07	1.39	1.40	1.40	1.41	I
Sept. 2	8:40 a. m.	6.63	1.68	1.68	1.66	1.65	I
			1.64	1.66	1.63	1.62	I y
	4:45 p. m.	6.96	1.63	1.63	1.62	1.63	S y
			1.97	2.01	2.03	2.03	I
			1.98	1.99	2.01	2.00	I y
Sept. 3	6:45 a. m.	7.38	2.66	2.67	2.65	2.62	I
	11:30 a. m.	7.01	2.64	2.63	2.56	2.59	S
	4:30 p. m.	7.52	2.87	2.93	2.92	2.91	I
	7:15 p. m.	7.81	3.02	3.02	3.00	3.00	I
			2.99	2.93	2.95	2.94	S
Sept. 4	8:45 a. m.	8.25	4.83	4.79	4.71	4.76	I
	3:40 p. m.	7.44	5.21	5.27	5.30	5.30	I
Sept. 5	9:30 a. m.	6.62	2.87	2.90	2.83	2.84	I
			2.78	2.80	2.83	2.83	I y
	4:40 p. m.	6.40	2.74	2.78	2.81	2.76	S y
			2.21	2.23	2.23	2.24	I
			2.20	2.23	2.25	2.23	I y
			2.17	2.19	2.17	2.15	S y
Sept. 6	6:40 a. m.	5.82	2.04	2.05	2.03	2.02	I
	11:50 a. m.	5.60	2.00	2.00	2.00	1.98	S
	4:30 p. m.	5.43	1.88	1.88	1.89	1.94	I
	7:20 p. m.	5.41	1.86	2.08	1.86	1.86	I
			1.89	1.90	1.88	1.86	I
			1.64	1.83	1.86	1.84	S
Sept. 7	8:40 a. m.	5.12	1.95	1.97	1.93	1.96	I
	4:20 p. m.	4.83	2.08	2.08	2.05	2.05	I

TABLE 10.—Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1935</i>							
Sept. 8	8:40 a. m.	4.60	1.80	1.81	1.82	1.83	I
	4:40 p. m.	4.41	1.46	1.47	1.46	1.45	I
Sept. 9	8:50 a. m.	4.26	1.15	1.16	1.15	1.13	I
			1.16	1.16	1.15	1.17	I x
	4:20 p. m.	4.13	.97	1.19	1.01	1.19	I
			1.09	1.11	1.08	1.08	I x
			1.11	1.10	1.12	1.11	S x
Sept. 10	6:40 a. m.	4.05	1.06	1.05	1.07	1.07	I
			1.06	1.06	1.05	1.05	S
	11:50 a. m.	4.00	.99	.99	.99	.99	I
	4:20 p. m.	4.00	.94	.94	.93	.94	I
	7:30 p. m.	4.08	.89	.89	.87	.90	S
			.89	.88	.89	.90	S
Sept. 11	9:10 a. m.	4.17	.75	.75	.75	.74	I
	4:50 p. m.	3.92	.69	.68	.68	.67	I
Sept. 12	9:30 a. m.	3.84	.65	.66	.66	.66	I
			.65	.66	.66	.66	I y
	7:10 p. m.	3.70	.64	.65	.66	.65	S y
			.61	.61	.61	.61	I
			.60	.61	.61	.61	I y
			.60	.60	.59	.60	S y
Sept. 13	6:45 a. m.	3.59	.58	.59	.59	.58	I
			.59	.59	.58	.59	S
	11:30 a. m.	3.74	.58	.58	.58	.57	I
	4:40 p. m.	4.02	.56	.53	.55	.55	I
	7:40 p. m.	4.09	.55	.55	.55	.56	I S
			.55	.54	.54	.54	S
Sept. 14	8:30 a. m.	4.25	.58	.58	.58	.58	I
	4:30 p. m.	4.22	.74	.73	.71	.71	I
Sept. 15	9:00 a. m.	4.17	.55	.56	.54	.55	I
	4:30 p. m.	4.16	.52	.52	.51	.54	I
Sept. 16	9:10 a. m.	4.45	.57	.59	.56	.58	I
			.57	.56	.56	.58	I x
	4:25 p. m.	4.62	.58	.56	.57	.58	S x
			.55	.55	.55	.55	I
			.56	.54	.54	.56	I x
			.56	.54	.54	.56	S x
Sept. 17	6:50 a. m.	4.82	.43	.42	.42	.42	I
			.42	.41	.41	.41	S
	11:50 a. m.	4.82	.39	.40	.40	.39	I
	4:30 p. m.	4.70	.38	.39	.38	.38	I
	7:40 p. m.	4.58	.39	.40	.39	.39	I S
			.39	.38	.38	.39	S
Sept. 18	8:40 a. m.	4.21	.35	.35	.34	.34	I
	4:20 p. m.	4.06	.32	.33	.31	.32	I
Sept. 19	8:50 a. m.	3.70	.41	.40	.41	.39	I
			.40	.40	.39	.39	I y
	4:00 p. m.	4.61	.43	.41	.41	.42	S y
			.41	.42	.41	.41	I
			.42	.42	.41	.42	I y
			.42	.42	.41	.42	S y
Sept. 20	6:45 a. m.	3.48	.35	.35	.35	.35	I
			.36	.36	.35	.36	S
	11:20 a. m.	3.43	.32	.32	.32	.32	I I
	4:30 p. m.	3.43	.29	.29	.29	.29	I I
	7:20 p. m.	3.46	.28	.29	.29	.29	I S
			.29	.28	.29	.28	S
Sept. 21	8:30 a. m.	3.55	.22	.22	.22	.22	I
	4:30 p. m.	3.40	.20	.20	.20	.21	I

## QUANTITIES OF SUSPENDED SEDIMENT

67

TABLE 10.—Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1935</i>							
Sept. 22	9:00 a. m.	3.26	0.17	0.18	0.17	0.17	I
	4:20 p. m.	3.08	.16	.16	.16	.15	I
Sept. 23	9:10 a. m.	2.94	.14	.14	.14	.13	I
	4:00 p. m.	2.88	.14	.13	.12	.13	I x
			.16	.16	.16	.15	S x
			.16	.16	.15	.16	I
			.17	.15	.15	.15	I x
Sept. 24	6:40 a. m.	2.80	.14	.14	.14	.13	I
	11:15 a. m.	2.74	.15	.15	.16	.15	S
	4:10 p. m.	2.69	.14	.14	.14	.14	I
	7:40 p. m.	2.67	.15	.15	.14	.14	S
			.18	.17	.17	.17	I
Sept. 25	8:50 a. m.	2.74	.12	.13	.13	.13	I
	4:45 p. m.	2.52	.12	.11	.11	.12	I
Sept. 26	9:30 a. m.	2.43	.13	.14	.13	.14	I
			.14	.14	.15	.15	I y
	3:50 p. m.	2.73	.14	.13	.14	.14	S y
			.16	.17	.16	.16	I
			.17	.16	.17	.17	I y
			.16	.16	.17	.16	S y
Sept. 27	6:50 a. m.	3.00	.18	.18	.19	.18	I
			.18	.19	.19	.19	S
	11:00 a. m.	2.85	.23	.23	.22	.22	I
	3:40 p. m.	3.50	.21	.21	.21	.21	I
	8:00 p. m.	8.32	.36	.39	.34	.31	S
			.34	.33	.33	.32	I
Sept. 28	8:50 a. m.	8.34	.81	.81	.81	.83	I
	4:20 p. m.	7.68	.98	.98	.99	.99	I
Sept. 29	9:00 a. m.	6.68	2.11	2.11	2.11	2.08	I
	3:40 p. m.	5.67	2.17	2.18	2.18	2.17	I
Sept. 30	8:50 a. m.	5.76	2.65	2.63	2.63	2.55	I
			2.63	2.64	2.69	2.59	I x
			2.64	2.64	2.60	2.54	S x
	1:00 p. m.	13.60	4.25	4.49	4.02	4.37	I
	4:15 p. m.	13.45	5.31	5.48	5.69	5.57	I
Oct. 1	10:00 a. m.	9.62	4.74	4.84	4.82	4.76	I
	4:20 p. m.	8.77	5.48	5.41	5.31	5.38	I
Oct. 2	9:20 a. m.	6.88	4.75	4.76	4.76	4.74	I
	4:20 p. m.	6.47	4.59	4.53	4.53	4.53	I
Oct. 3	9:05 a. m.	6.06	3.67	3.70	3.68	3.69	I
	4:10 p. m.	6.04	3.20	3.19	3.18	3.20	I
Oct. 4	8:55 a. m.	5.83	2.14	2.14	2.14	2.14	I
	4:20 p. m.	5.66	1.83	1.84	1.83	1.82	I
Oct. 5	9:00 a. m.	5.31	1.35	1.35	1.35	1.35	I
	5:00 p. m.	5.12	1.21	1.22	1.22	1.23	I
Oct. 6	9:50 a. m.	4.93	.91	.90	.91	.91	I
	3:40 p. m.	4.87	.85	.85	.84	.85	I
Oct. 7	9:50 a. m.	4.76	.70	.69	.70	.70	I
	4:30 p. m.	4.69	.67	.68	.67	.68	I
Oct. 8	9:40 a. m.	4.51	.50	.61	.58	.51	I
	4:30 p. m.	4.39	.48	.56	.44	.60	I
Oct. 9	9:00 a. m.	4.34	.52	.45	.45	.45	I
	4:50 p. m.	4.21	.42	.43	.43	.43	I

TABLE 10.—Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1935</i>							
Oct. 10.....	10:20 a. m.....	4.13	.44	.44	.44	.44	I
	4:10 p. m.....	4.04	.41	.41	.41	.41	I
Oct. 11.....	9:20 a. m.....	3.94	.34	.33	.34	.33	I
	4:50 p. m.....	3.74	.28	—	.24	.30	I
Oct. 12.....	9:10 a. m.....	3.81	.27	.26	.27	.27	I
	4:10 p. m.....	3.75	.25	.25	.25	.25	I
Oct. 13.....	9:50 a. m.....	3.61	.23	.23	.23	.21	I
	3:50 p. m.....	3.59	.22	.22	.22	.22	I
Oct. 14.....	9:00 a. m.....	3.43	.19	.19	.19	.19	I
	4:20 p. m.....	3.43	.18	.18	.19	.19	I
Oct. 15.....	9:10 a. m.....	3.18	.16	.16	.16	.16	I
	4:00 p. m.....	3.23	.16	.16	.16	.14	I
Oct. 16.....	9:40 a. m.....	3.12	.14	.15	.14	.15	I
	3:20 p. m.....	3.06	.13	.14	.14	.13	I
Oct. 17.....	8:50 a. m.....	3.11	.13	.13	.13	.13	I
	3:15 p. m.....	3.06	.13	.12	.13	.13	I
Oct. 18.....	9:00 a. m.....	3.01	.12	.12	.12	.12	I
	3:30 p. m.....	2.97	.12	.12	.12	.12	I
Oct. 19.....	9:20 a. m.....	2.89	.11	.11	.13	.13	I
	4:10 p. m.....	2.85	.10	.12	.09	.10	I
Oct. 20.....	10:10 a. m.....	2.86	.10	.11	.11	.11	I
	3:50 p. m.....	2.90	.11	.11	.12	.11	I
Oct. 21.....	9:50 a. m.....	2.86	.11	.11	.12	.11	I
	4:40 p. m.....	2.82	.11	.11	.12	.12	I
Oct. 22.....	9:15 a. m.....	2.98	.11	.12	.12	.12	I
	3:50 p. m.....	2.94	.12	.11	.11	.12	I
Oct. 23.....	9:00 a. m.....	2.83	.12	.11	.11	.11	I
	4:15 p. m.....	2.82	.11	.11	.10	.10	I
Oct. 24.....	9:10 a. m.....	3.25	.11	.13	.11	.11	I
	4:40 p. m.....	3.98	.13	.11	.13	.14	I
Oct. 25.....	9:10 a. m.....	3.53	.15	.15	.15	.15	I
	4:15 p. m.....	3.48	.12	.13	.13	.13	I
Oct. 26.....	9:20 a. m.....	3.52	.14	.13	.14	.14	I
	4:50 p. m.....	3.40	.16	.16	.16	.15	I
Oct. 27.....	10:05 a. m.....	3.21	.17	.17	.17	.16	I
	5:10 p. m.....	3.19	.15	.16	.16	.18	I
Oct. 28.....	9:10 a. m.....	3.10	.18	.18	.18	.18	I
	4:45 p. m.....	3.07	.21	.22	.22	.23	I
Oct. 29.....	8:20 a. m.....	3.14	.55	.49	.50	.53	I
	4:00 p. m.....	3.19	.43	.49	.47	.47	I
Oct. 30.....	8:30 a. m.....	3.18	.59	.47	.47	.47	I
	3:45 p. m.....	3.07	.37	.38	.38	.39	I
Oct. 31.....	8:30 a. m.....	3.25	.28	.27	.27	.27	I
	4:00 p. m.....	3.22	.25	.25	.25	.25	I
Nov. 1.....	9:40 a. m.....	3.34	.22	.23	.24	.23	I
	3:50 p. m.....	3.36	.22	.22	.22	.23	I
Nov. 2.....	9:20 a. m.....	3.35	.21	.21	.21	.21	I
	3:50 p. m.....	3.57	.19	.19	.20	.20	I

TABLE 10.—*Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued*

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1935</i>							
Nov. 3	9:40 a. m.	3.22	.15	.15	.16	.16	I
	3:50 p. m.	3.20	.15	.13	.15	.16	I
Nov. 4	8:20 a. m.	3.37	.14	.16	.16	.15	I
	3:20 p. m.	3.37	.14	.14	.15	.14	I
Nov. 5	8:40 a. m.	3.41	.13	.14	.12	.14	I
	3:20 p. m.	3.47	.13	.13	.14	.14	I
Nov. 6	8:20 a. m.	3.44	.13	.13	.14	.13	I
	4:30 p. m.	3.48	.13	.12	.13	.13	I
Nov. 7	11:20 a. m.	3.50	.12	.11	.12	.12	I
	4:05 p. m.	3.53	.11	.13	.12	.12	I
Nov. 8	8:30 a. m.	3.64	.13	.12	.13	.13	I
	3:10 p. m.	3.62	.13	.12	.12	.13	I
Nov. 9	8:40 a. m.	3.63	.12	.12	.13	.12	I
	4:40 p. m.	3.68	.13	.13	.13	.13	I
Nov. 10	10:15 a. m.	3.72	0.12	0.12	0.13	0.13	I
	4:30 p. m.	3.68	.12	.12	.12	.13	I
Nov. 11	9:05 a. m.	3.74	.12	.13	.13	.13	I
	3:45 p. m.	3.80	.12	.12	.13	.13	I
Nov. 12	8:30 a. m.	3.73	.13	.13	.12	.13	I
	4:00 p. m.	3.72	.13	.12	.13	.14	I
Nov. 13	8:30 a. m.	3.65	.13	.12	.12	.12	I
	3:30 p. m.	3.68	.11	.12	.12	.13	I
Nov. 14	9:00 a. m.	3.80	.11	.13	.12	.11	I
	4:50 p. m.	3.87	.11	.11	.12	.11	I
Nov. 15	8:25 a. m.	3.92	.11	.12	.12	.13	I
	4:00 p. m.	3.85	.12	.12	.11	.11	I
Nov. 16	8:30 a. m.	3.92	.12	.11	.11	.11	I
	4:00 p. m.	3.90	.10	.12	.11	.11	I
Nov. 17	10:00 a. m.	3.90	.11	.11	.10	.11	I
	4:00 p. m.	3.92	.11	.11	.11	.10	I
Nov. 18	8:15 a. m.	3.86	.10	.11	.10	.10	I
	3:10 p. m.	3.85	.10	.10	.11	.10	I
Nov. 19	9:00 a. m.	3.74	.10	.10	.11	.10	I
	3:30 p. m.	3.74	.10	.09	.09	.10	I
Nov. 20	8:40 a. m.	3.77	.09	.09	.10	.10	I
	3:25 p. m.	3.68	.09	.09	.09	.10	I
Nov. 21	8:20 a. m.	3.68	.10	.09	.10	.11	I
	4:30 p. m.	3.63	.09	.09	.09	.10	I
Nov. 22	8:30 a. m.	3.64	.10	.09	.09	.09	I
	3:15 p. m.	3.67	.08	.08	.08	.09	I
Nov. 23	8:40 a. m.	3.77	.08	.08	.08	.08	I
	3:35 p. m.	3.81	.09	.09	.10	.10	I
Nov. 24	10:00 a. m.	3.73	.11	.11	.11	.11	I
	3:15 p. m.	3.74	.11	.11	.11	.11	I
Nov. 25	8:30 a. m.	3.81	.12	.12	.12	.12	I
	3:20 p. m.	3.86	.10	.11	.11	.10	I
Nov. 26	8:20 a. m.	3.81	.11	.11	.12	.10	I
	3:30 p. m.	3.84	.10	.11	.10	.11	I

TABLE 10.—Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1935</i>							
Nov. 27.....	8:20 a. m.....	3.79	.10	.10	.11	.10	I
	3:15 p. m.....	3.78	.09	.09	.10	.11	I
Nov. 28.....	9:00 a. m.....	3.80	.12	.13	.12	.11	I
	3:05 p. m.....	3.84	.11	.11	.13	.12	I
Nov. 29.....	8:40 a. m.....	3.68	.11	.12	.11	.10	I
	3:15 p. m.....	3.62	.11	.11	.11	.11	I
Nov. 30.....	8:40 a. m.....	3.62	.15	.16	.16	.15	I
	4:00 p. m.....	3.65	.14	.15	.15	.15	I
Dec. 1.....	10:00 a. m.....	3.70	.16	.16	.14	.14	I
	4:40 p. m.....	3.71	.12	.13	.12	.12	I
Dec. 2.....	9:00 a. m.....	3.72	.12	.11	.11	.12	I
	3:15 p. m.....	3.76	.10	.10	.11	.11	I
Dec. 3.....	9:00 a. m.....	3.73	.11	.11	.11	.10	I
	3:10 p. m.....	3.79	.10	.10	.10	.10	I
Dec. 4.....	9:00 a. m.....	3.77	.10	.11	.10	.10	I
	3:25 p. m.....	3.76	.09	.09	.09	.10	I
Dec. 5.....	8:20 a. m.....	3.68	.10	.09	.09	.09	I
	3:25 p. m.....	3.69	.09	.09	.10	.10	I
Dec. 6.....	8:30 a. m.....	4.79	.10	.10	.10	.09	I
	4:00 p. m.....	4.49	.13	.14	.13	.13	I
Dec. 7.....	8:40 a. m.....	4.15	.19	.20	.19	.20	I
	4:00 p. m.....	3.96	.24	.24	.23	.23	I
Dec. 8.....	10:15 a. m.....	3.53	.22	.21	.21	.21	I
	3:15 p. m.....	3.45	.17	.17	.16	.16	I
Dec. 9.....	8:30 a. m.....	3.18	.13	.13	.14	.13	I
	3:00 p. m.....	3.12	.13	.13	.12	.14	I
Dec. 10.....	8:30 a. m.....	3.10	.13	.12	.13	.12	I
	4:00 p. m.....	3.12	.10	.10	.09	.09	I
Dec. 11.....	8:35 a. m.....	3.14	.09	.09	.09	.08	I
	3:20 p. m.....	3.10	.08	.08	.08	.07	I
Dec. 12.....	8:40 a. m.....	3.07	.08	.10	.07	.09	I
	4:10 p. m.....	3.05	.07	.07	.06	.07	I
Dec. 13.....	8:30 a. m.....	3.06	.09	.10	.09	.09	I
	3:25 p. m.....	3.11	.09	.08	.08	.08	I
Dec. 14.....	8:40 a. m.....	3.13	.10	.10	.10	.10	I
	4:00 p. m.....	3.13	.10	.10	.11	.10	I
Dec. 15.....	10:15 a. m.....	3.17	.09	.09	.10	.09	I
	4:00 p. m.....	3.20	.09	.08	.08	.09	I
Dec. 16.....	8:35 a. m.....	3.10	.09	.09	.09	.09	I
	3:10 p. m.....	3.10	.08	.09	.08	.08	I
Dec. 17.....	8:30 a. m.....	2.96	.09	.09	.09	.09	I
	3:10 p. m.....	2.90	.08	.10	.10	.09	I
Dec. 18.....	8:40 a. m.....	2.76	.10	.11	.10	.10	I
	3:15 p. m.....	2.73	.10	.08	.08	.08	I
Dec. 19.....	8:40 a. m.....	2.77	.10	.09	.09	.09	I
	3:25 p. m.....	2.82	.10	.09	.07	.08	I
Dec. 20.....	8:40 a. m.....	2.81	.09	.08	.08	.09	I
	3:10 p. m.....	2.82	.08	.08	.07	.08	I

## QUANTITIES OF SUSPENDED SEDIMENT

71

TABLE 10.—*Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued*

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1935</i>							
Dec. 21	8:40 a. m.	2.80	.09	.08	[.10	.08	I
	3:20 p. m.	2.78	.08	.08	.08	.08	I
Dec. 22	10:00 a. m.	2.51	.08	.07	.07	.07	I
	3:00 p. m.	2.48	.07	.07	.08	.07	I
Dec. 23	8:40 a. m.	2.07	.07	.08	.06	.06	I
	3:20 p. m.	1.91	.08	.07	.06	.07	I
Dec. 24	8:35 a. m.	1.80	.07	.07	.07	.06	I
	4:00 p. m.	1.80	.06	.06	.06	.06	I
Dec. 25	10:00 a. m.	1.76	.06	.06	.05	.05	I
	3:50 p. m.	1.71	.05	.05	.05	.05	I
Dec. 26	10:00 a. m.	1.64	.06	.05	.06	.05	I
	3:40 p. m.	1.60	.06	.06	.05	.06	I
Dec. 27	8:40 a. m.	1.64	.07	.06	.06	.06	I
	3:15 p. m.	1.68	.06	.07	.05	.06	I
Dec. 28	8:35 a. m.	1.79	.07	.06	.06	.06	I
	3:40 p. m.	1.80	.06	.06	.06	.06	I
Dec. 29	8:40 a. m.	1.99	.07	.07	.07	.06	I
	3:40 p. m.	1.98	.06	.06	.08	.06	I
Dec. 30	9:00 a. m.	2.13	.09	.09	.09	.16	I
	3:30 p. m.	2.17	.08	.07	.08	.06	I
Dec. 31	8:30 a. m.	2.41	.06	.07	.06	.07	I
	3:40 p. m.	2.35	.06	.06	.06	.06	I
<i>1936</i>							
Jan. 1	4:00 p. m.	2.11	.08	.07	.08	.07	I
Jan. 2	9:00 a. m.	2.21	.06	.07	.08	.08	I
	3:25 p. m.	2.24	.10	.08	.08	.09	I
Jan. 3	8:35 a. m.	2.44	.06	.06	.06	.06	I
	3:20 p. m.	2.46	.06	.06	.06	.06	I
Jan. 4	8:45 a. m.	2.53	.08	.06	.06	.06	I
	4:10 p. m.	2.65	.06	.06	.06	.06	I
Jan. 5	9:00 a. m.	2.53	.07	.07	.03	.08	I
	4:00 p. m.	2.40	.08	.08	.08	.07	I
Jan. 6	9:00 a. m.	2.53	.07	.07	.07	.08	I
	3:20 p. m.	2.55	.07	.07	.08	.08	I
Jan. 7	8:40 a. m.	2.59	.07	.07	.08	.07	I
	3:30 p. m.	2.58	.07	.07	.07	.07	I
Jan. 8	8:30 a. m.	2.50	.06	.07	.07	.06	I
	3:25 p. m.	2.55	.07	.08	.07	.07	I
Jan. 9	8:30 a. m.	2.54	.06	.06	.06	.06	I
	3:20 p. m.	2.49	.05	.07	.07	.06	I
Jan. 10	8:20 a. m.	2.26	.05	.05	.06	.06	I
	3:25 p. m.	2.22	.06	.06	.05	.16	I
Jan. 11	8:40 a. m.	2.57	.05	.05	.05	.05	I
	2:50 p. m.	2.68	.06	.06	.06	.05	I
Jan. 12	10:05 a. m.	2.77	0.05	0.05	0.07	0.05	I
	3:20 p. m.	2.84	.08	.07		.08	I
Jan. 13	8:30 a. m.	2.74	.06	.08	.07	.07	I
	3:00 p. m.	2.74	.07	.08	.07	.07	I

TABLE 10.—Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
1936							
Jan. 14	8:30 a. m.	2.64	.06	.06	.07	.06	I
	3:00 p. m.	2.68	.06	.07	.08	.08	I
Jan. 15	9:00 a. m.	2.60	.06	.05	.05	.06	I
	3:50 p. m.	2.69	.05	.05	.06	.06	I
Jan. 16	8:10 a. m.	2.74	.06	.06	.06	.06	I
	3:00 p. m.	2.86	.05	.06	.08	.06	I
Jan. 17	8:15 a. m.	2.91	.07	.06	.07	.07	I
	3:30 p. m.	2.88	.06	.06	.05	.05	I
Jan. 18	9:20 a. m.	3.09	.06	.06	.06	.06	I
	4:30 p. m.	3.24	.07	.06	.06	.06	I
Jan. 19	10:20 a. m.	3.27	.06	.06	.06	.06	I
	4:30 p. m.	3.36	.06	.06	.05	.06	I
Jan. 20	8:20 a. m.	3.34	.07	.06	.06	.07	I
	4:30 p. m.	3.31	.06	.05	.05	.06	I
Jan. 21	8:25 a. m.	3.19	.08	.07	.08	.07	I
	3:25 p. m.	3.18	.07	.08	.08	.07	I
Jan. 22	8:25 a. m.	3.15	.08	.06	.07	.08	I
	2:50 p. m.	3.19	.07	.08	.06	.08	I
Jan. 23	8:15 a. m.	2.98	.06	.06	.07	.06	I
	3:20 p. m.	3.02	.06	.06	.06	.06	I
Jan. 24	8:25 a. m.	2.95	.05	.06	.05	.05	I
	4:30 p. m.	2.91	.06	.06	.05	.05	I
Jan. 25	8:25 a. m.	2.80	.07	.07	.08	.07	I
	3:30 p. m.	2.72	.06	.07	.06	.06	I
Jan. 26	10:30 a. m.	2.71	.06	.07	.07	.07	I
	3:40 p. m.	2.69	.06	.06	.06	.06	I
Jan. 27	8:35 a. m.	2.65	.05	.06	.06	.06	I
	3:30 p. m.	2.64	.06	.06	.06	.06	I
Jan. 28	8:20 a. m.	2.64	.05	.04	.05	.05	I
	3:30 p. m.	2.66	.04	.04	.04	.03	I
Jan. 29	8:50 a. m.	2.83	.06	.06	.06	.06	I
	3:00 p. m.	2.96	.05	.05	.05	.05	I
Jan. 30	8:55 a. m.	3.05	.06	.06	.06	.06	I
	2:25 p. m.	3.12	.06	.05	.06	.05	I
Jan. 31	8:20 a. m.	3.20	.06	.07	.07	.08	I
	9:00 p. m.	3.27	.07	.07	.07	.08	I
Feb. 1	8:40 a. m.	3.38	.07	.08	.08	.08	I
	5:00 p. m.	3.34	.08	.08	.08	.07	I
Feb. 2	8:40 a. m.	3.51	.14	.14	.15	.15	I
	5:20 p. m.	3.40	.15	.15	.16	.16	I
Feb. 3	8:50 a. m.	3.41	.15	.17	.15	.17	I
	3:35 p. m.	3.24	.16	.17	.17	.16	I
Feb. 4	8:20 a. m.	3.63	.16	.16	.17	.16	I
	3:30 p. m.	3.54	.16	.16	.17	.18	I
Feb. 5	8:20 a. m.	3.53	.16	.17	.18	.19	I
	3:20 p. m.	3.47	.16	.17	.17	.18	I
Feb. 6	8:35 a. m.	3.60	.30	.32	.30	.30	I
	3:20 p. m.	3.57	.23	.23	.22	.24	I

TABLE 10.—*Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1936, to Sept. 30, 1936—Continued*

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1936</i>							
Feb. 7	8:50 a. m.	3.30	0.17	0.18	0.17	0.20	I
	3:10 p. m.	3.21	.18	.16	.16	.17	I
Feb. 8	9:15 a. m.	3.00	.17	.17	.19	.18	I
	2:30 p. m.	2.96	.17	.17	.16	.16	I
Feb. 9	9:25 a. m.	3.23	.16	.15	.16	.17	I
	3:05 p. m.	3.32	.16	.18	.20	.18	I
Feb. 10	8:20 a. m.	3.46	.16	.17	.19	.15	I
	2:30 p. m.	3.40	.10	.12	.11	.11	I
Feb. 11	8:40 a. m.	3.29	.10	.10	.09	.09	I
	2:45 p. m.	3.18	.09	.08	.09	.08	I
Feb. 12	8:50 a. m.	2.98	.13	.12	.11	.11	I
	3:40 p. m.	2.91	.08	.08	.08	.08	I
Feb. 13	8:20 a. m.	2.77	.10	.09	.09	.08	I
	3:20 p. m.	2.87	.08	.08	.07	.08	I
Feb. 14	8:20 a. m.	3.14	.07	.08	.08	.07	I
	3:20 p. m.	3.06	.07	.06	.07	.07	I
Feb. 15	8:20 a. m.	3.12	.06	.07	.08	.09	I
	3:30 p. m.	3.15	.07	.07	.07	.07	I
Feb. 16	10:20 a. m.	3.24	.12	.12	.12	.14	I
	5:10 p. m.	3.39	.16	.15	.14	.14	I
Feb. 17	8:10 a. m.	3.46	.09	.09	.09	.09	I
	3:30 p. m.	3.50	.10	.09	.11	.11	I
Feb. 18	8:25 a. m.	4.01	.12	.12	.12	.12	I
	3:30 p. m.	4.13	.13	.13	.13	.14	I
Feb. 19	8:20 a. m.	4.39	.16	.16	.17	.16	I
	3:20 p. m.	4.32	.16	.16	.17	.17	I
Feb. 20	8:20 a. m.	4.32	.15	.15	.17	.16	I
	3:25 p. m.	4.36	.16	.16	.16	.15	I
Feb. 21	8:20 a. m.	4.27	.16	.16	.17	.16	I
	3:05 p. m.	4.21	.15	.15	.15	.15	I
Feb. 22	8:35 a. m.	4.33	.15	.15	.16	.16	I
	4:30 p. m.	4.34	.17	.17	.17	.17	I
Feb. 23	9:55 a. m.	4.34	.18	.18	.19	.18	I
	5:15 p. m.	4.39	.19	.18	.19	.19	I
Feb. 24	8:30 a. m.	4.21	.19	.18	.19	.19	I
	3:00 p. m.	4.10	.18	.19	.19	.18	I
Feb. 25	8:15 a. m.	4.37	.18	.18	.18	.18	I
	2:35 p. m.	4.60	.19	.19	.20	.23	I
Feb. 26	8:25 a. m.	4.69	.32	.33	.33	.31	I
	3:35 p. m.	4.56	.32	.32	.34	.32	I
Feb. 27	8:50 a. m.	3.99	.19	.18	.19	.19	I
	2:40 p. m.	4.01	.16	.17	.19	.17	I
Feb. 28	8:45 a. m.	4.24	.26	.26	.25	.26	I
	2:45 p. m.	4.36	.29	.29	.29	.30	I
Feb. 29	8:25 a. m.	5.26	.28	.29	.28	.27	I
	4:00 p. m.	5.30	.42	.41	.42	.42	I
Mar. 1	11:00 a. m.	4.93	.48	.49	.48	.49	I
	5:40 p. m.	4.85	.46	.46	.46	.46	I

TABLE 10.—Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1936</i>							
Mar. 2	9:00 a. m.	4.50	.39	.39	.39	.39	I
	3:20 p. m.	4.40	.36	.36	.36	.39	I
Mar. 3	8:45 a. m.	4.20	.35	.36	.37	.37	I
	3:00 p. m.	4.12	.36	.36	.36	.36	I
Mar. 4	9:00 a. m.	3.95	.31	.30	.30	.30	I
	3:10 p. m.	3.87	.29	.29	.29	.29	I
Mar. 5	9:00 a. m.	3.86	.25	.25	.25	.25	I
	3:30 p. m.	3.88	.23	.24	.24	.25	I
Mar. 6	8:50 a. m.	4.69	.24	.25	.25	.25	I
	3:20 p. m.	5.04	.24	.24	.25	.25	I
Mar. 7	8:35 a. m.	5.68	.41	.40	.40	.41	I
	5:00 p. m.	5.49	.44	.44	.44	.45	I
Mar. 8	10:00 a. m.	5.66	.60	.60	.60	.60	I
	4:30 p. m.	5.67	.72	.73	.74	.73	I
Mar. 9	8:20 a. m.	5.84	1.12	1.12	1.12	1.10	I
	3:10 p. m.	5.51	1.23	1.22	1.22	1.22	I
Mar. 10	8:10 a. m.	5.77	1.27	1.27	1.26	1.26	I
	3:20 p. m.	5.52	1.29	1.29	1.30	1.29	I
Mar. 11	8:40 a. m.	5.62	1.09	1.10	1.10	1.10	I
	3:05 p. m.	5.47	1.11	1.11	1.11	1.10	I
Mar. 12	8:10 a. m.	5.72	1.03	1.04	1.09	1.09	I
	3:15 p. m.	5.60	.99	1.00	.99	1.03	I
Mar. 13	8:55 a. m.	5.81	.90	.91	.86	.85	I
	3:15 p. m.	5.70	.85	.84	.85	.85	I
Mar. 14	8:30 a. m.	6.14	.75	.74	.74	.76	I
	4:00 p. m.	5.90	.80	.79	.79	.79	I
Mar. 15	9:40 a. m.	5.99	.72	.78	.79	.86	I
	4:00 p. m.	5.90	.75	.82	.84	.92	I
Mar. 16	8:40 a. m.	5.81	.73	.74	.77	.71	I
Mar. 17	9:25 a. m.	5.93	.66	.68	.67	.66	I
	2:45 p. m.	6.13	.63	.63	.64	.64	I
Mar. 18	3:30 p. m.	6.30	.62	.61	.60	.63	I
Mar. 19	8:10 a. m.	6.34	.66	.69	.72	.71	I
	3:10 p. m.	6.24	.57	.64	.56	.56	I
Mar. 20	8:15 a. m.	6.21	.49	.53	.51	.51	I
	3:10 p. m.	6.22	.50	.51	.50	.51	I
Mar. 21	8:30 a. m.	5.71	.49	.47	.48	.48	I
	3:30 p. m.	5.84	.49	.50	.49	.50	I
Mar. 22	10:20 a. m.	5.68	.45	.44	.47	.46	I
	4:10 p. m.	5.57	.44	.45	.46	.46	I
Mar. 23	8:40 a. m.	5.35	.41	.41	.41	.44	I
	3:15 p. m.	5.50	.40	.35	.35	.35	I
Mar. 24	9:00 a. m.	5.51	.36	.37	.36	.37	I
	3:20 p. m.	5.41	.38	.37	.37	.37	I
Mar. 25	8:20 a. m.	5.49	.34	.35	.36	.35	I
	3:15 p. m.	5.56	.34	.34	.34	.34	I
Mar. 26	8:20 a. m.	5.54	.33	.34	.34	.34	I
	3:15 p. m.	5.42	.35	.36	.36	.38	I

TABLE 10.—*Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued*

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1936</i>							
Mar. 27	8:25 a. m.	5.78	0.39	0.36	0.35	0.34	I
	2:35 p. m.	5.66	.39	.33	.43	.40	I
Mar. 28	8:30 a. m.	5.41	.37	.37	.33	.36	I
	3:10 p. m.	5.30	.37	.39	.41	.36	I
Mar. 29	10:10 a. m.	5.13	.41	.39	.39	.39	I
	4:40 p. m.	5.08	.39	.40	.40	.39	I
Mar. 30	8:35 a. m.	5.54	.32	.32	.33	.31	I
	3:05 p. m.	5.20	.36	.36	.36	.38	I
Mar. 31	9:05 a. m.	5.03	.38	.30	.37	.38	I
	3:25 p. m.	4.87	.38	.39	.38	.38	I
Apr. 1	9:25 a. m.	4.59	.37	.38	.38	.37	I
	3:15 p. m.	4.50	.32	.33	.34	.34	I
Apr. 2	8:35 a. m.	4.64	.31	.31	.31	.30	I
	3:20 p. m.	4.67	.24	.25	.24	.23	I
Apr. 3	9:15 a. m.	5.13	.28	.29	.29	.29	I
	3:15 p. m.	5.21	.32	.32	.33	.29	I
Apr. 4	9:20 a. m.	5.11	.46	.44	.46	.46	I
	2:35 a. m.	5.24	.43	.44	.43	.44	I
Apr. 5	10:10 a. m.	5.49	.39	.39	.39	.38	I
	3:20 p. m.	5.31	.38	.40	.40	.40	I
Apr. 6	8:30 a. m.	4.84	.39	.39	.39	.40	I
	3:15 p. m.	4.91	.39	.39	.40	.40	I
Apr. 7	9:00 a. m.	4.98	.39	.38	.38	.39	I
	3:10 p. m.	5.15	.36	.37	.35	.38	I
Apr. 8	8:15 a. m.	5.29	.36	.36	.35	.36	I
	3:05 p. m.	5.21	.40	.41	.39	.40	I
Apr. 9	8:15 a. m.	4.96	.40	.39	.40	.39	I
	3:15 p. m.	4.71	.38	.37	.38	.39	I
Apr. 10	8:20 a. m.	4.69	.29	.29	.30	.29	I
	3:20 p. m.	4.53	.27	.28	.28	.28	I
Apr. 11	8:20 a. m.	4.56	.27	.28	.27	.28	I
	4:50 p. m.	4.54	.24	.24	.23	.24	I
Apr. 12	9:45 a. m.	4.63	.23	.24	.23	.23	I
	4:10 p. m.	5.03	.21	.21	.22	.22	I
Apr. 13	8:20 a. m.	6.86	.58	.51	.62	.59	I
	3:20 p. m.	6.54	.81	.86	.86	.87	I
Apr. 14	8:25 a. m.	6.81	.89	.87	.90	.86	I
	3:20 p. m.	6.53	.93	.88	.89	.87	I
Apr. 15	8:20 a. m.	7.28	1.07	1.17	1.13	1.09	I
	3:20 p. m.	7.03	1.04	1.07	1.07	1.07	I
Apr. 16	8:15 a. m.	8.14	1.15	1.22	1.21	1.22	I
	3:55 p. m.	9.01	1.15	1.19	1.16	1.17	I
Apr. 17	8:40 a. m.	9.60	1.42	1.42	1.37	1.50	I
	3:00 p. m.	10.41	1.48	1.52	1.46	1.52	I
Apr. 18	8:25 a. m.	11.44	1.74	1.66	1.68	1.56	I
	4:00 p. m.	11.87	1.64	1.72	1.73	1.70	I
Apr. 19	10:15 a. m.	12.21	1.62	1.68	1.60	1.63	I
	4:45 p. m.	12.44	1.72	1.67	1.61	1.59	I

TABLE 10.—Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1936</i>							
Apr. 20	8:25 a. m.	13.08	1.74	1.67	1.66	1.76	I
	3:15 p. m.	13.45	1.51	1.47	1.57	1.58	I
Apr. 21	8:40 a. m.	14.40	1.56	1.81	1.76	1.97	I
	3:25 p. m.	14.84	1.48	1.51	1.46		I
Apr. 22	9:05 a. m.	15.24	1.55	1.50	1.60	1.54	I
	3:15 p. m.	15.32	1.46	1.70	1.55	1.63	I
Apr. 23	9:30 a. m.	15.39	1.33	1.73	1.53	1.53	I
	3:05 p. m.	15.76	1.43	2.14	1.32	1.56	I
Apr. 24	9:30 a. m.	16.00	1.45	1.28	1.37	1.33	I
	3:00 p. m.	16.36	1.30	1.36	1.21	1.25	I
Apr. 25	8:40 a. m.	16.87	1.57	1.42	1.43	1.61	I
	4:10 p. m.	17.16	1.38	1.25	1.42	1.39	I
Apr. 26	8:50 a. m.	17.70	1.70	1.52	2.05	1.64	I
	4:45 p. m.	18.18	1.40	1.45	1.30	1.60	I
Apr. 27	8:35 a. m.	18.25	1.50	1.32	1.54	1.40	I
	4:30 p. m.	18.20	1.25	1.27	1.63	1.21	I
Apr. 28	8:40 a. m.	18.20	1.42	1.26	1.78	1.47	I
	2:50 p. m.	18.38	1.19	1.47	1.54	2.56	I
Apr. 29	8:20 a. m.	18.43	1.15	1.31	1.70	1.21	I
	3:20 p. m.	18.62	1.27	1.17	1.48	1.30	I
Apr. 30	8:35 a. m.	18.56	1.28	1.18	1.16	1.05	I
	3:05 p. m.	18.66	1.40	1.13	1.49	1.42	I
May 1	9:00 a. m.	18.55	1.14	1.23	1.11	1.08	I
	3:00 p. m.	18.59	1.04	1.14	1.51	1.01	I
May 2	8:30 a. m.	18.46	1.02	1.12	1.05	.98	I
	4:00 p. m.	18.56	1.00	.92	1.04	.95	I
May 3	8:45 a. m.	18.49	1.03	.88	.98	.89	I
	3:50 p. m.	18.17	.89	.93	.86	1.13	I
May 4	8:30 a. m.	17.59	.88	.74	.88	.92	I
	3:30 p. m.	17.40	.83	.63	.81	.75	I
May 5	9:00 a. m.	17.13	.89	.92	.76	.95	I
	3:10 p. m.	17.21	.80	.72	.69	.59	I
May 6	9:20 a. m.	17.19	.83	.60	.62	.61	I
	3:10 p. m.	17.55	.78	.59	.66	.65	I
May 7	8:45 a. m.	18.28	.84	.70	.78	.73	I
	3:20 p. m.	18.63	.73	.65	.71	.77	I
May 8	8:35 a. m.	19.84	.85	.83	1.20	.93	I
	3:20 p. m.	20.22	.99	.85	.76	1.10	I
May 9	9:35 a. m.	21.32	1.05	1.19	.90	1.13	I
	4:15 p. m.	21.50	1.11	.97	1.07	1.05	I
May 10	8:40 a. m.	21.11	1.08	.95	1.03	.88	I
	4:30 p. m.	20.86	.86	.84	.57	.95	I
May 11	8:30 a. m.	20.06	.72	.72	.61	.78	I
	3:05 p. m.	19.70	.75	.81	.66	.84	I
May 12	8:45 a. m.	18.91	.77	.54	.64	.60	I
	3:25 p. m.	18.43	.62	.52	.58	.62	I
May 13	8:45 a. m.	17.62	.54	.51	.69	.56	I
	3:00 p. m.	17.36	.49	.44	.59	.47	I

TABLE 10.—*Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued*

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1936</i>							
May 14	8:35 a. m.	16.63	.51	.45	.51	.61	I
	3:20 p. m.	16.33	.52	.50	.46	.50	I
May 15	8:25 a. m.	16.18	.46	.40	.46	.42	I
	3:10 p. m.	16.47	.49	.38	.34	.44	I
May 16	8:35 a. m.	16.86	.48	.46	.47	.55	I
	3:45 p. m.	17.41	.42	.39	.38	.37	I
May 17	10:45 a. m.	18.00	.78	.54	.45	.47	I
	4:00 p. m.	18.30	.51	.41	.42	.48	I
May 18	9:00 a. m.	19.11	.57	.51	.44	.49	I
	4:15 p. m.	19.59	.64	.61	.59	.52	I
May 19	8:45 a. m.	20.37	.62	.54	.45	.54	I
	3:45 p. m.	20.86	.56	.53	.52	.50	I
May 20	9:00 a. m.	21.51	.60	.52	.58	.62	I
	4:30 p. m.	21.77	.82	.65	.72	.60	I
May 21	9:00 a. m.	21.95	.65	.54	.57	.60	I
	4:00 p. m.	22.11	.59	.55	.61	.63	I
May 22	9:00 a. m.	22.02	.63	.49	.48	.62	I
	4:20 p. m.	21.94	.68	.59	.60	.65	I
May 23	9:00 a. m.	22.32	.67	.58	.65	.72	I
	4:00 p. m.	22.45	.30	.59	.54	.61	I
May 24	8:45 a. m.	22.58	.57	.49	.67	.61	I
	4:30 p. m.	22.51	.60	.57	.60	.56	I
May 25	9:15 a. m.	22.17	.51	.49	.42	.48	I
	4:15 p. m.	22.14	.41	.41	.37	.44	I
May 26	9:00 a. m.	21.73	.71	.49	.44	.51	I
	4:15 p. m.	21.60	.54	.44	.46	.47	I
May 27	9:00 a. m.	21.37	.60	.56	.48	.50	I
	4:30 p. m.	21.33	.53	.53	.48	.60	I
May 28	9:00 a. m.	21.34	.54	.51	.52	.56	I
	3:30 p. m.	21.34	.43	.39	.34	.44	I
May 29	8:45 a. m.	21.24	.39	.36	.40	.37	I
	4:30 p. m.	21.36	.56	.50	.53	.48	I
May 30	9:00 a. m.	21.27	.63	.51	.63	.59	I
	3:15 p. m.	21.33	.41	.38	.44	.38	I
May 31	8:30 a. m.	21.16	.46	.41	.34	.42	I
	4:30 p. m.	21.09	.56	.51	.49	.52	I
June 1	9:30 a. m.	20.75	.45	.43	.42	.41	I
	4:15 p. m.	20.85	.50	.49	.47	.50	I
June 2	9:00 a. m.	20.98	.55	.48	.50	.53	I
	4:30 p. m.	21.38	.56	.56	.54	.56	I
June 3	8:45 a. m.	21.67	.53	.53	.45	.47	I
	4:30 p. m.	21.81	.49	.41	.47	.45	I
June 4	9:00 a. m.	21.81	.53	.51	.47	.58	I
	5:20 p. m.	21.93	.65	.57	.59	.67	I
June 5	8:45 a. m.	21.53	.47	.49	.41	.43	I
	4:30 p. m.	21.18	.44	.44	.43	.50	I
June 6	9:45 a. m.	20.59	.48	.50	.53	.55	I
	4:30 p. m.	20.21	.49	.47	.48	.46	I

TABLE 10.—Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1936</i>							
June 7	9:15 a. m.	19.35	.46	.50	.48	.49	I
	4:30 p. m.	19.03	.44	.44	.42	.46	I
June 8	8:45 a. m.	18.57	.41	.42	.41	.39	I
	4:00 p. m.	18.33	.42	.41	.38	.36	I
June 9	9:30 a. m.	17.96	.41	.40	.41	.37	I
	4:15 p. m.	17.75	.34	.37	.40	.39	I
June 10	9:30 a. m.	17.47	.40	.41	.38	.37	I
	2:45 p. m.	17.38	.28	.28	.26	.28	I
June 11	9:00 a. m.	17.33	.45	.41	.40	.37	I
	3:30 p. m.	17.35	.38	.37	.44	.40	I
June 12	9:00 a. m.	17.80	.40	.35	.38	.37	I
	4:30 p. m.	18.03	.41	.37	.37	.39	I
June 13	8:45 a. m.	18.17	.36	.35	.34	.35	I
	4:00 p. m.	18.09	.38	.38	.36	.31	I
June 14	8:45 a. m.	18.02	.37	.40	.37	.37	I
	4:30 p. m.	18.05	.30	.30	.29	.33	I
June 15	8:50 a. m.	17.96	.30	.29	.28	.31	I
	4:35 p. m.	17.82	.36	.33	.33	.33	I
June 16	10:00 a. m.	17.67	.31	.34	.30	.40	I
	4:30 p. m.	17.67	.31	.31	.30	.34	I
June 17	9:00 a. m.	17.45	.31	.34	.32	.31	I
	5:15 p. m.	17.48	.34	.35	.32	.39	I
June 18	9:15 a. m.	17.31	.29	.32	.30	.35	I
	4:15 p. m.	17.13	.40	.34	.36	.34	I
June 19	9:15 a. m.	16.90	.28	.33	.29	.25	I
	3:30 p. m.	16.89	.26	.25	.26	.24	I
June 20	9:30 a. m.	16.75	.27	.27	.29	.32	I
	4:30 p. m.	16.61	.31	.28	.28	.36	I
June 21	8:45 a. m.	16.42	.25	.26	.27	.24	I
	7:00 p. m.	16.28	.24	.22	.21	.28	I
June 22	9:00 a. m.	16.08	.27	.29	.33	.30	I
	4:40 p. m.	16.01	.27	.24	.23	.23	I
June 23	9:00 a. m.	15.86	.28	.31	.26	.28	I
	4:15 p. m.	15.60	.30	.30	.27	.24	I
June 24	9:30 a. m.	15.36	.26	.31	.29	.31	I
	4:30 p. m.	15.24	.27	.25	.26	.26	I
June 25	9:00 a. m.	14.88	.23	.19	.19	.22	I
	5:00 p. m.	14.74	.24	.24	.24	.23	I
June 26	9:40 a. m.	14.49	.21	.21	.21	.17	I
	4:45 p. m.	14.38	.23	.18	.20	.24	I
June 27	8:45 a. m.	14.19	.21	.19	.18	.18	I
	3:00 p. m.	14.14	.19	.19	.19	.16	I
June 28	9:00 a. m.	13.84	.22	.20	.17	.21	I
	4:10 p. m.	13.68	.21	.18	.20	.20	I
June 29	9:00 a. m.	13.28	.24	.22	.29	.23	I
	3:30 p. m.	13.23	.23	.19	.20	.21	I
June 30	9:00 a. m.	13.07	.23	.20	.19	.19	I
	4:20 p. m.	13.08	.20	.18	.20	.20	I

## QUANTITIES OF SUSPENDED SEDIMENT

79

TABLE 10.—Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1936</i>							
July 1	10:00 a. m.	12.91	0.18	0.20	0.19	0.20	I
	4:30 p. m.	12.84	.19	.17	.16	.18	I
July 2	9:30 a. m.	12.50	.17	.18	.16	.15	I
	4:15 p. m.	12.37	.16	.17	.17	.18	I
July 3	9:30 a. m.	12.12	.17	.16	.17	.15	I
	4:00 p. m.	12.16	.19	.17	.19	.18	I
July 4	9:30 a. m.	11.88	.13	.15	.15	.16	I
	3:10 p. m.	11.85	.17	.16	.17	.17	I
July 4	9:30 a. m.	11.52	.16	.14	.16	.15	I
	3:00 p. m.	11.43	.16	.15	.15	.16	I
July 6	9:45 a. m.	10.89	.14	.17	.17	.16	I
	4:15 p. m.	10.71	.19	.18	.17	.17	I
July 7	9:45 a. m.	10.35	.20	.18	.17	.19	I
	4:00 p. m.	10.26	.15	.16	.20	.17	I
July 8	10:00 a. m.	9.94	.13	.15	.13	.12	I
	3:15 p. m.	9.80	.10	.13	.12	.12	I
July 9	9:30 a. m.	9.66	.12	.12	.12	.14	I
	3:00 p. m.	9.33	.14	.14	.13	.15	I
July 10	9:15 a. m.	8.94	.13	.14	.13	.13	I
	4:15 p. m.	8.79	.13	.12	.12	.12	I
July 11	9:30 a. m.	8.93	.12	.13	.12	.13	I
	2:30 p. m.	10.81	.12	.13	.12	.12	I
July 12	9:30 a. m.	8.52	.30	.29	.28	.27	I
	4:30 p. m.	8.52	4.19	4.20	4.12	4.11	I
July 13	9:30 a. m.	13.32	.80	.84	.81	.84	I
	2:30 p. m.	14.59	.82	.83	.77	.83	I
July 14	9:30 a. m.	14.58	6.13	6.03	6.30	6.24	I
	4:15 p. m.	13.67	3.27	3.23	3.30	3.29	I
July 15	9:30 a. m.	11.59	1.68	1.68	1.75	1.69	I
	3:30 p. m.	11.19	1.73	1.72	1.86	1.69	I
July 16	10:30 a. m.	10.33	3.04	3.06	3.09	3.08	I
	3:45 p. m.	10.31	3.20	3.18	3.20	3.19	I
July 17	9:15 a. m.	9.94	3.77	3.81	3.84	3.83	I
	2:45 p. m.	9.98	3.41	3.42	3.50	3.40	I
July 18	9:30 a. m.	9.80	2.41	2.46	2.43	2.46	I
	3:30 p. m.	9.66	2.36	2.34	2.34	2.33	I
July 19	9:30 a. m.	9.15	1.80	1.80	1.80	1.80	I
	3:45 p. m.	8.89	1.90	1.88	1.89	1.88	I
July 20	9:45 a. m.	8.66	1.14	1.16	1.16	1.12	I
	4:45 p. m.	8.48	.88	.89	.89	.88	I
July 21	9:45 a. m.	8.69	.89	.93	.91	.89	I
	4:30 p. m.	8.98	.86	.84	.92	.85	I
July 22	9:30 a. m.	9.24	.96	.97	.98	.97	I
	4:30 p. m.	9.16	.85	.84	.86	.86	I
July 23	9:15 a. m.	8.89	.75	.75	.76	.75	I
	4:30 p. m.	8.75	.76	.76	.76	.75	I
July 24	9:45 a. m.	8.83	.67	.68	.68	.65	I
	2:45 p. m.	8.73	.56	.56	.56	.56	I

TABLE 10.—*Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued*

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1936</i>							
July 25	9:30 a. m.	8.21	0.80	0.79	0.80	0.80	I
	4:15 p. m.	8.21	.67	.68	.67	.68	I
July 26	9:45 a. m.	7.82	.59	.58	.58	.59	I
	4:15 p. m.	7.78	.53	.53	.53	.54	I
July 27	9:30 a. m.	7.76	.61	.61	.61	.60	I
	4:00 p. m.	7.95	.66	.65	.91	.64	I
July 28	10:30 a. m.	7.04	1.33	1.31	1.33	1.31	I
	4:30 p. m.	7.33	.90	.90	.91	.91	I
July 29	9:15 a. m.	7.56	1.06	1.06	1.05	1.05	I
	4:00 p. m.	7.25	1.45	1.42	1.40	1.40	I
July 30	9:15 a. m.	7.33	1.44	1.45	1.46	1.46	I
	4:15 p. m.	6.81	1.16	1.19	1.17	1.18	I
July 31	9:45 a. m.	6.04	1.11	1.08	1.08	1.05	I
	4:15 p. m.	5.91	.91	.89	.89	.90	I
Aug. 1	10:10 a. m.	6.87	1.05	1.03	1.02	.97	I
	3:45 p. m.	6.79	1.23	1.23	1.30	1.23	I
Aug. 2	9:30 a. m.	6.45	.99	1.00	.99	.99	I
	4:30 p. m.	6.31	.88	.87	.94	.87	I
Aug. 3	9:30 a. m.	6.27	.79	.82	.80	.80	I
	4:00 p. m.	6.50	1.04	1.04	1.02	1.02	I
Aug. 4	9:30 a. m.	6.80	1.43	1.43	1.43	1.42	I
	4:30 p. m.	6.77	1.56	1.52	1.51	1.51	I
Aug. 5	9:30 a. m.	8.93	3.26	3.33	3.36	3.38	I
	2:30 p. m.	9.56	3.02	2.99	2.93	2.89	I
Aug. 6	9:30 a. m.	10.32	3.32	3.39	3.29	3.29	I
	4:30 p. m.	11.84	5.11	5.21	5.12	5.07	I
Aug. 7	10:00 a. m.	14.39	6.17	5.70	6.07	5.86	I
	4:30 p. m.	15.53	4.89	4.82	4.60	4.68	I
Aug. 8	10:00 a. m.	12.67	6.84	6.88	6.80	6.90	I
	4:30 p. m.	12.63	6.21	5.93	6.08	6.05	I
Aug. 9	9:45 a. m.	13.20	5.32	5.20	5.08	5.08	I
	4:00 p. m.	13.87	5.73	5.41	5.34	5.29	I
Aug. 10	9:45 a. m.	13.86	4.09	4.23	4.06	4.05	I
	4:00 p. m.	13.31	2.83	3.83	5.11	3.74	I
Aug. 11	10:00 a. m.	12.52	3.32	3.29	3.21	3.21	I
	4:30 p. m.	12.12	3.15	3.20	3.07	2.98	I
Aug. 12	10:00 a. m.	11.63	2.66	2.91	2.64	2.57	I
	6:00 p. m.	11.56	2.81	2.75	2.80	—	I
Aug. 13	9:45 a. m.	10.80	2.51	2.60	2.58	2.42	I
	5:00 p. m.	10.79	2.52	2.59	2.52	2.52	I
Aug. 14	9:20 a. m.	10.25	2.34	2.29	2.34	2.32	I
	5:10 p. m.	9.87	1.93	1.92	1.89	1.89	I
Aug. 15	9:20 a. m.	9.50	2.35	2.32	2.38	2.35	I
	4:15 p. m.	9.16	2.13	2.07	2.12	2.05	I
Aug. 16	10:20 a. m.	8.50	1.71	1.70	1.73	1.71	I
	2:15 p. m.	8.38	1.64	1.62	1.66	1.63	I
Aug. 17	9:15 a. m.	8.22	1.54	1.54	1.56	1.58	I
	4:30 p. m.	8.16	1.43	1.39	1.42	1.43	I

TABLE 10.—*Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued*

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1936</i>							
Aug. 18	10:15 a. m.	8.28	1.13	1.13	1.13	1.13	I
	4:10 p. m.	8.20	1.24	1.18	1.19	1.05	I
Aug. 19	9:20 a. m.	8.00	1.49	1.48	1.47	1.25	I
Aug. 20	10:00 a. m.	8.32	1.23	1.23	1.24	1.20	I
Aug. 21		11.40					I
Aug. 22		11.60					I
Aug. 23	3:30 p. m.	9.84	1.72	1.76	1.81	1.70	I
Aug. 24	10:00 a. m.	9.85	2.22	2.19	1.93	2.18	I
Aug. 25	9:15 a. m.	8.61	2.02	2.26	2.01	2.02	I
Aug. 26	9:20 a. m.	7.69	2.17	2.23	2.18	2.19	I
Aug. 27	9:20 a. m.	7.47	2.06	2.06	2.07	2.08	I
Aug. 28	9:45 a. m.	6.93	1.32	1.33	1.36	1.33	I
Aug. 29	9:45 a. m.	6.44	.97	.98	.99	.98	I
Aug. 30	9:30 a. m.	5.91	.92	.93	.92	.94	I
	2:30 p. m.	5.53	1.37	1.36	1.37	1.38	I
Aug. 31	9:30 a. m.	6.88	7.03	7.14	7.27	7.42	I
	4:00 p. m.		3.71	3.80	3.78	3.83	I
Sept. 1	10:00 a. m.	8.90	2.70	2.86	2.89	2.85	I
	4:00 p. m.	7.11	3.35	3.25	3.22	3.12	I
Sept. 2	9:45 a. m.	11.90	4.76	5.01	5.02	5.09	I
	3:00 p. m.	9.45	3.95	3.88	4.07	4.01	I
Sept. 3	9:45 a. m.	12.26	7.29	7.21	7.68	7.85	I
	3:45 p. m.	13.27	8.00	7.98	7.94	7.98	I
Sept. 4	9:45 a. m.	11.20	7.22	7.34	7.20	7.27	I
	4:30 p. m.	11.36	6.34	6.60	6.51	6.41	I
Sept. 5	9:15 a. m.	10.23	4.66	4.97	4.70	4.70	I
	4:45 p. m.	10.56	4.13	4.00	4.07	4.05	I
Sept. 6	9:30 a. m.	9.86	3.57	3.68	3.72	3.67	I
	4:30 p. m.	10.35	3.23	3.18	3.21	3.15	I
Sept. 7	9:30 a. m.	9.14	3.47	3.30	3.40	3.30	I
	4:30 p. m.	9.48	2.80	2.91	2.83	2.76	I
Sept. 8	9:15 a. m.	8.73	2.60	2.62	2.57	2.83	I
	3:30 p. m.	9.28	2.44	2.30	2.47	2.50	I
Sept. 9	9:30 a. m.	7.51	2.43	2.42	2.42	2.32	I
Sept. 10	9:30 a. m.	7.18	1.90	2.03	1.96	1.99	I
	3:45 p. m.	7.38	1.77	1.49	1.61	1.57	I
Sept. 11	9:30 a. m.	6.85	1.24	1.40	1.42	1.44	I
	3:30 p. m.	7.14	1.28	1.28	1.16	1.20	I
Sept. 12	9:00 a. m.	6.45		1.36	1.41	1.40	I
	3:00 p. m.	6.53	1.40	1.36	1.32	1.38	I
Sept. 13	9:30 a. m.	6.00	1.44	1.49	1.61	1.38	I
	4:20 p. m.	6.16	1.61	1.66	1.69	1.71	I

<sup>1</sup> Estimated.

TABLE 10.—*Suspended-sediment concentration in individual samples collected from the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 1, 1935, to Sept. 30, 1936—Continued*

Date	Time	Gage height (feet)	Suspended sediment at sampling points indicated (percent by weight)				Type of sample
			A	B	C	D	
<i>1936</i>							
Sept. 14	9:30 a. m.	6.98	2.56	2.82	2.32	2.62	I
	7:15 p. m.	7.44	2.63	2.80	2.85	2.39	I
Sept. 15	9:30 a. m.	6.50	1.73	1.91	2.00	1.94	I
	4:30 p. m.	6.72	1.92	1.89	1.86	1.69	I
Sept. 16	9:45 a. m.	6.21	1.49	1.61	1.37	1.43	I
	3:40 p. m.	6.34	1.45	1.58	1.49	1.53	I
Sept. 17	9:45 a. m.	5.91	1.38	1.29	1.33	1.51	I
	3:30 p. m.	6.09	1.36	1.24	1.23	1.18	I
Sept. 18	9:20 a. m.	5.63	1.06	.98	1.00	1.04	I
	2:50 p. m.	5.70	1.02	1.00	.96	.98	I
Sept. 19	9:15 a. m.	5.71	.84	.78	.82	.83	I
	3:40 p. m.	5.64	.79	.79	.78	.79	I
Sept. 20	9:50 a. m.	5.53	.72	.72	.72	.72	I
	4:30 p. m.	5.54	.68	.65	.66	.66	I
Sept. 21	9:20 a. m.	4.98	.53	.53	.53	.53	I
Sept. 22	9:50 a. m.	7.37	2.13	2.09	2.08	2.05	I
	4:30 p. m.	4.96	4.41	4.48	4.56	4.51	I
Sept. 23	9:50 a. m.	5.78	2.31	2.34	2.27	2.28	I
	4:30 p. m.	6.25	1.89	1.86	1.90	1.81	I
Sept. 24	9:30 a. m.	5.65	3.21	3.19	3.12	3.13	I
	3:30 p. m.	6.00	2.86	2.88	2.92	2.85	I
Sept. 25	9:40 a. m.	5.56	2.24	2.19	2.18	2.21	I
	4:45 p. m.	5.62	1.79	1.80	1.69	1.76	I
Sept. 26	9:30 a. m.	5.69	1.35	1.40	1.41	1.44	I
	3:45 p. m.	5.93	1.27	1.34	1.30	1.29	I
Sept. 27	8:45 a. m.	4.94	1.91	1.90	1.82	1.90	I
	4:10 p. m.	5.62	1.60	1.63	1.60	1.59	I
Sept. 28	9:30 a. m.	4.56	1.18	1.23	1.27	1.21	I
	4:00 p. m.	5.76	1.12	1.18	1.12	1.11	I
Sept. 29	9:20 a. m.	3.99	1.09	1.06	1.11	1.06	I
	3:00 p. m.	4.37	1.10	1.11	1.08	1.04	I
Sept. 30	9:15 a. m.	3.65	.98	.98	.97	.96	I
	3:50 p. m.	3.87	.85	.85	.86	.85	I

## QUANTITIES OF SUSPENDED SEDIMENT

83

TABLE 11.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Willow Beach, Ariz., Oct. 1, 1934, to Sept. 30, 1936*

1934

Day	October			November			December		
	Mean discharge (second- feet)	Suspended matter		Mean discharge (second- feet)	Suspended matter		Mean discharge (second- feet)	Suspended matter	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	3,620	0.98	96,800	3,020	0.22	17,900	4,310	0.27	31,400
2	4,220	.82	93,400	3,070	.21	17,400	4,340	.31	36,300
3	3,690	.94	93,700	3,080	.21	17,500	4,400	.30	35,600
4	3,370	.77	70,100	3,040	.22	18,100	4,430	.28	33,500
5	3,110	.60	50,400	3,080	.20	16,600	4,310	.27	31,400
6	3,580	.46	44,400	3,090	.21	17,500	4,370	.26	30,700
7	3,640	.56	55,000	3,010	.17	13,800	4,430	.28	33,500
8	3,530	.50	47,700	3,080	.18	15,000	4,370	.26	30,700
9	3,330	.76	68,300	3,050	.24	19,800	4,190	.25	28,800
10	3,310	2.82	258,000	3,050	.22	18,100	4,160	.26	29,200
11	3,210	3.05	264,000	3,020	.20	16,300	3,970	.26	27,900
12	3,170	2.45	210,000	2,970	.23	18,400	3,730	1.01	24,200
13	3,120	1.56	131,000	3,060	.19	15,700	3,580	.24	23,200
14	3,090	1.10	91,800	3,140	.18	15,300	3,640	.22	21,600
15	2,920	.86	67,800	3,270	.19	16,800	3,640	.24	23,600
16	2,880	.59	45,900	3,390	.18	16,500	3,880	.26	27,200
17	2,820	.46	35,000	3,360	.18	16,300	4,370	.78	119,000
18	2,910	.36	28,300	3,610	.20	19,500	4,120	.46	51,100
19	2,760	.34	25,300	3,700	.22	22,000	4,430	.29	34,700
20	2,790	.82	24,100	3,910	.20	21,100	4,590	.26	32,200
21	2,650	.29	20,700	4,160	.34	38,200	4,970	.26	34,900
22	2,650	.28	20,100	4,090	.29	32,000	5,100	.26	35,800
23	2,820	.32	24,400	3,940	.25	26,600	4,940	.25	33,300
24	2,770	.25	18,700	3,970	.26	27,900	5,000	.25	33,800
25	2,850	.21	16,100	4,190	.26	29,400	5,160	.26	36,200
26	2,870	.23	17,800	4,120	.23	25,600	5,200	.31	43,500
27	2,990	.21	17,000	4,280	.32	37,000	4,940	.27	36,000
28	2,920	.21	16,600	4,190	.25	28,300	4,780	.28	36,100
29	2,940	.21	16,700	4,310	.24	27,900	4,750	.27	34,600
30	2,900	.24	18,800	4,310	.26	30,300	4,810	.28	36,400
31	2,940	.20	15,800	-----	-----	-----	4,840	.25	32,700
Monthly load (tons)		2,004,000	-----	-----	652,800	-----	-----	1,099,000	-----

1935

	January			February			March		
	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day
1	4,940	0.27	36,000	2,890	0.32	25,000	6,910	0.09	16,800
2	4,970	.26	34,900	3,030	.12	14,700	6,990	.10	18,900
3	4,880	.23	30,300	2,760	.06	4,210	7,070	.10	19,100
4	4,880	.22	29,000	5,390	.10	14,600	6,980	.07	13,200
5	4,940	.22	29,300	5,420	.07	10,200	6,460	.07	12,300
6	5,130	.22	30,500	5,430	.07	10,300	5,860	.05	7,910
7	5,320	.26	37,300	4,360	.06	7,070	5,950	.05	8,050
8	4,970	.23	30,800	4,650	.05	6,260	6,770	.06	11,000
9	4,840	.20	26,100	3,610	.04	3,890	7,070	.08	15,300
10	4,880	.20	26,400	152	.02	81	7,030	.06	11,400
11	4,650	.17	21,300	171	.02	92	7,070	.06	11,400
12	5,130	.16	22,200	508	.02	275	6,980	.06	11,300
13	5,260	.20	28,400	540	.02	297	6,950	.06	11,300
14	5,000	.18	24,300	2,310	.04	2,480	6,970	.06	11,300
15	6,060	.28	45,800	3,090	.04	3,350	6,860	.06	11,100
16	7,450	.64	129,000	3,220	.09	7,830	6,940	.05	9,370
17	7,560	1.82	371,000	4,440	.04	4,780	7,010	.05	9,450
18	6,590	1.17	208,000	4,420	.04	4,780	7,020	.05	9,480
19	6,160	1.26	210,000	4,430	.08	9,560	7,150	.06	11,600
20	6,790	.76	139,000	4,440	.23	27,600	7,150	.03	5,780
21	6,760	2.12	387,000	3,840	.08	8,290	7,250	.04	7,880
22	6,430	1.47	255,000	5,330	.08	11,600	7,280	.05	9,830
23	6,000	.92	149,000	5,250	.24	34,000	7,190	.04	7,780
24	5,550	.84	126,000	5,310	.17	24,400	7,250	.06	11,700
25	5,420	.75	110,000	5,310	.07	10,000	7,220	.16	31,200
26	4,940	.60	80,000	5,230	.07	9,880	7,380	.52	103,000
27	4,530	.58	70,900	5,370	.06	8,690	7,380	.41	81,700
28	4,000	.65	70,200	6,000	.08	13,000	7,350	.34	67,500
29	3,530	.60	57,200	-----	-----	-----	7,420	.18	36,100
30	3,380	.56	51,100	-----	-----	-----	7,760	.30	62,900
31	3,540	.45	43,000	-----	-----	-----	7,720	.31	64,600
Monthly load (tons)		2,909,000	-----	-----	277,200	-----	-----	720,200	-----

TABLE 11.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Willow Beach, Ariz., Oct. 1, 1934, to Sept. 30, 1936—Continued*

1935

Day	April			May			June		
	Mean discharge (second-feet)	Suspended matter		Mean discharge (second-feet)	Suspended matter		Mean discharge (second-feet)	Suspended matter	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1.	7,720	0.07	14,600	6,470	0.04	6,990	15,200	0.06	24,600
2.	7,690	.06	12,400	7,220	.04	7,800	15,300	.06	24,800
3.	7,620	.06	12,300	7,350	.03	5,940	15,300	.04	16,500
4.	7,650	.06	12,400	7,650	.03	6,210	15,800	.07	29,900
5.	7,550	.07	14,300	7,720	.03	6,260	15,800	.06	25,600
6.	7,380	.07	14,000	7,690	.03	6,240	15,900	.05	21,500
7.	7,350	.14	27,800	7,350	.05	9,940	16,300	.05	22,000
8.	7,420	.32	64,100	7,320	.04	7,910	16,300	.05	22,000
9.	7,320	.38	75,100	7,420	.04	8,020	16,200	.04	17,500
10.	6,710	.53	95,900	7,120	.04	7,690	16,400	.06	26,600
11.	6,740	.95	173,000	6,860	.05	9,260	16,800	.05	22,700
12.	7,450	.70	141,000	7,320	.05	9,880	17,000	.06	27,500
13.	7,380	.72	143,000	6,830	.07	12,900	17,200	.05	23,200
14.	7,450	.95	191,000	6,520	.10	17,600	17,300	.04	18,700
15.	7,420	.81	162,000	6,610	.06	10,700	17,300	.04	18,700
16.	6,860	1.15	213,000	6,550	.06	10,600	17,600	.04	19,000
17.	6,800	.96	176,000	6,610	.06	10,700	17,800	.04	19,200
18.	6,830	.62	114,000	7,070	.07	13,400	18,000	.06	29,200
19.	7,090	.45	86,100	7,350	.05	9,940	18,400	.04	19,900
20.	7,320	.24	47,400	7,220	.05	9,750	18,500	.04	20,000
21.	7,280	.31	60,700	6,930	.04	7,480	18,600	.05	25,100
22.	7,520	.04	8,120	7,910	.06	12,800	18,900	.04	20,400
23.	7,380	.04	7,960	11,300	.08	24,400	19,100	.04	20,600
24.	7,220	.05	9,750	13,000	.05	24,600	16,800	.04	18,100
25.	7,280	.04	7,860	14,800	.08	32,000	14,400	.04	15,600
26.	7,420	.40	80,100	14,700	.08	31,800	14,500	.05	19,600
27.	7,250	.08	15,700	15,000	.09	36,400	14,800	.05	20,000
28.	7,380	.05	9,960	14,900	.09	36,200	14,700	.05	19,800
29.	7,150	.05	9,670	14,900	.06	24,100	14,700	.04	15,900
30.	7,280	.06	11,800	15,200	.07	28,700	15,100	.07	28,500
31.				15,000	.06	24,300			
Monthly load (tons)		2,011,000			470,600				652,700

1935

	July			August			September		
	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day
1.	15,000	0.04	16,200	10,100	0.04	10,900	10,100	0.03	8,180
2.	15,000	.05	20,200	10,200	.03	8,260	10,000	.02	5,400
3.	15,000	.06	24,300	10,500	.05	14,200	9,960	.86	231,000
4.	15,000	.07	28,300	10,000	.03	8,100	10,100	.99	270,000
5.	15,000	.04	16,200	10,200	.04	11,000	9,960	.68	183,000
6.	15,300	.05	20,700	10,200	.04	11,000	10,100	.17	46,400
7.	15,200	.08	32,800	10,200	.05	13,800	10,000	.42	113,000
8.	15,000	.04	16,200	10,200	.04	11,000	10,100	.94	256,000
9.	13,300	.05	18,000	10,200	.05	13,800	9,960	.70	188,000
10.	10,000	.04	10,800	10,300	.04	11,100	10,000	.57	154,000
11.	10,200	.04	11,000	10,100	.07	19,100	10,000	1.08	292,000
12.	10,100	.03	8,180	10,200	.05	13,800	10,100	1.37	374,000
13.	10,200	.03	8,260	10,200	.04	11,000	10,000	.71	192,000
14.	10,000	.02	5,400	10,000	.04	10,800	9,920	.27	72,300
15.	9,960	.03	8,070	10,300	.01	2,780	10,100	.01	2,730
16.	10,200	.04	11,000	10,200	.02	5,510	10,100	.03	8,180
17.	10,100	.01	2,730	10,400	.02	5,620	9,960	.01	2,700
18.	9,960	.01	2,000	10,200	.03	8,260	9,960	.02	5,370
19.	10,000	.03	8,100	10,200	.02	5,510	10,000	.01	2,700
20.	10,000	.02	5,400	10,300	.03	8,340	10,000	.01	2,700
21.	10,000	.04	10,800	10,000	.02	5,400	10,100	.01	2,730
22.	10,100	.04	10,900	10,200	.03	8,260	9,960	.03	2,670
23.	10,300	.04	11,100	10,200	.04	11,000	9,920	.01	2,670
24.	10,200	.04	11,000	10,200	.02	5,510	9,840	.01	2,650
25.	9,960	.03	8,080	10,100	.02	5,450	9,920	.01	2,670
26.	10,000	.03	8,100	10,200	.02	5,510	10,100	.01	2,730
27.	10,100	.03	8,180	10,000	.02	5,400	9,800	.01	2,650
28.	10,000	.02	5,400	9,840	.04	10,600	9,880	.01	2,670
29.	10,100	.02	5,450	10,100	.02	5,050	9,920	.02	5,350
30.	10,200	.03	8,260	10,400	.02	5,620	9,800	.01	2,650
31.	10,100	.03	8,180	10,200	.02	5,510			
Monthly load (tons)		369,300			277,200				2,444,000

## QUANTITIES OF SUSPENDED SEDIMENT

85

TABLE 11.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Willow Beach, Ariz., Oct. 1, 1934, to Sept. 30, 1936—Continued*

1935

Day	October			November			December		
	Mean discharge (second-feet)	Suspended matter		Mean discharge (second-feet)	Suspended matter		Mean discharge (second-feet)	Suspended matter	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	9,940	0.005	1,350	9,880	0.04	10,700	4,950	0.006	810
2	9,860	.007	1,860	9,760	.04	10,500	4,950	.006	810
3	10,000	.02	5,400	9,680	.04	10,400	4,920		
4	9,960	.007	1,890	9,800	.04	10,600	4,910	.005	675
5	9,980	.01	2,700	9,740	.04	10,500	4,890	.002	270
6	9,740	1.57	413,000	9,680	.05	13,100	4,910		
7	9,720	1.60	420,000	9,740	.04	10,500	4,920	.007	918
8	9,880	1.64	437,000	9,840	.03	7,960	4,940		
9	9,800	1.99	526,000	9,620	.04	10,400	4,950	.01	1,350
10	9,680	2.16	565,000	9,620	.04	10,400	4,870	.01	1,320
11	9,900	1.86	497,000	9,700	.04	10,500	4,870		
12	10,000	1.19	321,000	9,640	.04	10,400	4,860	.008	1,050
13	9,720	.34	89,200	9,680	.04	10,400	4,890		
14	9,860	.004	1,050	9,740	.04	10,500	4,920	.006	810
15	9,760	.002	540	9,740	.05	13,100	4,920		
16	9,840	.005	1,320	9,660	.04	10,400	4,940	.004	540
17	9,820	.009	2,380	9,720	.04	10,500	4,810	.005	648
18	9,840	.003	810	9,800	.03	7,940	4,920	.01	1,320
19	9,860	.02	5,320	9,620	.03	7,800	4,860	.01	1,320
20	9,900	.02	5,350	9,600	.03	7,780	4,810		
21	9,900	.02	5,350	9,620	.03	7,800	4,760	.01	1,300
22	9,760	.02	5,260	9,640	.03	7,800	4,790		
23	9,740	.01	2,620	9,740	.03	7,880	4,830	.004	513
24	9,760	.01	2,650	9,780	.04	10,600	4,860	.01	1,320
25	9,800	.01	2,650	9,640	.03	7,800	4,870		
26	9,780	.01	2,650	9,560	.04	10,300	4,890	.005	648
27	9,780	.01	2,650	9,760	.04	10,500	4,760	.004	513
28	9,800	.02	5,290	9,520	.04	10,300	4,870	.009	1,190
29	9,800	.02	5,290	9,480	.03	7,670	4,810	.005	648
30	9,760	.02	5,260	7,470	.03	6,050	4,830	.006	783
31	9,900	.01	2,670				4,870	.006	783
Monthly load (tons)		3,340,000				291,100			

1936

	January			February			March		
	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day
1	4,810	0.01	1,300	4,840	0.005	648	6,370	0.006	1,030
2	4,870	.01	1,320	4,890	.004	540	6,380	.01	1,730
3	4,860	.01	1,320	4,810	.006	783	6,620	.009	1,620
4	4,790	.007	918	4,810	.005	648	6,910	.009	1,670
5	4,920	.005	675	4,810	.005	648	7,320	.01	1,970
6	4,940	.002	270	4,760	.006	783	7,830	.01	2,110
7	4,860	.004	513	4,870	.004	513	8,770	.02	4,720
8	4,860	.006	783	4,790	.004	513	8,810	.02	4,750
9	4,810	.006	783	4,890	.006	783	9,190	.02	4,970
10	4,860	.007	918	4,870	.005	648	9,580	.02	5,180
11	4,840	.004	513	5,120	.003	405	9,520	.02	5,130
12	4,830	.009	1,160	6,180	.01	1,670	9,700	.02	5,240
13	4,910	.004	540	6,060	.009	1,480	9,760	.02	5,260
14	4,830	.004	513	6,110	.004	648	9,740	.02	5,260
15	4,890	.005	648	6,040	.005	810	9,680		
16	4,760	.02	2,560	6,500	.006	1,050	9,640	.03	7,800
17	4,860	.006	783	6,500	.008	1,400	9,680	.02	5,240
18	4,810	.004	513	6,570	.004	702	9,750	.03	7,910
19	4,870	.009	1,190	6,320	.006	1,030	9,780	.03	7,910
20	4,840	.008	1,050	6,180	.008	1,320	9,820	.02	5,290
21	4,790	.007	918	6,130	.005	837	9,860	.02	5,320
22	4,890	.008	1,050	5,940	.003	486	9,820	.03	7,960
23	4,790	.004	513	5,860	.01	1,590	9,820	.02	5,290
24	4,810	.003	378	5,960	.006	972	9,780	.03	7,910
25	4,750	.004	513	5,960	.006	972	9,680	.02	5,240
26	4,860	.004	513	5,860	.006	945	9,700	.02	5,240
27	4,830	.007	918	5,960	.007	1,130	9,600	.02	5,180
28	4,840	.004	513	6,130	.01	1,650	9,740	.02	5,260
29	4,810	.004	513	6,400	.01	1,730	9,780	.03	7,910
30	4,810	.004	513				9,780	.02	5,290
31	4,860	.002	270				9,720	.02	5,240
Monthly load (tons)		24,880				27,330			155,900

TABLE 11.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Willow Beach, Ariz., Oct. 1, 1934, to Sept. 30, 1936—Continued*

1936

Day	April			May			June		
	Mean discharge (second-feet)	Suspended matter	Tons per day	Mean discharge (second-feet)	Suspended matter	Tons per day	Mean discharge (second-feet)	Suspended matter	Tons per day
Mean percent	Mean percent	Tons per day	Mean percent	Mean percent	Tons per day	Mean percent	Mean percent	Tons per day	
1	9,740	0.02	5,260	9,460	0.10	25,500	9,880	0.02	5,350
2	9,780	.02	5,290	9,220	.03	7,480	9,860	.01	2,670
3	9,560	.02	5,160	10,100	.02	5,450	9,700	.01	2,620
4	9,760	.02	5,260	10,300	.02	5,560	9,900	.01	2,670
5	9,700	.02	5,240	10,200	.02	5,510	10,000	.01	2,700
6	9,560	.02	5,160	10,300	.02	5,560	9,840	.01	2,650
7	9,900	.02	5,350	10,000	.02	5,400	9,420	.02	5,080
8	9,740	.02	5,260	9,980	.02	5,400	9,440	.01	2,540
9	9,600	.01	2,590	10,100	.01	2,730	9,500	.01	2,560
10	9,720	.02	5,240	10,100	.01	2,730	9,190	.02	4,970
11	9,660	.02	5,210	9,890	.01	2,670	9,130	.01	2,460
12	9,480	.01	2,560	8,840	.01	2,380	8,780	.01	2,380
13	9,700	.01	2,620	9,150	.005	1,240	8,840	.01	2,380
14	9,740	.01	2,620	9,580	.01	2,590	9,660	.008	2,080
15	9,680	.02	5,240	9,310	.008	2,000	9,760	.01	2,650
16	9,740	.01	2,620	8,620	.01	2,320	9,780	.01	2,650
17	9,760	.01	2,650	8,670	.008	1,860	9,960	.01	2,700
18	9,760	.01	2,650	8,650	.007	1,650	10,800	.01	2,920
19	9,820	.04	10,600	8,840	.008	1,920	10,500	.02	5,670
20	9,860	.02	5,320	9,070	.02	4,890	10,700	.01	2,890
21	9,680	.02	5,240	8,130	.008	1,760	10,800	.01	2,920
22	9,840	.21	55,800	7,900	.01	2,130	10,900	.01	2,940
23	9,740	1.16	305,000	8,010	.01	2,160	11,200	.009	2,730
24	9,860	1.31	349,000	8,030	.009	1,940	11,200	.008	2,430
25	9,960	1.41	379,000	8,010	.008	1,730	11,400	.01	3,080
26	10,200	1.44	397,000	8,300	.007	1,570	11,400	.01	3,080
27	10,200	1.12	308,000	8,600	.01	2,320	11,500	.01	3,100
28	10,700	.74	214,000	9,110	.01	2,460	11,500	.01	3,100
29	11,100	.71	213,000	9,440	.01	2,540	11,700	.01	3,160
30	10,900	.77	227,000	5,940	-----	-----	11,500	.01	3,100
31	-----	-----	-----	10,200	.01	2,750	-----	-----	92,230
Monthly load (tons)			2,545,000	117,800			92,230		

1936

	July			August			September		
	Mean discharge (second-feet)	Suspended matter	Tons per day	Mean discharge (second-feet)	Suspended matter	Tons per day	Mean discharge (second-feet)	Suspended matter	Tons per day
	Mean percent	Mean percent	Tons per day	Mean percent	Mean percent	Tons per day	Mean percent	Mean percent	Tons per day
1	11,400	0.02	6,160	11,000	0.007	2,080	9,580	0.006	1,540
2	11,500	.01	3,100	11,100	.008	2,400	9,600	.006	1,570
3	11,600	.01	3,130	10,900	.009	2,650	9,580	.01	2,590
4	11,500	.01	3,100	10,600	.03	8,590	9,640	.008	2,080
5	11,500	.009	2,810	10,600	.009	2,560	9,780	.01	2,650
6	11,300	.01	3,050	10,500	.02	5,670	9,620	.01	2,590
7	11,400	.02	6,160	10,400	.007	1,970	9,540	.01	2,560
8	11,500	.01	3,100	10,600	.008	2,300	10,000	.02	5,400
9	11,500	.01	3,100	10,500	.006	1,700	9,520	.007	1,810
10	11,500	.01	3,100	10,200	.006	1,650	9,640	.01	2,590
11	11,400	.02	6,160	9,880	.009	2,400	9,920	.006	1,620
12	11,400	.01	3,080	9,760	.01	2,650	9,600	.006	1,570
13	11,400	.01	3,080	9,760	.009	2,380	9,660	.005	1,300
14	11,400	.008	2,460	9,740	.005	1,320	9,700	.004	1,050
15	11,500	.01	3,100	9,680	.006	1,570	10,000	.006	1,620
16	11,300	.01	3,050	9,640	.006	1,570	9,640	.003	783
17	11,500	.009	2,810	9,640	.005	1,300	9,620	.006	1,570
18	11,400	.008	2,460	9,680	.005	1,300	9,460	.003	756
19	11,300	.008	2,430	9,600	.004	1,030	9,520	.005	1,300
20	11,400	.008	2,460	9,720	.009	2,350	9,720	.01	2,620
21	11,300	.01	3,050	9,760	.005	1,320	9,150	.006	1,480
22	11,200	.007	2,110	9,700	.006	1,570	9,030	.008	1,940
23	11,000	.005	1,480	9,600	.005	1,300	9,020	.002	486
24	11,100	.009	2,700	9,580	.003	783	8,900	.005	1,190
25	11,100	.008	2,400	9,220	.003	756	8,810	.008	1,890
26	11,200	.01	3,020	9,500	.006	1,540	8,750	.005	1,190
27	11,100	.009	2,700	9,500	.001	270	8,500	.005	1,130
28	11,000	.02	5,940	9,680	.002	513	8,310	.003	675
29	11,200	.008	2,430	9,660	.009	2,350	8,300	.007	1,570
30	11,000	.007	2,080	9,540	.003	783	8,130	.005	1,110
31	11,100	.01	3,000	9,560	.003	783	-----	-----	52,230
Monthly load (tons)			98,810	61,410			52,230		

## QUANTITIES OF SUSPENDED SEDIMENT

87

TABLE 12.—Mean daily concentration of suspended sediment in the Colorado River at gaging station near Topock, Ariz., Oct. 1, 1925, to Sept. 30, 1934

1926-27

1.				0.13	0.76						
2.	2.03	0.42				0.44	0.96		2.11	0.91	1.71
3.			0.22		.14	.66		1.37			
4.											
5.	5.74										
6.		.28				.78	.82		1.75	1.37	2.39
7.			.37		.12			1.18			
8.											
9.	2.27	.24				.70	1.10				
10.				0.16					1.10	1.13	1.81
11.			.36			.77			.69		
12.	2.20							.89		.79	
13.		.29			.15		1.16				1.34
14.			.34				1.29	1.34			4.39
15.		.23				.64	1.23		.66		
16.	1.18						1.31			1.63	2.37
17.											* 7.91
18.		.42	.16		.39						
19.	1.01					.58					
20.		.24				.42					
21.							1.22				
22.		.84	.26	.20		.47	.39		1.13		
23.										.60	1.16
24.								.79			3.86
25.					.17						
26.	.74		.27		1.80		.72		.72	.96	
27.		.27									.72
28.			.26								2.02
29.											
30.	.53	.43		.18		.36	.90		72		
31.										.82	
			.26			.45		1.18			1.76

TABLE 12.—Mean daily concentration of suspended sediment in the Colorado River at gaging station near Topock, Ariz., Oct. 1, 1925, to Sept. 30, 1934—Continued

1927-28

Day	Octo- ber	No- vember	Decem- ber	Janu- ary	Febru- ary	March	April	May	June	July	August	Sep- tember
1	1.09							0.55				
2		1.12										
3			0.21	0.75	0.70	0.48	0.83		0.89	0.64	0.83	0.48
4								.77				
5		1.30	1.63									
6						.41			.81			
7							2.08			.58		
8		1.06	.67	.53	1.03	.41						1.25
9								1.17				
10							.21	1.02		1.14	.98	.76
11		.72			.74	.40						1.06
12			.95									
13				.21			.34			3.01		
14					.19	.47		1.20				
15			.87					.56	.72			.71
16		.43		.34						1.33		
17					.36		.46				.52	
18						.74					.53	
19		.42	.98					.78	1.63	1.60		.64
20				.24			.45					
21		.50			.41	.36					.51	
22											.49	
23			.85									.33
24				.32			.28	.34				
25					.32						.65	
26		.61	.29	.26					2.40	.97		
27							.43				1.20	
28								.94				.55
29		.35	.20						1.03			.34
30										.84		
31				.64			.78				1.22	.74

1928-29

TABLE 12.—*Mean daily concentration of suspended sediment in the Colorado River at gaging station near Topock, Ariz., Oct. 1, 1925, to Sept. 30, 1934—Continued*

1929-30

Day	Octo- ber	No- vember	Decem- ber	Janu- ary	Febru- ary	March	April	May	June	July	August	Sep- tember
1					0.38	0.77	0.89	1.16		0.58		
2	2.92											
3		0.39	0.33		.56	.62			0.92	.41		1.11
4		0.75							.92			
5							.87					
6		1.84						1.33		.49	3.08	.84
7		.68	.77	.39			.66	.71				
8												
9								1.15				
10		1.18								1.02	2.70	.98
11			.98			.46					.42	
12							.48	.72		.82		
13											6.71	
14		1.04		.73	.56			.96	.80			1.20
15		.89				.36		1.13			.48	
16												6.35
17												
18		.84			.46	.32	.60		1.15	.70	.62	
19		.90	.81					1.24		.76	1.58	1.40
20											5.86	
21				.52					.90	.90		
22					.42	.36	.44					1.13
23		.94	.80					1.16			2.60	
24									.84	1.10	3.17	.97
25					.28							
26												
27		1.18			.42		.76	.59	1.23		.75	3.04
28					.43	.28				.70	.69	
29											3.01	
30												1.52
31		1.18		.52					.85		2.14	

1930-31

1	0.64				0.34		0.56		0.66			0.99
2												
3		0.42	0.28				0.48	.56		0.75		
4		0.76									1.56	
5		.75										1.00
6					.48	.30	.28					
7							.44	.40	.52	.74		.68
8		.48				.41						
9									.84	.70		.41
10					.55							
11		.95	.53				.28	.47	.75			
12												
13					.82	.38						
14							.28	.46				
15		1.41									1.00	
16												
17					.56	.44					.72	
18		1.04										
19					.54							
20												
21		1.08										
22		.86										
23					.47	.29						
24						.26						
25												
26		.76										
27					.40							
28												
29		.69				.26	.86	.44				
30		.52										
31		.60			.64							

## SEDIMENT IN COLORADO RIVER, 1925-41

TABLE 12.—*Mean daily concentration of suspended sediment in the Colorado River at gaging station near Topock, Ariz., Oct. 1, 1925, to Sept. 30, 1934—Continued*

1931-32

Day	Octo- ber	Novem- ber	Decem- ber	Janu- ary	Febru- ary	March	April	May	June	July	August	Septem- ber
1.	3.76						*					
2.				0.75	0.26	1.58	1.50			0.58	0.54	
3.		1.75						1.44				6.50
4.	2.52		0.78	.79					1.36			
5.						1.54	1.30			.67		
6.					.28						1.05	4.48
7.			.68					1.31	1.28			
8.				.62	.35							
9.	2.72	1.09				1.84	1.52			.75	1.52	
10.								1.14				2.88
11.		.68	.91	.68					.98			
12.						1.86				.80		
13.					2.82		1.79				.82	1.65
14.	2.28		.84					1.12				
15.		.64		.47					1.08			
16.						1.54				.78		
17.							1.96	.90			.47	1.25
18.	1.62	.80	.58		3.18				.85			
19.						1.14				2.62		
20.				.30			1.46				.39	.82
21.		2.40	.37		2.03	1.18		.68	.70			
22.	1.26			.50			1.30				1.17	.39
23.		2.08						.76				.50
24.					1.56				.74			
25.												
26.	1.25					1.46				.96		
27.		1.21	.36	.31			1.74		.74	.62		.46
28.												.60
29.	1.08		1.35	.76	.28		1.68	1.66			.63	4.35
30.												
31.								.80				

1932-33

1.					0.34		0.46	0.36		0.92		0.80
2.	0.52	0.72							0.90			
3.					0.34	.40	0.58					
4.							.44	.28		.68	1.68	.96
5.	.87	.54										
6.									.88			
7.						.30						
8.	1.36	.47			.25		.40	.71			1.04	
9.										.77	.72	.68
10.												
11.	1.66				.41		.58	.88				
12.		.42					.40			.78	.76	.72
13.						.29						
14.					0.44	.22						
15.	.73	.40					.40		.91	2.41	.94	
16.								.50				1.15
17.												
18.												
19.									.76		1.88	1.68
20.	.55	.44	.36			.30		.33				
21.										.70		
22.		.36									1.29	2.28
23.												5.28
24.	.77				.24		.29					
25.							.54				1.18	1.51
26.		.40			.26							3.40
27.												
28.												
29.	.41	.54				.40	.27	.47				
30.												
31.						.32						

TABLE 12.—*Mean daily concentration of suspended sediment in the Colorado River at gaging station near Topock, Ariz., Oct. 1, 1925, to Sept. 30, 1934—Continued*

1933-34

Day	Octo- ber	No- vember	Decem- ber	Janu- ary	Febru- ary	March	April	May	June	July	August	Sep- tember
1								0.60		0.15	0.22	0.92
2			0.55	0.52					0.72	.14	.22	1.48
3					0.32	0.31	0.38			.13	.17	1.93
4		0.54								.16	.22	2.20
5	1.66		1.16						.64		.14	.67
6				.84	.47	.24			1.64	.17	.22	3.93
7	1.05	.43							.18		.12	.18
8											.17	.14
9			.59	.56					.74	.96	.22	.15
10	.91					.28	.27	.18			.18	.25
11		.45									.18	.48
12			.76							.65	.82	.15
13				.48		.26	.27				.20	.24
14	4.27	.42								.18		.15
15				.53						.83		.20
16											.99	.16
17	3.90											.28
18		.54										.15
19				.30								.78
20						.28	.32					.14
21	1.51			.48								.14
22												.64
23				.46	.40							.12
24	1.40											.76
25	.36											.16
26				.50								.12
27					.30	.28	.21					.32
28	1.28											.12
29		.56			.40	.30						.49
30												.12
31	1.04											.78
												.18
												.96

TABLE 13.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Topock, Ariz., Oct. 1, 1934, to Mar. 31, 1939*

1934

Day	October			November			December		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	1,760	0.55	26,100	2,620	0.36	25,500	4,010	0.46	49,800
2	1,780	.71	34,100	2,700	.34	24,500	4,010	.54	58,500
3	3,820	1.87	193,000	2,790	.37	27,900	4,040	.53	57,800
4	3,690	1.10	110,000	2,820	.39	29,700	4,130	.48	53,500
5	3,200	.90	77,800	2,870	.37	28,700	4,260	.59	66,900
6	2,990	.89	71,800	2,870	.36	27,900	4,040	.47	51,300
7	2,900	.74	57,900	2,840	.32	24,500	4,130	.51	56,900
8	3,320	.72	64,500	2,820	.33	25,100	4,070	.45	49,500
9	3,480	.73	68,600	2,840	.32	24,500	3,970	.60	64,300
10	3,200	.65	56,200	2,840	.29	22,200	3,940	.46	48,900
11	3,110	.53	44,500	2,900	.29	22,700	3,970	.43	46,100
12	2,990	1.64	132,000	2,900	.29	22,700	3,880	.43	45,000
13	2,870	2.60	202,000	2,730	.26	19,200	3,940	.42	44,700
14	2,840	2.65	203,000	2,760	.36	26,800	3,640	.34	33,000
15	2,760	1.93	144,000	2,840	.34	26,100	3,720	.39	39,200
16	2,730	1.33	98,000	2,960	.28	22,400	3,480	.34	31,900
17	2,590	.97	67,800	3,110	.30	25,200	3,410	.37	34,100
18	2,450	.74	49,000	3,140	.36	30,500	4,210	.80	90,900
19	2,620	.69	48,800	3,110	.34	28,500	3,880	.68	71,200
20	2,540	.54	37,000	3,260	.34	29,900	3,940	.56	59,500
21	2,590	.46	32,200	3,510	.46	43,600	4,200	.50	56,700
22	2,420	.44	28,800	3,910	.48	50,700	4,590	.54	67,000
23	2,300	.43	26,700	4,040	.47	51,340	4,700	.54	68,500
24	2,450	.51	33,800	3,940	.52	55,300	4,730	.60	76,600
25	2,610	.48	32,600	3,790	.48	49,100	4,630	.44	55,000
26	2,480	.44	29,500	3,790	.42	43,200	4,830	.35	45,600
27	2,560	.43	29,700	3,940	.44	46,800	4,900	.43	56,900
28	2,640	.43	30,600	4,070	.55	60,400	4,940	.40	53,400
29	2,640	.42	29,900	4,130	.48	53,500	4,870	.34	44,700
30	2,730	.44	32,400	4,010	.45	48,700	4,590	.33	40,900
31	2,730	.40	29,500	-	-	-	4,300	.56	65,000
Total load (tons)		2,122,000	-	-	1,017,000	-	-	-	1,683,000

1935

	January			February			March		
	4,330	0.56	65,500	3,420	0.66	60,900	5,270	0.37	52,700
1	4,660	.51	64,200	3,210	.54	46,800	6,150	.39	64,800
2	4,760	.54	69,400	2,570	.36	25,000	7,120	.40	76,900
3	4,730	.56	71,500	3,210	.40	34,700	7,040	.39	74,100
4	4,590	.55	68,200	4,170	.58	65,300	6,780	.35	64,100
5	4,760	.46	59,100	5,830	.47	74,000	6,510	.40	70,300
6	4,760	.45	57,800	5,590	.38	57,400	5,610	.32	48,500
7	4,800	.52	67,400	4,690	.36	45,600	5,580	.34	51,200
8	4,830	.42	54,800	4,790	.51	66,000	6,000	.36	58,300
9	4,760	.41	52,700	4,320	.36	42,000	6,620	.55	98,300
10	4,490	.52	63,100	1,690	.14	6,400	6,700	.44	79,600
11	4,630	.47	58,800	960	.04	972	6,800	.40	73,400
12	4,330	.36	42,100	570	.02	308	6,890	.42	78,100
13	4,970	.42	56,400	422	.02	227	6,720	.30	54,400
14	4,800	.54	70,000	747	.02	405	6,550	.38	67,200
15	5,110	.56	77,300	2,670	.25	18,000	6,690	.44	79,500
16	6,210	.68	114,000	2,846	.17	13,000	6,540	.38	67,100
17	7,780	.95	200,000	3,580	.33	31,300	6,430	.32	55,600
18	6,390	1.88	324,000	4,000	.53	57,200	6,640	.43	75,900
19	6,280	1.24	210,000	4,080	.38	41,900	7,060	.30	57,200
20	6,280	1.77	300,000	4,200	.32	36,300	6,760	.31	56,600
21	6,360	1.14	196,000	3,950	.40	42,700	7,060	.33	62,900
22	6,100	2.64	435,000	4,420	.36	43,000	7,140	.30	57,800
23	5,800	1.62	254,000	4,890	.37	48,800	7,020	.32	60,600
24	5,500	.96	143,000	4,800	.53	68,700	7,060	.27	51,500
25	5,200	.98	138,000	4,800	.52	67,400	6,950	.28	52,500
26	4,900	.88	116,000	4,810	.36	46,300	7,060	.57	109,000
27	4,700	.73	92,600	4,840	.34	44,400	7,020	.70	133,000
28	4,010	.62	67,100	-	-	-	6,800	.57	105,000
29	3,690	.68	67,800	-	-	-	6,840	.58	107,000
30	3,470	.63	59,000	-	-	-	7,250	.54	106,000
Total load (tons)		3,715,000	-	-	1,086,000	-	-	-	2,249,000

## QUANTITIES OF SUSPENDED SEDIMENT

93

TABLE 13.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Topock, Ariz., Oct. 1, 1934, to Mar. 31, 1939—Continued*

1935

Day	April		May		June	
	Mean discharge (second-feet)	Suspended sediment	Mean discharge (second-feet)	Suspended sediment	Mean discharge (second-feet)	Suspended sediment
		Mean percent		Tons per day		Mean percent
1	7,500	0.44	89,700	6,730	0.26	47,200
2	7,020	.35	66,300	6,500	.25	70,900
3	7,290	.31	61,000	6,730	.28	50,900
4	7,100	.32	61,300	6,950	.26	48,800
5	7,100	.27	51,800	7,170	.22	42,600
6	7,170	.30	58,100	7,290	.24	47,200
7	6,910	.25	47,300	7,100	.22	42,200
8	6,730	.25	45,400	6,880	.21	39,000
9	7,210	.40	77,900	6,800	.21	38,600
10	7,290	.46	90,500	7,100	.20	38,300
11	6,580	.46	81,700	6,800	.20	36,700
12	6,540	.66	117,000	6,690	.19	34,300
13	7,330	.82	162,000	6,650	.24	43,100
14	6,990	.77	145,000	6,690	.27	48,800
15	6,800	.99	182,000	6,280	.22	37,300
16	7,020	1.00	190,000	6,070	.19	31,100
17	6,840	1.00	185,000	6,180	.22	36,700
18	6,360	1.24	213,000	6,250	.27	45,600
19	6,500	.91	160,000	6,280	.25	42,400
20	6,430	.70	122,000	7,060	.24	45,700
21	6,800	.60	110,000	7,250	.27	52,900
22	7,170	.54	105,000	6,580	.20	35,700
23	6,950	.42	78,800	6,730	.23	41,800
24	6,650	.48	86,200	10,200	.40	110,000
25	6,620	.30	53,600	12,700	.47	161,000
26	6,800	.26	47,700	13,600	.45	165,000
27	6,760	.26	47,500	13,700	.35	129,000
28	6,540	.57	95,300	14,000	.38	143,000
29	6,690	.26	47,000	14,000	.30	113,000
30	6,840	.29	53,600	14,100	.38	145,000
31				14,400	.30	117,000
Total load (tons)		2,932,000			2,082,000	
						3,623,000

1935

	July		August		September	
	Mean discharge (second-feet)	Suspended sediment	Mean discharge (second-feet)	Suspended sediment	Mean discharge (second-feet)	Suspended sediment
1	14,000	0.26	98,300	9,280	0.18	45,100
2	14,100	.29	110,000	9,480	.20	51,200
3	13,900	.26	97,600	9,400	.21	53,300
4	14,100	.36	137,000	9,480	.22	56,300
5	13,900	.26	97,600	9,400	.16	40,600
6	14,000	.26	98,300	9,600	.16	41,500
7	14,100	.26	100,000	9,560	.28	72,300
8	13,600	.24	88,100	9,400	.39	99,000
9	14,500	.26	102,000	9,400	.20	50,800
10	13,000	.26	91,300	9,600	.16	41,500
11	9,720	.26	68,200	9,640	.21	54,700
12	9,720	.18	47,200	9,600	.22	57,000
13	9,760	.18	47,400	9,720	.17	44,600
14	9,760	.17	44,800	9,560	.22	56,800
15	9,480	.21	53,800	9,520	.25	64,300
16	9,680	.23	60,100	9,360	.17	43,000
17	9,520	.16	41,100	9,680	.19	49,700
18	9,680	.19	49,700	9,720	.23	60,400
19	9,760	.16	42,200	9,360	.24	60,600
20	9,800	.20	52,900	9,320	.18	45,300
21	9,640	.20	52,100	9,400	.20	50,800
22	9,640	.21	54,600	9,360	.25	63,200
23	9,680	.22	57,500	9,400	.15	38,100
24	9,240	.23	57,400	9,640	.14	36,500
25	9,320	.26	65,400	9,640	.16	41,600
26	9,480	.26	66,600	9,560	.15	38,700
27	9,600	.40	104,000	9,640	.15	39,000
28	9,480	.23	58,900	9,560	.15	38,700
29	9,600	.31	80,400	9,480	.19	48,600
30	9,000	.24	58,300	9,280	.13	32,600
31	9,120	.22	54,200	9,560	.14	36,100
Total load (tons)		2,237,000		1,552,000		3,551,000
Total load for year						27,800,000

TABLE 13.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Topock, Ariz., Oct. 1, 1934, to Mar. 31, 1939—Continued*

1935

Day	October			November			December		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1.	9,360	0.26	65,700	9,480	0.24	61,400	8,050	0.22	47,800
2.	9,440	.21	53,500	9,280	.25	62,600	5,040	.14	19,100
3.	9,640	.27	70,300	9,440	.28	71,400	4,900	.13	17,200
4.	9,680	.24	62,700	9,480	.30	76,800	4,870	.13	17,100
5.	9,600	.20	51,800	9,680	.31	81,000	4,830	.14	18,300
6.	9,520	.28	72,000	9,120	.26	64,000	4,700	.14	17,800
7.	9,640	.58	151,000	9,280	.24	60,100	4,730	.13	16,600
8.	9,640	1.62	422,000	9,440	.22	56,100	4,700	.15	19,000
9.	9,400	1.71	434,000	9,120	.27	66,500	4,730	.20	25,500
10.	9,480	1.79	458,000	9,640	.31	80,700	4,700	.18	22,800
11.	9,520	2.12	545,000	9,320	.26	65,400	4,700	.18	22,800
12.	9,320	2.34	589,000	9,520	.25	64,300	4,800	.14	18,100
13.	9,240	2.00	499,000	9,400	.29	73,600	4,560	.16	19,700
14.	9,240	1.24	309,000	9,520	.26	66,800	4,660	.19	23,900
15.	9,280	.51	128,000	9,440	.30	76,500	4,530	.24	29,300
16.	9,640	.30	78,100	9,240	.22	54,900	4,700	.31	39,300
17.	9,480	.25	64,000	9,280	.20	50,100	4,530	.23	28,100
18.	9,120	.28	69,000	9,280	.28	70,100	4,730	.19	24,300
19.	9,080	.26	63,700	9,480	.28	71,700	4,630	.16	20,000
20.	9,440	.27	68,800	9,520	.29	74,500	4,630	.14	17,500
21.	9,560	.31	80,000	9,360	.32	80,900	4,700	.12	15,200
22.	9,520	.30	77,100	9,360	.27	68,200	4,630	.12	15,000
23.	9,560	.34	87,700	9,540	.23	59,200	4,560	.12	14,800
24.	9,160	.40	98,900	9,470	.24	61,400	4,660	.15	18,900
25.	9,360	.26	65,700	9,640	.23	59,900	4,630	.16	20,000
26.	9,240	.27	67,400	9,320	.21	52,800	4,730	.17	21,700
27.	9,560	.28	72,300	9,520	.29	74,500	4,700	.19	24,100
28.	9,280	.26	65,100	9,560	.30	77,400	4,590	.23	28,500
29.	9,240	.27	67,400	9,440	.26	66,300	4,630	.17	21,200
30.	9,160	.24	59,300	9,360	.25	63,200	4,900	.22	29,100
31.	9,520	.33	84,800				4,660	.15	18,900
Total load (tons)		5,080,000			2,012,000				691,600

1936

	January			February			March		
	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day
1.	4,830	0.19	24,800	4,490	0.16	19,400	6,000	0.17	27,500
2.	4,560	.19	23,400	4,700	.11	14,000	6,320	.18	30,700
3.	4,760	.20	25,700	4,800	.18	23,300	6,070	.14	23,000
4.	4,660	.16	20,100	4,760	.18	23,100	6,280	.15	25,400
5.	4,700	.20	25,400	4,660	.19	23,900	6,500	.14	24,600
6.	4,700	.20	25,400	4,730	.16	20,400	6,920	.25	46,700
7.	4,630	.21	26,200	4,590	.19	23,500	7,260	.16	31,400
8.	4,630	.16	20,000	4,760	.19	24,400	8,660	.22	51,400
9.	4,490	.20	24,200	4,700	.22	27,900	8,660	.16	37,400
10.	4,730	.20	25,500	4,660	.20	25,200	8,820	.20	47,600
11.	4,730	.16	20,400	4,730	.22	28,100	9,340	.19	47,900
12.	4,590	.18	22,300	4,700	.25	31,700	9,460	.19	48,500
13.	4,730	.24	30,600	5,280	.26	37,100	9,460	.16	40,900
14.	4,700	.23	29,200	6,210	.16	26,800	9,620	.23	59,700
15.	4,760	.18	23,100	6,180	.11	18,400	9,540	.18	46,400
16.	4,760	.15	19,300	6,180	.16	26,700	9,780	.24	63,400
17.	4,830	.24	31,300	6,360	.17	29,200	9,540	.18	46,400
18.	4,730	.20	25,500	6,540	.21	37,100	9,420	.16	40,700
19.	4,760	.20	25,700	6,620	.18	32,200	9,960	.22	59,200
20.	4,730	.18	23,000	6,620	.18	32,200	9,620	.22	57,100
21.	4,760	.17	21,800	6,320	.16	27,300	9,620	.14	36,400
22.	4,630	.18	22,500	5,920	.19	30,400	9,580	.15	38,800
23.	4,630	.14	17,500	5,960	.14	22,500	9,640	.25	65,100
24.	4,700	.13	16,500	5,780	.16	25,000	9,480	.16	41,000
25.	4,700	.18	22,800	5,780	.17	26,500	9,400	.16	40,600
26.	4,630	.19	23,800	5,960	.20	32,200	9,720	.20	52,500
27.	4,700	.16	20,300	5,780	.17	26,500	9,600	.24	62,200
28.	4,530	.19	23,200	5,740	.19	29,500	9,600	.18	46,700
29.	4,800	.18	23,300	6,000	.16	25,900	9,400	.18	45,700
30.	4,700	.19	24,100				9,640	.17	44,300
31.	4,630	.20	25,000				9,670	.19	49,600
Total load (tons)		731,900			770,400				1,379,000

TABLE 13.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Topock, Ariz., Oct. 1, 1934, to Mar. 31, 1939—Continued*

1936

Day	April			May			June		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	9,690	0.19	49,700	10,600	0.80	229,000	8,050	0.22	47,800
2	9,720	.19	49,900	9,540	.88	227,000	8,960	.19	46,000
3	9,400	.17	43,100	8,170	.40	88,200	8,920	.25	60,200
4	9,160	.19	47,000	9,520	.22	56,500	9,000	.18	43,700
5	9,840	.22	58,500	9,720	.22	57,700	9,240	.20	49,900
6	9,640	.22	57,300	10,000	.32	86,400	9,200	.18	44,700
7	9,360	.18	45,500	9,960	.27	72,600	9,280	.12	30,100
8	9,400	.25	63,400	9,760	.22	58,000	8,840	.14	33,400
9	9,520	.15	38,600	9,440	.20	51,000	8,880	.15	36,000
10	9,360	.18	45,500	9,440	.23	58,600	8,880	.18	43,100
11	9,200	.16	39,700	9,800	.19	50,300	8,840	.17	40,600
12	9,560	.17	43,900	9,760	.18	47,400	8,560	.13	30,100
13	9,440	.16	40,800	8,400	.15	34,000	8,560	.15	34,700
14	9,200	.14	34,800	8,170	.16	35,300	7,860	.15	31,800
15	9,480	.19	48,600	9,240	.14	34,900	8,720	.15	35,300
16	9,360	.18	45,500	9,200	.17	42,200	8,960	.16	38,700
17	9,520	.16	41,100	8,290	.14	31,300	9,320	.16	40,300
18	9,480	.15	38,400	7,980	.12	25,900	9,280	.16	40,100
19	9,400	.17	43,100	8,020	.18	39,000	9,880	.15	40,000
20	9,520	.16	41,100	8,130	.24	52,700	10,200	.15	41,300
21	9,440	.14	35,700	8,960	.30	72,600	9,840	.13	34,500
22	9,160	.12	29,700	7,900	.22	46,900	10,200	.16	44,100
23	9,440	.22	56,100	7,330	.20	39,600	10,300	.16	44,500
24	9,640	.48	125,000	7,210	.18	35,000	10,400	.17	47,700
25	9,600	1.26	327,000	7,520	.20	40,600	10,800	.14	40,800
26	9,600	1.37	355,000	7,670	.14	29,000	10,600	.13	37,200
27	9,700	1.50	393,000	7,980	.22	47,400	10,800	.18	52,500
28	9,700	1.44	377,000	7,900	.18	38,400	10,700	.15	43,300
29	10,200	1.26	347,000	8,250	.13	28,900	10,700	.16	46,200
30	10,600	.79	226,000	8,720	.17	40,000	11,000	.14	41,600
31				6,780	.14	25,600			
Total load (tons)			3,187,000			1,822,000			1,240,000

1936

	July			August			September		
	11,100	0.13	39,000	10,600	0.12	34,300	9,000	0.12	29,200
1	11,100	0.13	39,000	10,600	0.12	34,300	9,000	0.12	29,200
2	11,000	.15	44,600	10,600	.16	45,800	9,320	.11	27,700
3	10,800	.16	46,700						
4	11,100	.14	42,000						
5	10,900	.11	32,400	10,100	.10	27,300			
6	11,000	.13	38,600						
7	11,000	.13	38,600	9,760	.16	42,200	9,280	.10	25,100
8	10,700	.15	43,300						
9	10,600	.14	40,100				9,080	.08	19,600
10	10,500	.14	39,700	10,100	.14	38,200	9,400	.12	30,500
11	11,000	.16	47,500						
12	11,100	.15	45,000	9,520	.14	36,000	8,960	.10	24,200
13	10,900	.14	41,200				9,400	.14	35,500
14	10,900	.10	29,400	8,960	.14	33,900	9,120	.12	29,500
15	10,700	.14	40,400						
16	10,500	.15	42,500				9,600	.15	38,900
17	10,600	.15	42,900	9,240	.14	34,900	9,200	.11	27,300
18	10,700	.16	46,200						
19	10,600	.15	42,900	9,120	.13	32,000			
20	10,600	.14	40,100						
21	10,500	.13	36,900	9,040	.12	29,300	9,160	.14	34,600
22	10,500	.12	34,000						
23	10,400	.12	33,700	9,040	.12	29,300	8,560	.14	32,300
24	10,400	.10	28,100				8,800	.15	35,600
25	10,400	.08	22,500	9,000	.14	34,000			
26	10,500	.15	42,500				8,680	.20	46,900
27	10,800	.14	40,900				8,170	.18	39,700
28	10,500	.12	34,000	9,240	.13	32,400	8,090	.14	30,600
29	10,900	.13	38,300						
30	10,900	.14	41,200				7,900	.14	29,900
31	10,700	.13	37,600	9,240	.08	20,000			953,400
Total load (tons)			1,213,000			1,030,000			

<sup>1</sup> Estimated.

TABLE 13.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Topock, Ariz., Oct. 1, 1934, to Mar. 31, 1939—Continued*

1936

Day	October			November			December		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1.	7,780	.16	31,500	6,210	.13	21,800	5,110	.20	27,600
2.	7,500	.16	32,800	6,100	.12	19,800	5,110	.15	34,500
3.	7,670	.17	35,200	6,070	.16	26,200	4,940	.20	26,700
4.	7,780	.19	39,900	5,960	.12	19,300	4,830	.18	23,500
5.	7,940	.20	42,900	6,070	.13	21,300	5,040	.20	27,200
6.	7,980	.20	43,100	6,140	.14	23,200	4,800	.17	22,000
7.	7,670	.19	39,300	6,100	.20	32,900	4,660	.26	32,700
8.	7,290	.17	33,500	6,030	.14	22,800	4,590	.17	21,100
9.	7,060	.16	30,500	5,640	.18	27,400	4,830	.15	19,600
10.	7,290	.13	25,600	5,920	.20	32,000	4,970	.19	25,500
11.	7,360	.13	25,800	5,890	.21	33,400	4,660	.19	23,900
12.	6,910	.14	26,100	5,920	.20	32,000	4,730	.25	31,900
13.	6,760	.15	27,400	5,820	.17	26,700	4,870	.15	19,700
14.	7,250	.15	29,400	6,180	.20	33,400	4,630	.18	22,500
15.	6,930	.10	18,800	6,250	.17	28,700	4,660	.13	16,400
16.	7,440	.13	26,100	5,850	.17	26,900	4,970	.15	20,100
17.	6,950	.13	24,400	6,800	.20	36,700	5,110	.17	23,500
18.	6,990	.10	18,900	6,030	.16	26,000	5,040	.17	23,100
19.	7,550	.12	24,500	6,030	.17	27,700	4,870	.23	30,200
20.	7,170	.14	27,100	5,740	.16	24,800	4,700	.16	20,300
21.	6,880	.18	33,400	5,710	.11	17,000	4,830	.19	24,800
22.	6,840	.12	22,200	5,740	.14	21,700	4,590	.13	16,100
23.	6,910	.15	28,000	5,820	.12	18,900	4,760	.15	19,300
24.	6,180	.12	20,000	5,740	.18	27,900	4,760	.13	16,700
25.	6,470	.14	24,500	5,710	.17	26,200	4,760	.11	14,100
26.	7,140	.11	21,200	5,420	.15	22,000	4,760	.18	23,100
27.	6,470	.14	24,500	5,110	.14	19,300	4,940	.13	17,300
28.	6,320	.10	17,100	4,900	.12	15,900	5,220	.17	24,000
29.	7,100	.12	23,000	5,110	.14	19,300	4,900	.11	14,600
30.	6,840	.10	18,500	5,180	.12	16,800	4,870	.16	21,000
31.	6,280	.11	18,700	-----	-----	-----	5,480	.22	32,400
Total load (tons)		853,900	-----	748,000	-----	-----	-----	-----	715,400

1937

	January			February			March		
	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day
1.	5,820	.22	34,600	4,590	.24	29,700	6,910	.22	41,000
2.	5,080	.20	27,400	4,010	.14	15,200	6,840	.14	25,900
3.	3,880	.19	19,900	4,830	.28	36,500	6,840	.22	40,600
4.	4,760	.23	29,600	4,940	.26	34,700	6,650	.22	39,500
5.	4,260	.17	19,600	4,830	.28	36,500	6,690	.18	32,500
6.	4,870	.22	28,900	4,870	.23	30,200	6,650	.21	37,700
7.	5,250	.26	36,900	4,970	.18	24,200	6,730	.18	32,700
8.	4,970	.26	34,900	4,900	.24	31,800	6,730	.16	29,100
9.	4,730	.25	31,900	4,940	.20	26,700	7,250	.20	39,200
10.	4,660	.24	30,200	4,870	.22	28,900	7,480	.13	26,300
11.	4,490	.22	26,700	4,830	.22	28,700	8,210	.21	46,600
12.	3,630	.16	15,700	5,080	.24	32,900	9,080	.25	61,300
13.	4,900	.25	33,100	5,080	.28	38,400	9,320	.22	55,400
14.	4,940	.20	26,700	5,180	.30	42,000	9,440	.22	56,100
15.	4,800	.18	23,300	5,320	.34	48,800	9,120	.18	44,300
16.	4,560	.22	27,100	5,110	.20	27,600	9,280	.15	37,600
17.	4,560	.18	22,200	5,220	.20	28,200	9,360	.17	43,000
18.	4,300	.19	22,100	5,530	.23	34,300	9,320	.24	60,400
19.	4,170	.16	18,000	5,530	.26	38,800	9,120	.24	59,100
20.	4,830	.24	31,300	5,500	.23	34,200	8,600	.13	30,200
21.	4,730	.23	29,400	5,320	.22	31,600	8,680	.20	46,900
22.	5,000	.28	37,800	5,110	.20	27,600	8,480	.20	45,800
23.	4,660	.24	30,200	5,140	.20	27,500	8,760	.22	52,000
24.	4,700	.25	31,700	5,110	.19	26,200	8,680	.23	53,900
25.	4,300	.21	24,400	5,220	.21	29,600	8,960	.24	53,100
26.	3,970	.18	19,300	5,600	.22	33,300	7,400	.23	46,000
27.	4,800	.23	29,800	5,960	.24	38,600	7,060	.16	30,500
28.	4,700	.20	25,400	6,470	.26	45,400	7,210	.28	54,500
29.	4,660	.17	21,400	-----	-----	-----	7,860	.20	42,400
30.	4,730	.16	20,400	-----	-----	-----	7,860	.26	55,200
31.	4,800	.18	23,300	-----	-----	-----	8,520	.24	55,200
Total load (tons)		833,200	-----	908,400	-----	-----	-----	-----	1,379,000

<sup>1</sup> Estimated.

## QUANTITIES OF SUSPENDED SEDIMENT

97

TABLE 13.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Topock, Ariz., Oct. 1, 1934, to Mar. 31, 1939—Continued*

1937

Day	April			May			June		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	8,760	0.20	47,300	9,320	0.18	45,300	8,250	0.08	17,800
2	9,000	1.18	43,700	9,600	.10	25,900	8,090	.10	21,800
3	9,240	.16	39,900	9,640	.12	31,200	7,900	.11	23,500
4	8,940	1.18	43,400	9,680	.10	26,100	7,940	.10	21,400
5	8,640	.19	44,300	9,280	.10	25,100	8,170	.12	26,500
6	8,680	.19	44,500	8,880	.08	19,200	8,440	.12	27,300
7	8,920	.21	50,600	9,480	.14	35,800	8,920	.12	28,900
8	8,600	.16	37,200	9,600	.14	36,300	8,480	.10	22,900
9	8,720	.16	37,700	9,200	.12	29,800	8,370	.11	24,900
10	8,520	.18	41,400	9,040	.12	29,300	8,480	.10	22,900
11	8,760	.16	37,800	9,200	.14	34,800	9,200	.12	29,800
12	8,760	.16	37,800	9,320	.14	35,200	9,360	.12	30,300
13	8,480	.16	36,600	9,240	.15	37,400	9,320	.11	27,700
14	8,960	.18	43,500	9,080	.12	29,400	8,920	.09	21,700
15	8,760	.13	30,700	8,560	.15	34,700	8,840	.07	16,700
16	9,200	.16	39,700	8,290	1.12	26,900	8,840	.10	23,900
17	9,040	1.18	43,900	8,330	.10	22,500	8,760	.10	23,700
18	8,760	.20	47,300	8,330	.14	31,500	9,080	.11	27,000
19	8,760	.18	42,600	8,050	.14	30,400	9,760	.10	26,400
20	9,120	.14	34,500	7,820	.13	27,400	10,700	.10	28,900
21	8,920	.14	33,700	7,780	.10	21,000	10,200	1.10	27,500
22	9,080	.16	39,200	7,860	.11	23,300	9,880	.09	24,000
23	8,960	.19	46,000	7,900	.11	23,500	10,000	.08	21,600
24	8,960	.17	41,100	7,670	.08	16,600	9,880	.08	21,300
25	9,000	.24	58,300	7,590	.10	20,500	10,500	.16	45,400
26	9,320	.22	55,400	7,590	.10	20,500	10,600	.07	20,000
27	9,000	.18	43,700	7,780	.11	23,100	10,700	.10	28,900
28	9,280	.15	37,600	7,630	.12	24,700	10,700	.07	20,200
29	8,880	.19	45,600	7,860	.11	23,300	10,800	1.08	23,300
30	8,960	.24	58,100	8,050	.09	19,600	10,700	.09	26,000
31				8,330	.10	22,500			
Total load (tons)		1,283,000			852,800				752,200

1937

	July			August			September		
	10,700	0.12	34,700	10,200	0.11	30,300	9,560	0.08	20,600
1	10,300	.08	22,200	10,300	.11	30,600	9,880	.08	21,300
2	10,700	1.08	23,100	10,600	.11	31,500	10,100	.08	21,800
3	10,300	.08	22,200	10,600	1.11	31,500	10,500	.09	25,500
4	10,500	.09	25,500	10,500	.11	31,200	9,680	.10	26,100
5	10,500	.11	31,200	10,400	.08	22,500	9,640	.09	23,400
6	10,500	.10	28,400	10,200	.08	22,000	9,520	.06	15,400
7	10,400	.10	28,100	10,400	1.09	25,300	9,840	.10	26,600
8	10,400	.10	28,100	10,400	.10	28,100	9,680	.11	28,700
9	10,700	.09	26,000	10,400	.08	22,500	9,600	.10	25,900
10	11,000	1.09	26,700	10,300	.10	27,800	9,400	.08	20,300
11	10,700	.08	23,100	10,300	.08	22,200	9,240	.08	20,000
12	10,500	.08	22,700	10,200	.08	22,000	9,280	.08	20,000
13	10,500	.08	22,700	10,200	.08	22,000	9,200	.11	27,300
14	10,500	.09	25,500	10,300	.06	16,700	8,960	.12	29,000
15	10,500	1.10	28,400	10,300	.08	22,200	8,920	.10	24,100
16	10,300	.11	30,600	10,500	.10	28,400	8,520	.06	13,800
17	10,500	.08	22,700	10,700	.10	28,900	8,520	.10	23,000
18	10,500	.12	34,000	10,600	.09	25,800	8,520	.10	23,000
19	10,300	1.10	27,800	10,500	.10	28,400	8,370	1.08	18,100
20	10,300	.10	27,800	10,500	.08	22,700	8,250	.07	15,600
21	10,300	.08	22,200	10,500	.16	46,700	8,330	.08	18,000
22	10,100	.08	21,900	10,800	.09	26,200	8,330	.12	27,000
23	10,400	.08	22,500	10,700	.07	20,200	8,370	.12	27,100
24	10,400	.10	28,100	11,000	.09	26,700	8,400	.12	27,200
25	10,300	1.10	27,800	10,600	.16	45,800	7,980	.11	23,700
26	10,300	.11	30,600	10,500	.09	25,500	7,980	.10	21,500
27	10,400	.10	28,100	10,300	.10	27,800	7,860	.12	25,500
28	10,600	.11	31,500	10,200	.11	30,300	7,820	.09	19,000
29	10,500	.09	26,500	9,920	.08	21,400	8,090	.10	21,800
30	10,600	.12	34,300	9,880	.09	24,000	7,980	.10	21,500
31	10,100	.11	36,000	9,600	.14	36,300			
Total load (tons)		841,200			851,500				678,800

1 Estimated.

TABLE 13.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Topock, Ariz., Oct. 1, 1934, to Mar. 31, 1939—Continued*

1937

Day	October			November			December		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	8,120	0.10	21,900	7,330	0.08	15,800	6,500	0.10	17,600
2	8,210	.10	22,200	7,670	.08	16,600	6,730	.09	16,400
3	8,210	.08	17,700	7,670	.10	20,700	6,580	.12	21,300
4	8,130	.14	30,700	7,360	.08	15,900	6,390	.16	27,600
5	8,080	.10	21,800	7,440	.10	20,100	6,100	.13	21,400
6	8,020	.10	21,700	7,600	.12	24,600	5,960	.10	16,100
7	8,020	.08	17,300	7,360	.11	21,900	5,670	.09	13,800
8	8,020	.10	21,700	6,990	.15	28,300	6,070	.13	21,300
9	8,090	.12	26,200	6,320	.10	17,100	6,470	.13	22,700
10	7,980	.10	21,500	6,840	.13	24,000	6,800	.14	25,700
11	8,020	.11	23,800	7,140	.10	19,200	7,060	.14	26,700
12	8,090	.12	26,200	6,910	.12	22,400	6,950	.17	31,900
13	8,050	.09	19,600	6,210	.09	15,100	6,800	.14	25,700
14	8,170	.08	17,600	6,580	.12	21,300	5,710	.14	21,600
15	8,050	.09	19,600	6,540	.08	14,100	6,250	.16	27,000
16	8,290	.10	22,400	6,210	.08	13,400	6,500	.16	28,100
17	8,050	.12	26,100	6,840	.12	22,200	6,390	.15	25,900
18	8,090	.10	21,800	7,020	.10	19,000	6,320	.15	25,600
19	8,090	.10	21,800	6,990	.10	18,900	6,180	.19	31,700
20	7,900	.11	23,500	6,540	.08	14,100	6,070	.20	32,800
21	7,710	.12	25,000	6,360	.09	15,500	6,070	.17	27,900
22	7,330	.09	17,800	6,210	.12	20,100	6,070	.21	34,400
23	7,290	.12	23,600	6,320	.10	17,100	6,250	.18	30,400
24	7,330	.12	23,700	6,650	.11	19,800	6,250	.15	25,300
25	7,250	.12	23,500	6,730	.08	14,500	6,500	.22	38,600
26	7,520	.08	16,200	6,500	.07	12,300	6,140	.21	34,800
27	7,780	.10	21,000	6,430	.09	15,600	6,650	.19	34,100
28	7,710	.08	16,700	6,180	.11	18,400	6,030	.14	22,800
29	7,580	.08	16,400	6,390	.13	22,400	6,000	.14	22,700
30	7,440	.12	24,100	6,070	.08	13,100	6,140	.15	24,900
31	7,480	.11	22,200	-----	-----	-----	6,280	.14	23,700
Total load (tons)			675,300	553,600			800,500		

1938

	January			February			March		
	Mean	discharge	(second-feet)	Mean	discharge	(second-feet)	Mean	discharge	(second-feet)
1	6,030	0.15	24,400	5,740	0.10	15,500	6,620	0.10	17,900
2	5,640	.12	18,300	6,430	.16	27,800	6,470	.10	17,500
3	5,960	.14	22,500	6,500	.22	38,600	6,950	.15	28,100
4	5,390	.13	18,900	6,690	.13	23,500	7,480	.25	50,500
5	5,920	.14	22,400	6,620	.17	30,400	6,360	.24	41,200
6	6,030	.14	22,800	6,280	.20	33,900	5,140	.11	15,300
7	5,820	.15	23,600	6,360	.20	34,300	5,360	.13	18,800
8	6,030	.22	35,800	5,670	.14	21,400	5,420	.11	16,100
9	6,210	.16	26,800	6,650	.20	35,900	5,670	.14	21,400
10	6,000	.14	22,700	6,910	.20	37,300	5,850	.13	20,500
11	5,220	.14	19,700	6,650	.12	21,500	5,850	.15	23,700
12	5,740	.13	20,100	6,390	.18	31,100	5,560	.08	12,000
13	6,030	.10	16,300	6,390	.16	27,600	6,250	.08	13,500
14	6,320	.13	22,200	6,320	.11	18,800	7,400	.12	24,000
15	6,280	.09	15,300	5,710	.10	15,400	6,990	.10	18,900
16	6,320	.13	22,200	6,760	.15	27,400	7,400	.12	24,000
17	6,070	.11	18,000	6,620	.16	28,600	7,210	.10	19,500
18	5,670	.11	16,800	6,140	.19	31,500	7,360	.15	29,800
19	6,470	.14	24,500	6,140	.16	26,500	7,440	.15	30,100
20	6,990	.12	22,600	6,540	.16	28,300	7,590	.09	18,400
21	6,850	.12	22,200	6,180	.17	28,400	8,210	.17	37,700
22	6,390	.14	24,200	5,280	.12	17,100	8,290	.15	33,600
23	6,000	.16	25,900	5,960	.18	29,000	8,330	.16	36,000
24	5,820	.17	26,700	6,000	.14	22,700	8,600	.16	37,200
25	5,460	.12	17,700	6,070	.13	21,300	8,640	.16	37,300
26	6,100	.22	36,200	5,780	.13	20,300	8,840	.14	33,400
27	6,320	.15	25,600	5,740	.13	20,100	9,080	.16	39,200
28	6,100	.17	28,000	6,180	.14	23,400	9,480	.14	35,800
29	6,000	.14	22,700	-----	-----	-----	9,160	.13	32,200
30	6,250	.20	33,800	-----	-----	-----	9,160	.20	49,500
31	6,250	.18	30,400	-----	-----	-----	9,160	.15	37,100
Total load (tons)			729,300	737,600			870,200		

<sup>1</sup> Estimated.

## QUANTITIES OF SUSPENDED SEDIMENT

99

TABLE 13.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Topock, Ariz., Oct. 1, 1934, to Mar. 31, 1939—Continued*

1938

Day	April			May			June		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	9,160	0.17	42,000	9,360	0.10	25,300	8,440	0.10	22,800
2	9,040	.12	29,300	9,360	.12	30,300	8,440	.10	22,800
3	9,160	.13	32,200	9,440	.14	35,700	8,520	.14	32,200
4	9,000	.14	34,000	9,480	.15	38,400	9,080	.12	29,400
5	9,040	.24	58,600	9,360	1.16	40,400	9,120	1.12	29,500
6	9,120	.15	36,900	9,400	.16	40,600	9,080	.12	29,400
7	9,200	.15	37,300	9,360	.15	37,900	9,040	.15	36,600
8	9,200	.16	39,700	9,400	.13	33,000	9,120	.12	29,500
9	9,160	.11	27,200	9,360	.11	27,800	8,840	.15	35,800
10	9,240	.10	24,900	9,360	.14	35,400	8,880	1.19	45,600
11	9,280	.10	25,100	9,320	.10	25,200	9,120	.19	46,800
12	9,320	.10	25,200	9,040	.11	26,800	9,000	.14	34,000
13	9,280	.14	35,100	8,480	.11	25,200	9,000	.11	26,700
14	9,240	.10	24,900	8,480	.08	18,300	9,240	.11	27,400
15	9,480	.14	35,800	8,520	.09	20,700	9,160	.10	24,700
16	9,320	.10	25,200	8,520	.06	13,800	9,200	.09	22,400
17	9,400	.14	35,700	8,370	.10	22,600	9,040	.12	29,300
18	9,560	.10	25,800	8,400	.12	27,200	9,160	.15	37,100
19	11,000	.12	35,600	8,370	.11	24,900	9,120	.16	39,400
20	11,400	.16	49,200	8,290	.10	22,400	9,120	.15	36,900
21	11,600	.13	40,700	8,210	.10	22,200	9,200	1.12	29,800
22	10,300	.10	27,800	8,370	.09	20,300	9,200	1.10	24,800
23	9,400	.09	22,800	8,370	.11	24,900	9,240	.08	20,000
24	9,400	.08	20,300	8,250	.12	26,700	9,360	.07	17,700
25	8,440	.09	20,500	8,210	.08	17,700	12,700	.24	82,300
26	9,600	.09	23,300	8,480	.09	20,600	14,100	.14	53,300
27	9,480	.08	20,500	8,330	.10	22,500	14,100	.14	53,300
28	9,360	.12	30,300	8,210	.09	20,000	14,600	.17	67,000
29	9,360	.08	20,200	8,400	1.08	18,100	15,400	.18	74,800
30	9,360	.10	25,300	8,640	.07	16,300	10,100	.11	30,000
31				8,370	.09	20,300			
	Total load (tons)		931,400			801,500			1,091,000

1938

	July			August			September		
	July	August	September	July	August	September	July	August	September
1	9,480	0.12	30,700	10,600	0.08	22,900	9,480	0.12	30,700
2	11,100	.16	48,000	10,500	.10	28,400	9,200	.10	24,800
3	16,900	.07	31,900	10,500	.09	25,500	9,200	.07	17,400
4	10,700	.10	28,900	10,700	1.10	28,900	9,200	.10	24,800
5	10,500	.08	22,700	10,800	.10	29,200	9,040	.10	24,400
6	10,500	.12	34,000	10,700	.12	34,700	9,080	.09	22,100
7	10,400	.10	28,100	10,700	.11	31,800	9,240	.07	17,500
8	10,300	.10	27,800	10,700	.11	31,800	9,280	.09	22,600
9	10,400	.10	28,100	10,600	.10	28,600	8,960	.10	16,900
10	10,400	.09	25,300	10,500	.12	34,000	9,200	.10	17,400
11	10,500	.08	22,700	10,700	.10	28,900	9,280	.09	22,600
12	10,500	.07	19,800	10,600	.08	22,900	9,360	.12	30,300
13	10,400	.08	22,500	10,700	.09	26,000	9,320	.09	22,600
14	10,600	.06	17,200	10,900	.14	41,200	9,320	.13	32,700
15	10,400	.10	28,100	10,800	.16	46,700	9,320	.09	22,600
16	10,500	.10	28,400	10,200	.18	49,600	9,080	.10	24,500
17	10,500	.09	25,500	10,200	.14	38,600	9,280	.10	25,100
18	10,400	.08	22,500	9,760	.09	23,700	9,440	.10	25,500
19	10,400	.08	22,500	9,800	1.10	26,500	9,280	.09	22,600
20	11,000	.08	23,800	9,720	.12	31,500	9,200	.14	34,800
21	11,200	.08	24,200	9,920	.11	29,500	9,240	.12	29,900
22	10,800	.08	23,300	9,760	.11	29,000	9,240	.12	29,900
23	10,500	.10	28,400	9,640	1.11	28,600	9,200	.12	29,800
24	10,500	.10	28,400	9,760	.11	29,000	9,040	.12	29,800
25	10,700	.12	34,700	9,640	.10	26,000	8,800	.08	19,000
26	10,600	.12	34,300	9,800	.10	26,500	8,720	.11	25,900
27	10,500	.12	34,000	9,600	.09	23,300	8,600	.10	23,200
28	10,500	.09	25,500	9,200	.07	17,400	8,680	.11	25,900
29	10,600	.11	31,500	9,120	.11	27,100	8,560	.10	23,100
30	10,600	.10	28,600	9,120	.11	27,100	8,640	.07	16,300
31	10,700	1.10	28,900	9,480	.10	25,600			
	Total load (tons)		860,300			920,500			734,100

1 Estimated

TABLE 13.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Colorado River at gaging station near Topock, Ariz., Oct. 1, 1934, to Mar. 31, 1939—Continued*

1938

Day	October			November			December		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	8,600	0.11	25,500	15,200	0.18	73,900	7,430	0.01	2,010
2	8,600	.12	27,900	15,000	.17	68,800	7,500	.01	2,230
3	8,440	.10	22,800	16,200	.19	83,100	7,500	.01	1,420
4	8,600	.10	23,200	17,500	.18	85,000	7,430	.01	1,000
5	8,400	.12	27,200				7,680	.01	1,870
6				17,900	.24	116,000	7,500	.01	1,220
7	8,090	.16	34,900	17,600	.19	90,300			
8							6,060	.00	
9							6,000	.00	
10				17,400	.14	65,800	6,060	.01	1,640
11				17,300	.15	70,100			
12				17,300	.10	46,700	5,430	.01	1,170
13	12,900	.15	52,200	17,400	.09	43,700			
14	13,000	.09	31,200	17,400	.13	61,100	9,400	.19	48,200
15	12,800	.12	41,500	17,300	.14	65,400	10,700	.13	37,600
16	13,100	.18	63,700	15,600	.08	35,800	6,950	.01	1,310
17	13,000	.25	87,800	9,790	.05	12,400	6,590	.00	
18	13,100	.18	63,700	7,620	.04	9,260	6,350	.00	
19	13,100	.18	63,700	7,560	.04	7,550	5,660	.00	
20	12,800	.18	62,200	7,500	.04	7,700	5,600	.01	1,360
21	12,900	.17	59,200	7,700	.04	7,690	6,000	.00	
22	13,000	.16	56,200	7,680	.02	3,730			
23	13,000	.18	63,200						
24	12,900	.14	48,800	7,620	.02	3,290	6,150	.00	
25	13,300	.16	58,300	7,430	.02	3,210			
26	14,600	.16	63,100	7,500	.01	2,230	5,600	.00	
27	14,800	.13	51,900	7,560	.01	2,040	4,930	.00	
28	14,800	.16	63,900	7,560	.01	2,040	4,650	.01	879
29	15,000	.11	44,600	7,500	.01	1,820	5,770	.01	1,250
30	14,800	.10	40,000	7,430	.01	1,600	6,060	.02	2,450
31	14,800	.16	63,900				6,000	.01	2,110
Total load (tons) <sup>1</sup>			1,480,000			1,240,000			120,000

1939

	January			February			March		
1									
2	5,770	0.01	1,090				20,200	0.18	98,200
3	4,980	.00		24,600	0.07	46,500	19,600	.08	43,400
4	4,930	.01	1,600	19,700	.04	23,400	13,900	.06	23,300
5	5,890	.01	1,910	19,200	.10	49,800			
6	6,000	.01	1,780	19,500	.06	32,600	5,530	.02	2,390
7	6,300	.01	2,040	21,600	.13	75,800	4,760	.01	890
8	5,890	.01	1,750	25,400	.11	75,400	8,170	.03	6,840
9	5,610	.01	1,670	24,000	.09	58,300	9,080	.03	8,340
10	4,870	.01	1,050	24,200	.08	52,900	11,100	.04	11,700
11	5,660	.01	1,380	24,800	.15	100,000	10,100	.03	7,360
12	5,830	.01	1,260	24,300	.16	105,000	7,940	.03	6,430
13	6,060	.01	1,960	24,800	.08	53,600	8,370	.02	5,200
14	6,180	.01	2,000	26,600	.31	223,000			
15	6,590	.01	2,140	26,600	.10	71,800	10,300	.03	8,900
16	4,860	.01	1,180				9,440	.03	7,140
17	5,040	.01	1,360	6,250	.02	3,210	7,780	.02	4,410
18	5,720	.01	2,010	13,600	.24	88,100	10,600	.02	4,580
19				25,100	.14	94,900	9,200	.02	5,960
20	12,600	.10	32,300	25,500	.14	96,400	9,680	.03	8,620
21	13,600	.11	40,400	23,700	.16	102,000	9,960	.03	8,070
22	13,700	.08	28,500	23,900	.16	103,000	9,480	.04	9,980
23	14,700	.14	55,600	24,500	.10	66,200	9,440	.03	8,410
24	16,000	.11	47,500	24,800	.14	93,700	9,720	.04	9,970
25				23,600	.12	76,500	10,800	.04	12,000
26	17,800	.10	47,100				12,900	.02	7,660
27	18,200	.33	162,000	24,000	.14	90,700			
28	20,000	.24	130,000						
29	23,900	.16	103,000				9,720	.04	
30	26,000	.12	84,200				8,600	.05	10,900
31	29,500	.20	159,000				10,000	.04	11,900
Total load (tons) <sup>1</sup>			991,000			2,200,000			469,000

<sup>1</sup> Includes estimates for missing days.

## QUANTITIES OF SUSPENDED SEDIMENT

101

TABLE 14.—*Mean daily concentration of suspended sediment in the Green River at gaging station near Green River, Utah, May 1, 1929, to Sept. 30, 1939*

1929-30

Day	Octo- ber	No- vember	De- cember	Janu- ary	Febru- ary	March	April	May	June	July	August	Septem- ber
1								.44	.57	.16	.12	
2								.42	.54	.12	.31	.33
3								.42	.55	.11	.30	.48
4								.38	.59		.378	.64
5								.36	.56	.09	.219	.53
6								.40	.48	.08	.208	.62
7								.47	.44	.07	.186	.26
8								.36	.41	.07	.134	.20
9								.31	.40	.10	.325	.50
10								.31	.45	.08		1.05
11								.27	.36	.07	4.22	.54
12								.30	.36	.15	3.43	.32
13								.27	.40	3.65	3.53	.21
14								.25	.42	.18	2.55	.14
15								.24	.41	.17	3.49	.11
16								.24	.43	.27	2.99	.09
17								.23	.48	.82	3.10	.09
18								.26	.44	.32	3.10	.08
19								.19	.72	.31	2.40	.09
20								.21	.66	.60	2.04	.10
21								.18	.39	.49	1.56	.11
22								.28	.31	.28	1.17	.08
23								.23	.30	.59	.88	.65
24								.24	.27	.70	.58	.38
25								.24	.26	.30	.44	.36
26								.28	.24	.35	1.16	.79
27								.25	.18	.20	.41	
28								.22	.18	.13	.38	
29								.36	.16	.26	.33	.74
30								.50	.14	.17	.22	1.52
31								.58		.11	.29	

1930-31

1	0.97					0.05	0.12	0.16	0.25	0.02	2.49	0.30	
2	.62					.05	.12	.15	.21	.13	.73	.94	
3	.59					.06	.09	.18	.23	.02	.26	.30	
4	.76					.06	.11	.14	.20	.04	.10	.16	
5	.60					.08	.12	.20	.18	.06	.11	.07	
6	.51					.08	.13	.22	.24	.08	.50	.04	
7	.47					.09	.18	.22	.27	.07	1.30	.11	
8	.24					.07	.22	.26	.26	.07	1.56	.07	
9	.26					.08	.19	.38	.24	.03	.55	.11	
10	.25					.07	.39	.32	.27	.08	.36	.11	
11	.28					.06	.30	.29	.32	.06	2.13	.08	
12	.26					.07	.25	.30	.35	.05	1.67	.08	
13	.28					.09	.27	.30	.26	.04	1.33	.08	
14	.22					.14	.32	.24	.20	.03	.80	.05	
15	.18					.16	.36	.21	.21	.03	.46	.04	
16	.17					.17	.40	.20	.20	.02	.18	.04	
17	.17					.21	.42	.17	.17	.02	.12	.13	
18	.16					.26	.38	.26	.18	.02	.19	.06	
19	.16				0.04	.26	.40	.66	.18	.02	.10	.04	
20	.15				.04	.25	.41	.76	.16	.02	.10	.03	
21	.12					.05	.29	.34	.68	.14	.02	.16	.04
22	.12					.05	.36	.30	.63	.13	.02	.12	.05
23	.10					.04	.39	.40	.49	.12	.01	.13	.05
24	.09					.04	.34	.49	.41	.12	.02	.12	.07
25	.09					.05	.34	.41	.27	.06	.03	.09	.20
26	.10					.05	.42	.35	.18	.06	.03	.11	.10
27	.08					.06	.43	.33	.17	.08	.03	.11	.09
28	.08					.06	.35	.29	.24	.08	.03	.09	.14
29	.19					.30	.21	.32	.03	.03	.03	.10	.10
30	.09					.26	.18	.30	.03	.03	.03	.16	
31	.06					.20		.28		.20	.22		1.52

TABLE 14.—*Mean daily concentration of suspended sediment in the Green River at gaging station near Green River, Utah, May 1, 1929, to Sept. 30, 1939—Continued*

1931-32

Day	Octo- ber	No- vember	De- cember	Janu- ary	Febru- ary	March	April	May	June	July	August	Sep- tember
1.	1.08				0.06				0.49		0.17	2.52
2.	.26	0.22			.04	0.07	0.46	0.38	.48	0.50	.54	
3.			0.06		.05	.06					.36	1.08
4.		.41					.42	.82	.35			
5.	.37	.40				.06		.80		.35	1.26	.32
6.					.06		1.38	1.03	.36		.93	
7.		.22	.05			.19	1.80				.31	.58
8.	.26				.07				.40		.17	.49
9.		.08				.23	1.35	.76	.41			
10.	.13		.01		.13	.17					.08	.23
11.		.31			.09		.99	.66	.35	.40	.07	
12.		.16			.07	.15		.66		1.16		.71
13.	.13						.62	.68	.37			
14.		.04				.11	.55			.78		.12
15.					.06				.38			.08
16.	.03	.04			.05	.08	.31		.38	.48	.08	
17.	.01				.04	.07						.05
18.		.06			.04		.52	.84	.40	.16		
19.	.04	.08				.09	.56				.68	.04
20.	.12				.06	.09		.78	.81	.42	.32	
21.		.05			.06		.72		.40		.39	
22.	.14						.63		.40		.46	.05
23.	.07	.04			.04	.07	1.30		.73	.43	.22	
24.						.06	.86				1.33	
25.					.01		.04		.62	.62	.40	.51
26.	.01					.05	.12	.65	.62		.15	
27.		.02				.14		.46		.42		1.60
28.	.02	.02					.60	.36	.64		.14	
29.	.08					.05	.11			.37		3.41
30.		.04					.04		.54	.32	.42	
31.	.17						.47					2.90

1932-33

1.	0.01	0.03	0.01		0.05	0.06		0.84	0.49	0.10	0.30	0.02
2.		.02	.04		.01	.05			.64	.09	.61	
3.					.02	.04						
4.					.02	.04						
5.		.04	.04					.52			.35	
6.	.02		.02		.02		.14		.43	.48	.07	.02
7.		.04	.02				.14		.45		.66	.02
8.						.02	.22		.37		2.26	
9.						.02				.42		
10.	.01	.04	.03		.03	.12	0.36			.38	.32	.08
11.						.04	.18	.34	.30			.08
12.	.01		.04				.18			.34	.51	.29
13.		.02				.03	.21		.28	.32	.78	.25
14.	.05	.05	.02			.04				.32		.06
15.						.02	.29	.23			.74	.03
16.		.05				.03	.58			.34		.03
17.	.18					.05		.20		.32	1.07	
18.						.03	.26	.12			.07	
19.	.02	.02					.10	.16			.36	
20.	.02					.03			.16		.23	
21.	.06	.02						.11			.07	.02
22.								.13	.30			.05
23.						.03						
24.	.16					.04		.58	.66			.03
25.						.03		.52	.60		.16	
26.		.06										
27.	.04					.03		.41	.35		.11	.02
28.		.04						.56				.01
29.	.05	.02								.12		
30.					0.05						.37	.02
31.	.06				.05						.04	

TABLE 14.—Mean daily concentration of suspended sediment in the Green River at gaging station near Green River, Utah, May 1, 1929, to Sept. 30, 1939—Continued

1933-34

Day	Octo-ber	No- vember	De-cem-ber	Janu- ary	Februa- ry	March	April	May	June	July	August	Sep-tem-ber
1					0.03*	0.02						0.09
2	3.42	0.04										.05
3		.03		0.09	.04	.03	0.07	.14	0.07			
4		.25		0.05								.03
5		.08		.04	.10	.05	.02		.11	.06		
6		.03			0.09					.07	0.02	.03
7		.06				.06			.11			
8				.12		.08				.04		.11
9		.04		.12	.03				.09	.03		
10						.04		.11				.05
11		.04	.05	.04		.14	.06		.16	.02		0.02
12		.04			.04		.04			.02	.01	
13		.04	.02	.04								
14		.03		.03		.12			.25			.05
15		.04			.04	.12				.02		
16		.02	.03	.05					.22	.02	.01	
17					.05			.07	.25			.04
18		.03	.04	.06	.04					.01	.01	.07
19		.03				.09			.19		.02	
20				.04	.06	.03				.01	.02	.05
21		.02							.12	.01	.01	.04
22		.05	.02	.03								.04
23		.03	.04			.04			.10	.01	.02	.04
24			.02		.03	.04	.04		.10			.04
25		.02								.01		.08
26		.02			.04				.10			.03
27		.01	.02			.04				.01		.03
28		.02				.03		.24	.12	.01		.02
29				.02		.03						.04
30		.03				.03			.08	.01		.05
31					.03				.08			

1934-35

TABLE 14.—Mean daily concentration of suspended sediment in the Green River at gaging station near Green River, Utah, May 1, 1929, to Sept. 30, 1939—Continued

1935-36

1936-37

1.	0.07	0.74							0.23		2.84
2.	.06		0.10						.47	0.56	
3.	.07			0.03	0.22	0.30		0.40		1.66	3.04
4.				.03				.41			
5.	.06	.69									
6.			.05	0.02		.28			.36	.14	.36
7.		.28		.03			.41	0.41	.37		
8.		.16								1.20	
9.										.35	.22
10.		.15	.06		.06	.28	.60	.77		.72	.38
11.		.12		.02						.71	.61
12.		.12	.02						.21	1.04	
13.					.06					2.25	.16
14.	.07	.11							.16	2.90	.81
15.				.06						3.29	
16.			.03			1.07			.18	2.82	.09
17.	.06										
18.		.27			.06				.16	2.36	.18
19.									.13	1.90	.06
20.	.26		.08	.04		2.20		.44			
21.	.68	.21					1.58			1.04	.41
22.	.28				.12				.15	.86	.05
23.											
24.		.25		.05						.12	.07
25.				.10							
26.	.73		.07			.61			.28	.47	.12
27.										.24	.10
28.										.19	
29.	.24									.16	.35
30.				.03		.36			.15	.32	.60
31.				.06		.35		.66		1.04	

TABLE 14.—Mean daily concentration of suspended sediment in the Green River at gaging station near Green River, Utah, May 1, 1929, to Sept. 30, 1939—Continued

1937-38

1938-39

TABLE 15.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Green River at gaging station near Green River, Utah, Oct. 1, 1939, to Sept. 30, 1941*

1939

Day	October			November			December		
	Mean discharge (second-feet)		Suspended sediment	Mean discharge (second-feet)		Suspended sediment	Mean discharge (second-feet)		Suspended sediment
	Mean percent	Tons per day	Mean percent	Tons per day	Mean percent	Tons per day	Mean percent	Tons per day	Mean percent
1	1,850	0.08	4,000	1,840	0.10	4,970	1,560	0.03	1,260
2	1,850	.07	3,500	1,820	.16	7,860	1,620	.01	437
3	1,850	.14	6,990	1,780	.09	4,330	1,630	.02	880
4	1,960	.21	11,100	1,770	.04	1,910	1,620	.02	875
5	1,800	.26	12,600	1,770	.04	1,910	1,580	.02	853
6	1,890	.20	10,200	1,770	.04	1,910	1,550	.02	837
7	2,240	.12	7,260	1,750	.03	1,420	1,550	.02	837
8	2,340	.15	9,480	1,730	.03	1,400	1,630	.02	880
9	2,780	1.02	76,600	1,750	.04	1,890	1,670	.03	1,350
10	2,340	.47	29,700	1,730	.03	1,400	1,680	.03	1,360
11	2,670	.28	20,200	1,730	.03	1,400	1,700	.02	918
12	2,670	.56	40,400	1,730	.02	934	1,700	.02	918
13	2,340	.64	40,400	1,720	.03	1,390	1,700	.02	918
14	2,180	.55	32,400	1,720	.02	929	1,700	.02	918
15	2,140	.28	16,200	1,700	.03	1,380	1,680	.04	1,810
16	2,110	.16	9,120	1,680	.02	907	1,770	.05	2,390
17	2,090	.23	13,000	1,680	.02	907	1,750	.04	1,890
18	2,090	.14	7,900	1,680	.02	907	1,670	.02	902
19	2,030	.09	4,930	1,650	.02	891	1,560	.02	842
20	1,980	.07	3,740	1,600	.02	864	1,500	.02	810
21	1,920	.06	3,110	1,550	.02	837	1,400	.02	756
22	1,910	.06	3,090	1,510	.02	815	1,260	.02	680
23	1,870	.05	2,520	1,480	.02	799	1,190	.03	964
24	1,840	.05	2,480	1,480	.02	799	1,160	.03	940
25	1,820	.06	2,950	1,480	.03	1,200	1,080	.02	583
26	1,800	.04	1,940	1,470	.02	794	938	.03	760
27	1,780	.04	1,920	1,450	.03	1,170	1,050	.02	567
28	1,750	.03	1,420	1,450	.02	783	1,110	.04	599
29	1,910	.04	2,060	1,500	.02	810	976	.02	527
30	1,940	.04	2,100	1,530	.03	1,240	902	.03	731
31	1,870	.04	2,020				819	.04	885
Monthly load (tons)		385,200				48,760			29,880

1940

	January			February			March			
	1	786	0.02	424	1,620	.02	875	2,670	.08	5,770
2	786	.02		264	1,630	.02	880	3,810	.31	31,900
3	976	.01		356	1,680	.02	907	4,710	.48	61,000
4	1,320	.01		929	1,670	.02	902	4,240	.40	45,800
5	1,720	.02		1,515	1,670	.02	902	4,240	.28	32,100
6	1,870	.03		2,120	1,730	.03	1,400	4,550	.39	47,900
7	1,960	.04		999	1,720	.02	929	4,400	.26	30,900
8	1,850	.02		1,030	1,750	.02	945	3,950	.23	24,500
9	1,910	.02		1,530	1,730	.02	934	3,400	.27	24,800
10	1,890	.03		961	1,720	.02	929	3,270	.27	23,800
11	1,780	.02		945	1,700	.02	918	3,140	.24	20,400
12	1,750	.02		264	1,650	.02	891	3,140	.20	17,000
13	1,840	.03		1,490	1,650	.02	891	3,140	.17	14,400
14	1,850	.03		1,500	1,650	.02	891	2,900	.15	11,700
15	1,700	.03		1,380	1,720	.02	929	3,270	.15	11,300
16	1,430	.05		1,930	1,720	.02	929	2,780	.10	7,210
17	1,220	.01		329	1,620	.01	437	2,670	.09	6,490
18	976	.01		264	1,560	.01	421	2,670	.08	5,530
19	539		(1)		1,650	.01	446	2,560	.09	6,490
20	690	.02		373	1,650	.01	446	2,670	.09	6,490
21	866	.01		234	1,630	.01	440	2,670	.09	6,490
22	1,110	.01		300	1,680	.01	454	2,670	.08	5,770
23	1,150	.01		310	1,680	.01	454	2,780	.09	6,700
24	1,020	.02		551	1,620	.01	437	2,900	.11	8,610
25	963	.01		260	1,630	.01	440	2,900	.11	8,610
26	1,000	.01		270	1,730	.01	467	2,780	.12	9,010
27	1,000	.01		270	1,770	.02	956	2,900	.22	17,200
28	1,070	.01		289	1,820	.02	983	3,020	.22	17,900
29	1,250	.02		675	1,890	.02	1,020	3,270	.24	21,200
30	1,430	.02		772				3,540	.26	24,800
31	1,450	.03		1,170				3,810	.28	28,800
Monthly load (tons)		23,900				22,320			586,300	

<sup>1</sup> Less than 50 tons per day.

## QUANTITIES OF SUSPENDED SEDIMENT

107

TABLE 15.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Green River at gaging station near Green River, Utah, Oct. 1, 1939, to Sept. 30, 1941—Continued*

1940

Day	April			May			June		
	Mean discharge (second- feet)		Suspended sediment	Mean dis- charge (second- feet)		Suspended sediment	Mean dis- charge (second- feet)		Suspended sediment
	Mean percent	Tons per day	Mean percent	Tons per day	Mean percent	Tons per day	Mean percent	Tons per day	Mean percent
1	3,950	0.30	32,000	8,920	0.68	164,000	12,800	0.24	82,900
2	3,950	.28	29,900	8,700	.52	122,000	13,400	.31	112,000
3	3,810	.32	32,900	8,060	.38	82,700	13,100	.30	106,000
4	3,540	.38	36,300	7,240	.30	58,600	13,600	.35	128,000
5	3,400	.32	29,400	6,270	.26	44,000	13,600	.36	132,000
6	3,540	.26	24,800	5,720	.22	34,000	13,400	.28	101,000
7	3,810	.22	22,600	6,270	.22	37,200	12,800	.27	93,300
8	3,950	.23	24,500	9,140	.39	96,200	12,100	.22	71,900
9	3,670	.20	19,800	10,800	.52	152,000	11,600	.22	68,900
10	3,400	.16	14,700	10,600	.43	123,000	10,600	.19	54,400
11	3,400	.14	12,800	10,400	.38	107,000	9,600	.16	41,500
12	3,540	.14	13,400	10,800	.37	108,000	9,140	.16	39,500
13	3,540	.13	12,400	12,400	.46	154,000	8,480	.12	27,500
14	3,270	.12	10,600	13,600	.54	198,000	7,440	.11	22,100
15	3,140	.11	9,330	14,100	.48	183,000	6,650	.10	18,000
16	3,140	.10	8,480	15,100	.46	188,000	6,460	.11	19,200
17	3,020	.10	8,150	15,700	.48	204,000	6,270	.05	8,460
18	2,900	.07	5,480	15,100	.40	163,000	6,080	.06	9,850
19	2,900	.07	5,480	14,600	.33	130,000	5,900	.07	11,200
20	3,400	.08	7,340	15,100	.38	155,000	5,540	.06	8,970
21	4,240	.16	18,300	15,700	.33	140,000	5,370	.06	8,700
22	4,400	.22	26,100	14,100	.35	133,000	5,370	.07	10,200
23	4,400	.19	22,600	13,600	.29	106,000	5,040	.04	5,440
24	4,550	.21	25,800	13,100	.26	92,000	5,040	.04	5,440
25	5,370	.36	52,200	12,400	.25	83,700	5,040	.04	5,440
26	6,080	.43	70,600	11,600	.22	68,900	5,200	.05	7,020
27	6,270	.41	69,400	10,800	.22	64,200	5,040	.05	6,800
28	6,460	.37	64,500	10,600	.16	45,800	4,550	.05	6,140
29	7,850	.54	114,000	10,800	.13	37,900	4,840	.02	2,610
30	8,920	.70	169,000	11,100	.22	65,900	4,100	.14	15,500
31	Monthly load (tons)...		992,900	3,423,000			1,230,000		

1940

	July			August			September		
	Mean discharge (second- feet)	Suspended sediment	Mean percent	Mean discharge (second- feet)	Suspended sediment	Mean percent	Mean discharge (second- feet)	Suspended sediment	Mean percent
1	3,540	0.08	7,650	878	0.01	237	926	0.48	12,000
2	3,400	.08	7,340	830	.02	448	902	.28	6,820
3	3,020	.10	8,150	808	.02	436	830	.14	3,140
4	2,780	.03	2,250	808	.02	436	1,280	.73	25,200
5	2,560	.05	3,460	742	.02	401	1,050	4.03	114,000
6	2,410	.10	6,510	720	.01	194	890	.61	14,700
7	2,280	.09	5,540	819	.04	885	854	.24	5,530
8	2,180	.06	3,530	775	.12	2,510	866	.10	2,340
9	2,180	.06	3,530	710	.09	1,720	819	.06	1,330
10	2,140	.03	1,730	700	.04	756	797	.03	646
11	2,030	.02	1,100	690	.02	373	786	.02	424
12	1,910	.02	1,030	680	.02	367	775	.02	418
13	1,820	.01	491	680	.02	367	819	.04	885
14	1,700	.01	459	640	.02	346	1,080	.05	1,460
15	1,560	.01	421	630	.02	340	1,250	4.95	167,000
16	1,530	.01	413	620	.02	335	1,260	3.74	127,000
17	1,430	.06	2,320	611	.02	330	1,120	.97	29,300
18	1,320	.01	356	620	.02	335	2,660	4.38	315,000
19	1,300	.01	375	620	.02	335	1,960	3.98	211,000
20	1,450	.01	392	660	.02	356	2,010	2.64	143,000
21	1,300	.06	2,110	710	.03	575	1,870	1.92	96,900
22	1,190	.10	3,210	650	.08	1,400	1,650	1.87	83,300
23	1,110	.11	3,300	630	.06	1,020	1,850	1.06	52,900
24	1,040	.06	1,680	660	.05	891	1,960	.92	48,700
25	1,000	.06	1,620	742	.11	2,200	1,700	.46	21,110
26	950	.05	1,280	950	.22	5,640	1,620	.42	18,400
27	938	.04	1,010	1,050	3.48	98,700	1,560	1.48	62,300
28	950	.02	513	1,360	.56	20,600	1,470	.64	25,400
29	926	.04	1,000	1,550	.34	14,200	1,910	1.30	67,000
30	902	.02	487	1,310	.22	7,780	2,320	3.55	222,000
31	890	.02	481	1,090	.50	14,700			
Monthly load (tons)...				73,740	179,200		1,879,000		

TABLE 15.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Green River at gaging station near Green River, Utah, Oct. 1, 1939, to Sept. 30, 1941—Continued*

1940

Day	October			November			December		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	2,280	1.46	89,900	1,810	0.18	8,800	1,560	0.06	2,530
2	4,210	2.48	282,000	1,770	.30	14,340	1,620	.05	2,190
3	3,960	2.99	320,000	1,810	.14	6,840	1,840	.06	2,980
4	3,030	2.39	196,000	1,860	.12	6,030	2,020	.10	5,450
5	3,400	1.88	173,000	1,860	.10	5,020	2,140	.09	5,200
6	3,760	1.64	166,000	1,950	.10	5,260	2,140	.09	5,200
7	3,560	1.54	148,000	2,040	.11	6,060	2,160	.09	5,250
8	3,430	1.36	126,000	2,090	.12	6,770	2,180	.10	5,890
9	2,970	1.68	135,000	2,060	.11	6,120	2,210	.06	3,580
10	2,850	1.44	111,000	2,060	.14	7,790	2,210	.09	5,370
11	2,630	1.34	95,200	2,060	.11	6,120	2,140	.08	4,620
12	2,500	1.12	75,600	2,060	.12	6,670	2,000	.07	3,780
13	2,410	.65	42,300	2,090	.10	5,640	2,040	.04	2,200
14	2,340	.53	33,500	2,040	.09	4,960	1,540	.06	2,500
15	2,240	.35	21,200	1,950	.08	4,210	1,180	.10	3,190
16	2,140	.26	15,000	1,810	.07	3,420	664	.02	359
17	2,110	.22	12,500	1,730	.07	3,270	734	.03	595
18	2,060	.18	10,000	1,730	.08	3,740	776	.04	838
19	2,000	.18	9,720	1,810	.10	4,890	790	.04	853
20	1,930	.17	8,860	1,700	.07	3,210	546	.04	590
21	1,860	.32	16,100	1,860	.10	5,020	508	.04	549
22	1,810	.13	6,350	2,020	.10	5,450	720	.08	1,560
23	1,810	.12	5,860	2,110	.11	6,270	1,130	.12	3,660
24	1,770	.11	5,260	2,060	.10	5,560	1,360	.10	3,670
25	1,730	.10	4,670	1,930	.07	3,650	1,620	.11	4,810
26	1,730	.16	7,470	1,950	.08	4,210	1,790	.12	5,800
27	2,110	.22	12,500	1,880	.05	2,540	1,840	.12	5,960
28	1,950	.80	42,100	1,640	—	—	1,840	.08	3,470
29	1,840	.26	12,900	1,640	.09	3,990	1,620	.06	2,620
30	2,040	.24	13,200	1,660	.06	2,690	1,640	.07	3,100
31	1,930	.15	7,820	—	—	—	1,680	.06	2,720
Monthly load (tons)		2,205,000		162,200			101,100		

1941

	January			February			March		
1	1,790	0.04	1,930	1,500	0.03	1,210	4,510	0.51	62,100
2	1,970	.04	2,130	1,540	.02	832	4,580	.57	70,500
3	1,860	.09	4,520	1,520	.02	821	4,400	.56	66,500
4	2,160	.03	1,750	1,770	.02	956	4,470	.46	55,500
5	1,860	.06	3,010	1,660	.04	1,790	4,430	.61	73,000
6	1,700	.06	2,750	1,660	.05	2,240	3,760	.56	56,900
7	1,380	.03	1,120	1,640	.04	1,770	3,660	.52	51,400
8	1,360	.02	734	1,600	.04	1,730	3,660	.52	51,400
9	1,310	.02	707	1,460	.02	788	3,400	.40	36,700
10	1,250	.03	1,010	1,420	.03	1,150	3,090	.33	27,500
11	1,360	.03	1,100	1,480	.02	799	2,850	.40	30,800
12	1,520	.03	1,230	1,580	.04	1,710	2,600	.34	23,900
13	1,520	.01	410	1,600	.05	2,160	2,520	.21	14,300
14	1,580	.02	853	1,620	.04	1,750	2,410	.18	11,700
15	1,580	.03	1,280	1,640	.05	2,210	2,240	.14	8,470
16	1,680	.02	907	1,700	.05	2,300	2,140	.13	7,510
17	1,580	.04	1,710	1,840	.06	2,980	2,040	.09	4,960
18	1,640	.05	2,210	2,000	.19	10,300	2,000	.09	4,860
19	1,790	.04	1,930	2,280	.18	11,100	2,110	.10	5,700
20	1,810	.04	1,960	2,470	.32	21,300	2,310	.37	23,100
21	1,730	.06	2,800	2,580	.34	23,700	2,440	.36	23,700
22	1,420	.04	1,530	2,830	.30	22,900	2,500	.35	23,600
23	1,460	.05	1,970	3,000	.33	26,700	2,740	.43	31,800
24	1,420	.06	2,300	3,430	.85	78,700	3,660	.64	63,200
25	1,640	.05	2,210	4,360	.89	105,000	5,480	.80	118,000
26	1,580	.05	2,130	4,320	.81	94,500	5,440	.70	103,000
27	1,770	.06	2,870	4,580	.74	91,500	5,320	.89	128,000
28	1,860	.03	1,510	4,470	.58	70,000	5,240	.88	124,000
29	1,640	.04	1,770	—	—	—	4,960	.91	122,000
30	1,640	.05	2,210	—	—	—	4,140	.75	83,800
31	1,660	.05	2,240	—	—	—	3,830	.50	51,700
Monthly load (tons)		56,790		582,900			1,560,000		

1 Includes estimates for missing days.

## QUANTITIES OF SUSPENDED SEDIMENT

109

TABLE 15.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the Green River at gaging station near Green River, Utah, Oct. 1, 1939, to Sept. 30, 1941—Continued.*

1941

Day	April			May			June		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	3,790	0.41	42,000	6,550	0.41	72,500	25,000	0.38	256,000
2	3,790	.32	32,700	7,740	.59	123,000	23,400	.44	278,000
3	4,210	.35	39,800	8,450	.76	173,000	21,600	.38	222,000
4	4,730	.36	46,000	9,470	.78	199,000	20,000	.39	211,000
5	5,560	.48	72,100	10,100	.91	248,000	18,900	.26	133,000
6	6,600	.73	130,000	11,200	.94	284,000	18,200	.29	142,000
7	6,960	.87	164,000	14,000	1.25	472,000	19,300	1.34	698,000
8	7,180	.72	140,000	18,600	1.33	668,000	21,100	1.08	615,000
9	6,640	.60	108,000	17,300	1.08	504,000	21,300	1.90	518,000
10	6,330	.52	88,900	14,300	.87	336,000	21,100	.71	404,000
11	6,160	.46	76,500	13,700	.89	329,000	20,400	.51	281,000
12	5,860	.42	66,500	14,700	.97	385,000	20,400	.39	215,000
13	5,480	.31	45,900	17,700	1.01	483,000	20,500	.31	172,000
14	5,400	.32	46,700	20,200	1.08	589,000	21,500	.33	192,000
15	5,360	.35	50,700	20,000	.98	529,000	20,500	.30	166,000
16	5,280	.32	45,600	25,100	.90	610,000	19,000	.39	200,000
17	5,160	.30	41,800	25,700	.78	541,000	18,500	.30	150,000
18	5,730	.33	51,100	25,400	.63	432,000	18,700	.26	131,000
19	5,650	.34	51,900	23,900	.72	465,000	19,200	.27	140,000
20	5,480	.26	38,500	23,300	.58	365,000	20,300	.31	170,000
21	5,480	.29	42,900	22,900	.63	390,000	20,000	.23	124,000
22	5,120	.24	33,200	22,100	.61	364,000	20,200	.25	136,000
23	4,770	.19	24,500	20,600	.53	295,000	19,900	.28	150,000
24	4,360	.22	25,900	20,700	.44	246,000	19,000	.20	123,000
25	4,000	.21	22,700	23,000	.77	478,000	18,000	.23	112,000
26	3,830	.19	19,600	23,600	.88	561,000	16,900	.14	63,900
27	3,930	.24	25,500	25,500	2.01	1,384,000	15,600	.21	88,500
28	4,400	.22	26,100	25,400	.69	473,000	14,100	.17	64,700
29	5,160	.30	41,800	26,700	.44	317,000	13,200	.20	71,300
30	5,650	.32	48,800	26,800	.44	318,000	12,100	.18	58,800
31	Monthly load (tons)			26,200	.36	955,000			6,286,000

1941

	July			August			September		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	11,300	0.12	36,600	3,400	0.09	8,260	4,690	0.49	62,000
2	10,700	.14	40,400	3,210	.07	6,070	4,180	.50	56,400
3	9,970	.12	32,300	3,240	.05	4,370	3,630	.55	53,900
4	9,030	.13	31,700	3,240	.05	4,370	3,310	.48	42,900
5	8,450	.12	27,400	3,360	.07	6,350	3,090	.56	46,700
6	7,970	.12	25,800	2,880	.07	5,440	2,970	.57	45,700
7	7,690	.10	20,800	2,740	.04	2,960	2,740	.66	48,800
8	7,180	.09	17,400	2,520	.19	12,900	2,550	.24	16,500
9	6,600	.10	17,800	2,630	.09	6,390	2,440	.17	11,200
10	6,160	.12	20,000	3,400	.31	28,500	2,310	.15	9,360
11	5,650	.14	21,400	4,850	1.28	168,000	2,180	.16	9,420
12	5,400	.08	11,700	5,900	.70	112,000	2,110	.15	8,550
13	5,280	.10	14,300	4,100	1.93	214,000	2,300	.24	16,200
14	5,040	.08	10,900	3,560	2.39	230,000	2,830	.67	51,200
15	5,200	.08	11,200	3,630	1.07	105,000	2,580	1.48	103,000
16	5,400	.11	16,040	6,110	.85	140,000	2,550	.46	31,700
17	5,080	.17	23,300	5,770	.59	91,900	2,800	.30	22,700
18	4,850	.10	13,100	7,320	3.97	785,000	2,970	.21	16,800
19	4,850	.33	43,200	6,460	1.96	342,000	2,880	.36	28,000
20	5,520	.39	58,100	5,400	1.88	274,000	2,690	.50	36,300
21	4,660	.25	31,500	7,140	2.06	397,000	2,550	.26	17,900
22	4,580	.16	19,800	6,460	1.64	286,000	2,580	.55	38,300
23	4,470	.11	13,300	5,650	2.62	400,000	2,580	.26	18,100
24	3,960	.10	10,700	4,770	1.56	201,000	3,730	.30	30,200
25	3,630	.09	8,820	4,280	.99	114,000	5,440	.94	138,000
26	3,660	.08	7,910	3,860	1.85	88,600	4,320	1.58	184,000
27	3,930	.08	8,490	3,630	.72	70,600	3,360	.98	88,900
28	3,790	.10	10,200	3,430	.58	53,700	3,120	.69	58,100
29	3,660	.12	11,900	3,470	.31	29,000	3,120	.39	32,900
30	3,530	.16	15,200	3,760	.30	30,500	2,910	.16	12,600
31	3,530	.10	9,530	4,690	1.36	198,000			1,336,000

1 Estimated.

TABLE 16.—*Suspended-sediment concentration at different sampling times, mean daily discharge, mean daily concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Aug. 13 to Sept. 21, 1928*

Date	Time of collection	Mean daily discharge (sec.-ft.)	Suspended sediment			
			Number of samples	Mean percent at sampling period	Mean daily percent	Tons per day
<i>1928</i>						
Aug. 13	10:00 a. m.	1,580	9	1.10	3.38	144,000
	3:30 p. m.		9	4.11		
	4:30 p. m.		8	5.13		
Aug. 14	9:30 a. m.	1,280	5	2.57	2.44	84,200
	11:00 a. m.		4	2.41		
	11:45 a. m.		2	2.34		
	2:00 p. m.		3	2.30		
	3:00 p. m.		2	2.44		
	3:45 p. m.		2	2.62		
	4:30 p. m.		2	2.27		
Aug. 15	6:30 a. m.	760	2	2.00	1.94	39,800
	9:00 a. m.		3	2.12		
	11:30 a. m.		2	1.89		
	2:00 p. m.		3	1.89		
	4:30 p. m.		3	1.80		
	7:30 p. m.		3	1.82		
Aug. 16	6:30 a. m.	747	3	1.98	1.75	35,200
	9:00 a. m.		3	1.79		
	11:30 a. m.		3	1.75		
	2:00 p. m.		2	1.62		
	4:30 p. m.		3	1.58		
Aug. 17	7:00 a. m.	774	3	1.54	1.62	33,800
	5:00 p. m.		3	1.70		
Aug. 18	8:00 a. m.	650	3	1.07	1.08	18,900
	12:00 m.		2	1.08		
	4:00 p. m.		3	1.06		
Aug. 19	8:00 a. m.	612	3	1.88	1.92	31,700
	12:00 m.		2	2.02		
	4:00 p. m.		3	1.92		
Aug. 20	8:00 a. m.	482	3	1.74	1.76	22,900
	9:00 a. m.		8	1.70		
	12:00 m.		2	1.72		
	4:30 p. m.		3	1.93		
Aug. 21	8:00 a. m.	482	3	1.77	1.68	21,800
	12:00 m.		2	1.54		
	4:00 p. m.		1	1.40		
Aug. 22	8:00 a. m.	428	3	1.13	1.02	11,800
	12:00 m.		3	1.06		
	5:00 p. m.		3	.87		
Aug. 23	6:30 a. m.	499	3	.89	1.95	26,200
	12:00 m.		3	.81		
	4:45 p. m.		3	.83		
	7:30 p. m.		3	1.27		
	8:30 p. m.		3	6.61		
Aug. 24	5:30 a. m.	669	3	13.6	8.73	158,000
	7:00 a. m.		3	10.9		
	9:00 a. m.		3	9.38		
	11:45 a. m.		3	7.14		
	2:00 p. m.		3	5.99		
	5:00 p. m.		3	5.37		
Aug. 25	8:30 a. m.	450	3	2.97	2.66	32,300
	11:00 a. m.		3	2.99		
	1:30 p. m.		3	2.48		
	6:30 p. m.		3	2.21		
Aug. 26	5:30 a. m.	320	3	1.67	1.52	13,100
	12:30 p. m.		3	1.60		
	7:00 p. m.		3	1.28		

TABLE 16.—*Suspended-sediment concentration at different sampling times, mean daily discharge, mean daily concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Aug. 13 to Sept. 21, 1928—Continued*

Date	Time of collection	Mean daily discharge (sec.-ft.)	Suspended sediment			
			Number of samples	Mean percent at sampling period	Mean daily percent	Tons per day
<i>1928</i>						
Aug. 27	1:30 p. m. 5:00 p. m.	1,000	3 3	3.14 2.61	2.88	77,700
Aug. 28	9:00 a. m. 1:00 p. m. 5:00 p. m.	850	3 3 3	2.51 2.52 2.15	2.37	54,300
Aug. 29	6:00 a. m. 9:00 a. m. 12:00 m. 3:15 p. m. 4:15 p. m. 6:00 p. m. 8:00 p. m.	980	8 3 3 3 3 3 3	1.92 1.71 1.35 2.89 3.21 2.34 1.49	2.09	55,200
Aug. 30	6:00 a. m. 12:00 m. 4:30 p. m.	970	3 3 3	1.71 1.67 1.48	1.61	42,100
Aug. 31	6:00 a. m. 10:30 a. m. 2:30 p. m. 4:00 p. m. 5:00 p. m. 6:30 p. m. 9:00 p. m.	2,020	8 10 2 3 3 7 2	2.12 1.79 3.36 5.64 6.27 5.37 5.14	2.51	137,000
Sept. 1	6:00 a. m. 10:30 a. m. 4:30 p. m.	1,180	3 3 3	3.13 2.97 2.47	2.86	91,000
Sept. 2	7:00 a. m. 2:00 p. m. 4:30 p. m.	1,140	2 3 3	2.62 2.45 2.14	2.48	76,200
Sept. 3	6:30 a. m. 9:00 a. m. 4:30 p. m.	1,580	3 9 3	2.41 2.59 1.90	2.41	103,000
Sept. 4	6:00 a. m. 12:00 m. 6:00 p. m.	1,270	3 3 3	1.55 1.52 1.46	1.51	51,700
Sept. 5	8:00 a. m. 9:00 a. m. 4:30 p. m.	1,020	3 9 3	1.15 1.01 1.06	1.05	28,900
Sept. 6	8:45 a. m. 5:00 p. m.	900	7 3	.69 .66	.68	16,500
Sept. 7	8:00 a. m. 12:00 m. 4:30 p. m.	760	3 3 3	.78 1.08 .55	.81	16,600
Sept. 8	8:00 a. m. 12:00 m. 1:00 p. m. 2:00 p. m. 5:00 p. m.	695	3 3 3 6 5	.48 .41 .49 .35 .43	.42	7,880
Sept. 9	6:00 a. m. 4:30 p. m.	695	3 3	.33 .34	.34	6,360
Sept. 10	8:30 a. m. 1:30 p. m. 3:15 p. m. 5:45 p. m.	662	3 3 3 3	.60 .63 .61 .58	.60	10,700

TABLE 16.—*Suspended-sediment concentration at different sampling times, mean daily discharge, mean daily concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Aug. 13 to Sept. 21, 1928—Continued*

Date	Time of collection	Mean daily discharge (sec.-ft.)	Suspended sediment			
			Number of samples	Mean percent at sampling period	Mean daily percent	Tons per day
<i>1928</i>						
Sept. 11	8:30 a. m.	546	3	.38	.31	4,560
	10:00 a. m.		9	.31		
	5:00 p. m.		3	.25		
Sept. 12	6:45 a. m.	582	3	.46	.36	5,660
	6:45 a. m.		7	.44		
	1:00 p. m.		3	.23		
	4:15 p. m.		3	.18		
Sept. 13	6:00 a. m.	528	3	.29	.28	3,990
	4:30 p. m.		3	.28		
Sept. 14	8:00 a. m.	534	3	.29	.40	5,770
	8:30 a. m.		7	.35		
	4:30 p. m.		3	.32		
Sept. 15	9:00 a. m.	594	3	.42	.37	5,930
	12:00 m.		3	.36		
	5:00 p. m.		3	.34		
Sept. 16	6:30 a. m.	540	10	.30	.28	4,070
	4:30 p. m.		3	.23		
Sept. 17	9:00 a. m.	472	3	.30	.27	3,430
	9:30 a. m.		7	.29		
	4:00 p. m.		3	.21		
Sept. 18	9:00 a. m.	472	3	.29	.26	3,320
	9:50 a. m.		8	.26		
	4:30 p. m.		3	.21		
Sept. 19	9:00 a. m.	444	3	.23	.23	2,750
	4:30 p. m.		3	.23		
Sept. 20	9:00 a. m.	450	3	.17	.27	3,290
	4:30 p. m.		3	.37		
Sept. 21	9:00 a. m.	411	3	.24	.24	2,670

TABLE 17.—*Suspended-sediment concentration at different sampling times, mean daily discharge, mean daily concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, July 1 to Sept. 30, 1929*

Date	Time of collection	Mean daily discharge (sec.-ft.)	Suspended sediment			
			Number of samples	Mean percent at sampling period	Mean daily percent	Tons per day
<i>1929</i>						
July 1		4,340			0.66	77,300
2		4,150			.42	47,100
3		3,820			.41	42,300
4		3,750			.32	32,400
5		3,520			.31	29,500
July 6		3,240			.29	25,400
7		3,040			.31	25,400
8		2,540			.25	17,100
9		2,460			.29	19,300
July 10	2:30 p. m.	2,420	3	0.46	.50	32,700
	3:00 p. m.		2	.54		
July 11	5:45 a. m.	2,220	2	.52	.52	31,200
July 12	8:45 a. m.	2,310	7	3.59	2.47	154,000
	5:20 p. m.		6	1.16		
July 13	9:45 a. m.	2,620	2	.67	.73	51,600
	6:50 p. m.		3	.77		
July 14	8:00 a. m.	2,560	3	.65	.65	44,900
July 15	9:15 a. m.	2,430	7	.64	.71	46,600
	2:15 p. m.		3	.81		
	7:45 p. m.		3	.79		
July 16	8:15 a. m.	2,080	8	.64	.67	37,600
	5:40 p. m.		3	.77		
July 17	8:15 a. m.	2,100	7	.51	.75	42,500
	1:10 p. m.		3	1.07		
	7:40 p. m.		3	.96		
July 18	8:00 a. m.	2,000	8	.89	.83	44,800
	3:30 p. m.		3	.68		
July 19	6:35 a. m.	1,990	7	.80	.90	48,400
	12:45 p. m.		3	.96		
	4:30 p. m.		3	.82		
	7:00 p. m.		3	1.19		
July 20	6:30 a. m.	1,680	7	.63	.54	24,500
	1:20 p. m.		2	.38		
	5:15 p. m.		3	.45		
July 21	8:15 a. m.	1,860	3	.44	.44	22,100
July 22	7:20 a. m.	2,140	7	.56	.53	30,600
	2:00 p. m.		3	.51		
	7:30 p. m.		3	.47		
July 23	8:40 a. m.	2,990	7	.43	.92	74,300
	1:45 p. m.		3	.61		
	5:50 p. m.		3	1.30		
	8:30 p. m.		3	1.31		
	11:45 p. m.		3	1.57		
July 24	8:30 a. m.	3,030	7	1.56	1.52	124,000
	1:10 p. m.		3	1.42		
	4:15 p. m.		3	1.54		
July 25	8:50 a. m.	3,100	6	3.89	2.80	234,000
	2:00 p. m.		3	1.79		
	7:15 p. m.		3	2.52		
July 26	8:00 a. m.	3,460	7	1.75	1.80	168,000
	1:30 p. m.		3	1.80		
	5:40 p. m.		3	1.91		

TABLE 17.—*Suspended-sediment concentration at different sampling times, mean daily discharge, mean daily concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, July 1 to Sept. 30, 1929—Continued*

Date	Time of collection	Mean daily discharge (sec.ft.)	Suspended sediment			
			Number of samples	Mean percent at sampling period	Mean daily percent	Tons per day
<i>1929</i>						
July 27	9:00 a. m. 6:10 p. m. 7:45 p. m.	5,090	7 3 3	3.55 7.31 4.35	4.60	632,000
July 28	7:10 a. m. 10:20 a. m. 1:00 p. m. 7:15 p. m.	7,690	2 3 3 3	22.2 15.7 13.6 8.69	14.4	2,990,000
July 29	8:20 a. m. 12:30 p. m. 4:45 p. m.	14,600	3 3 3	13.8 12.9 8.85	11.8	4,650,000
July 30	6:40 a. m. 12:50 p. m. 4:45 p. m.	11,100	3 3 3	7.18 5.48 8.42	6.85	2,050,000
July 31	11:00 a. m. 2:30 p. m.	10,300	2 2	12.1 9.12	10.6	2,950,000
Aug. 1	11:00 a. m. 2:00 p. m. 5:00 p. m. 7:20 p. m.	13,500	3 3 3 1	6.09 7.20 7.95 15.0	7.87	2,870,000
Aug. 2	1:25 p. m.	20,500	3	6.37	6.37	3,530,000
Aug. 3	8:00 a. m. 2:00 p. m. 5:00 p. m.	11,800	9 3 3	3.78 3.38 3.32	3.61	1,150,000
Aug. 4	6:30 p. m.	12,600	1	13.9	13.9	4,730,000
Aug. 5	8:15 a. m. 1:45 p. m. 5:25 p. m.	15,800	3 3 2	5.03 5.42 9.40	6.28	2,680,000
Aug. 6	8:00 a. m. 9:00 a. m. 10:15 a. m. 11:15 a. m. 3:20 p. m. 4:25 p. m.	18,800	3 3 3 3 3 3	10.5 13.6 13.1 10.4 5.77 5.99	9.88	5,020,000
Aug. 7	7:40 a. m.	13,300	3	5.68	5.68	2,040,000
Aug. 8	8:15 a. m. 4:50 p. m.	11,100	3 8	3.20 4.62	4.24	1,270,000
Aug. 9	8:15 a. m. 1:10 p. m.	12,200	3 3	5.47 7.17	6.32	2,080,000
Aug. 10	7:40 a. m. 1:05 p. m. 5:30 p. m.	8,470	3 9 3	3.94 3.12 3.05	3.27	748,800
Aug. 11	8:00 a. m.	16,700	3	4.44	4.44	2,000,000
Aug. 12	8:45 a. m. 12:45 p. m. 1:45 p. m. 4:50 p. m.	38,300	3 3 3 4	8.94 7.76 7.74 6.94	7.77	8,040,000
Aug. 13	8:20 a. m. 1:05 p. m. 5:00 p. m.	19,300	2 2 3	6.20 6.19 6.39	6.28	3,270,000
Aug. 14	8:15 a. m. 5:10 p. m.	9,270	3	3.41 2.40	2.91	728,000

TABLE 17.—*Suspended-sediment concentration at different sampling times, mean daily discharge, mean daily concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, July 1 to Sept. 30, 1929—Continued.*

Date	Time of collection	Mean daily discharge (sec.-ft.)	Suspended sediment			
			Number of samples	Mean percent at sampling period	Mean daily percent	Tons per day
<i>1929</i>						
Aug. 15	7:30 a. m. 12:55 p. m. 5:40 p. m.	7,080	3 3 9	1.62 1.46 1.30	1.39	266,000
Aug. 16	9:10 a. m. 3:10 p. m.	5,780	3 3	1.16 1.08	1.12	175,000
Aug. 17	9:00 a. m.	5,120	9	1.44	1.44	199,000
Aug. 18	8:45 a. m.	4,550	9	.92	.92	113,000
Aug. 19	8:50 a. m. 4:10 p. m.	4,320	9 3	1.06 .77	.99	115,000
Aug. 20	8:00 a. m. 4:05 p. m.	3,580	7 3	.84 .80	.83	80,200
Aug. 21	8:35 a. m.	3,380	9	.83	.83	75,700
Aug. 23	9:35 a. m. 5:15 p. m.	2,720	9 3	.92 .82	.90	66,100
Aug. 24	8:40 a. m.	2,890	9	.92	.92	71,800
Aug. 25	8:25 a. m.	2,660	7	1.10	1.10	79,000
Aug. 26	8:25 a. m. 5:00 p. m.	2,530	3 3	.96 .81	.88	60,100
Aug. 27	8:40 a. m. 4:10 p. m.	3,440	9 3	.99 3.27	1.56	145,000
Aug. 28	8:35 a. m.	3,110	9	2.67	2.67	224,000
Aug. 29	7:30 a. m.	2,560	3	1.57	1.57	100,000
Aug. 30	10:00 a. m.	4,000	3	4.08	4.08	441,000
Aug. 31	6:30 a. m.	6,850	3	5.38	5.38	995,000*
Sept. 1	8:10 a. m.	5,040	3	6.58	6.58	895,000
Sept. 2	10:00 a. m.	5,600	3	5.14	5.14	777,000
Sept. 3	10:00 a. m.	8,070	3	7.46	7.46	1,630,000
Sept. 4	8:20 a. m. 3:45 p. m.	13,100	3 3	7.88 7.41	7.65	2,710,000
Sept. 5	7:40 a. m. 12:25 p. m. 2:25 p. m. 4:25 p. m.	11,100	3 3 3 3	6.61 5.93 6.14 6.00	6.17	1,850,000
Sept. 6	7:30 a. m. 11:20 a. m. 3:30 p. m. 4:30 p. m.	8,070	3 3 3 3	4.21 3.79 3.86 3.86	3.93	856,000
Sept. 7	8:00 a. m. 1:55 p. m. 3:00 p. m.	7,010	3 3 3	3.90 3.64 3.34	3.63	687,000
Sept. 8	8:20 a. m.	6,220	9	2.75	2.75	462,000
Sept. 9	3:00 p. m.	5,280	3	1.71	1.71	244,000
Sept. 10	8:45 a. m.	4,800	8	1.48	1.48	192,000

TABLE 17.—*Suspended-sediment concentration at different sampling times, mean daily discharge, mean daily concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, July 1 to Sept. 30, 1929—Continued*

Date	Time of collection	Mean daily discharge (sec.-ft.)	Suspended sediment			
			Number of samples	Mean percent at sampling period	Mean daily percent	Tons per day
<i>1929</i>						
Sept. 11	8:45 a. m.	4,320	4	1.27	1.17	136,000
	1:15 p. m.		3	1.08		
	5:15 p. m.		3	1.13		
Sept. 12	9:30 a. m.	4,080	9	1.13	1.19	131,000
	5:15 p. m.		3	1.38		
Sept. 13	9:20 a. m.	4,190	7	1.28	1.26	143,000
	5:45 p. m.		3	1.19		
Sept. 14	9:35 a. m.	3,720	8	1.02	1.00	100,000
	5:45 p. m.		3	.97		
Sept. 15	10:10 a. m.	3,310	7	.83	.83	74,200
Sept. 16	9:05 a. m.	3,030	7	.83	.85	69,500
	3:10 p. m.		3	.90		
Sept. 17	10:05 a. m.	2,720	9	.65	.65	47,700
Sept. 18	10:15 a. m.	2,480	7	.67	.69	46,200
	1:50 p. m.		3	.75		
Sept. 19		2,250	3	.61	.61	37,100
Sept. 20		4,180	2	.44	.44	49,700
Sept. 21		13,100	3	40.8	30.9	10,900,000
			3	21.1		
Sept. 22		8,870	3	7.40	7.40	1,770,000
Sept. 23	10:00 a. m.	20,000	3	28.5	21.2	11,400,000
	4:00 p. m.		3	14.0		
Sept. 24	8:30 a. m.	21,500	3	8.32	7.69	4,460,000
	2:00 p. m.		3	7.07		
Sept. 25		14,000	3	4.83	4.83	1,830,000
26		9,880	3	2.42	2.42	646,000
27		7,580	3	2.53	2.53	518,000
28		6,830	3	2.53	2.53	467,000
29		6,040	3	2.35	2.35	383,000
30		4,990	3	1.52	1.52	205,000

## QUANTITIES OF SUSPENDED SEDIMENT

117

TABLE 18.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941*

1929

Day	October			November			December		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	4,300	2.15	249,000	1,310	0.55	19,400	930	1.14	28,600
2	3,810	2.80	288,000	1,320	.37	13,200	922	.66	16,400
3	3,410	2.12	195,000	1,260	.47	16,000	922	.54	13,400
4	3,410	3.39	312,000	1,230	.44	15,000	907	.71	17,400
5	2,910	1.74	137,000	1,200	.45	15,000	848	.47	10,700
6	2,680	.89	64,400	1,230	.42	14,000	827	.47	10,500
7	2,510	1.70	115,000	1,250	.45	15,200	798	.43	9,250
8	2,350	1.07	67,800	1,230	.21	6,970	855	.37	8,530
9	2,350	.68	43,100	1,250	.35	11,800	855	.39	8,990
10	2,200	1.01	60,000	1,240	.42	14,000	777	.39	8,170
11	2,290	.96	59,300	1,220	.33	10,900	743	.37	7,410
12	2,290	.81	50,000	1,220	.64	21,100	791	.38	8,110
13	2,120	.60	34,300	1,090	.49	14,400	855	.47	10,800
14	2,290	1.06	65,500	1,120	.61	18,400	812	.33	7,230
15	2,020	.80	43,600	1,050	.56	15,900	770	.46	9,550
16	2,350	.86	54,500	922	.46	11,400	743	.46	9,220
17	2,240	1.72	104,000	884	.59	14,100	777	.40	8,380
18	2,180	2.27	133,000	1,010	.52	14,200	784	.29	6,130
19	2,040	.78	42,900	1,000	.60	17,600	791	.44	9,390
20	1,920	.90	46,600	1,090	.58	17,100	696	.45	8,450
21	1,850	1.20	60,000	1,030	.55	15,300	670	.15	2,710
22	1,710	.74	34,100	968	.54	14,100	386	.10	1,040
23	1,580	.76	32,400	930	.49	12,300	264	.12	853
24	1,530	.63	26,000	841	.71	16,100	229	.11	679
25	1,520	.67	27,500	791	.58	12,400	264	.32	2,280
26	1,460	.70	27,600	827	.64	14,300	268	.54	3,900
27	1,420	.90	34,500	863	.55	12,800	287	.56	4,330
28	1,370	.39	14,400	819	.40	8,840			
29	1,360	1.35	50,000	863	.47	10,900	553	.40	5,970
30	1,350	.45	16,400	877	.65	15,400	496	.47	6,290
31	1,400	.41	15,500				530	.52	7,430
Monthly load (tons)		2,503,000			428,100				1 257,100

1930

	January			February			March		
	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day
1	485	0.30	3,920	743	0.45	9,020	1,050	0.45	12,700
2	507	.22	3,010	784	.77	16,300	1,060	.62	17,700
3	485	.35	4,580	601	.54	8,750	907	.37	9,050
4	452	.15	1,830	645	.55	9,570	798	.36	7,750
5	524	.39	5,510	723	.42	8,190	757	.28	5,720
6	690	.43	8,000	729	.42	8,260	870	.51	12,000
7	834	1.29	29,000	798	.40	8,610	930	.79	19,800
8	577	.27	4,200	777	.38	7,960	960	.83	21,500
9	524	.30	4,240	934	.48	12,100	975	.87	22,900
10	474	.50	6,390	999	.53	14,300	930	.75	18,800
11	479	.37	4,780	1,140	.71	21,800	892	.50	12,000
12	518	.26	3,630	1,190	.92	29,500	900	.43	10,400
13	468	.33	4,160	1,410	.57	21,700	877	.42	9,950
14	426	.52	5,970	1,660	3.64	158,000	907	.44	10,800
15	463	.53	6,620	1,960	3.01	159,000	960	.47	12,200
16	613	.22	3,640	2,010	.77	41,700	1,090	.39	11,500
17	518	.16	2,240	1,830	.88	43,500	1,260	.55	18,700
18	474	.36	4,600	1,460	.60	23,600	1,630	.77	33,900
19	349	.20	1,880	1,260	.53	18,000	1,980	1.16	61,900
20	536	.19	2,750	1,200	.46	14,900	1,590	.89	38,200
21	426	.15	1,720	1,250	1.00	33,700	1,300	.65	22,800
22	396	.22	2,350	1,320	.77	27,400	1,170	.68	21,500
23	319	.13	1,120	1,420	.89	34,100	1,150	.45	14,000
24	298	.17	1,370	2,180	.82	48,200	1,250	.43	14,500
25	268	.28	2,020	1,770	.93	44,400	1,800	1.32	64,100
26	243	.26	1,700	1,870	.87	43,900	2,020	.95	51,800
27	240	.17	1,100				1,910	.71	36,600
28	315	.32	2,720	1,240	1.30	43,500	2,130	1.14	65,500
29	458	.23	2,840				1,810	.90	43,900
30	632	.36	6,140				1,500	.58	23,500
31	777	.75	15,700				1,280	.37	12,800
Monthly load (tons)		149,700			1 952,900				738,500

\* Includes estimates for missing days.

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1930

Day	April			May			June		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	1,270	.0.71	24,300	4,560	1.01	124,000	10,400	1.75	491,000
2	1,360	.99	36,300	4,270	.74	85,200	10,400	1.59	446,000
3	1,470	1.03	40,800	4,270	.99	114,000	7,200	1.21	235,000
4	1,500	.63	25,500	5,330	1.28	184,000	5,920	.78	125,000
5				5,580	1.34	202,000	5,490	.74	110,000
6				4,640	.93	116,000	5,580	.61	91,800
7	2,930	1.77	140,000	3,920	.80	84,600	6,360	.74	127,000
8	4,340	2.33	273,000	3,380	.76	69,300	8,080	.94	205,000
9	5,490	1.44	213,000	3,130	.68	57,400	8,490	.92	211,000
10	5,920	1.56	249,000	2,890	.72	56,100	8,380	.83	188,000
11	6,000	1.22	197,000	2,600	.70	49,100	7,980	.73	157,000
12	5,740	1.57	243,000	2,490	.51	34,200	7,380	.84	167,000
13	5,090	1.22	167,000	2,380	.47	30,200	7,380	1.17	233,000
14	4,640	1.24	155,000	2,220	.63	37,700	7,480	.93	188,000
15	4,860	1.27	166,000	2,100	.45	25,500	7,380	.78	155,000
16	5,330	1.31	188,000	2,160	.30	17,500	6,540	.80	141,000
17	5,090	.98	135,000	2,950	.86	68,400	5,660	.85	130,000
18	4,480	1.22	147,000	4,130	1.29	144,000	5,170	.65	90,600
19	3,640	.77	75,600	3,780	.74	75,400	4,940	.58	77,300
20	3,260	.82	72,100	3,380	.55	50,100	5,010	.63	85,100
21	3,450	.95	88,400	2,950	.43	34,200	4,340	.51	59,700
22	4,100	1.19	132,000	2,890	4.14	323,000	4,130	.45	50,100
23	5,280	1.30	185,000	4,940	1.16	155,000	3,990	.59	63,500
24	6,310	1.47	250,000	5,740	1.85	286,000	3,710	.34	34,000
25	6,910	1.33	248,000				3,380	.60	54,700
26	6,910	1.15	214,000	5,090	.64	87,900	2,710	.43	31,400
27	7,200	1.19	231,000	6,270	.75	127,000	2,320	.46	28,800
28	6,090	1.23	202,000	6,820	.81	149,000	2,100	.39	22,100
29	5,660	.92	140,000	7,880	1.01	215,000	1,900	.41	21,000
30	5,170	.81	113,000	8,280	.75	167,000	1,730	.28	13,100
31				10,600	.92	263,000			
Monthly load (tons)			14,451,000	13,582,000			4,032,000		

1930

	July			August			September		
	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day
1	1,600	0.28	12,100	3,990	6.14	661,000	421	0.31	3,520
2	1,320	.21	7,480	4,130	3.40	379,000	381	.24	2,470
3	1,150	.25	7,750	4,200	4.51	511,000	381	.21	2,160
4	1,050	.20	5,660	3,640	3.00	295,000	381	.25	2,570
5	922	.16	3,980	3,920	16.6	1,750,000	431	1.52	17,700
6	855	.18	4,150	2,170	6.51	476,000	607	.27	37,200
7	743	.23	4,610	2,490	2.58	173,000	812	.26	58,300
8	716	.16	3,090	3,320	2.66	238,000	798	.19	47,100
9	664	.16	2,870	13,900	23.0	8,620,000	651	1.06	18,600
10	710	.24	4,600	11,400	11.2	3,430,000	577	.69	10,700
11	952	4.04	104,000	15,800	14.7	6,270,000	507	.68	9,300
12	4,480	6.59	796,000	12,400	10.1	3,370,000	501	.60	8,110
13	1,600	18.4	792,000	8,910	7.81	1,880,000	441	.47	5,590
14	2,270	10.3	633,000	5,490	6.55	970,000	426	.40	4,600
15	2,270	10.2	626,000	4,130	3.60	401,000	411	.34	3,770
16	1,420	4.10	157,000	3,520	2.35	228,000	377	.35	3,560
17	1,410	2.96	113,000	3,070	1.57	130,000	354	.32	3,060
18	2,380	3.87	248,000	2,600	1.29	90,500	354	.36	3,440
19	2,490	6.46	434,000	2,380	.94	60,300	363	.36	3,520
20	4,710	8.87	1,130,000	2,050	.87	48,100	319	.28	2,410
21	3,850	8.24	856,000	1,800	.65	31,600	323	.30	2,610
22	5,170	8.61	1,200,000	1,420	.66	25,300	319	.24	2,060
23	5,660	5.48	837,000	1,310	.54	19,100	315	.23	1,950
24	5,010	3.56	481,000	1,050	.45	12,700	298	.21	1,690
25	4,130	2.58	287,000	900	.43	10,400	287	.20	1,550
26	3,320	2.21	198,000	827	.55	12,300	290	.24	1,880
27	2,890	1.82	142,000	777	.79	16,600	401	.30	3,240
28	2,770	1.94	145,000	729	.39	7,670	463	.41	5,120
29	5,010	4.38	592,000	696	.41	7,700	406	.33	3,610
30	4,060	3.08	337,000	607	.44	7,200	447	.40	4,800
31	4,940	5.47	729,000	501	.32	4,320			
Monthly load (tons)			10,890,000	30,130,000			276,200		

\*Includes estimates for missing days.

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1930

Day	October			November			December		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	1,190	2.95	94,700	460	0.28	3,480	652	0.69	12,100
2	715	2.57	49,600	449	.36	4,370	659	.52	9,250
3	427	.73	8,410	438	.24	2,830	638	.33	5,690
4	508	.87	11,900	432	.21	2,450	593	.33	5,290
5	550	.54	8,010	449	.35	4,230	556	.22	3,290
6	508	.43	5,880	449	.46	5,580	574	.26	4,020
7	484	.49	6,390	460	.33	4,100	574	.32	4,960
8	484	.42	5,470	490	.27	3,560	562	.32	4,850
9	484	.41	5,340	484	.27	3,530	562	.33	4,990
10	400	.34	3,670	466	.22	2,780	574	.38	5,880
11	427	.32	3,690	484	.23	2,990	586	.46	7,280
12	438	.34	4,020	460	.26	3,240	586	.43	6,800
13	490	.36	4,750	454	.27	3,320	586	.50	7,900
14	606	.42	6,880	427	.33	3,800	612	.52	8,580
15	775	.74	15,500	466	.31	3,880	574	.36	5,580
16	673	.56	10,200	454	.52	6,360	568	.28	4,290
17	645	.57	9,920	514	.38	5,260	520	.19	2,670
18	600	.51	8,250	730	.77	15,200	466	.24	3,020
19	574	.43	6,660	830	.77	17,200	227	.09	539
20	593	.47	7,520	806	.84	18,300	173	.06	270
21	568	.40	6,120	752	.55	11,200	206	.05	270
22	556	.37	5,560	673	.55	9,980	170	.06	270
23	532	.41	5,880	687	.50	9,280	113	.01	27
24	544	.41	6,010	632	.46	7,850	113	.18	539
25	556	.39	5,850	626	.48	8,090	113	.02	54
26	496	.38	5,070	606	.48	7,850	150	.17	701
27	496	.31	4,150	580	.40	6,260	150	.04	162
28	496	.28	3,750	600	.39	6,310	150	.10	405
29	484	.28	3,670	612	.49	8,090	175	.03	135
30	484	.33	4,320	638	.56	9,630	200	.05	270
31	460	.30	3,720	—	—	—	250	.04	270
Monthly load (tons)		330,900	201,000			110,400			

1931

	January			February			March		
	300	0.07	566	1,200	0.95	30,700	526	0.27	3,830
1	300	.05	405	1,240	.58	19,400	520	.21	2,940
2	300	.10	809	1,180	.72	22,900	490	.24	3,180
3	300	.08	647	995	.78	20,900	466	.23	2,890
4	300	.12	971	950	.62	15,900	416	.34	3,800
6	300	.08	647	1,090	.81	23,800	427	.27	3,100
7	300	.10	809	1,170	.77	24,300	478	.39	5,020
8	300	.12	971	1,050	.74	21,000	508	.37	5,070
9	300	.06	485	822	.76	16,900	508	.26	3,560
10	300	.04	324	752	.72	14,600	466	.30	3,780
11	300	.01	81	738	.69	13,700	405	.37	4,050
12	300	.01	81	673	.53	9,630	416	.29	3,260
13	300	.02	162	854	.76	17,500	438	.39	4,610
14	300	.05	405	1,010	.79	21,500	478	.35	4,500
15	300	.11	890	1,220	1.10	36,200	544	.40	5,880
16	350	.07	647	1,560	2.83	119,000	580	.43	6,720
17	350	.05	485	1,290	1.93	67,200	580	.45	7,040
18	350	.03	270	1,040	1.39	39,000	568	.44	6,740
19	350	.03	270	830	1.06	23,706	612	.44	7,250
20	350	.03	270	708	.71	13,600	680	.49	8,980
21	350	.03	270	666	.56	10,100	768	.71	14,700
22	350	.05	485	659	.57	10,100	745	.67	13,500
23	350	.02	189	701	.47	8,870	708	.56	10,700
24	350	.03	270	652	.47	8,250	659	.56	9,950
25	350	.07	647	693	.35	6,550	760	.55	11,300
26	350	.04	378	532	.34	4,880	1,220	1.88	61,900
27	350	.07	647	526	.39	5,530	968	.62	16,200
28	350	.12	1,130	544	.35	5,120	934	.61	15,400
29	400	.07	755	—	—	—	708	.42	8,010
30	450	.09	1,080	—	—	—	738	.36	7,170
31	500	.19	2,560	—	—	—	694	.49	9,170
Monthly load (tons)		18,610	630,800			274,200			

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1931

Day	April			May			June		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1.	680	0.36	6,610	2,590	1.06	74,000	3,890	0.84	88,100
2.	673	.38	6,900	2,350	1.22	77,300	4,590	.92	114,000
3.	606	.26	4,260	2,530	.96	65,500	5,400	.92	134,000
4.	659	.43	7,630	2,830	1.73	132,000	4,820	.77	100,000
5.	846	.61	13,900	3,140	1.51	128,000	5,640	.86	131,000
6.	959	.59	15,300	3,480	1.59	149,000	5,560	.84	128,000
7.	846	.67	15,300	3,080	1.20	99,700	4,460	.63	75,800
8.	782	.48	10,100	2,770	.96	71,700	4,590	.69	85,400
9.	806	.50	10,900	2,890	1.01	78,700	5,240	.64	90,500
10.	1,010	.82	22,300	3,280	1.24	110,000	5,560	.74	111,000
11.	1,190	.66	21,200	3,150	.94	79,900	4,440	.55	65,900
12.	1,120	.58	17,500	2,770	.80	59,800	3,890	.51	53,500
13.	1,080	.46	13,400	2,350	.69	43,700	3,220	.59	51,200
14.	1,270	.60	20,600	2,180	.58	34,100	3,340	.70	62,800
15.	1,390	.69	25,900	2,290	.87	53,700	3,410	.83	76,300
16.	1,430	.59	22,800	2,830	1.23	93,900	3,220	2.00	174,000
17.	1,410	.55	20,900	4,030	.90	97,800	3,220	.48	41,700
18.	1,550	.79	33,000	4,820	1.30	169,000	3,150	.52	44,200
19.	1,440	.59	22,900	4,740	1.25	160,000	3,020	.41	33,400
20.	1,290	.36	12,500	5,400	1.40	204,000	2,590	.56	39,100
21.	1,300	.51	17,900	5,000	1.09	147,000	2,240	.38	23,000
22.	1,560	.62	26,100	4,100	.88	97,300	1,960	.41	21,700
23.	1,670	.54	24,300	3,280	.56	49,500	1,850	.46	23,000
24.	1,660	.58	26,000	2,710	.68	49,700	1,630	.28	12,300
25.	1,820	.79	38,800	2,710	.78	57,000	1,500	.35	14,200
26.	2,020	.84	45,800	3,410	1.00	92,000	1,490	.29	11,700
27.	2,180	.84	49,400	4,520	.86	105,000	1,480	.30	11,900
28.	2,305	.79	50,100	5,000	.64	86,300	1,360	.66	24,200
29.	2,070	.63	35,200	4,240	.65	74,300	1,360	.43	15,800
30.	2,240	.73	44,100	3,340	.54	48,700	1,900	2.22	114,000
31.				3,220	.61	53,000			
Monthly load (tons)		681,600				2,842,000			1,970,000

1931

	July			August			September		
	July	August	September	July	August	September	July	August	September
1.	2,070	1.24	69,200	2,550	11.5	791,000	148	1.55	6,180
2.	3,020	1.01	82,300	3,480	9.64	905,000	113	1.57	4,770
3.	3,610	.86	83,700	3,150	7.89	670,000	176	1.99	9,440
4.	4,740	1.80	230,000	1,170	4.97	157,000	117	1.36	4,290
5.	3,340	2.25	203,000	680	3.39	62,200	82	.40	890
6.	3,410	1.95	179,000	432	2.30	26,800	62	.26	432
7.	2,350	1.27	80,500	1,930	3.65	190,000	95	1.26	3,240
8.	1,740	.85	39,900	1,290	3.53	123,000	133	1.33	4,770
9.	1,430	.59	22,800	1,160	3.62	113,000	88	.48	1,130
10.	1,140	.43	13,200	1,050	2.73	77,300	161	1.02	4,420
11.	918	.36	8,900	1,060	1.92	54,900	89	.53	1,270
12.	775	.28	5,850	1,120	2.13	64,400	66	3.21	5,720
13.	619	.24	4,020	822	1.35	29,900	82	2.36	5,230
14.	526	.20	2,830	632	.99	16,900	124	1.35	4,500
15.	460	.22	2,720	508	.84	11,500	1,560	3.65	15,300
16.	380	.16	1,650	454	.65	7,960	2,180	5.12	30,100
17.	258	.24	1,670	680	7.05	129,000	918	3.99	98,800
18.	309	.33	2,750	562	2.50	37,900	1,820	2.46	121,000
19.	380	1.50	15,400	606	1.74	28,400	3,450	6.57	611,000
20.	176	.26	1,240	318	1.90	16,300	2,120	5.15	294,000
21.	213	.26	1,480	632	2.14	36,500	1,850	3.60	180,000
22.	460	.73	9,060	490	1.68	22,200	3,340	5.53	498,000
23.	314	.77	6,530	514	1.93	26,800	2,240	2.70	163,000
24.	186	.59	2,970	270	2.59	18,900	3,960	4.87	520,000
25.	143	1.33	5,120	176	1.32	6,260	2,530	3.21	219,000
26.	104	.83	2,320	153	.95	3,910	2,410	2.92	190,000
27.	99	.63	1,670	135	.68	2,480	2,890	2.10	164,000
28.	83	.38	863	128	.44	1,510	2,180	1.34	78,800
29.	1,020	.18	4,960	111	.49	1,460	2,020	1.27	69,200
30.	870	4.22	99,000	95	.33	836	1,690	.99	45,100
31.	910	2.48	60,900	108	.47	1,380			
Monthly load (tons)		1,246,000				3,635,000			3,354,000

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1931

Day	October			November			December		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	1,440	0.83	32,200	872	0.64	15,000	925	0.53	13,200
2	5,800	7.18	1,120,000	850	.75	17,200	720	.28	5,450
3	6,120	9.40	1,550,000	720	.59	11,500	625	.27	4,560
4	6,120	6.03	995,000	707	.47	8,950	344	.23	2,130
5	5,160	3.76	523,000	707	.46	8,740	249	.21	1,400
6	3,520	1.86	177,000	700	.57	10,800	220	.23	1,380
7	2,730	1.58	116,000	688	.50	9,490	300	.23	1,860
8	2,310	1.22	75,900	694	.53	9,930	400	.19	2,050
9	1,980	1.00	53,400	1,100	.83	24,600	553	.17	2,540
10	1,720	.92	42,600	1,440	2.05	79,600	539	.28	4,450
11	3,660	2.86	282,000	1,100	.98	29,100	1,670	.69	31,100
12	2,250	3.10	188,000	4,080	3.91	430,000	1,350	1.39	50,600
13	1,820	1.98	97,200	4,380	3.17	374,000	902	.35	8,520
14	1,620	1.34	58,600	2,730	2.97	219,000	643	.32	5,560
15	1,480	1.02	40,700	1,680	1.87	79,700	480	.35	4,530
16	1,350	.86	31,300	1,220	1.40	46,100	339	.22	2,020
17	1,260	.84	28,500	1,020	1.03	28,300	294	.09	701
18	1,220	.80	26,300	940	.88	22,300	228	.06	378
19	1,870	5.83	294,000	988	.77	20,500	298	.16	1,290
20	6,800	7.31	1,340,000	910	.65	15,900	380	.05	512
21	4,840	5.27	688,000	940	.67	17,000	447	.09	1,080
22	3,940	3.26	346,000	1,020	.72	19,800	607	.08	1,320
23	1,620	4.09	179,000	902	.47	11,400	842	.07	1,590
24	1,260	1.82	60,500	688	.52	9,660	980	.11	2,910
25	1,140	1.28	39,400	245	.17	1,120	1,260	.11	3,750
26	1,100	1.01	30,000	192	.11	569	1,220	.39	12,800
27	1,060	.91	26,000	217	.14	820	1,140	.22	6,770
28	996	.68	18,300	269	.17	1,230	1,060	.37	10,600
29	964	.60	15,600	812	.32	7,010	1,350	.88	32,000
30	902	.60	14,000	1,350	.83	30,200	1,480	.53	21,100
31	880	.59	14,000				1,060	.59	16,900
Monthly load (tons)			8,502,000			1,206,000			255,100

1932

	January			February			March		
	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day
1	674	0.18	3,260	508	0.27	3,700	4,230	6.83	779,000
2	469	.12	1,510	649	.31	5,430	4,530	3.51	429,000
3	565	.26	3,960	858	.52	12,000	5,320	3.94	565,000
4	668	.28	5,040	1,220	.42	13,800	4,230	3.34	381,000
5	595	.22	3,530	1,220	.38	12,500	2,920	3.14	247,000
6	583	.16	2,510	850	.32	7,330	2,310	2.14	133,000
7	553	.25	3,720	1,060	.76	21,700	1,980	1.04	55,500
8	643	.25	4,340	10,500	4.87	1,380,000	1,920	1.09	56,400
9	776	.21	4,400	15,700	4.47	1,890,000	2,310	1.92	120,000
10	748	.39	7,880	11,900	6.20	1,990,000	3,250	2.24	196,000
11	694	.33	6,180	8,220	4.63	1,030,000	3,250	2.40	210,000
12	681	.43	7,900	5,480	3.44	505,000	2,990	2.41	194,000
13	835	.52	11,700	3,520	2.34	222,000	2,250	1.41	85,600
14	762	.40	8,230	3,060	2.10	173,000	2,030	1.32	72,300
15	583	.28	4,400	2,550	1.98	136,000	1,820	.93	45,700
16	524	.30	4,230	2,490	2.09	140,000	1,980	1.58	84,400
17	571	.21	3,240	2,250	2.10	127,000	2,490	1.06	71,200
18	458	.14	1,730	2,030	3.14	172,000	2,920	1.22	96,100
19	513	.28	3,880	1,720	1.91	88,600	3,250	1.90	167,000
20	513	.36	4,990	3,520	4.99	474,000	4,080	2.78	306,000
21	480	.14	1,810	2,670	2.56	184,000	5,800	3.80	594,000
22	535	.14	2,020	2,670	3.85	277,000	5,800	3.70	579,000
23	571	.13	2,000	2,430	1.99	130,000	4,080	2.92	321,000
24	607	.12	1,970	2,460	2.10	141,000	3,120	1.60	135,000
25	625	.09	1,510	2,430	2.23	146,000	2,610	1.34	94,300
26	625	.16	2,700	2,430	1.86	122,000	3,120	1.25	105,000
27	553	.15	2,240	3,060	2.54	210,000	4,530	5.54	677,000
28	452	.13	1,590	3,380	3.42	312,000	3,940	2.10	223,000
29	294	.22	1,750	3,660	4.12	407,000	3,180	1.28	110,000
30	145	.09	351				3,660	1.26	124,000
31	425	.17	1,940				4,080	1.64	180,000
Monthly load (tons)			116,500			10,340,000			7,436,000

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1932

Day	April			May			June		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	5,160	1.32	184,000	4,680	0.75	94,700	11,700	0.85	271,000
2	4,530	1.20	147,900	4,680	.93	117,000	9,350	.63	159,000
3	6,460	2.96	516,000	5,000	.81	109,000	9,350	.62	156,000
4	8,220	3.53	783,000	6,120	.82	135,000	9,730	.70	184,000
5	8,590	4.02	931,000	7,320	.96	190,000	9,350	.60	151,000
6	8,970	3.56	861,000	8,220	.88	195,000	8,040	.58	126,000
7	8,970	3.74	905,000	8,400	.91	206,000	7,140	.52	100,000
8	7,680	5.49	1,140,000	7,500	.76	154,000	5,960	.45	72,300
9	6,630	3.40	608,000	6,460	.62	108,000	5,480	.42	62,100
10	7,320	4.25	839,000	6,630	.52	93,000	6,120	.52	85,800
11	6,970	4.42	831,000	7,500	.60	121,000	7,140	.67	129,000
12	7,140	3.94	759,000	8,040	.67	145,000	7,860	.53	112,000
13	8,220	1.63	361,000	8,780	1.34	317,000	8,220	.54	120,000
14	9,350	3.70	933,000	10,300	.84	233,000	9,540	.62	159,000
15	10,500	3.82	1,080,000	11,500	.78	242,000	11,100	.60	180,000
16	10,100	1.91	520,000	11,500	1.00	310,000	11,700	.62	196,000
17	10,100	1.89	515,000	11,700	.83	262,000	11,700	.71	224,000
18	11,300	1.79	546,000	12,900	1.03	358,000	11,700	.62	196,000
19	11,100	1.78	533,000	13,700	.94	347,000	10,500	.62	176,000
20	9,920	1.89	506,000	15,300	1.18	487,000	9,730	.62	163,000
21	10,100	1.50	409,000	15,300	1.26	520,000	9,350	.54	136,000
22	9,730	1.46	383,000	14,700	1.06	420,000	9,540	.33	84,900
23	8,780	1.34	317,000	14,100	1.14	433,000	9,540	.55	141,000
24	8,220	1.25	277,000	16,100	1.23	534,000	9,920	.70	187,000
25	6,630	1.09	195,000	15,300	1.09	450,000	10,900	.76	223,000
26	5,480	.96	142,000	14,500	1.02	399,000	10,500	.65	184,000
27	5,480	1.10	163,000	13,300	1.08	387,000	10,500	.56	159,000
28	5,480	1.07	158,000	10,700	1.04	300,000	9,730	.56	147,000
29	5,160	1.02	142,000	9,350	.85	214,000	8,780	.56	133,000
30	5,000	.62	83,600	10,700	.78	225,000	7,860	.51	108,000
31				12,500	.85	287,000			
Monthly load (tons)		15,770,000			8,393,000				4,525,000

1932

	July			August			September		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	7,500	0.59	119,000	4,680	1.96	247,000	4,230	1.22	139,000
2	7,140	.64	123,000	4,680	2.40	303,000	3,380	.81	73,800
3	7,140	.79	152,000	3,660	.95	93,800	2,860	.73	56,300
4	6,460	.52	90,600	2,990	.69	55,600	2,490	.46	30,900
5	6,120	.43	71,000	2,310	.53	33,000	2,080	.48	26,900
6	6,120	.46	75,900	2,030	.36	19,700	1,870	.45	22,700
7	5,480	.35	51,700	1,720	.30	13,900	1,620	.48	21,000
8	4,840	.28	36,500	1,480	.25	9,980	1,350	.37	13,500
9	4,230	.42	47,900	1,300	.18	6,310	1,300	.40	14,000
10	3,940	.29	30,800	1,220	.17	5,590	1,220	.36	11,800
11	3,940	.33	35,100	1,010	.14	3,810	1,060	.28	8,000
12	3,940	.35	37,200	880	.12	2,850	906	.29	7,790
13	4,680	.46	58,100	769	.18	3,730	932	.28	7,040
14	5,320	.56	80,400	707	.16	3,050	850	.24	5,500
15	5,160	.49	68,200	655	.13	2,300	805	.22	4,780
16	4,530	.33	40,300	547	.22	3,250	776	.36	7,530
17	3,940	.43	45,700	688	.89	16,500	734	.28	5,540
18	3,660	.34	33,600	940	1.83	46,400	707	.22	4,190
19	3,520	.41	38,900	1,100	1.52	45,100	668	.29	5,220
20	3,060	1.30	107,000	3,180	3.00	257,000	619	.23	3,840
21	3,250	1.03	90,300	8,040	8.25	1,790,000	553	.19	2,830
22	2,800	.58	43,800	9,160	11.3	2,790,000	541	.18	2,630
23	2,370	.46	29,400	4,680	4.26	538,000	910	.22	5,400
24	2,140	.36	20,800	3,250	2.77	243,000	3,380	3.91	356,000
25	1,980	.30	16,000	3,060	1.95	161,000	4,840	6.05	790,000
26	1,980	.30	16,000	2,490	1.55	104,000	2,310	4.00	249,000
27	2,080	.44	24,700	3,520	2.00	190,000	2,250	3.22	195,000
28	1,920	.48	24,900	4,230	2.84	324,000	1,400	2.57	97,000
29	1,870	.36	18,200	16,500	12.4	5,520,000	1,180	1.47	46,800
30	4,230	2.67	305,000	10,900	4.12	1,210,000	948	1.16	29,700
31	3,520	2.82	268,000	5,800	1.76	275,000			
Monthly load (tons)		2,200,000			14,320,000				2,244,000

<sup>1</sup> Estimated.

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1932

Day	October			November			December		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	798	0.73	15,700	769	0.33	6,850	631	0.35	5,960
2	762	.64	13,500	727	.32	6,280	613	.29	4,800
3	720	.51	9,900	720	.25	4,850	607	.31	5,070
4	694	.43	8,040	727	.25	4,910	625	.34	5,720
5	734	.51	10,100	734	.28	5,560	674	.30	5,450
6	668	.13	2,350	700	.28	5,290	655	.24	4,230
7	661	.18	3,210	687	.27	4,960	565	.27	4,130
8	625	.08	1,350	700	.24	4,530	530	.22	3,160
9	776	.58	12,100	681	.24	4,400	541	.27	3,940
10	741	.93	18,600	649	.25	4,370	535	.22	3,180
11	727	.65	12,800	681	.26	4,770	520	.28	3,940
12	741	.48	9,600	694	.22	4,130	501	.43	5,800
13	805	.48	10,400	643	.33	5,720	480	.14	1,810
14	776	.39	8,170	631	.24	4,070	460	.18	2,240
15	755	.36	7,340	601	.23	3,720	450	.09	1,080
16	734	.36	7,120	577	.23	3,590	440	.13	1,540
17	694	.31	5,600	571	.23	3,530	430	.09	1,050
18	688	.35	6,500	589	.22	3,510	420	.12	1,350
19	681	.32	5,880	583	.25	3,940	411	.24	2,670
20	649	.25	4,370	571	.22	3,400	422	.22	2,510
21	681	.28	5,150	583	.24	3,780	431	.15	1,750
22	727	.25	4,910	595	.26	4,180	342	.13	1,190
23	1,620	1.18	51,600	613	.24	3,960	268	.15	1,080
24	1,100	1.65	49,000	601	.20	3,240	280	.09	674
25	1,060	1.26	36,000	601	.21	3,400	300	.06	485
26	1,010	.74	20,100	583	.23	3,610	330	.16	1,430
27	932	.49	12,300	595	.28	4,500	278	.11	836
28	910	.48	11,800	524	.30	4,230	206	.10	566
29	828	.37	8,250	571	.27	4,150	134	.10	351
30	776	.34	7,120	583	.27	4,230	26	.04	.27
31	805	.34	7,390	386,100	131,700		310	.24	2,000
	Monthly load (tons)								80,000

1933

	January			February			March		
	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day
1	300	0.10	809	800	0.04	863	2,490	1.35	90,700
2	290	.10	782	750	.01	202	2,370	1.07	68,400
3	251	.07	485	700	.09	170	2,200	1.08	64,100
4	328	.02	178	700	.10	1,890	1,820	1.53	75,100
5	308	.08	674	700	.04	755	1,400	.76	28,700
6	355	.07	674	700	.05	944	1,140	.80	24,600
7	350	.08	755	650	.06	1,050	1,100	.64	19,000
8	346	.06	566	600	.02	324	1,220	.57	18,700
9	304	.08	647	600	.02	324	1,300	.54	18,900
10	320	.08	701	600	.03	485	1,350	.73	26,600
11	355	.04	378	600	.02	324	1,480	.83	33,100
12	373	.05	512	650	.03	539	1,620	.83	36,300
13	380	.08	809	700	.04	755	1,670	.73	32,900
14	343	.08	728	700	.07	1,320	1,530	.78	32,200
15	377	.06	620	750	.06	1,210	1,300	.70	24,500
16	419	.11	1,240	800	.08	1,730	1,060	.61	17,400
17	404	.04	432	800	.05	1,080	956	.51	13,200
18	422	.04	458	800	.12	2,590	925	.48	12,000
19	362	.04	378	800	.10	2,160	842	.44	9,980
20	400	.06	647	850	.12	2,750	820	.39	8,630
21	450	.07	863	850	.17	3,880	790	.36	7,660
22	500	.11	1,483	850	.08	1,830	790	.32	6,820
23	550	.20	2,970	900	.18	4,320	720	.26	5,040
24	600	.06	971	900	.33	8,010	688	.30	5,560
25	700	.07	1,320	1,000	.56	15,100	713	.33	6,340
26	800	.07	1,510	1,500	.45	18,200	694	.29	5,420
27	800	.07	1,510	1,980	1.65	88,100	649	.25	4,370
28	800	.04	863	2,030	1.27	69,500	649	.30	5,260
29	800	.02	432	-----	-----	-----	655	.27	4,770
30	800	.01	216	-----	-----	-----	873	.46	10,800
31	800	.08	1,726	-----	-----	-----	1,100	.42	12,500
	Monthly load (tons)		26,300		930,300				729,600

TABLE 18.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1933

Day	April			May			June		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	1,300	0.82	28,800	1,260	0.43	14,600	9,350	1.04	262,000
2	1,140	.53	16,300	1,480	.47	18,800	10,300	1.25	347,000
3	1,060	.43	12,200	1,440	.43	16,700	11,900	1.20	385,000
4	1,140	.43	13,200	1,400	.54	20,400	11,700	.92	290,000
5	1,440	.47	18,300	1,530	.43	17,700	9,540	.92	237,000
6	1,770	.57	27,200	1,480	.49	19,600	8,780	.87	206,000
7	1,720	.57	26,400	1,530	.49	20,200	8,460	.80	181,000
8	1,350	.46	16,700	1,580	.42	17,900	7,140	.68	131,000
9	1,100	.37	11,000	1,480	.47	18,800	5,800	.70	109,000
10	1,100	.42	12,500	1,400	.48	18,100	4,840	.58	75,700
11	1,060	.41	11,700	1,480	.48	19,100	6,800	.68	125,000
12	1,020	.40	11,000	1,350	.45	16,400	8,970	.83	201,000
13	880	.27	6,420	1,220	.39	12,800	9,540	.90	232,000
14	805	.27	5,860	1,220	.38	12,500	8,970	.71	172,000
15	948	.33	8,440	1,140	.31	9,520	8,220	.59	131,000
16	948	.33	8,440	1,100	.31	9,200	7,320	.64	126,000
17	865	.26	6,070	980	.25	6,610	6,970	.53	99,600
18	748	.22	4,450	776	.21	4,400	7,140	.60	116,000
19	956	.40	10,300	865	.20	4,670	7,320	.66	130,000
20	1,140	.34	10,500	1,920	.72	37,300	6,970	.69	130,000
21	1,440	.61	23,700	3,660	1.15	114,000	7,320	.76	150,000
22	1,450	.47	18,800	5,640	1.06	161,000	7,320	.80	158,000
23	1,260	.35	11,900	6,460	1.26	220,000	7,320	1.18	233,000
24	1,060	.27	7,710	5,640	1.02	155,000	6,970	2.73	513,000
25	980	.28	7,390	4,230	.58	66,200	5,960	.98	158,000
26	820	.25	5,530	3,520	.59	56,000	5,160	.64	89,100
27	783	.24	5,070	3,380	.80	72,900	4,530	.55	67,200
28	783	.26	5,500	4,530	.84	103,000	4,080	.52	57,200
29	842	.35	7,960	6,290	.91	154,000	3,520	.47	44,600
30	842	.30	6,820	7,140	.90	173,000	3,180	.36	30,900
31				8,400	1.12	254,000			
Monthly load (tons)		366,200			1,844,000				5,187,000

1933

	July			August			September		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	2,920	0.40	31,500	631	2.04	34,700	118	0.86	2,720
2	2,490	.29	19,500	655	1.67	29,500	92	.98	2,430
3	2,140	.31	17,900	565	1.29	19,700	92	.77	1,910
4	2,030	.30	16,400	524	1.13	16,000	94	.50	1,270
5	2,140	.40	23,100	441	1.03	12,200	94	.43	1,080
6	2,550	1.59	109,000	674	1.22	22,200	86	.31	728
7	3,520	3.31	314,000	1,820	6.71	329,000	82	.32	701
8	5,000	3.14	423,000	3,180	6.98	599,000	100	.49	1,320
9	3,800	2.98	305,000	2,610	6.97	491,000	1,260	.83	28,200
10	4,530	2.41	294,000	1,530	5.47	226,000	5,960	13.2	2,120,000
11	3,800	2.58	264,000	1,060	3.93	112,000	7,320	10.0	1,990,000
12	3,060	1.30	107,000	842	2.17	49,300	3,520	8.34	792,000
13	2,920	1.46	115,000	643	1.44	25,000	2,430	4.08	267,000
14	3,250	1.44	126,000	577	1.07	16,600	2,730	2.90	214,000
15	2,140	1.62	93,500	452	.91	11,100	3,250	3.93	344,000
16	1,720	1.30	60,300	430	.65	7,550	3,660	3.80	375,000
17	1,530	1.07	44,100	357	.53	5,100	2,610	2.85	201,000
18	1,720	3.03	141,000	261	.49	3,450	1,980	1.94	104,000
19	1,770	1.77	84,500	245	.43	2,830	2,920	3.20	252,000
20	1,260	2.32	78,800	231	.29	1,810	3,660	3.78	373,000
21	1,060	1.38	39,500	308	.35	2,910	5,640	2.68	408,000
22	858	.89	20,600	375	14.6	148,000	5,320	4.10	588,000
23	895	.63	15,200	257	5.08	35,200	2,730	3.84	283,000
24	948	.56	14,300	166	3.52	15,800	2,370	2.33	149,000
25	1,580	1.15	49,000	231	1.73	10,800	1,870	1.55	78,200
26	2,460	6.16	414,000	172	1.00	5,560	1,620	1.09	47,600
27	1,480	5.42	216,000	163	1.21	5,310	1,440	1.00	38,800
28	980	3.12	82,500	157	.86	3,640	1,260	.87	29,600
29	948	3.05	78,000	160	.68	2,940	1,100	.75	22,300
30	748	1.42	28,600	182	.94	4,610	1,020	.55	15,100
31	619	1.39	23,200	166	.68	3,050			
Monthly load (tons)		3,648,000			2,252,000				8,732,000

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1933

Day	October			November			December		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	972	0.60	1,570	681	0.58	10,700	1,920	2.48	129,000
2	835	.53	12,000	553	.42	6,260	925	1.28	32,000
3	1,020	.52	14,300	631	.61	10,400	902	1.02	24,800
4	1,350	6.03	220,000	668	.42	7,590	850	.83	19,100
5	2,030	26.7	1,470,000	755	.54	11,000	748	.65	13,100
6	5,800	15.8	2,480,000	687	.42	7,800	662	.60	10,700
7	5,480	8.50	1,260,000	769	.57	11,800	619	.50	8,370
8	3,380	5.04	460,000	741	.59	11,800	565	.43	6,560
9	1,870	3.32	168,000	682	.40	7,370	559	.46	6,940
10	1,670	1.75	78,900	637	.48	8,260	530	.40	5,720
11	1,870	2.47	125,000	631	.41	6,990	553	.43	6,430
12	3,060	3.15	260,000	595	.37	5,940	553	.45	6,720
13	1,820	3.37	166,000	619	.44	7,340	530	.52	7,450
14	1,300	2.25	79,000	674	.38	6,910	577	.44	6,860
15	1,580	1.51	64,400	607	.38	6,240	643	.47	8,150
16	2,430	4.32	283,000	607	.44	7,210	662	.52	9,290
17	1,480	3.33	133,000	577	.44	6,860	681	.53	9,750
18	1,140	1.75	53,900	559	.41	6,180	502	.31	4,210
19	1,060	1.32	37,800	513	.44	6,100	458	.30	3,700
20	972	1.14	29,900	541	.38	5,560	442	.26	3,100
21	900	.81	19,700	571	.41	6,320	425	.20	2,300
22	828	.69	15,400	541	.36	5,260	571	.26	4,000
23	895	1.12	27,000	513	.35	4,860	577	.36	5,620
24	818	.74	16,300	553	.42	6,260	595	1.50	8,050
25	741	.68	13,600	547	.27	4,000	583	1.50	7,880
26	812	.68	14,900	474	.37	4,720	643	.54	9,370
27	835	.49	11,000	496	.46	6,160	655	.63	11,200
28	805	.51	11,100	518	.35	4,890	707	.64	12,200
29	769	.51	10,600	502	.32	4,350	662	.51	9,130
30	720	.50	9,720	1,140	1.00	30,600	655	.58	10,300
31	755	.51	10,400				681	.55	10,100
Monthly load (tons)		7,556,000			235,700				412,100

1934

	January			February			March		
	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day
1	714	0.46	8,860	442	0.35	4,180	613	0.42	6,940
2	748	.36	7,260	469	.28	3,540	619	.41	6,860
3	842	.43	9,770	486	.32	4,210	619	.43	7,180
4	835	.46	10,400	518	.35	4,890	565	.35	5,350
5	707	.37	7,070	535	.46	6,640	513	.31	4,290
6	668	.45	8,130	513	.39	5,400	535	.33	4,780
7	662	.37	6,620	530	.33	4,720	530	.29	4,160
8	458	.24	2,970	513	.40	5,540	452	.23	2,810
9	430	.25	2,920	541	.32	4,670	577	.29	4,510
10	316	.20	1,700	571	.37	5,700	619	.34	5,670
11	339	.21	1,920	553	.34	5,080	613	.46	7,610
12	375	.20	2,020	571	.34	5,240	637	.40	6,880
13	385	.15	1,570	583	.30	4,720	607	.44	7,210
14	362	.20	1,940	496	.30	4,020	601	.52	8,450
15	436	.19	2,240	496	.28	3,750	637	.60	10,300
16	458	.15	1,860	458	.26	3,210	762	.48	9,880
17	649	.46	8,070	518	.27	3,780	805	.63	13,700
18	565	.40	6,100	635	.33	4,780	769	.72	15,000
19	681	.52	9,560	513	.42	5,800	948	.80	20,500
20	668	1.05	18,900	535	.33	4,780	925	.92	23,000
21	589	.39	6,210	571	.31	4,780	762	.52	10,700
22	601	.49	7,940	565	.25	3,810	707	.48	9,150
23	649	.60	10,500	601	.28	4,540	741	.49	9,800
24	619	.56	9,370	835	.69	15,600	828	.49	11,000
25	565	.39	5,940	713	.47	9,040	880	.39	9,260
26	559	.44	6,640	842	.55	12,500	812	.49	10,700
27	565	.42	6,400	932	.68	17,100	842	.52	11,800
28	559	.35	5,290	700	.42	7,940	820	.42	9,290
29	571	.37	5,700				783	.41	8,670
30	508	.31	4,240				727	.39	7,670
31	480	.37	4,810				694	.47	8,800
Monthly load (tons)		192,900			170,000				281,900

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1934

Day	April			May			June		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	707	0.38	7,260	3,190	0.87	74,900	2,670	1.13	81,500
2	812	.33	7,240	2,990	.86	69,400	2,730	3.29	243,000
3	910	.60	14,700	3,660	1.15	114,000	1,820	1.42	69,800
4	1,150	.50	15,500	3,250	1.00	87,800	1,530	.73	30,200
5	1,060	.54	15,400	2,610	.84	59,200	1,260	.56	19,100
6	964	.51	13,300	2,200	.89	52,900	1,100	.40	11,900
7	858	.43	9,960	1,920	.74	38,400	956	.40	10,300
8	762	.43	8,860	2,080	.96	53,900	820	.31	6,860
9	727	.37	7,260	3,120	1.40	118,000	720	.29	5,640
10	649	.35	6,130	3,250	1.02	89,500	631	.31	5,290
11	631	.29	4,940	3,380	.84	76,700	547	.21	3,100
12	700	.64	12,100	4,230	1.05	120,000	452	.20	2,430
13	940	.58	14,700	3,940	1.17	124,000	366	.21	2,080
14	1,770	.88	42,100	3,800	1.16	119,000	370	.13	1,300
15	2,200	1.26	74,800	3,660	1.09	108,000	265	.11	783
16	2,140	.86	49,700	3,250	.83	72,800	203	.11	594
17	2,140	.92	53,200	2,610	.79	55,700	192	.07	351
18	2,430	1.07	70,200	2,550	1.01	69,600	175	.05	243
19	2,250	.99	60,200	2,490	.93	62,500	125	.05	162
20	1,980	.89	47,600	2,370	.71	45,400	95	.04	108
21	1,720	.68	31,600	2,200	.93	55,200	70	.03	54
22	1,920	.77	39,900	1,720	.62	28,300	60	.04	54
23	2,610	.97	68,400	1,530	.47	19,400	40	.05	54
24	3,120	1.14	96,000	1,480	.87	34,800	35	.01	11
25	2,860	1.17	90,300	1,300	.53	18,600	24	.01	5
26	3,060	.89	73,500	1,140	.36	11,100	18		5
27	3,520	1.18	112,000	1,060	.43	12,300	10	.01	3
28	3,660	1.01	99,800	1,000	.49	13,200	9	.01	3
29	3,380	.93	84,900	1,180	.40	12,700	9	.01	3
30	3,250	.91	79,900	1,440	.40	15,600	5	.01	3
31				1,530	.54	22,300			
Monthly load (tons)			1,311,000			1,856,000			494,900

1934

	July			August			September		
	1	2	3	4	5	6	7	8	9
1	1			154	3.75	15,600	910	5.17	127,000
2	1			138	3.62	13,500	714	4.09	78,800
3	0			108	2.87	8,370	607	3.42	56,100
4	0			95	2.05	5,260	508	2.86	39,200
5	0			100	1.96	5,290	316	2.78	23,700
6	0			55	1.02	1,500	189	1.89	9,640
7	0			45	.66	810	112	1.41	4,270
8	0			45	1.48	1,810	699	4.28	80,800
9	0			147	.72	10,500	547	5.32	78,600
10	0			203	3.38	18,500	375	2.75	27,800
11	0			183	4.46	22,000	321	5.49	47,600
12	0			95	3.90	9,990	224	4.73	28,600
13	0			80	4.53	9,770	281	3.58	27,200
14	2			65	4.83	8,480	547	4.60	67,900
15	30			424	9.95	85,000	491	3.38	44,800
16	20	0.03	3	502	5.78	72,100	366	4.10	40,500
17	10	.01	3	339	4.16	39,800	169	4.97	22,700
18	8	.01	3	175	4.66	25,100	151	3.66	14,900
19	4	.02	3	118	5.10	16,300	140	2.70	10,200
20	704	10.0	35,600	120	3.94	12,800	105	1.63	4,620
21	1,050	5.20	147,000	151	3.65	14,900	90	1.24	3,020
22	769	10.9	227,000	265	4.80	34,300	85	1.12	2,560
23	353	4.12	44,700	135	5.22	19,000	90	.84	2,050
24	1,220	10.9	334,000	65	3.75	6,590	500	.74	55,100
25	518	8.00	109,000	125	4.54	15,300	1,980	7.43	367,000
26	273	6.62	48,800	55	2.86	4,240	3,120	7.82	659,000
27	745	6.98	157,000	192	3.74	19,400	1,720	3.09	144,000
28	1,000	8.76	237,000	1,030	8.69	242,000	1,180	1.98	63,100
29	880	7.40	176,000	4,920	20.3	2,700,000	980	1.44	38,100
30	385	5.96	62,000	2,370	16.0	1,020,000	940	.96	24,400
31	224	4.37	26,400	1,770	8.38	400,000			
Monthly load (tons)			1,605,000			4,858,000			2,193,000

## QUANTITIES OF SUSPENDED SEDIMENT

127

TABLE 18.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1934

Day	October			November			December		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	850	0.81	18,380	160	0.14	594	316	0.34	2,890
2	720	.74	14,390	125	.15	513	290	.24	1,890
3	619	.61	10,200	135	.13	486	115	.16	486
4	547	.56	8,260	166	.15	675	100	.10	270
5	474	.45	5,750	285	.10	756	125	.08	270
6	425	.42	4,810	203	.15	810	175	.38	1,780
7	420	.41	4,640	308	.24	2,000	150	.10	405
8	385	.38	3,940	265	.18	1,300	200	.11	594
9	344	.29	2,700	303	.19	1,570	250	.20	1,350
10	334	.30	2,700	316	.19	1,620	316	.24	2,050
11	290	.27	2,110	290	.21	1,650	339	.16	1,460
12	269	.27	1,970	334	.31	2,810	312	.16	1,350
13	245	.22	1,460	285	.21	1,620	375	.44	4,460
14	257	.21	1,460	321	.22	1,920	762	1.72	35,400
15	217	.27	1,590	303	.25	2,050	964	.78	20,300
16	228	.21	1,300	312	.23	1,940	1,060	.75	21,500
17	308	.20	1,670	366	.22	2,190	828	.81	18,100
18	326	.20	1,760	469	.78	9,880	707	.55	10,500
19	281	.18	1,380	410	.34	3,750	655	.42	7,420
20	294	.18	1,430	464	.44	5,510	565	.40	6,100
21	344	.20	1,860	486	.50	6,560	547	.38	5,620
22	334	.20	1,810	458	.34	4,210	425	.28	3,210
23	326	.19	1,670	508	.44	6,050	405	.29	3,160
24	334	.17	1,540	442	.36	4,290	464	.39	4,890
25	298	.15	1,220	474	.39	5,000	447	.43	5,180
26	277	.13	972	415	.33	3,700	458	.38	4,700
27	273	.14	1,030	415	.31	3,480	464	.32	4,000
28	269	.16	1,160	474	.37	4,720	442	.28	3,350
29	249	.17	1,130	385	.30	3,130	380	.27	2,780
30	238	.17	1,080	464	.33	4,130	420	.31	3,510
31	192	.13	675				513	.34	4,700
Monthly load (tons)		106,000				88,910			183,700

1935

	January			February			March		
	513	0.39	5,400	948	1.27	32,500	619	0.57	9,530
1	513	.35	4,370	1,060	1.41	40,400	547	.51	7,530
2	410	.34	3,750	1,060	1.54	44,100	681	.73	13,400
3	348	.24	2,270	1,000	1.50	40,500	966	1.40	37,600
4	344	.32	2,970	910	1.28	31,500	1,220	1.14	37,600
5	425	.44	5,050	888	1.02	24,500	1,300	1.12	39,300
6	366	.22	2,190	910	.84	20,600	1,020	.85	23,400
7	513	.50	6,910	1,020	.68	18,700	835	.71	16,000
8	583	.57	8,960	1,140	1.11	34,200	700	.60	11,300
9	571	.66	10,200	1,060	.78	22,300	741	.56	11,200
10	565	.47	7,180	980	.74	19,600	748	.55	11,100
11	1,400	3.22	122,000	902	.54	13,100	625	.43	7,260
12	1,140	1.56	48,000	835	.50	11,300	688	.47	8,720
13	1,000	1.00	27,000	925	.70	17,500	755	.63	12,900
14	1,300	.52	82,800	880	.48	11,400	835	.76	17,100
15	1,020	1.65	45,400	842	.47	10,700	1,480	2.93	117,000
16	1,100	2.07	61,500	755	.40	8,150	1,870	1.87	94,400
17	776	1.07	22,400	655	.34	6,020	1,620	2.25	98,400
18	613	.91	15,100	553	.44	6,560	1,400	1.67	63,100
19	273	.52	3,830	508	.52	7,130	1,260	1.09	37,100
20	100	.14	378	571	.50	9,100	1,180	.98	31,200
21	100	.01	27	734	1.04	20,600	1,260	1.05	35,700
22	150	.00	11	1,020	1.25	34,400	1,260	1.36	46,300
23	200	.02	108	1,260	1.66	56,500	1,400	1.43	54,100
24	300	.03	243	1,220	2.13	70,200	1,440	1.87	72,700
25	300	.04	324	918	1.64	40,600	1,480	1.39	55,500
26	700	.10	1,890	872	1.16	27,300	1,820	1.65	81,100
27	932	.92	23,200	714	.86	16,600	1,820	1.27	62,400
28	1,820	.95	46,700				2,200	1.65	98,000
29	918	.74	18,300				2,310	1.65	103,000
30	988	1.46	38,900				2,370	1.51	96,600
31	Monthly load (tons)		617,400			696,100			1,411,000

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

Day	1935					
	April		May		June	
	Mean discharge (second-feet)	Suspended sediment	Mean discharge (second-feet)	Suspended sediment	Mean discharge (second-feet)	Suspended sediment
	Mean percent	Tons per day	Mean percent	Tons per day	Mean percent	Tons per day
1	3,120	1.76	148,000	4,080	1.56	172,000
2	3,520	2.32	220,000	4,230	1.00	114,000
3	3,380	1.96	179,000	4,230	1.02	116,000
4	3,660	1.83	181,000	3,660	.91	89,900
5	4,230	1.92	219,000	3,660	.98	96,800
6	4,080	1.86	205,000	3,120	.94	79,200
7	3,660	1.46	144,000	3,120	1.03	86,800
8	3,380	1.06	96,700	3,060	.83	68,600
9	3,180	1.12	96,200	3,060	.68	56,200
10	4,680	1.49	188,000	3,380	.84	76,700
11	4,380	2.38	281,000	3,940	.86	91,500
12	2,800	1.45	110,000	4,530	.97	119,000
13	2,490	1.21	81,400	5,320	1.34	192,000
14	2,670	1.23	88,700	6,120	1.32	218,000
15	3,380	1.29	118,000	7,500	1.47	298,000
16	4,530	1.48	181,000	6,970	1.13	213,000
17	5,480	1.68	249,000	6,460	1.78	310,000
18	5,960	1.34	216,000	5,960	1.83	295,000
19	5,800	1.83	287,000	6,460	1.81	316,000
20	6,120	1.44	238,000	6,120	1.93	319,000
21	5,800	1.68	263,000	7,140	1.25	241,000
22	5,480	1.64	243,000	11,300	2.51	766,000
23	5,320	1.42	204,000	8,590	1.99	462,000
24	5,320	1.41	203,000	7,140	1.06	204,000
25	5,000	1.32	178,000	6,970	1.16	218,000
26	5,160	1.39	194,000	7,680	1.14	236,000
27	3,940	.96	102,000	8,590	1.17	271,000
28	3,520	.96	91,200	9,160	1.35	334,000
29	3,800	1.05	108,000	9,160	1.08	267,000
30	4,080	1.35	149,000	8,970	1.07	259,000
31				8,590	1.09	253,000
Monthly load (tons)...		5,262,000			6,839,000	
						10,010,000

	1935					
	July		August		September	
	Mean discharge (second-feet)	Suspended sediment	Mean discharge (second-feet)	Suspended sediment	Mean discharge (second-feet)	Suspended sediment
	Mean percent	Tons per day	Mean percent	Tons per day	Mean percent	Tons per day
1	8,590	0.87	202,000	2,610	4.45	314,000
2	8,400	.76	172,000	2,080	1.84	103,000
3	7,860	.65	138,000	2,370	1.90	122,000
4	7,320	.70	138,000	1,980	2.95	158,000
5	7,140	.70	135,000	2,140	2.48	143,000
6	6,800	.41	75,300	2,610	3.25	229,000
7	6,290	.72	122,000	2,670	3.40	245,000
8	5,960	.52	83,700	2,310	3.21	200,000
9	5,960	.69	111,000	2,800	4.13	312,000
10	5,800	.63	98,700	3,520	3.68	350,000
11	5,640	.54	82,200	2,550	1.47	101,000
12	5,640	.48	73,100	2,080	3.25	182,000
13	5,000	.46	62,100	1,670	2.13	96,000
14	4,840	.38	49,600	1,770	1.39	66,400
15	4,680	.53	67,000	1,720	1.70	78,900
16	4,530	.63	77,100	1,670	1.09	49,100
17	4,380	.78	92,200	2,250	1.91	116,000
18	3,660	.54	53,400	1,440	2.09	81,300
19	5,800	2.71	424,000	1,440	1.11	43,100
20	3,940	1.17	124,000	1,530	.80	33,000
21	4,230	.83	94,800	1,220	.55	18,100
22	4,080	.77	84,800	964	.43	11,200
23	3,660	.66	65,200	880	.36	8,560
24	3,660	.54	53,400	1,220	.51	16,800
25	3,120	1.00	84,200	2,140	2.63	152,000
26	2,550	.52	35,800	2,920	4.41	348,000
27	2,250	.28	17,010	2,020	3.26	257,000
28	1,980	1.06	56,700	2,200	2.90	172,000
29	1,820	1.28	62,900	2,550	2.25	155,000
30	2,080	1.38	77,500	2,030	1.28	70,100
31	2,730	1.77	19,800	1,870	1.61	81,300
Monthly load (tons)...		3,211,000			4,813,000	
						9,971,000

## QUANTITIES OF SUSPENDED SEDIMENT

129

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1935

Day	October			November			December		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	2,310	2.98	185,900	842	0.43	9,770	613	0.24	3,970
2	1,870	1.05	53,000	835	.34	7,670	601	.23	3,730
3	1,870	1.57	70,800	762	.32	6,590	565	.34	5,180
4	1,530	.75	31,000	727	.33	6,480	601	.36	5,830
5	1,400	.54	20,410	748	.32	6,450	625	.29	4,890
6	1,300	.44	15,440	748	.29	5,860	643	.26	4,510
7	1,260	.38	12,930	720	.29	5,640	688	.26	4,830
8	1,260	.40	13,610	688	.24	4,460	694	.25	4,700
9	1,100	.41	12,180	655	.24	4,240	668	.24	4,320
10	1,060	.36	10,310	643	.26	4,510	655	.24	4,240
11	980	.38	10,040	688	.24	4,460	625	.20	3,380
12	895	.37	8,940	707	.25	4,780	595	.21	3,380
13	895	.30	7,240	707	.26	4,970	547	.20	2,940
14	872	.29	6,830	714	.25	4,810	502	.19	2,560
15	828	.27	6,060	643	.26	4,510	496	.22	2,940
16	812	.22	4,830	649	.26	4,560	496	.23	3,080
17	776	.24	5,020	637	.22	3,780	496	.19	2,540
18	748	.29	5,860	625	.22	3,730	420	.15	1,701
19	720	.26	5,050	619	.31	5,180	405	.12	1,323
20	734	.25	4,970	655	.23	4,080	312	.12	999
21	1,260	.19	22,100	655	.21	3,730	321	.12	1,053
22	1,620	1.90	83,100	674	.23	4,180	321	.13	1,134
23	1,260	3.01	102,400	637	.23	3,940	348	.14	1,323
24	1,100	1.43	42,500	601	.26	4,210	513	.22	3,050
25	932	.99	24,920	649	.21	3,670	518	.20	2,810
26	980	.94	24,870	694	.31	5,800	518	.32	4,480
27	940	.69	17,520	707	.29	5,540	474	.19	2,430
28	910	.55	13,500	734	.27	5,350	370	.19	1,800
29	850	.43	9,880	727	.28	5,510	420	.29	3,290
30	860	.51	11,720	674	.24	4,370	535	.23	3,320
31	842	.40	9,100	-----	-----	-----	535	.19	2,750
Monthly load (tons)		852,000	-----	-----	152,800	-----	-----	-----	98,57

1936

	January			February			March		
	Mean	discharge	Suspended sediment	Mean	discharge	Suspended sediment	Mean	discharge	Suspended sediment
1	559	0.23	3,480	727	0.29	5,700	734	0.79	15,660
2	425	.21	2,403	727	.27	5,290	865	.69	16,120
3	447	.18	2,160	918	.39	9,670	1,530	1.34	55,400
4	474	.23	2,940	727	.31	6,080	3,120	2.17	18,280
5	420	.13	1,480	688	.30	5,560	3,660	.07	303,000
6	370	.17	1,701	607	.24	3,940	3,800	.00	308,000
7	518	.29	4,050	513	.13	1,809	3,380	.25	297,000
8	577	.15	2,349	436	.13	1,539	2,990	.40	193,800
9	619	.06	999	452	.14	1,701	2,920	.95	153,700
10	595	.15	2,403	541	.21	3,080	3,120	.82	153,300
11	571	.18	2,780	625	.19	3,210	3,250	.76	154,400
12	595	.23	3,700	631	.20	3,400	3,120	.68	141,500
13	601	.38	5,160	681	.25	4,590	2,430	.53	100,400
14	589	.18	2,860	783	.35	7,400	2,200	.18	70,100
15	649	.29	5,080	956	.45	11,610	2,430	.16	76,100
16	694	.26	4,860	1,220	.86	28,300	2,670	.23	88,700
17	681	.23	4,240	1,180	.77	24,540	2,670	.11	80,000
18	783	.24	5,080	1,060	.66	18,900	2,370	.13	72,300
19	631	.24	4,080	1,180	.81	25,800	2,140	.00	57,800
20	442	.18	2,160	1,060	.66	18,900	1,920	.14	59,100
21	405	.16	1,760	902	.59	14,360	2,030	.79	43,300
22	452	.19	2,320	812	.54	11,830	1,820	.74	36,400
23	491	.11	1,458	741	.52	10,390	1,870	.92	46,400
24	458	.14	1,728	798	.48	10,340	2,200	.12	66,500
25	565	.19	2,890	1,000	1.42	38,300	1,920	.64	33,200
26	637	.25	4,290	1,820	2.20	108,100	1,480	.54	21,570
27	748	.25	5,050	1,670	2.29	103,200	1,440	.64	24,890
28	880	.32	7,610	1,020	1.39	38,300	1,260	.44	14,960
29	842	.27	6,130	805	1.23	26,700	1,180	.48	15,280
30	820	.24	5,320	-----	-----	-----	1,260	.51	17,360
31	762	.31	6,370	-----	-----	-----	1,530	.56	23,140
Monthly load (tons)		109,800	-----	-----	552,500	-----	-----	-----	2,758,000

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1936

Day	April			May			June		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	1,820	0.86	42,300	6,460	0.84	146,500	7,320	0.80	158,100
2	2,490	1.17	78,600	5,480	.64	94,700	7,140	.74	142,700
3	1,980	.86	46,000	5,320	.67	96,200	6,120	.61	100,800
4	1,670	.84	37,900	6,970	.80	150,600	5,000	.49	66,100
5	2,080	.90	50,500	8,590	.88	204,100	3,940	.45	47,900
6	1,770	.75	35,900	9,920	1.23	329,000	3,380	.29	26,500
7	1,530	.63	26,000	11,500	1.21	376,000	2,920	.22	17,330
8	1,530	.64	26,400	10,300	1.33	370,000	2,990	.35	28,200
9	1,580	.82	35,000	7,680	.98	203,200	3,380	.37	33,800
10	3,060	1.22	100,800	6,120	.65	107,400	3,940	.29	30,900
11	3,940	1.48	157,500	4,840	.47	61,400	4,230	.35	40,000
12	4,230	.99	113,100	4,230	.48	54,800	4,230	.35	40,000
13	5,160	1.26	175,600	4,080	.54	59,500	4,080	.32	35,300
14	6,800	1.74	319,000	5,160	.53	73,800	4,080	.34	37,400
15	7,680	1.62	336,000	6,120	.60	99,100	3,800	.29	29,800
16	7,680	1.50	311,000	6,120	.50	82,600	3,520	.24	22,820
17	7,140	1.41	272,000	6,460	.55	95,900	3,120	.24	20,220
18	7,680	1.27	263,000	6,800	.63	115,700	2,920	.25	19,710
19	8,040	1.32	287,000	7,500	.64	129,600	2,730	.24	17,680
20	7,680	1.18	244,700	7,140	.80	154,200	2,490	.23	15,490
21	7,500	1.18	239,000	7,500	.81	164,000	2,250	.21	12,740
22	7,500	.93	188,300	7,680	.88	182,500	1,980	.21	11,230
23	7,680	.96	199,000	7,320	.75	148,200	1,720	.16	7,420
24	8,220	1.14	253,000	6,800	.55	101,000	1,480	.17	6,800
25	8,040	1.03	223,600	6,970	.63	118,600	1,440	.16	6,210
26	7,140	.83	160,000	6,970	.64	120,400	1,400	.17	6,430
27	7,140	1.00	192,800	7,500	.84	170,100	1,350	.19	6,910
28	6,970	.96	180,700	7,140	.69	133,000	1,220	.14	4,620
29	6,800	.92	168,900	6,630	.57	102,000	1,180	.13	4,130
30	6,630	.80	143,200	6,120	.55	90,900	1,000	.19	5,130
31				6,630	.58	103,800			
Monthly load (tons)				4,907,000		4,439,000			1,002,000

1936

	July			August			September		
		Suspended sediment			Suspended sediment			Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	872	0.18	4,240	326	0.24	2,106	6,970	6.17	1,161,000
2	828	.12	2,670	850	4.96	13,800	6,800	5.72	1,050,000
3	902	.11	2,670	607	2.56	42,000	5,480	6.27	928,000
4	769	.08	1,674	915	2.25	55,600	5,160	5.31	740,000
5	631	.11	1,863	3,950	21.4	2,282,000	3,380	3.34	305,000
6	571	.13	1,998	7,140	8.81	1,698,000	3,520	1.95	185,300
7	508	.10	1,377	6,460	6.42	1,120,000	2,730	1.27	93,600
8	469	.06	756	6,800	4.48	823,000	2,250	.96	58,300
9	405	.09	972	4,530	3.26	399,000	1,980	.77	41,200
10	400	.07	756	3,250	1.79	157,100	1,720	.68	31,600
11	430	.13	1,512	2,550	1.14	78,500	1,720	.73	33,900
12	980	1.11	29,400	1,920	.83	43,000	1,620	.77	33,700
13	474	1.25	15,980	1,670	.74	33,400	1,820	.93	45,700
14	1,920	1.16	60,100	1,530	.62	25,600	1,720	1.54	71,500
15	1,350	.50	18,220	1,350	.71	25,900	1,440	.84	32,700
16	980	.27	7,155	1,220	.43	14,180	1,220	.57	18,700
17	918	.33	8,180	1,100	.45	13,360	1,100	.52	15,440
18	688	.23	4,270	1,400	2.01	76,000	1,020	.42	11,560
19	674	.26	4,720	1,140	1.65	50,800	1,010	.44	11,990
20	583	.39	6,130	888	1.51	36,200	1,260	.80	27,200
21	553	.23	3,430	2,380	3.75	241,000	1,400	1.19	45,000
22	707	.30	5,720	4,530	5.03	615,000	1,620	8.12	355,000
23	607	.60	9,830	3,180	5.69	489,000	2,670	3.73	269,000
24	502	.28	3,810	1,720	3.55	164,900	2,030	3.79	207,700
25	469	.21	2,650	1,180	2.54	80,900	1,670	2.79	125,800
26	480	.19	2,457	888	1.52	36,400	1,260	1.73	58,900
27	415	.28	3,130	727	.96	18,850	1,060	1.09	31,200
28	344	.21	1,940	625	.65	10,960	1,100	1.00	29,700
29	357	1.33	12,820	667	.54	9,720	1,400	1.58	59,700
30	395	.70	7,450	5,440	6.56	964,000	1,140	1.98	60,900
31	410	.63	6,970	7,500	7.50	1,519,000			
Monthly load (tons)				234,800		11,240,000			6,139,000

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1936

Day	October			November			December		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	1,060	1.38	39,500	2,490	4.21	283,000	902	0.39	9,500
2	996	1.01	27,200	2,430	2.95	194,000	872	.42	9,890
3	964	.82	21,300	1,980	2.23	119,000	842	.48	10,900
4	988	.76	20,300	2,030	2.04	112,000	842	.31	7,050
5	948	.66	16,900	1,400	1.19	45,000	805	.32	6,960
6	902	.56	13,600	1,140	1.03	31,700	714	.30	5,780
7	858	.51	11,800	1,060	.83	23,800	734	.43	8,520
8	1,020	.57	15,700	1,140	.87	26,800	734	.43	8,520
9	1,060	.65	18,600	1,180	.84	26,800	649	.35	6,130
10	980	.76	20,100	1,140	.76	23,400	613	.31	5,130
11	888	.54	12,900	1,060	.72	20,600	577	.19	2,960
12	842	.52	11,800	1,020	.64	17,600	577	.23	3,580
13	769	.52	10,800	1,060	.67	19,200	565	.22	3,360
14	727	.46	9,030	1,020	.57	15,700	491	.16	2,120
15	681	.38	6,990	1,020	.71	19,600	452	.21	2,560
16	714	.35	6,750	1,020	.60	16,500	631	.28	4,770
17	694	.35	6,560	1,060	.51	14,600	1,010	.61	16,600
18	649	.33	5,780	1,020	.53	14,600	902	.38	9,250
19	681	.38	6,990	1,060	.50	14,300	980	.40	10,600
20	1,000	.86	24,600	1,100	.63	18,700	902	.39	9,500
21	1,870	2.01	101,000	1,140	.68	20,900	828	.36	8,050
22	1,670	2.78	125,000	1,100	.57	16,900	798	.34	7,330
23	1,260	1.49	50,700	1,060	.55	15,700	842	.36	8,180
24	1,260	1.43	48,600	980	.74	19,600	798	.34	7,330
25	1,060	.82	23,500	972	.55	14,400	812	.35	7,670
26	940	.65	16,500	948	.44	11,300	940	.65	16,500
27	895	.55	13,300	932	.47	11,800	972	.56	14,700
28	872	.58	13,700	872	.55	12,900	940	.38	9,640
29	865	.67	15,600	888	.49	11,700	872	.40	9,420
30	1,180	1.15	36,600	910	.42	10,300	783	.41	8,670
31	4,120	9.00	1,000,000	-----	-----	-----	850	.40	9,180
Monthly load (tons)			1,752,000	1,202,000			250,400		

1937

	January			February			March		
	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day
1	688	0.26	4,830	1,000	0.06	1,620	1,060	1.30	37,200
2	625	.29	4,890	1,000	.07	1,890	1,000	.94	25,400
3	234	.19	1,200	1,000	.04	1,080	1,140	1.02	31,400
4	140	.15	567	1,500	.10	4,050	1,350	.59	58,000
5	400	.39	4,210	2,000	.07	3,780	1,480	1.75	69,900
6	400	.06	648	3,380	.11	10,000	1,260	1.86	63,300
7	400	.09	972	4,080	.11	12,100	1,180	1.47	46,800
8	400	.03	324	5,160	4.43	617,000	1,260	1.39	47,300
9	400	.03	324	2,310	2.31	144,000	1,720	1.79	83,100
10	400	.04	432	1,350	.94	34,300	2,490	2.45	165,000
11	490	.10	1,080	1,600	.42	18,100	3,060	2.37	196,000
12	400	.09	972	2,550	.50	34,400	3,520	3.20	304,000
13	400	.04	432	1,580	.42	17,900	3,800	3.82	392,000
14	400	.03	324	2,200	.46	27,300	4,080	3.21	354,000
15	400	.02	216	7,200	2.94	572,000	5,480	4.15	614,000
16	400	.05	540	5,130	1.69	234,000	4,530	3.11	380,000
17	400	.06	648	2,140	2.79	538,000	5,000	3.02	408,000
18	400	.09	972	3,940	3.47	369,000	6,120	3.69	610,000
19	400	.07	756	3,250	2.71	238,000	7,680	4.04	838,000
20	400	.05	540	2,430	2.13	140,000	4,840	2.83	370,000
21	400	.06	648	1,620	1.78	77,900	3,380	1.76	161,000
22	400	.08	864	1,140	1.46	44,900	2,670	1.44	104,000
23	400	.08	864	1,100	1.12	33,300	3,180	1.45	124,000
24	400	.04	432	1,220	1.02	33,600	4,840	2.82	369,000
25	400	.04	432	1,400	1.31	49,500	3,940	2.62	279,000
26	400	.04	432	1,580	3.21	137,000	2,920	2.09	165,000
27	400	.08	864	1,720	1.75	81,300	2,730	1.28	94,300
28	400	.09	972	1,260	1.77	60,200	2,490	1.02	68,600
29	400	.06	648	-----	-----	-----	3,120	1.13	95,200
30	400	.08	864	-----	-----	-----	3,060	1.25	103,000
31	400	.09	972	-----	-----	-----	2,920	2.01	158,000
Monthly load (tons)			32,870	3,536,000			6,814,000		

TABLE 18.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1937

Day	April			May			June		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	2,550	1.10	75,700	6,800	0.87	160,000	8,970	0.96	233,000
2	3,660	2.01	199,000	5,800	.72	113,000	7,860	.78	166,000
3	5,480	2.35	348,000	6,120	.69	114,000	6,800	.49	90,000
4	6,120	2.65	438,000	7,860	.89	189,000	7,140	.51	98,300
5	5,000	2.18	288,000	9,730	1.06	278,000	6,800	.52	95,500
6	4,080	1.46	161,000	11,500	1.28	397,000	6,460	.63	110,000
7	4,380	1.80	213,000	11,500	1.02	317,000	5,800	.63	98,700
8	4,230	1.71	195,000	10,300	.91	253,000	5,160	.50	69,700
9	4,530	1.71	209,000	10,500	.94	266,000	5,000	.56	75,600
10	5,800	1.55	243,000	12,500	.98	331,000	5,160	.45	62,700
11	7,320	2.32	450,000	13,100	1.08	382,000	5,160	.62	86,400
12	9,160	2.66	658,000	13,100	1.02	361,000	4,680	.54	68,200
13	10,900	2.49	733,000	12,900	1.08	376,000	5,480	.44	65,100
14	11,900	2.69	864,000	13,300	1.12	402,000	5,960	.37	59,500
15	12,700	2.31	792,000	14,300	.99	382,000	5,640	.40	60,900
16	14,300	2.49	961,000	14,900	.95	382,000	5,480	.39	57,700
17	16,500	2.43	1,080,000	14,900	.88	354,000	4,840	.35	45,700
18	15,300	2.35	971,000	14,900	.94	378,000	4,840	.40	52,300
19	12,900	1.94	676,000	14,900	.95	382,000	5,480	.42	62,100
20	11,700	1.90	600,000	14,100	.93	354,000	5,800	.38	59,500
21	11,500	1.75	543,000	12,100	.84	274,000	5,480	.36	53,300
22	11,300	1.72	525,000	11,700	.80	253,000	5,160	.34	47,400
23	12,500	1.94	655,000	11,300	.76	232,000	5,160	.61	85,000
24	12,500	2.00	675,000	11,700	.77	243,000	5,160	.45	62,700
25	9,920	1.44	386,000	11,300	.82	250,000	4,840	.41	53,600
26	8,220	1.10	244,000	9,730	.69	181,000	4,840	.33	43,100
27	8,780	1.07	254,000	8,220	.58	129,000	4,230	.38	43,400
28	10,500	1.27	360,000	6,800	.60	110,000	5,000	.67	90,400
29	8,590	1.49	346,000	6,970	.54	102,000	4,840	1.54	144,000
30	8,220	1.21	269,000	7,860	.82	174,000	3,940	.59	62,800
31				9,160	.79	195,000			
Monthly load (tons)		14,420,000			8,314,000				2,403,000

1937

	July			August			September		
	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day
1	3,660	0.43	42,500	2,250	4.07	247,000	1,480	5.14	205,000
2	3,660	.69	68,200	1,220	2.20	72,500	1,720	8.48	394,000
3	3,380	.49	44,700	1,260	1.57	53,400	1,220	14.2	468,000
4	3,380	.54	49,300	902	1.16	28,300	790	4.82	103,000
5	3,060	.44	36,400	812	.77	16,900	655	5.37	95,000
6	2,490	.33	22,200	1,100	1.97	44,600	486	2.84	37,300
7	2,490	1.60	108,000	1,400	2.40	90,700	783	2.17	45,900
8	2,310	.39	24,300	940	2.45	62,200	790	6.78	145,000
9	2,140	.60	34,700	762	1.60	32,900	535	3.33	48,100
10	3,660	5.92	585,000	714	1.15	22,200	688	2.66	49,400
11	4,530	8.40	1,030,000	571	.84	13,000	607	2.38	39,000
12	8,970	7.86	1,900,000	480	.56	7,260	390	2.46	25,900
13	6,460	7.64	1,330,000	410	.46	5,090	312	1.88	15,800
14	3,520	3.18	302,000	348	.37	3,480	308	1.32	11,000
15	2,860	1.67	129,000	303	.31	2,540	285	.90	6,930
16	2,430	.86	56,400	269	.40	2,910	249	.67	4,500
17	2,080	.78	43,800	196	.32	1,690	245	.64	4,230
18	1,920	.64	33,200	217	1.54	9,020	206	.46	2,560
19	1,670	.66	29,800	281	.77	5,840	189	.41	2,090
20	1,350	.47	17,100	496	.97	13,000	157	.40	1,700
21	1,140	.39	12,000	425	.77	8,840	154	.35	1,460
22	940	.33	8,380	334	.78	7,030	157	.39	1,650
23	828	.32	7,150	298	.69	5,550	189	.34	1,740
24	688	.30	5,570	265	.43	3,080	178	.32	1,540
25	535	.21	3,030	220	.42	2,490	140	.40	1,510
26	595	.24	3,860	178	.32	1,540	138	.39	1,450
27	790	.37	7,890	160	.28	1,210	169	.40	1,830
28	1,830	2.42	120,000	130	.33	1,160	206	.47	2,610
29	2,480	4.44	297,000	210	3.22	18,300	245	.84	5,560
30	3,250	7.90	693,000	776	4.10	85,900	10,200	13.3	2,840,000
31	3,380	8.93	815,000	1,440	3.88	151,000			4,664,000
Monthly load (tons)		7,859,000			1,021,000				

TABLE 18.—*Mean daily discharge, mean daily concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1937

Day	October			November			December		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	14,000	14.20	5,370,000	700	0.35	6,620	460	0.18	2,240
2	4,560	7.95	979,000	707	.33	6,300	450	.16	1,940
3	2,260	4.68	286,000	674	.32	5,820	465	.17	2,130
4	1,350	3.09	113,000	655	.27	4,770	508	.26	3,570
5	1,040	2.06	57,800	649	.25	4,380	565	.35	5,340
6	910	1.21	29,700	649	.25	4,380	625	.39	6,580
7	850	.91	20,900	637	.24	4,130	577	.26	4,050
8	805	.72	15,600	649	.28	4,910	637	.32	5,500
9	734	.55	10,900	649	.32	5,610	607	.22	3,610
10	727	.52	10,200	655	.33	5,840	619	.27	4,510
11	674	.38	6,920	776	.52	10,900	619	.29	4,850
12	637	.40	6,880	700	.37	6,990	637	.19	3,270
13	589	.28	4,450	649	.30	5,260	681	.31	5,700
14	595	.27	4,340	668	.31	5,590	707	.40	7,640
15	631	.27	4,600	649	.27	4,730	769	.42	8,720
16	920	.39	9,780	619	.28	4,680	720	.31	6,030
17	1,500	1.56	63,200	589	.25	3,980	714	.33	6,360
18	1,390	2.00	75,100	601	.22	3,570	694	.31	5,810
19	1,350	2.28	83,100	571	.22	3,390	643	.27	4,690
20	1,030	1.62	45,100	565	.23	3,510	613	.30	4,970
21	880	1.28	30,400	589	.26	4,130	565	.29	4,420
22	850	.93	21,300	559	.23	3,470	595	.38	6,100
23	798	.74	15,900	559	.27	4,080	513	.19	2,630
24	776	.55	11,500	530	.21	3,010	465	.17	2,130
25	762	.48	9,880	530	.25	3,580	475	.14	1,800
26	741	.44	8,800	547	.21	3,100	553	.20	2,990
27	755	.36	7,340	518	.21	2,940	583	.21	3,310
28	762	.36	7,410	530	.20	2,860	589	.17	2,700
29	762	.36	7,410	524	.25	3,540	607	.28	4,590
30	714	.33	6,360	502	.19	2,580	649	.23	4,030
31	694	.32	6,000				607	.26	4,260
Monthly load (tons)...			7,338,000			138,600			136,500

1938

	January			February			March		
	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day
1	571	0.17	2,620	643	0.46	7,990	3,250	4.43	389,000
2	530	.17	2,430	835	.40	9,020	5,340	5.64	813,000
3	595	.17	2,730	720	.65	12,600	6,010	5.18	841,000
4	783	.62	13,100	681	.48	8,830	9,020	6.67	1,620,000
5	700	.30	5,670	681	.33	6,070	8,620	5.39	1,250,000
6	700	.40	7,560	700	.35	6,620	4,270	2.89	333,000
7	688	.29	5,390	625	.31	5,230	2,480	1.78	119,000
8	625	.29	4,890	565	.18	2,750	1,740	1.22	57,300
9	583	.20	3,150	502	.18	2,440	2,200	1.95	116,000
10	460	.18	2,240	530	.23	3,290	1,640	1.01	44,700
11	440	.10	1,190	787	.20	4,250	1,500	.85	34,400
12	450	.20	2,430	1,500	1.65	66,800	1,460	.82	32,300
13	475	.28	3,590	1,890	2.51	128,000	1,640	1.14	50,500
14	513	.27	3,740	1,740	1.65	77,500	2,370	1.43	91,500
15	530	.22	3,150	1,790	2.27	110,000	3,080	1.80	150,000
16	559	.28	4,230	1,170	1.66	52,400	2,540	1.75	120,000
17	613	.29	4,800	948	1.06	27,100	1,640	1.18	52,300
18	688	.29	5,390	835	.81	18,300	1,550	1.20	50,200
19	835	.58	13,100	755	.73	14,900	1,740	1.20	56,400
20	850	.48	11,000	688	.53	9,850	1,690	1.02	46,500
21	762	.43	8,850	631	.44	7,500	1,600	1.12	48,400
22	714	.29	5,590	637	.55	9,460	1,890	1.07	54,600
23	649	.27	4,730	681	.48	8,830	2,540	1.27	87,100
24	553	.19	2,840	681	.38	6,990	1,990	1.22	65,600
25	518	.17	2,380	631	.35	5,960	1,740	1.00	47,000
26	425	.15	1,720	607	.33	5,410	2,590	1.27	88,800
27	323	.11	959	607	.38	6,230	3,610	1.87	182,000
28	384	.17	1,760	727	.32	6,280	3,740	1.71	173,000
29	588	.48	7,560				3,740	1.81	132,000
30	607	.39	6,390				3,870	1.42	148,000
31	649	.48	8,410				3,370	1.26	115,000
Monthly load (tons)...			153,600			630,600			7,409,000

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1938

Day	April			May			June		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	2,810	1.23	93,000	11,600	1.31	410,000	15,800	1.10	469,000
2	2,200	1.23	73,100	12,900	1.26	439,000	15,400	.99	370,000
3	1,990	.83	44,600	10,300	1.34	373,000	15,100	.92	375,000
4	1,790	.88	42,500	7,480	1.03	212,000	14,000	.69	261,000
5	2,040	.86	47,400	6,370	1.12	193,000	15,400	.77	320,000
6	3,250	1.27	111,000	5,330	.65	93,500	15,800	.89	380,000
7	3,490	1.51	142,000	4,710	.66	83,900	14,700	.85	337,000
8	3,310	1.39	124,000	4,410	.54	64,300	13,300	.81	291,000
9	2,860	.93	71,800	4,060	.55	60,300	11,100	.74	222,000
10	2,540	.79	54,200	3,680	.51	50,700	9,630	.66	172,000
11	2,540	.78	53,500	3,550	.55	52,700	9,020	.62	151,000
12	3,550	.98	93,900	3,250	.45	39,500	9,020	.63	153,000
13	4,710	1.24	158,000	3,250	.50	43,900	8,620	.57	133,000
14	5,840	1.66	262,000	3,680	.69	68,600	9,840	.68	181,000
15	6,190	1.69	282,000	4,860	.71	93,200	12,900	.70	244,000
16	5,670	1.54	236,000	8,620	.95	221,000	10,000	.75	202,000
17	4,270	.91	105,000	11,800	1.06	338,000	9,220	.61	152,000
18	4,410	.91	108,000	11,600	1.10	345,000	9,220	.59	147,000
19	5,840	1.70	268,000	9,840	1.04	276,000	9,420	.68	173,000
20	8,820	2.20	524,000	8,240	.79	176,000	9,420	.73	186,000
21	10,500	1.98	561,000	7,290	.75	148,000	8,430	.68	155,000
22	10,500	1.80	510,000	6,190	.73	122,000	9,630	.87	226,000
23	11,800	1.83	583,000	6,010	.71	115,000	13,300	.87	312,000
24	12,200	1.60	527,000	6,370	.76	131,000	14,900	1.21	487,000
25	12,900	1.67	582,000	6,190	.70	117,000	12,200	1.22	402,000
26	13,100	1.61	569,000	7,480	.78	158,000	9,840	.85	226,000
27	13,300	1.51	542,000	9,020	.84	205,000	9,220	.66	164,000
28	10,700	1.49	430,000	11,100	.95	285,000	10,000	.74	200,000
29	8,820	1.09	260,000	13,100	.88	311,000	10,500	1.19	337,000
30	10,500	1.39	394,000	15,600	1.00	421,000	9,420	.69	175,000
31				17,000	1.13	519,000			
Monthly load (tons)		7,852,000				6,166,000			7,603,000

1938

	July			August			September		
	1	16,500	1.15	512,000	1,180	0.22	7,010	1,250	1.94
2	12,500	.91	307,000	1,020	.18	4,960	3,080	4.46	371,000
3	9,020	.68	166,000	895	.15	3,620	7,480	8.69	1,760,000
4	7,670	.64	133,000	820	.15	3,320	8,820	11.0	2,620,000
5	6,910	.45	84,000	734	.11	2,180	7,650	7.89	1,630,000
6	6,010	.47	76,300	734	.13	2,580	3,870	4.27	446,000
7	5,170	.27	37,700	681	.14	2,570	3,490	2.71	255,000
8	4,560	.35	43,100	981	.15	3,970	3,870	2.97	310,000
9	4,000	.28	30,200	1,190	2.03	65,200	4,630	5.48	685,000
10	3,490	.27	25,400	755	1.07	21,800	2,480	3.98	267,000
11	3,140	.27	22,900	1,360	1.13	41,500	3,280	2.13	189,000
12	2,860	.23	17,800	700	2.93	55,400	4,270	4.08	470,000
13	2,700	.25	18,200	895	12.1	292,000	6,370	4.60	791,000
14	2,420	.21	13,700	1,740	2.22	104,000	6,010	2.49	404,000
15	2,320	.28	17,500	1,490	4.08	164,000	4,860	1.42	186,000
16	2,540	.25	17,100	2,590	6.01	420,000	3,870	.99	103,000
17	2,760	.36	26,800	1,420	3.96	152,000	4,630	2.13	266,000
18	2,260	1.05	64,100	948	2.29	58,600	3,080	2.00	166,000
19	2,100	.51	28,900	700	1.30	24,600	2,700	1.74	127,000
20	1,990	.35	18,800	613	.82	13,600	2,320	1.10	68,900
21	1,990	.34	18,300	496	.57	7,630	2,040	.77	42,400
22	2,200	.47	27,900	445	.46	5,530	1,840	.61	30,300
23	1,690	1.44	65,700	416	.31	3,480	1,600	.48	20,700
24	1,640	.38	16,800	389	.28	2,940	1,420	.60	23,000
25	1,460	.27	10,600	346	.20	1,870	1,260	.36	12,200
26	1,360	.27	9,910	288	.17	1,320	1,160	.33	10,300
27	1,200	.22	7,130	232	.16	1,000	1,110	.28	8,390
28	1,140	.22	6,770	220	.12	713	1,040	.24	6,740
29	1,120	.34	10,300	204	.09	496	964	.25	6,510
30	980	.36	9,530	210	.09	510	872	.23	5,420
31	1,240	.29	9,710	198	.08	428			
Monthly load (tons)		1,853,000				1,469,000			11,350,000

## QUANTITIES OF SUSPENDED SEDIMENT

135

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1938

Day	October			November			December		
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	888	0.25	5,990	1,250	0.32	10,800	790	0.22	4,690
2	858	.22	5,100	1,330	.32	11,500	918	.44	10,900
3	828	.20	4,470	1,420	.36	13,800	880	.38	9,030
4	790	.20	4,270	1,370	.34	12,600	835	.30	6,760
5	727	.21	4,120	1,340	.34	12,300	850	.30	6,880
6	755	.26	5,300	1,250	.29	9,790	835	.22	4,960
7	783	.22	4,650	1,170	.36	11,400	783	.24	5,070
8	925	.21	5,240	1,180	.28	8,920	776	.23	4,820
9	4,410	3.19	380,000	1,080	.28	8,160	776	.24	5,080
10	4,270	2.39	276,000	996	.21	5,650	776	.29	6,080
11	2,860	1.42	110,000	940	.21	5,330	741	.28	5,600
12	2,420	.88	57,500	1,030	.24	7,400	734	.35	6,940
13	2,150	.71	41,200	1,040	.30	8,420	727	.30	5,890
14	1,990	.61	32,800	1,000	.28	7,560	714	.28	5,400
15	1,890	.48	24,500	980	.26	6,880	720	.29	5,640
16	1,840	.46	22,800	902	.20	2,930	727	.35	6,870
17	1,990	.59	31,700	895	.24	5,800	748	.35	7,070
18	2,040	.50	27,500	925	.22	5,490	762	.33	6,790
19	2,040	.50	27,500	918	.25	6,200	828	.35	7,820
20	2,260	.61	37,200	910	.24	5,900	812	.28	6,140
21	2,100	.53	30,100	880	.24	5,700	1,050	.74	21,000
22	1,940	.48	25,100	888	.22	5,280	910	.32	7,860
23	1,790	.47	20,700	895	.30	7,250	888	.32	7,670
24	1,690	.44	20,100	835	.24	5,410	865	.33	7,710
25	1,600	.39	16,800	649	.19	3,330	783	.26	5,500
26	1,550	.39	16,300	595	.13	2,090	649	.22	3,860
27	1,460	.34	13,400	577	.17	2,650	565	.22	3,360
28	1,420	.36	13,800	607	.21	3,440	571	.26	4,010
29	1,320	.33	11,800	593	.21	3,360	595	.19	3,050
30	1,260	.30	10,200	589	.17	2,700	607	.21	3,440
31	1,270	.30	10,300	-----	-----	-----	649	.22	3,860
Monthly load (tons)			1,296,000	208,000			199,700		

1939

	January			February			March		
	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day	Mean discharge (second-feet)	Mean percent	Tons per day
1	619	0.20	3,340	643	0.18	3,120	637	0.28	4,820
2	619	.20	3,340	571	.25	3,850	649	.18	3,150
3	637	.31	5,330	524	.19	2,690	668	.31	5,590
4	720	.36	7,000	235	.10	634	674	.27	4,910
5	748	.27	5,450	259	.11	770	688	.31	5,760
6	727	.24	4,710	435	.19	2,230	707	.31	5,920
7	700	.20	3,780	421	.13	1,480	637	.29	4,990
8	727	.37	7,260	583	.16	2,520	625	.20	3,380
9	769	.28	5,810	700	.43	8,130	727	.53	10,400
10	790	.29	6,190	619	.21	3,510	1,010	.54	14,700
11	769	.21	4,360	407	.16	1,760	1,600	.93	40,200
12	707	.24	4,580	565	.17	2,590	1,600	1.06	45,800
13	714	.30	5,780	518	.13	1,820	1,890	1.42	72,500
14	662	.25	4,470	631	.27	4,600	1,840	1.50	74,500
15	607	.25	4,100	655	.18	3,180	1,990	1.74	93,500
16	625	.38	6,410	755	.38	7,750	2,200	2.03	121,000
17	571	.27	4,160	850	.46	10,600	2,150	2.23	130,000
18	513	.13	1,800	741	.27	5,400	2,100	2.08	118,000
19	631	.21	3,580	828	.22	4,920	2,200	1.88	112,000
20	571	.24	3,700	776	.25	5,240	2,320	1.67	105,000
21	674	.30	5,460	714	.30	5,780	2,590	2.19	153,000
22	798	.43	9,260	707	.33	6,300	3,140	1.86	158,000
23	996	.54	14,500	674	.22	4,000	4,130	1.81	202,000
24	858	.29	6,720	643	.21	3,640	5,670	2.25	344,000
25	805	.30	6,520	637	.25	4,300	5,670	2.45	375,000
26	700	.28	5,290	694	.31	5,810	4,710	1.61	205,000
27	674	.23	4,180	714	.21	4,050	4,130	1.07	119,000
28	668	.25	4,510	727	.27	5,300	4,060	1.04	114,000
29	734	.50	9,910	-----	-----	4,270	1.06	122,000	
30	700	.40	7,560	-----	-----	3,490	.75	70,700	
31	662	.28	5,010	-----	-----	2,930	.66	52,200	
Monthly load (tons)			174,100	116,000			2,891,000		

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1939

Day	April			May			June		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	2,700	0.59	43,000	5,010	0.61	82,500	5,010	0.61	82,500
2	2,540	.67	45,900	5,010	.81	110,000	4,860	.61	80,000
3	2,860	.75	57,900	5,010	.82	111,000	4,710	.62	78,800
4	3,490	.75	70,700	5,840	.92	145,000	4,130	.51	56,900
5	4,000	.82	88,600	5,010	.76	103,000	4,410	.59	70,300
6	5,170	2.31	322,000	5,010	.79	107,000	5,010	.61	82,500
7	4,270	1.59	183,000	6,010	.94	152,000	5,500	.68	101,000
8	3,940	1.09	116,000	6,370	1.01	174,000	4,560	.55	67,700
9	3,370	.88	80,100	5,010	.70	94,700	3,800	.38	39,000
10	3,370	.75	68,200	4,860	.67	87,900	3,490	.41	38,600
11	3,740	.97	98,000	5,500	.68	101,000	3,430	.29	26,900
12	3,490	1.10	104,000	6,550	1.00	177,000	3,370	.36	32,800
13	3,080	.85	70,700	6,730	.84	153,000	3,200	.34	29,400
14	2,920	.86	67,800	6,010	.75	122,000	2,860	.29	22,400
15	2,980	.75	60,300	5,330	.67	96,400	2,700	.31	22,600
16	2,920	.88	69,400	4,710	.59	75,000	2,700	.33	24,100
17	2,760	.85	63,300	4,560	.61	75,100	2,480	.30	20,100
18	2,540	.70	48,000	4,270	.71	81,900	2,200	.33	19,600
19	2,260	.33	20,100	3,610	.61	59,500	2,040	.28	15,400
20	1,990	.39	21,000	3,430	.77	71,300	1,790	.19	9,180
21	1,990	.36	19,300	4,410	.72	85,700	1,550	.20	8,370
22	2,260	.38	23,200	6,010	.97	157,000	1,260	.19	6,460
23	2,810	.50	37,900	6,190	.87	145,000	1,050	.15	4,250
24	3,610	.66	64,300	6,190	.79	132,000	812	.12	2,630
25	4,270	.70	80,700	6,010	.82	133,000	707	.11	2,100
26	3,740	.52	52,500	4,860	.50	65,600	694	.13	2,435
27	3,250	.57	50,000	4,000	.44	47,500	637	.07	1,204
28	3,030	.54	44,200	3,550	.48	46,000	655	.07	1,237
29	3,080	.64	53,200	3,870	.83	86,700	625	.08	1,350
30	3,800	.78	80,000	4,410	.74	88,100	589	.08	1,272
31				4,710	.69	87,700			
Monthly load (tons)		2,203,000			3,253,000				951,000

1939

	July			August			September		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	583	0.12	1,890	266	2.10	15,100	281	2.57	19,500
2	565	.07	1,070	204	3.23	17,800	342	3.39	31,300
3	585	.06	948	292	3.78	29,800	249	7.96	53,500
4	553	.07	1,040	223	.89	5,360	189	1.60	8,160
5	535	.08	1,160	159	2.64	11,300	259	2.48	17,300
6	518	.11	1,540	134	.45	1,630	715	6.75	130,000
7	421	.08	910	109	.35	1,030	435	1.57	18,400
8	412	.08	891	84	.21	475	465	4.22	53,000
9	376	.06	610	99	.21	562	812	3.86	84,600
10	371	.05	502	97	.30	786	1,090	2.43	71,500
11	288	.04	310	68	.12	221	4,060	5.07	556,000
12	259	.04	281	68	.06	111	11,000	20.9	6,210,000
13	281	.03	227	69	.04	76	7,100	5.57	1,068,000
14	252	.05	340	69	.09	167	3,800	3.18	326,000
15	207	.01	57	46	.07	86	3,430	2.65	245,000
16	168	.01	46	34	.04	38	3,430	1.27	118,000
17	137	.02	73	24	.02	13	3,310	1.41	126,000
18	115	.02	62	14	.01	4	2,420	1.46	95,400
19	127	.02	68	11	.00	0	1,990	.80	43,000
20	124	.01	32	7	.01	1	1,840	.68	33,800
21	86	.01	23	3	.01	0	1,690	.81	37,000
22	95	.01	26	1	.01	0	1,330	.87	31,200
23	76	.01	20	1	.00	0	1,240	.52	17,400
24	56	.01	15	0	.00	0	1,040	.89	25,000
25	38	.01	10	0	.00	0	980	.89	23,600
26	25	.01	7	0	.00	0	1,510	2.76	112,000
27	13	.01	4	0	.00	0	2,800	2.69	203,000
28	46	.01	12	1	.76	21	1,140	1.87	57,600
29	631	.99	16,900	0	.00	0	1,080	1.35	39,400
30	246	3.50	23,200	140	8.00	30,200	1,180	.83	26,400
31	144	3.51	13,600	270	5.83	42,500			
Monthly load (tons)		65,870			157,300				9,881,000

## QUANTITIES OF SUSPENDED SEDIMENT

137

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1939

Day	October		November		December				
	Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment		Mean discharge (second-feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	974	.76	20,000	578	.36	5,620	582	.31	4,870
2	878	.49	11,600	568	.32	4,910	587	.22	3,490
3	854	.36	8,300	612	.28	4,630	534	.33	4,760
4	776	.30	6,290	602	.25	4,060	544	.26	3,820
5	724	.31	6,060	578	.25	3,900	558	.25	3,770
6	681	.20	3,680	558	.24	3,620	516	.23	3,200
7	628	.20	3,390	568	.25	3,830	511	.20	2,760
8	602	.14	2,280	582	.25	3,930	511	.30	4,140
9	691	.26	4,850	649	.31	5,430	563	.26	3,950
10	643	.43	7,470	800	.45	9,720	549	.23	3,410
11	607	.48	7,870	854	.36	8,300	539	.21	3,060
12	648	.51	8,850	794	.39	8,360	516	.26	3,620
13	684	.46	8,120	713	.49	9,430	488	.24	3,160
14	628	1.02	17,300	708	.34	6,500	506	.21	2,870
15	582	.46	7,230	638	.29	5,000	506	.18	2,460
16	563	.48	7,300	654	.34	5,860	488	.19	2,480
17	539	.27	3,930	638	.33	5,680	475	.15	1,920
18	475	.25	3,210	628	.32	5,430	441	.16	1,900
19	475	.24	3,080	582	.40	6,290	432	.17	1,980
20	468	.24	2,970	597	.31	5,000	449	.24	2,910
21	441	.15	1,790	587	.24	3,800	480	.22	2,850
22	453	.15	1,840	573	.23	3,560	462	.20	2,500
23	445	.22	2,640	568	.33	5,060	441	.20	2,380
24	424	.14	1,600	558	.32	4,820	357	.17	1,640
25	408	.16	1,760	553	.25	3,730	470	.18	2,280
26	420	.15	1,700	520	.22	3,090	520	.20	2,810
27	404	.27	2,950	553	.33	4,930	506	.15	2,050
28	484	.20	2,610	549	.25	3,710	506	.07	956
29	1,556	.54	22,600	530	.25	3,580	294	.05	397
30	776	.40	8,380	563	.29	4,410	166	.03	134
31	659	.34	6,050	-----	-----	-----	259	.16	1,120
Monthly load (tons)		197,700	-----	156,200	-----	-----	-----	83,650	

1940

	January		February		March	
	Mean discharge (second-feet)	Suspended sediment	Mean discharge (second-feet)	Suspended sediment	Mean discharge (second-feet)	Suspended sediment
1	266	0.09	646	670	0.36	4,700
2	332	.20	1,790	1,130	1.27	38,700
3	441	.63	7,500	1,690	1.58	72,100
4	794	.65	13,900	1,960	1.28	67,700
5	981	.43	11,400	1,480	1.87	74,700
6	830	.23	5,150	994	1.12	30,000
7	776	.44	9,220	860	1.04	24,200
8	708	.47	8,980	747	.84	16,900
9	633	.24	4,100	643	.70	12,200
10	654	.24	4,240	633	.86	14,700
11	794	.54	11,600	602	.53	8,610
12	890	.71	17,100	558	.55	8,290
13	1,620	1.41	61,700	539	.55	8,000
14	1,120	.85	25,700	558	.44	6,630
15	782	.51	10,800	558	.42	6,330
16	530	.35	5,010	530	.35	5,000
17	453	.29	3,550	544	.34	4,990
18	462	.36	4,490	582	.43	6,760
19	432	.23	2,680	582	.39	6,130
20	354	.16	1,530	502	.23	3,120
21	400	.30	3,240	525	.24	3,400
22	502	.44	5,960	558	.36	5,420
23	428	.23	2,660	534	.22	3,170
24	278	.19	1,430	582	.38	5,970
25	420	.27	3,060	649	.32	5,610
26	563	.52	7,900	788	.51	10,800
27	670	.49	8,860	1,060	1.01	28,900
28	764	.38	7,840	1,880	7.28	370,000
29	649	.37	6,480	2,220	4.24	254,000
30	602	.33	5,360	-----	-----	1,990
31	649	.35	6,130	-----	-----	1,620
Monthly load (tons)		270,000	-----	1,107,000	-----	1,035,000

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah. Oct. 1, 1929, to Sept. 30, 1941—Continued*

1940

Day	April			May			June		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	1,420	0.68	26,100	2,510	0.65	44,100	4,990	0.46	62,000
2	1,330	.44	15,800	2,320	.52	32,600	5,250	.36	51,000
3	1,500	.52	21,100	1,910	.51	26,300	5,180	.24	33,600
4	1,460	.51	20,100	2,030	.37	20,300	4,930	.57	75,900
5	1,410	.48	18,300	2,520	.44	29,900	4,100	.62	68,600
6	1,230	.40	13,300	3,990	.73	78,600	3,660	.44	43,500
7	1,200	.39	12,600	4,930	.96	128,000	3,270	.54	47,700
8	1,260	.45	15,300	4,930	.93	124,000	2,860	1.36	105,000
9	1,200	.34	11,000	5,270	.82	117,000	2,560	.34	23,500
10	1,170	.42	13,300	5,010	.88	119,000	2,270	.45	27,600
11	1,140	.33	10,200	5,100	.82	112,900	2,060	.20	11,100
12	1,090	.34	10,000	5,690	.78	119,800	1,880	.21	10,700
13	1,100	.33	9,800	5,950	1.15	185,000	1,650	.35	15,600
14	1,120	.45	13,600	6,030	.79	128,600	1,600	.19	8,210
15	1,200	.43	13,900	5,990	.94	152,000	1,530	.22	9,090
16	1,720	.66	30,700	6,620	.86	153,000	1,490	.32	12,900
17	2,520	.93	63,300	6,620	1.14	204,000	1,550	.22	9,210
18	2,510	.72	48,800	6,440	.64	111,000	1,460	.20	7,880
19	2,220	.65	39,000	6,800	.67	123,000	1,370	.24	8,880
20	1,900	.57	29,200	6,530	.82	145,000	1,300	.22	7,720
21	1,730	.49	22,900	4,960	.69	92,400	1,100	.13	3,860
22	2,340	.77	48,600	4,640	.64	80,200	1,040	.09	2,530
23	3,200	.79	68,300	4,020	.53	57,500	955	.15	3,870
24	3,410	.79	72,700	3,870	.69	72,100	916	.13	3,220
25	4,450	.93	112,000	3,720	.75	75,300	910	.15	3,690
26	4,230	.88	100,000	3,940	.56	59,600	848	.11	2,520
27	3,710	.78	78,100	4,300	.57	66,200	854	.16	3,690
28	3,570	.75	72,300	4,380	.49	57,900	697	.15	2,820
29	3,780	.71	72,500	4,780	.66	85,200	724	.15	2,930
30	3,030	.66	54,000	4,940	.61	81,400	623	.13	2,190
31				4,850	.70	91,700			
Monthly load (tons)				1,137,000		2,974,000			670,900

1940

	July			August			September		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	913	0.09	2,200	384	4.44	46,000	506	1.18	16,100
2	549	.30	4,450	224	3.76	22,700	462	1.02	12,700
3	719	.44	8,540	148	3.20	12,800	388	.63	6,600
4	854	.33	7,610	112	1.63	4,930	380	.79	8,110
5	659	.22	3,910	93	.65	1,630	318	.80	6,870
6	558	.21	3,160	74	.35	699	361	.82	7,990
7	416	.31	3,480	52	.20	281	269	.61	4,430
8	388	.12	1,260	47	.14	1,780	199	1.86	9,990
9	328	.12	1,060	120	2.09	6,770	202	1.43	7,800
10	301	.12	975	339	3.72	34,000	181	.54	2,640
11	281	.06	455	154	4.12	17,100	157	.33	1,400
12	235	.07	444	124	3.92	13,100	139	.33	1,240
13	196	.05	265	114	3.26	10,000	678	7.13	130,000
14	150	.04	162	96	2.12	5,500	281	5.47	41,500
15	118	.03	96	83	1.07	2,400	275	10.1	75,000
16	118	2.88	9,180	62	.50	837	194	4.02	21,100
17	280	3.36	25,400	59	.83	1,320	311	3.38	28,400
18	218	9.45	55,600	54	.53	773	3,000	7.02	569,000
19	77	5.42	11,300	41	.30	332	3,330	11.0	989,000
20	46	3.34	4,150	31	2.13	1,780	5,450	7.98	1,174,000
21	74	1.35	2,700	137	3.23	12,000	2,930	5.42	429,000
22	253	1.75	12,000	154	3.36	14,000	4,880	7.30	962,000
23	150	1.54	6,240	328	5.60	49,600	4,100	6.14	680,000
24	100	.69	1,860	1,650	10.8	481,000	2,770	6.52	488,000
25	78	.17	358	4,500	16.3	1,980,000	2,220	2.41	144,000
26	51	.11	151	5,300	8.97	1,280,000	2,090	1.60	90,300
27	552	.08	1,190	2,930	5.68	449,000	1,710	1.37	63,300
28	1,430	5.93	229,000	974	5.36	141,000	1,710	.99	45,700
29	3,140	15.3	1,297,000	994	4.11	110,000	6,170	9.92	1,653,000
30	2,220	7.23	433,000	697	2.68	50,400	12,130	12.1	3,960,000
31	890	5.74	138,000	602	2.28	37,100			
Monthly load (tons)				2,265,000		4,789,000			11,630,000

QUANTITIES OF SUSPENDED SEDIMENT

139

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1940

Day	October			November			December		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	9,820	12.5	3,320,000	1,060	0.77	22,800	878	0.56	13,300
2	4,100	4.13	457,000	1,000	.62	16,700	854	.53	12,200
3	3,100	4.27	357,000	981	.73	19,300	848	.57	13,000
4	2,340	1.93	122,000	988	.58	15,500	878	.79	18,700
5	5,590	7.94	1,200,000	903	.63	15,400	866	.44	10,300
6	6,240	4.01	676,000	884	.53	12,600	872	.46	10,800
7	3,310	2.85	255,000	896	.31	7,500	848	.60	13,700
8	3,990	2.23	240,000	884	.40	9,550	848	.43	9,850
9	3,000	1.50	122,000	812	.44	9,650	884	.51	12,200
10	2,650	1.28	91,600	788	.42	8,940	878	.60	14,200
11	2,290	1.06	65,500	836	.50	11,300	1,010	.58	15,800
12	2,140	.77	44,500	916	.46	11,400	1,150	.61	18,900
13	1,900	.78	40,000	903	.50	12,200	1,950	1.21	63,700
14	1,750	.73	34,500	903	.66	16,100	1,760	1.42	67,500
15	1,590	.64	27,500	794	.33	7,070	1,370	1.52	56,200
16	1,530	.61	25,200	747	.30	6,050	974	1.13	29,700
17	1,440	.43	16,700	742	.45	9,020	878	.61	14,500
18	1,370	.60	22,200	794	.39	8,360	759	.50	10,200
19	1,270	.63	22,400	2,780	3.86	290,000	1,430	3.75	145,000
20	1,250	.42	14,700	3,260	2.50	220,000	1,450	2.47	96,700
21	1,210	.54	18,300	1,930	1.38	71,900	1,290	1.50	52,200
22	1,110	.50	15,500	1,560	1.00	42,100	1,250	1.07	36,100
23	1,030	.53	14,700	1,300	1.45	50,900	1,030	.89	24,800
24	903	.40	9,750	1,130	1.17	35,700	948	.57	14,600
25	818	.43	9,500	1,050	.96	27,200	3,110	2.49	209,000
26	878	.40	9,480	994	.84	22,500	2,960	4.55	364,000
27	1,900	1.80	92,300	974	.90	23,700	2,070	2.77	155,000
28	1,410	1.37	52,200	936	.55	13,900	1,420	2.17	83,200
29	1,080	.82	23,900	910	.66	16,200	1,170	1.68	53,100
30	1,370	.95	35,100	903	.56	13,600	1,760	2.33	111,000
31	1,150	.69	21,400	-----	-----	-----	2,620	2.14	151,000
Monthly load (tons)		7,456,000	-----	-----	1,047,000	-----	-----	-----	1,900,000

1941

	January			February			March		
	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day	Mean discharge (second- feet)	Mean percent	Tons per day
1	3,200	3.43	296,000	1,340	0.89	32,200	2,080	1.85	104,000
2	2,590	3.28	229,000	1,220	.70	23,100	1,890	1.16	59,200
3	1,850	2.48	124,000	1,280	.93	32,100	2,220	1.38	82,700
4	1,320	1.89	67,400	1,160	.88	27,600	3,400	2.14	196,000
5	1,100	1.11	33,000	955	.80	20,600	2,440	1.54	102,000
6	910	.90	22,100	903	.75	18,300	2,090	1.38	77,900
7	836	.79	17,800	1,120	.63	19,000	2,330	1.96	123,000
8	818	.71	15,700	1,710	1.47	67,900	2,320	1.45	90,800
9	788	.92	19,600	1,520	.93	38,200	1,960	1.25	66,200
10	788	.89	18,900	1,330	.80	28,700	1,760	1.13	53,700
11	830	.85	19,100	1,200	.97	31,400	1,660	.87	39,000
12	981	.75	19,900	1,460	1.05	41,400	1,520	.74	30,400
13	1,360	1.70	62,400	1,680	1.23	55,800	1,520	.83	34,100
14	1,420	1.81	69,400	1,660	1.05	47,100	1,670	.82	37,000
15	1,920	1.51	78,300	1,580	1.37	58,400	4,700	6.09	773,000
16	1,450	1.93	75,600	1,550	1.61	67,400	4,290	5.62	651,000
17	1,150	1.53	47,500	1,710	1.57	72,500	4,460	3.20	385,000
18	974	1.11	29,200	1,920	1.89	98,000	4,560	2.99	368,000
19	836	1.03	23,200	2,030	2.53	200,000	4,200	3.25	369,000
20	776	.90	18,900	2,990	2.44	197,000	4,400	3.19	379,000
21	747	.66	13,300	4,290	3.38	392,000	4,820	3.16	411,000
22	842	.58	13,200	4,670	3.24	409,000	4,500	2.28	277,000
23	1,080	1.23	35,900	4,770	3.98	513,000	5,500	2.89	429,000
24	1,090	.95	28,000	4,080	3.43	378,000	5,640	2.70	411,000
25	1,240	.93	31,100	4,140	2.82	315,000	5,640	2.88	439,000
26	1,660	1.53	68,600	4,110	3.05	338,000	5,990	2.55	412,000
27	1,280	1.23	42,500	3,690	2.62	261,000	4,500	1.74	216,000
28	1,170	1.18	37,300	2,910	2.19	172,000	3,690	1.61	160,000
29	1,260	1.20	40,800	-----	-----	-----	3,220	1.93	168,000
30	1,500	1.19	48,200	-----	-----	-----	3,500	1.36	128,000
31	1,440	.90	35,000	-----	-----	-----	3,960	1.82	195,000
Monthly load (tons)		1,681,000	-----	-----	3,955,000	-----	-----	-----	7,267,000

1 Estimated.

## SEDIMENT IN COLORADO RIVER, 1925-41

TABLE 18.—*Mean daily discharge, mean concentration, and daily load of suspended sediment in the San Juan River at gaging station near Bluff, Utah, Oct. 1, 1929, to Sept. 30, 1941—Continued*

1941

Day	April			May			June		
	Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment		Mean discharge (second- feet)	Suspended sediment	
		Mean percent	Tons per day		Mean percent	Tons per day		Mean percent	Tons per day
1	4,450	1.72	207,000	14,400	2.05	797,000	13,400	0.91	329,000
2	5,800	2.27	355,000	14,100	1.71	651,000	12,900	1.17	408,000
3	7,250	2.26	442,000	20,000	2.70	1,460,000	12,900	.82	286,000
4	5,240	1.79	253,000	20,000	2.59	1,400,000	13,400	1.12	405,000
5	4,480	1.25	151,000	27,100	3.59	2,630,000	13,900	.87	327,000
6	4,260	1.54	177,000	25,700	3.76	2,610,000	13,900	.94	353,000
7	4,530	1.62	198,000	20,500	3.06	1,690,000	15,100	1.04	424,000
8	4,080	1.10	121,000	21,600	3.08	1,800,000	14,100	1.26	480,000
9	4,020	1.06	115,000	21,600	2.86	1,670,000	18,900	1.37	699,000
10	4,380	1.35	160,000	23,500	3.05	1,940,000	20,200	1.63	889,000
11	5,270	1.84	262,000	25,200	2.59	1,760,000	17,900	1.18	570,000
12	6,330	1.30	222,000	26,000	2.28	1,600,000	14,100	1.01	385,000
13	6,330	1.42	243,000	28,000	2.40	1,810,000	11,400	.77	237,000
14	6,330	1.55	265,000	33,800	2.33	2,130,000	11,100	.66	198,000
15	5,800	1.49	233,000	32,600	2.23	1,960,000	11,400	.62	191,000
16	4,900	1.04	138,000	28,300	1.80	1,380,000	12,000	.68	247,000
17	4,930	1.02	136,000	22,900	1.59	983,000	12,500	.69	233,000
18	4,690	1.24	157,000	22,100	1.40	835,000	13,400	.75	271,000
19	4,750	1.24	159,000	22,600	1.43	873,000	14,400	.75	292,000
20	4,610	1.14	142,000	22,600	1.24	757,000	16,600	.87	390,000
21	4,380	1.18	140,000	18,100	1.01	494,000	18,100	.79	386,000
22	4,120	.99	110,000	15,100	.92	375,000	18,400	.84	417,000
23	6,150	3.64	604,000	15,800	1.34	572,000	18,400	.74	368,000
24	7,630	2.19	451,000	25,200	4.96	3,370,000	18,600	.77	387,000
25	6,150	1.78	311,000	18,900	4.82	2,460,000	20,000	.87	470,000
26	7,560	3.74	763,000	18,900	3.59	1,830,000	20,200	.94	513,000
27	13,000	7.20	2,530,000	18,400	2.09	1,040,000	17,900	.81	391,000
28	14,800	6.66	2,660,000	18,400	1.44	715,000	16,600	.79	354,000
29	16,800	3.04	1,380,000	16,600	.93	417,000	15,600	.79	333,000
30	14,800	2.36	943,000	14,600	1.07	422,000	14,100	.73	278,000
31				14,400	1.05	408,000			
Monthly load (tons)		14,030,000			42,830,000			11,510,000	

1941

	July			August			September		
1	12,900	0.83	289,000	3,110	0.30	25,200	922	0.20	4,980
2	12,200	.75	247,000	2,850	.39	30,000	948	.21	5,380
3	11,600	.69	216,000	2,560	.30	20,700	922	.15	3,730
4	11,400	.57	175,000	2,420	.28	18,300	836	.15	3,390
5	11,600	.66	207,000	2,280	.14	8,620	788	.12	2,550
6	12,000	.73	237,000	2,090	.10	5,640	854	.15	2,460
7	12,500	.81	273,000	1,910	.14	7,220	638	.10	1,720
8	11,100	.74	222,000	2,480	.44	29,500	664	.09	1,610
9	10,300	.69	192,000	3,380	1.09	99,500	659	.12	2,140
10	10,300	.71	198,000	8,370	6.79	1,530,000	623	.11	1,850
11	10,500	.68	193,000	7,010	9.93	1,880,000	617	.13	2,170
12	10,000	.54	146,000	3,870	3.86	146,000	628	.10	1,700
13	10,000	.56	151,000	2,860	1.40	108,000	759	.10	2,050
14	9,840	.61	162,000	2,440	.75	49,400	3,370	.74	695,000
15	9,210	.59	147,000	3,800	.63	64,600	5,100	.17	987,000
16	8,410	.44	99,900	5,800	4.18	655,000	5,290	6.51	930,000
17	7,630	.36	74,200	4,850	4.25	557,000	3,570	3.80	366,000
18	7,060	.41	78,200	3,740	2.29	231,000	3,110	2.10	176,000
19	6,690	.37	66,800	3,400	1.43	131,000	4,060	5.49	602,000
20	7,250	.40	78,300	2,700	1.45	106,000	3,150	3.17	270,000
21	7,440	.51	102,000	2,290	.60	37,100	4,780	2.94	379,000
22	7,060	.79	151,000	1,960	.40	21,200	5,630	2.98	453,000
23	6,330	.44	75,200	1,760	.33	15,700	12,700	6.49	2,220,000
24	6,690	.51	92,100	1,600	.31	13,400	11,800	6.02	1,920,000
25	6,150	.71	118,000	1,470	.27	10,700	6,330	1.63	279,000
26	6,510	1.17	206,000	1,330	.23	8,260	4,480	1.16	140,000
27	5,560	.98	147,000	1,200	.18	5,830	3,750	.67	67,800
28	4,740	.46	58,900	1,140	.22	6,770	3,380	.60	54,800
29	4,510	.37	45,100	1,060	.19	5,440	3,360	.56	50,800
30	4,120	.29	32,300	1,000	.25	6,750	8,220	3.46	768,000
31	3,580	.38	36,700	903	.22	5,360			
Monthly load (tons)		4,517,000			5,839,000			10,390,000	

TABLE 19.—Suspended-sediment concentration in individual samples collected from the San Juan River at gaging station near Bluff, Utah, in Sept. and Oct. 1937, Sept. 1939, July to Oct. 1940, and March, April, and September 1941

Sampling points, measured from zero mark on cable at north bank: A, one-fourth, the distance across the river; B, one-half; C, three-fourths.

Date of collection	Time	Gage height	Suspended sediment				Mean daily percent	Tons per day		
			At sampling points—							
			A (percent)	B (percent)	C (percent)					
<i>1937</i>										
Sept. 26	8:15 a. m.	4.02	0.36	0.34	0.46	0.39	1,450			
Sept. 27	8:30 a. m.	4.16	.43	.40	.38	.40	1,830			
Sept. 28	6:50 a. m.	4.20	.56	.48	.37	.47	2,610			
Sept. 29	8:30 a. m.	4.22	.41	.40	.44	.84	5,560			
	8:10 p. m.	4.80	1.34	1.39	1.08					
Sept. 30	9:15 a. m.	8.00	5.88	6.02	5.03	13.3	2,840,000			
	2:20 p. m.	13.00	16.8	15.8	15.8					
	7:50 p. m.	15.30	16.1	17.4	17.8					
	11:45 p. m.	15.40	14.2	14.3	14.2					
Oct. 1	6:30 a. m.	116.70	14.8	15.2	15.4	14.2	5,370,000			
	12:30 p. m.	16.00	17.4	17.5	17.9					
	5:50 p. m.	12.10	13.1	13.4	13.5					
	11:45 p. m.	10.15	10.5	10.8	11.2					
Oct. 2	8:35 a. m.	8.45	7.88	8.09	7.87	7.95	979,000			
Oct. 3	12:00 p. m.	6.40	4.65	4.70	4.70	4.68	286,000			
Oct. 4	10:10 a. m.	5.48	3.06	3.12	3.08	3.09	113,000			
Oct. 5	8:15 a. m.	5.10	2.09	2.08	2.01	2.06	57,800			
Oct. 6	4:45 p. m.	4.90	1.17	1.26	1.19	1.21	29,700			
Oct. 7	2:30 p. m.	4.85	.89	.88	.95	.91	20,900			
<i>1939</i>										
Sept. 10	5:40 p. m.	4.90	2.50	2.58	2.21	2.43	71,500			
Sept. 11	1:00 p. m.	6.70	2.86	3.86	3.24	5.07	556,000			
	6:00 p. m.	9.60	4.26	4.77	5.29					
	10:00 p. m.	10.80	6.23	7.22	7.92					
Sept. 12	10:00 a. m.	13.00	15.9	17.8	18.6	20.9	6,210,000			
	6:00 p. m.	11.80	25.7	26.4	21.2					
Sept. 13	10:00 a. m.	9.60	5.22	5.84	6.60	5.57	1,070,000			
	3:30 p. m.	8.90	5.05	5.77	6.81					
	9:30 p. m.	8.20	5.12	5.27	4.46					
Sept. 14	11:00 a. m.	7.60	3.17	2.89	3.48	3.18	326,000			
Sept. 15	10:00 a. m.	7.30	1.88	2.55	3.53	2.65	245,000			
Sept. 16	1:30 p. m.	7.40	1.41	1.17	1.22	1.27	118,000			
<i>1940</i>										
July 15	7:00 p. m.	.02	.03	.03	.03		96			
July 16	5:00 p. m.	3.40	1.25	1.21	1.38	2.88	9,180			
	8:15 p. m.	3.40	4.79	4.24	4.38					
July 17	6:40 p. m.	4.70	1.40	1.41	2.82	3.36	25,400			
	11:20 p. m.	4.20	4.74	5.17	4.71					
July 18	1:00 p. m.	3.30	9.73	9.30	9.31	9.45	55,600			
July 19	8:00 p. m.	2.76	4.15	5.94	6.16	5.42	11,300			
July 20	10:05 a. m.	2.60	4.29	2.83	2.90	3.34	4,150			
July 21	5:45 p. m.	3.43	1.56	.99	1.50	1.35	2,700			
July 22	11:45 a. m.	3.77	2.55	1.29	1.41	1.75	12,000			
Aug. 21	10:40 a. m.	3.26	3.37	3.24	3.08	3.23	12,000			
Aug. 22	12:25 a. m.	3.30	4.10	4.18	4.39	3.36	14,000			
	7:20 a. m.	3.40	2.46	2.63	2.42					
Aug. 23	9:10 a. m.	3.80	5.83	5.93	5.04	5.60	49,600			
Aug. 24	8:10 a. m.	6.05	5.91	6.02	6.08	10.8	481,000			
	6:55 p. m.	6.52	9.02	8.48	8.87					
	11:15 p. m.	7.68	16.3	17.8	18.4					
Aug. 25	6:10 a. m.	7.82	13.3	12.5	16.5	16.3	1,980,000			
	3:10 p. m.	8.20	12.3	11.7	9.17					
	9:45 p. m.	7.28	21.0	25.6	25.5					
Aug. 26	9:35 a. m.	9.65	11.7	11.4	9.97	8.97	1,284,000			
	1:45 p. m.	9.70	8.68	8.89	9.45					
	9:20 p. m.	8.02	6.48	6.64	7.48					
Aug. 27	7:25 a. m.	7.03	5.20	5.47	7.20	5.68	449,000			
	5:25 p. m.	7.00	5.09	5.36	5.26					
	8:25 p. m.	7.05	5.22	5.66	7.32					
	11:20 p. m.	7.01	5.26	5.58	5.58					

<sup>1</sup> Estimated.

TABLE 19.—*Suspended-sediment concentration in individual samples collected from the San Juan River at gaging station near Bluff, Utah, in Sept. and Oct. 1937, Sept. 1939, July to Oct. 1940, and March, April, and September 1941—Continued*

Sampling points, measured from zero mark on cable at north bank: A, one-fourth, the distance across the river; B, one-half; C, three-fourths.

Date of collection	Time	Gage height	Suspended sediment				
			At sampling points—			Mean daily percent	Tons per day
			A (percent)	B (percent)	C (percent)		
<i>1940</i>							
Aug. 28	9:30 a. m.	6.30	4.94	5.12	5.00	5.36	141,000
	3:25 p. m.	5.99	5.83	5.38	5.92		
	7:50 p. m.	5.67	5.26	5.81	4.97		
Aug. 29	9:25 a. m.	5.11	4.08	4.28	3.98	4.11	110,000
Aug. 30	3:00 p. m.	4.57	2.78	2.67	2.58	2.68	50,400
Aug. 31	3:20 p. m.	4.35	2.98	1.66	2.19	2.28	37,100
Sept. 12	10:25 a. m.	3.20	0.32	0.31	0.35	0.33	1,240
Sept. 13	7:55 a. m.	4.47	3.57	3.52	3.38	7.13	130,000
	12:40 p. m.	4.82	13.6	16.5	21.9		
	3:50 p. m.	4.92	3.19	3.02	4.12		
	9:40 p. m.	4.40	4.28	4.32	4.17		
Sept. 14	10:10 a. m.	3.80	1.39	1.80	1.09	5.47	41,500
	9:55 p. m.	4.71	9.10	10.5	8.94		
Sept. 15	7:55 a. m.	4.10	10.6	10.3	9.43	10.1	75,000
Sept. 17	7:15 a. m.	3.90	3.31	3.55	3.28	3.38	8,400
Sept. 18	12:40 a. m.	5.48	6.41	6.34	8.58	7.02	569,000
	11:15 a. m.	7.95	6.64	5.32	6.35		
	4:20 p. m.	7.05	8.09	9.09	8.28		
	9:45 p. m.	7.05	6.27	6.24	6.61		
Sept. 19	6:50 a. m.	7.02	16.6	14.7	13.5	11.0	989,000
	12:50 p. m.	7.40	10.6	11.4	10.7		
	6:35 p. m.	7.35	8.33	8.83	9.16		
	9:55 p. m.	7.65	8.92	11.8	7.35		
Sept. 20	7:25 a. m.	9.20	8.84	9.49	9.32	7.98	1,174,000
	2:50 p. m.	10.25	7.03	7.26	7.67		
	6:25 p. m.	9.15	6.50	7.01	7.39		
	11:15 p. m.	8.40	8.20	8.49	8.58		
Sept. 21	7:00 a. m.	7.30	6.22	6.54	6.32	5.42	429,000
	11:25 a. m.	7.25	5.62	6.11	5.63		
	10:50 p. m.	7.00	4.07	3.91	4.34		
Sept. 22	10:00 a. m.	6.95	3.14	3.18	3.46	7.30	962,000
	3:30 p. m.	8.30	3.91	4.53	5.03		
	6:30 p. m.	11.50	7.00	9.06	8.07		
	10:30 p. m.	10.50	13.1	14.9	12.2		
Sept. 23	7:25 a. m.	8.45	7.92	7.59	8.12	6.14	680,000
	5:15 p. m.	7.40	3.70	4.71	4.78		
Sept. 24	10:00 a. m.	7.30	5.26	7.08	7.23	6.52	488,000
Sept. 25	11:45 a. m.	6.80	2.47	2.34	2.42	2.41	144,000
Sept. 26	2:00 p. m.	6.30	1.59	1.65	1.55	1.60	90,300
Sept. 27	2:30 p. m.	5.97	1.27	1.62	1.23	1.37	63,300
Sept. 28	3:00 p. m.	5.67	.86	1.03	1.08	.99	45,700
Sept. 29	12:20 p. m.	10.05	11.3	10.6	11.9	9.92	1,653,000
	5:05 p. m.	8.65	10.1	10.2	10.8		
	10:00 p. m.	8.70	7.87	8.39	8.14		
Sept. 30	9:05 a. m.	11.60	14.2	13.4	14.7	12.1	3,960,000
	2:30 p. m.	10.20	10.6	9.63	9.93		
	6:40 p. m.	10.40	6.56	7.70	13.1		
Oct. 1	6:35 a. m.	11.50	8.21	10.2	10.0	12.5	3,320,000
	11:40 a. m.	9.90	18.6	23.0	16.1		
	4:45 p. m.	8.60	8.91	8.78	8.84		
Oct. 2	2:55 p. m.	7.95	3.84	4.30	4.25	4.13	457,000
Oct. 3	7:00 a. m.	7.55	3.29	5.94	3.57	4.27	357,000
<i>1941</i>							
Mar. 14	11:15 a. m.	5.68	.79	.93	.73	.82	37,000
Mar. 15	10:20 a. m.	8.40	6.61	6.98	6.21	6.09	773,000
	3:45 p. m.	8.55	6.27	6.91	7.15		
	6:55 p. m.	8.40	5.62	6.29	6.34		
	11:30 p. m.	8.15	4.48	4.82	5.36		
Mar. 16	8:00 a. m.	8.70	5.44	5.96	6.28	5.62	651,000
	5:25 p. m.	7.30	5.27	5.31	5.47		

<sup>1</sup> Estimated.

## QUANTITIES OF SUSPENDED SEDIMENT

143

TABLE 19.—*Suspended-sediment concentration in individual samples collected from the San Juan River at gaging station near Bluff, Utah, in Sept. and Oct. 1937, Sept. 1939, July to Oct. 1940, and March, April, and September 1941—Continued*

Sampling points, measured from zero mark on cable at north bank: A, one fourth, the distance across the river; B, one-half; C, three-fourths.

Date of collection	Time	Gage height	Suspended sediment				Mean daily percent	Tons per day		
			At sampling points—							
			A (percent)	B (percent)	C (percent)					
<i>1941</i>										
Mar. 17	10:40 a. m.	8.10	3.10	3.56	4.28	3.20	385,000			
	3:30 p. m.	8.15	2.33	2.89	3.05					
Mar. 18	8:40 a. m.	7.65	2.16	2.25	2.50	2.99	368,000			
	6:50 p. m.	8.21	3.22	3.79	4.01					
Apr. 22	9:45 a. m.	7.45	.89	1.06	1.02	.99	110,000			
Apr. 23	9:50 a. m.	8.42	4.38	4.87	4.97	3.64	604,000			
	5:15 p. m.	9.25	2.92	3.53	3.74					
	9:30 p. m.	9.50	2.04	3.10	3.25					
Apr. 24	7:45 a. m.	9.90	2.02	2.65	2.88	2.19	451,000			
	3:15 p. m.	9.58	1.43	2.01	2.21					
	6:50 p. m.	9.25	1.44	2.19	3.05					
Apr. 25	9:20 a. m.	8.50	1.65	1.98	1.98	1.87	311,000			
Apr. 26	7:45 a. m.	8.88	1.57	2.00	2.00	3.74	763,000			
	5:30 p. m.	9.95	2.47	3.44	3.53					
	8:50 p. m.	10.23	5.32	6.52	6.79					
Apr. 27	7:40 a. m.	11.15	10.0	10.8	11.2	7.20	2,530,000			
	1:30 p. m.	10.64	9.16	7.99	7.66					
	4:15 p. m.	12.85	4.92	5.92	6.33					
	8:15 p. m.	14.50	3.61	3.98	4.89					
Apr. 28	6:50 a. m.	12.00	8.34	9.22		6.66	2,660,000			
	4:55 p. m.	12.32	3.92	5.27	6.56					
Ap. 29	6:50 a. m.	13.30	3.17	3.25	3.46	3.04	1,380,000			
	5:00 p. m.	14.20	3.02	2.69	2.68					
Apr. 30	9:05 a. m.	13.30	2.18	2.31	2.59	2.36	943,000			
Sept. 13	10:40 a. m.	4.60	.08	.10	.11	.10	2,050			
Sept. 14	5:50 a. m.	10.50	10.3	10.1	9.84	7.64	695,000			
	12:45 p. m.	7.68	7.98	8.44	7.01					
	6:10 p. m.	6.82	5.06	5.10	4.89					
Sept. 15	7:10 a. m.	7.27	3.68	3.46	3.50	7.17	987,000			
	11:20 a. m.	9.30	9.01	9.20	8.40					
	9:45 p. m.	9.68	7.77	10.3	9.18					
Sept. 16	5:40 a. m.	9.50	7.09	7.79	7.65	6.51	930,000			
	6:15 p. m.	8.27	5.64	5.41	5.50					
Sept. 17	5:55 a. m.	8.00	3.93	3.70	3.78	3.80	366,000			
Sept. 18	11:10 a. m.	6.69	2.04	2.08	2.18	2.10	176,000			

TABLE 20.—Suspended-sediment concentration at different sampling times, mean daily discharge, mean daily concentration, and daily load of suspended sediment in Little Colorado River at gaging station at Grand Falls, Ariz., July 6 to Sept. 26, 1931

Date	Time of collection	Mean daily discharge (sec.-ft.)	Suspended sediment			
			Number of samples	Mean percent at sampling period	Mean daily percent	Tons per day
<i>1931</i>						
July 6	12:36 p. m.	292	5	8.14	8.14	64,200
July 7	11:00 a. m.	134	5	6.87	6.87	24,900
July 10	11:20 a. m.	20	4	7.24	6.97	3,760
	3:50 p. m.		3	6.70		
July 11	11:10 a. m.	9	3	5.91	5.91	1,440
July 12	11:55 a. m.	4	2	3.66	3.66	395
July 13	2:30 p. m.	1	2	4.06	4.06	110
July 14	12:30 p. m.	0	3	8.01		0
July 16	9:55 a. m.	15	1	1.06	.77	312
	4:05 p. m.		2	.48		
July 17	11:00 a. m.	44	5	3.74	3.38	4,020
	2:30 p. m.		5	3.01		
July 18	10:10 a. m.	164	6	3.87	4.26	17,700
	1:05 p. m.		5	4.09		
	3:05 p. m.		6	4.83		
July 19	8:55 a. m.	292	6	5.50	5.50	43,400
July 20	1:35 p. m.	599	6	7.05	7.05	114,000
July 21	11:00 a. m.	1,490	3	13.2	12.4	499,000
	12:15 p. m.		4	13.4		
	3:30 p. m.		4	11.4		
	4:15 p. m.		4	11.4		
July 22	11:56 a. m.	460	5	7.96	7.88	97,900
	3:20 p. m.		5	7.80		
July 23	10:25 a. m.	196	3	7.52	7.52	39,800
	11:46 a. m.		4	7.52		
July 24	11:00 a. m.	102	5	6.50	6.42	17,700
	2:15 p. m.		4	6.33		
July 25	11:05 a. m.	148	3	5.89	5.89	23,500
July 26	9:15 a. m.	346	5	7.46	7.46	69,700
July 27	12:15 p. m.	215	6	5.81	5.87	34,100
	3:15 p. m.		6	5.93		
July 28	10:40 a. m.	142	6	6.07	6.08	23,300
	1:50 p. m.		5	6.09		
July 29	10:30 a. m.	101	4	6.03	6.14	16,700
	11:40 a. m.		4	6.25		
	3:05 p. m.		4	6.14		
July 30	12:00 m.	2,300	4	12.2	12.0	745,000
	2:35 p. m.		4	11.8		
July 31	10:40 a. m.	1,970	6	10.9	10.4	553,000
	1:45 p. m.		6	9.82		
Aug. 1	1:20 p. m.	3,680	6	15.0	15.5	1,540,000
	5:00 p. m.		5	16.0		
Aug. 2	11:45 a. m.	3,020	7	11.5	11.5	938,000
Aug. 3	12:45 p. m.	1,110	4	8.50	8.50	265,000
Aug. 4	11:50 a. m.	550	5	7.17	7.17	106,000
Aug. 5	10:05 a. m.	428	5	6.22	6.22	71,900
Aug. 6	11:45 a. m.	1,030	6	6.55	6.96	194,000
	3:05 p. m.		6	7.37		
Aug. 7	11:35 a. m.	3,580	5	11.8	10.6	1,020,000
	3:55 p. m.		5	9.36		
Aug. 8	3:20 p. m.	3,050	6	6.98	6.98	575,000
Aug. 9	12:55 p. m.	906	5	4.30	4.30	105,000
Aug. 10	9:50 a. m.	1,310	4	7.28	7.13	252,000
	11:20 a. m.		4	6.93		
	2:15 p. m.		4	7.19		
Aug. 11	10:45 a. m.	1,630	5	8.33	7.98	351,000
	2:25 p. m.		3	7.63		
Aug. 12	12:25 p. m.	468	5	5.62	5.62	71,000
Aug. 13	12:05 p. m.	312	4	4.94	5.02	42,300
	2:00 p. m.		4	5.11		
Aug. 14	11:00 a. m.	244	6	4.89	4.91	32,300
	2:00 p. m.		5	4.93		
Aug. 15	12:00 m.	262	5	3.87	3.87	27,400
Aug. 16	11:10 a. m.	904	5	5.81	5.81	142,000
Aug. 17	10:20 a. m.	301	5	2.70	2.56	20,800
	2:20 p. m.		5	2.43		

TABLE 20.—*Suspended-sediment concentration at different sampling times, mean daily discharge, mean daily concentration, and daily load of suspended sediment in Little Colorado River at gaging station at Grand Falls, Ariz., July 6 to Sept. 26, 1931—Continued.*

Date	Time of collection	Mean daily discharge (sec.-ft.)	Suspended sediment			
			Number of samples	Mean percent at sampling period	Mean daily percent	Tons per day
1931						
Aug. 18.....	11:00 a. m.....	244	6	1.90	1.92	12,600
	2:10 p. m.....		4	1.95		
Aug. 19.....	10:55 a. m.....	180	4	4.21	4.58	22,300
	1:35 p. m.....		4	4.94		
Aug. 21.....	4:30 p. m.....	190	4	5.96	5.96	30,600
Aug. 22.....	2:10 p. m.....	182	6	5.27	5.27	25,900
Aug. 23.....	11:00 a. m.....	561	3	6.61	8.76	133,000
	1:25 p. m.....		5	10.9		
Aug. 24.....	10:05 a. m.....	651	3	5.52	5.42	95,300
	3:15 p. m.....		3	5.32		
Aug. 25.....	10:40 a. m.....	267	3	3.58	3.53	25,400
	2:25 p. m.....		4	3.48		
Aug. 26.....	10:35 a. m.....	155	6	3.68	3.69	15,400
	2:05 p. m.....		3	3.70		
Aug. 27.....	11:00 a. m.....	90	5	3.58	3.56	8,650
	3:15 p. m.....		4	3.55		
Aug. 28.....	11:10 a. m.....	54	4	2.87	2.82	4,110
	2:30 p. m.....		4	2.76		
Aug. 29.....	11:20 a. m.....	31	3	2.26	2.40	2,010
	3:15 p. m.....		3	2.55		
Aug. 30.....	12:30 p. m.....	22	3	2.51	2.51	1,490
Aug. 31.....	10:30 a. m.....	272	3	4.79	4.76	35,000
	12:15 p. m.....		3	4.86		
	2:45 p. m.....		4	4.62		
Sept. 1.....	12:50 p. m.....	455	5	4.00	4.11	50,500
	3:35 p. m.....		4	4.22		
Sept. 2.....	10:15 a. m.....	291	5	3.72	3.67	28,800
	2:40 p. m.....		4	3.62		
Sept. 3.....	1:00 p. m.....	155	5	3.07	3.16	13,200
	3:30 p. m.....		3	3.25		
Sept. 4.....	10:40 a. m.....	113	5	2.96	2.96	9,030
Sept. 5.....	11:55 a. m.....	75	3	4.44	4.30	8,710
	2:15 p. m.....		3	4.16		
Sept. 6.....	11:30 a. m.....	43	3	3.30	3.30	3,830
Sept. 7.....	12:00 m.....	20	4	2.42	2.42	1,310
Sept. 8.....	10:35 a. m.....	94	4	1.97	1.97	5,000
Sept. 9.....	4:40 p. m.....	534	4	5.52	5.52	79,600
Sept. 10.....	11:25 a. m.....	316	4	6.61	6.48	55,300
	3:00 p. m.....		4	6.35		
Sept. 11.....	11:15 a. m.....	160	5	5.52	5.44	23,500
	2:30 p. m.....		4	5.36		
Sept. 12.....	2:45 p. m.....	95	3	4.72	4.72	12,100
Sept. 13.....	4:00 p. m.....	72	3	5.31	5.31	10,300
Sept. 14.....	11:00 a. m.....	74	3	4.98	4.78	9,550
	3:00 p. m.....		3	4.58		
Sept. 15.....	11:30 a. m.....	40	4	3.46	3.56	3,840
	3:30 p. m.....		4	3.67		
Sept. 16.....	11:15 a. m.....	57	4	3.59	3.36	5,170
	3:40 p. m.....		4	3.12		
Sept. 17.....	10:30 a. m.....	732	2	9.68	9.08	179,00
	11:30 a. m.....		3	9.34		
	2:05 p. m.....		4	8.60		
	3:05 p. m.....		4	8.72		
Sept. 18.....	11:05 a. m.....	514	3	8.61	8.42	117,000
	2:45 p. m.....		3	8.24		
Sept. 19.....	11:40 a. m.....	411	5	8.50	8.50	94,300
Sept. 20.....	11:45 a. m.....	382	5	7.79	7.79	80,300
Sept. 21.....	1:50 p. m.....	512	4	5.10	5.10	70,500
Sept. 22.....	4:55 p. m.....	1,370	4	8.28	8.28	306,000
Sept. 23.....	10:45 a. m.....	474	4	7.27	7.20	92,100
	2:15 p. m.....		4	7.14		
Sept. 24.....	10:40 a. m.....	302	4	5.86	5.86	47,800
Sept. 25.....	11:25 a. m.....	209	3	4.07	4.07	23,000
Sept. 26.....	9:35 a. m.....	151	3	2.99	2.99	12,200

## SEDIMENT IN COLORADO RIVER, 1925-41

TABLE 21.—Velocity and suspended-sediment concentration of water in the Colorado River at gauging station near Grand Canyon, Ariz., Apr. 6, to July 24, 1935

Type of measurement: R, Regular; V, velocity observations taken just before and just after collection of silt samples at each point. Sampling points: Samples were taken at points A to D at distances of 120, 180, 240, and 300 feet, respectively, from zero mark on cable at north bank.

Type of sample: I, Integrated; S, surface.

Date	Time	Gage height (feet)	Type of measurement	Mean velocity (ft./sec.)				Depth (feet)				Suspended sediment (percent by weight)				Type of samples
				A		B	C	A		B	C	A		B	C	
				9:45 a. m.	9:45 a. m.	7.28	R	3.90	5.11	4.99	4.48	11.5	8.5	4.7	1.43	I
Apr. 6	9:45 a. m.	6.11	R	4.97	6.10	5.44	5.68	12.0	11.0	10.2	5.2	1.29	1.17	1.18	1.32	S
Apr. 8	9:45 a. m.	6.38	R	4.74	6.93	4.94	5.77	14.6	11.9	7.9	2.5	1.48	1.40	1.60	1.52	I
Apr. 14	9:15 a. m.	6.98	V	4.30	6.18	5.95	4.44	14.6	11.5	6.5	2.0	1.24	1.50	1.47	1.21	S
Apr. 17	4:25 p. m.	6.38	V	5.07	6.92	5.94	5.33	15.3	15.1	8.9	3.5	1.23	1.85	.59	.68	S
Apr. 20	9:00 a. m.	7.94	R	5.26	6.57	6.57	5.26	16.0	13.3	8.8	4.3	1.25	1.33	1.28	1.21	I
Apr. 21	9:20 a. m.	8.28	V	5.46	7.34	5.98	5.44	14.8	12.6	9.0	3.9	1.25	1.17	1.10	.92	S
Apr. 24	9:30 a. m.	8.04	V	5.72	7.58	7.20	5.82	15.6	13.6	9.6	6.4	1.45	1.46	1.46	1.48	I
Apr. 28	4:05 p. m.	9.46	V	5.38	6.88	5.48	5.54	16.0	12.8	9.8	3.9	1.23	1.03	.85	.78	S
May 1	10:00 a. m.	9.80	V	5.71	7.28	6.78	5.92	16.7	15.1	10.8	6.3	1.46	1.22	1.30	1.16	I
May 5	12:00 n.	8.17	V	5.09	6.80	6.25	5.31	15.6	12.4	9.2	4.8	1.04	1.04	.97	1.06	S
May 8	5:00 p. m.	7.96	R	5.18	6.28	5.81	5.27	15.8	12.8	9.0	3.8	1.04	.97	.73	.65	I
May 12	9:00 a. m.	8.01	V	5.26	6.35	6.91	6.23	16.8	13.7	9.4	4.0	1.04	.57	.59	.31	S
May 15	4:10 p. m.	9.96	R	5.39	7.55	6.40	6.48	17.7	15.0	11.3	7.4	1.04	.66	.75	.87	I
May 15	9:05 a. m.	10.15	V	6.59	7.90	6.94	6.65	16.8	14.0	10.0	6.3	1.04	.90	.91	.82	I
May 19	9:20 a. m.	11.55	V	6.03	8.75	7.75	6.30	18.6	16.8	12.6	7.7	1.04	.62	.62	.60	S
May 22	9:00 a. m.	12.56	R	6.54	7.69	7.65	6.26	21.5	20.3	14.3	9.5	1.04	.02	.85	1.25	S
	4:35 p. m.	12.53	R	6.42	8.91	8.76	6.35	20.6	16.9	12.6	8.4	1.04	.91	.98	.83	I

Observations at sampling points indicated

May 26	9:50 a. m.	12.30	V	7.17	8.18	7.74	6.16	20.4	17.2	13.4	10.0	S
May 29	8:40 a. m.	15.07	R	7.48	9.73	8.60	7.02	24.2	19.6	16.6	13.3	I
	3:55 p. m.	15.38	V	6.81	9.93	9.16	6.88	24.0	19.0	16.9	13.3	S
June 3	9:20 a. m.	17.82	V	7.26	9.76	10.07	6.26	27.0	29.3	23.8	18.0	I
June 9	8:50 a. m.	19.02	R	7.01	9.04	9.22	8.19	28.5	29.5	24.5	20.0	S
	4:10 p. m.	19.20	V	7.92	8.96	9.31	8.02	27.6	27.7	24.2	20.8	I
June 22	8:40 a. m.	23.23	R	8.45	9.81	10.04	9.40	30.5	30.5	27.0	22.0	S
	4:50 p. m.	23.00	V	7.84	9.74	9.75	9.09	31.8	34.1	31.6	29.6	I
June 26	8:45 a. m.	21.44	R	7.55	8.85	9.16	8.07	30.4	31.8	28.3	28.0	S
	4:00 p. m.	21.07	V	7.79	8.84	9.20	7.94	30.4	31.8	28.3	28.0	I
June 29	8:35 a. m.	19.44	R	6.62	8.00	8.15	7.47	28.4	27.2	25.4	24.9	S
	4:20 p. m.	19.08	V	6.95	8.27	8.32	7.61	28.4	27.2	25.4	24.9	I
July 6	9:55 a. m.	15.35	V	5.12	5.80	5.80	5.36	24.1	26.4	23.2	23.1	S
July 11	4:10 p. m.	12.93	V	4.06	5.07	5.23	4.94	21.4	23.4	20.8	19.4	S
July 13	10:05 a. m.	12.24	V	3.91	4.98	5.08	4.23	20.7	21.5	18.7	16.6	S
July 17	11:25 a. m.	11.50	V	3.70	4.08	4.74	4.16	20.2	23.0	18.8	19.2	S
July 20	9:35 a. m.	10.43	V	3.30	3.94	3.80	3.64	19.1	21.3	19.8	18.6	I
July 24	9:30 a. m.	9.97	V	3.40	3.70	3.63	3.32	18.7	21.4	20.2	19.3	I

## SEDIMENT IN COLORADO RIVER, 1925-41

TABLE 22.—Velocity and suspended-sediment concentration of water in the Colorado River at gaging station near Topock, Ariz., Apr. 3 to June 29, 1935

Type of measurement: R, Regular.  
 Sampling points: Samples were taken at points A to D at distances of 70, 200, 300, and 450 feet, respectively, from zero mark on cable at north bank.  
 Type of sample: I, Integrated; S, surface.

Date	Time	Gage height (feet)	Type of measurement	Mean velocity (ft./sec.)				Depth (feet)				Observations at sampling points indicated				Type of samples
				A		B	C	A		B	C	A		B	C	
				A	B	C	D	A	B	C	D	A	B	C	D	
1935																
Apr. 3	10:00 a. m. ....	12.22	R	3.71	5.00	4.87	2.31	15.5	3.0	2.9	2.7	0.23	0.24	0.22	0.16	S
	12:15 p. m. ....	12.23	R	4.16	5.34	4.81	3.10	13.5	3.4	3.0	2.4	.38	.33	.29	.23	I
	11:15 a. m. ....	12.24	R	3.37	5.22	5.10	3.08	14.9	2.6	2.4	3.4	.25	.32	.31	.25	S
	12:25 p. m. ....	12.23	R	3.58	5.40	5.16	3.96	13.8	2.9	2.8	3.3	.43	.39	.34	.36	I
	11:05 a. m. ....	12.11	R	3.62	5.15	4.87	3.85	13.0	3.0	2.9	3.6	.50	.50	.49	.46	S
	9:50 a. m. ....	12.15	R	3.44	5.13	4.90	2.80	14.6	2.8	2.9	2.6	.86	.81	.76	.72	S
	11:30 a. m. ....	12.32	R	3.52	5.31	5.15	3.39	13.0	3.5	3.1	2.7	.84	.84	.81	.79	I
	1:25 p. m. ....	12.37	R	3.46	4.80	4.44	3.40	14.8	3.0	3.1	3.0	.86	.81	.76	.72	S
	9:35 a. m. ....	12.30	R	4.06	4.99	4.69	3.15	15.6	2.7	2.8	4.2	.71	.72	.65	.65	I
	10:05 a. m. ....	12.20	R	3.96	5.06	4.78	3.10	13.5	2.8	2.8	4.2	.75	.73	.76	.76	S
	3:45 p. m. ....	12.29	R	3.18	4.74	4.59	3.33	14.9	2.8	2.7	2.7	.38	.31	.34	.32	I
	10:25 a. m. ....	12.27	R	3.73	4.36	4.82	3.32	8.0	2.6	2.4	6.9	.17	.12	.13	.16	S
	10:45 a. m. ....	12.24	R	3.49	4.40	4.40	3.88	9.0	2.4	2.6	7.9	.20	.21	.17	.16	S
	10:00 a. m. ....	12.21	R	2.98	4.54	4.44	4.26	10.6	2.3	2.5	9.8	.14	.13	.15	.18	I
	10:30 a. m. ....	13.41	R	4.52	6.20	6.56	4.72	10.0	4.0	4.6	10.6	.28	.27	.23	.23	I
												.41	.41	.48	.39	

June 1	9:50 a. m.	14.25	R	4.40	5.72	6.12	5.10	14.2	4.1	4.9	10.7
June 5	10:30 a. m.	14.38	R	4.60	5.82	5.64	5.30	13.0	5.5	5.3	11.5
June 12	11:00 a. m.	14.38	R	5.08	5.79	5.74	4.52	14.3	5.3	5.4	11.0
June 15	9:15 a. m.	14.62	R	4.36	6.00	5.92	4.47	16.5	5.5	5.8	8.8
June 19	9:40 a. m.	14.68	R	4.80	5.90	5.90	4.40	17.3	6.3	4.8	9.8
June 22	9:40 a. m.	14.57	R	4.38	6.90	6.28	4.02	17.4	7.0	5.2	9.2
June 26	9:45 a. m.	13.85	R	4.36	5.30	5.46	4.12	16.8	5.8	4.2	6.9
June 29	9:40 a. m.	13.57	R	4.32	5.70	5.77	4.35	16.6	5.1	4.9	9.0

TABLE 23.—*Mechanical analyses of suspended sediment in samples collected in the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 5, 1935, to Sept. 30, 1941*

Date of collection	Mean daily discharge (sec.-ft.)	Suspended sediment							
		Mean daily concentration (percent)	Tons per day	Percent in indicated size range					
				<0.005 mm.	0.005-0.020 mm.	0.020-0.050 mm.	0.050-0.074 mm.	0.074-0.149 mm.	>0.149 mm.
<i>1935</i>									
Apr. 5	9,330	1.31	330,000	26.5	16.1	15.7	12.1	18.8	10.8
Apr. 9	11,600	1.42	445,000	23.6	17.7	17.0	9.1	21.7	10.9
Apr. 12	14,400	2.16	840,000	21.2	13.5	13.6	12.8	19.3	19.6
Apr. 16	10,200	.89	245,000	27.8	17.1	25.4	4.0	15.1	10.6
Apr. 19	12,300	1.11	369,000	19.7	17.1	14.7	15.3	24.6	8.6
Apr. 20	13,500	1.46	532,000	20.1	14.9	15.8	16.4	27.8	5.0
Apr. 23	14,400	1.23	478,000	19.7	19.0	17.5	15.8	21.9	6.1
Apr. 26	14,000	1.06	401,000	16.2	16.4	13.4	15.3	26.8	11.9
Apr. 27	15,800	1.26	538,000	13.8	11.3	15.5	12.2	34.8	12.4
Apr. 28	16,900	1.40	639,000	9.7	13.4	17.1	17.0	31.0	11.8
Apr. 29	15,200	1.08	443,000	10.9	14.5	15.7	13.5	34.7	10.7
Apr. 30	14,000	.92	348,000	12.1	14.9	13.8	20.4	25.4	13.4
May 3, 10:20 a. m.	15,600	1.04	438,000	{	8.6	9.8	10.4	11.5	36.6
May 3, 7:35 p. m.	16,700	1.22	550,000		9.1	15.3	12.6	9.8	30.0
May 4	17,400	1.28	601,000	5.4	7.6	7.6	35.6	22.9	20.9
May 5	16,400	1.04	461,000	10.8	8.8	8.7	7.7	26.0	42.9
May 6	15,300	.99	409,000	12.8	12.6	8.7	11.5	31.1	23.3
May 8	14,100	1.06	404,000	22.5	19.5	11.2	12.6	22.5	11.7
May 10	13,400	.73	264,000	29.1	19.5	9.9	15.0	22.1	4.4
May 11	13,100	.68	241,000	13.8	20.0	12.6	13.7	32.9	7.0
May 13	14,300	.77	297,000	9.7	11.1	11.3	15.6	39.9	12.4
May 14	16,200	.80	350,000	11.6	15.7	14.5	18.6	29.6	10.0
May 15	18,500	.98	490,000	5.9	9.2	9.1	10.9	31.9	33.0
May 16	20,900	1.13	638,000	4.2	5.6	7.2	10.6	33.7	38.7
May 17	24,100	1.45	944,000	6.3	7.1	10.6	12.6	38.1	25.3
May 19	23,300	1.36	856,000	9.5	10.9	11.3	13.6	45.0	9.7
May 21	25,200	1.26	857,000	7.5	11.7	10.6	11.5	47.4	11.3
May 22	26,300	1.22	866,000	14.6	13.8	12.0	13.4	37.9	8.3
May 23, 9:08 a. m.	29,700	1.38	1,110,000	{	11.0	7.2	8.2	10.3	47.4
May 23, 4:35 p. m.	31,000	1.48	1,240,000		11.4	9.5	7.2	12.7	39.2
May 24	26,800	1.48	1,070,000	20.4	14.9	11.6	11.2	32.7	9.2
May 25	26,000	1.08	758,000	25.2	16.1	10.0	10.3	26.2	12.2
May 26	27,300	1.01	744,000	20.5	17.9	12.4	8.6	27.9	8.2
May 27	31,100	1.01	848,000	{	12.5	10.7	12.1	11.7	33.1
May 28, 10:45 a. m.	31,100	1.01	848,000		10.5	11.6	7.6	9.1	38.0
May 28, 4:25 p. m.	36,200	1.26	1,230,000	15.1	8.6	11.7	10.9	35.2	18.5
May 29, 8:40 a. m.	40,000	1.38	1,490,000	14.1	9.9	14.2	13.1	32.5	16.2
May 30	40,000	1.38	1,490,000	14.7	15.0	14.4	15.1	23.2	17.6
May 31, 7:10 a. m.	44,500	1.54	1,850,000	{	16.1	15.9	14.0	10.6	33.8
May 31, 7:30 p. m.	44,500	1.54	1,850,000		13.1	13.5	9.5	10.1	30.3
June 2	48,600	1.90	2,490,000	14.1	12.0	9.5	8.3	35.7	20.4
June 3	49,400	1.58	2,110,000	16.1	14.1	10.4	8.4	32.0	19.0
June 5	46,200	1.31	1,630,000	8.4	10.4	7.8	7.9	24.3	41.2
June 7	47,100	1.08	1,370,000	8.8	8.7	8.4	8.4	35.3	30.4
June 8	50,700	1.10	1,510,000	10.3	9.9	11.7	10.3	37.7	20.1
June 9, 8:50 a. m.	54,200	1.28	1,870,000	{	2.9	5.3	4.9	7.3	29.0
June 9, 4:10 p. m.	54,200	1.28	1,870,000		7.9	9.6	8.4	7.2	25.7
June 10	57,800	1.28	2,000,000	9.5	11.1	9.9	11.0	36.3	22.2
June 11	63,600	1.25	2,150,000	7.2	9.0	8.2	6.7	31.9	37.0
June 12	69,800	1.26	2,370,000	10.3	12.0	13.8	13.3	31.9	18.7
June 13	72,600	1.14	2,230,000	5.9	7.9	9.0	9.3	34.1	33.8
June 14	84,300	1.22	2,780,000	7.5	7.8	12.8	7.8	35.0	29.1
June 15	86,400	1.06	2,470,000	6.3	7.8	10.5	8.9	40.6	25.9
June 16	87,200	1.09	2,570,000	10.2	13.6	13.0	10.7	33.2	19.3
June 17	91,900	1.03	2,560,000	14.7	15.7	21.8	15.6	27.5	4.7
June 18	101,400	1.01	2,770,000	9.5	10.8	14.1	10.2	26.4	29.0
June 19	103,100	.82	2,280,000	12.5	12.4	17.0	12.5	30.3	15.3
June 20, 8:50 a. m.	89,000	.79	1,900,000	{	13.5	10.1	12.3	13.0	31.6
June 20, 3:55 p. m.	89,000	.79	1,900,000		15.3	16.0	20.5	9.9	28.1
June 21, 8:50 a. m.	80,900	.72	1,570,000	7.7	9.2	11.6	11.2	30.7	29.6
June 21, 8:00 p. m.	80,900	.55	1,140,000	12.7	11.2	15.7	16.5	30.3	13.6
June 22	77,000	.56	1,060,000	10.7	10.5	15.1	12.5	37.7	13.5
June 25	70,300	.44	777,000	9.5	11.6	14.1	11.3	32.5	21.0
June 26	65,400	.44	699,000	{	7.4	8.0	11.8	9.5	42.1
June 28, 8:55 a. m.	58,800	.44	699,000		8.3	8.6	13.4	13.3	34.8
June 28, 7:10 p. m.	58,800	.37	537,000	11.9	14.6	17.8	13.4	25.2	21.6
June 29	53,700	.37	537,000	11.9	14.6	17.8	13.4	25.2	17.1

## QUANTITIES OF SUSPENDED SEDIMENT

151

TABLE 23.—*Mechanical analyses of suspended sediment in samples collected in the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 5, 1935, to Sept. 30, 1941—Continued*

Date of collection	Mean daily discharge (sec.-ft.)	Suspended sediment							
		Mean daily concentration (percent)	Tons per day	Percent in indicated size range					
				<0.005 mm.	0.005-0.020 mm.	0.020-0.050 mm.	0.050-0.074 mm.	0.074-0.149 mm.	>0.149 mm.
<i>1935</i>									
July 1	47,600	0.36	463,000	9.7	10.7	15.3	13.1	31.9	19.3
July 2	43,800	.35	414,000	8.9	10.8	13.1	11.4	32.8	23.0
July 4	39,200	.28	296,000	10.3	12.2	15.2	14.2	30.4	17.7
July 6	35,000	.30	284,000	7.9	7.4	13.1	13.1	42.5	16.0
July 8	31,800	.23	197,000	11.0	10.3	15.6	15.3	31.3	16.5
July 24	17,100	.35	162,000	36.9	33.7	11.7	6.3	7.9	3.5
July 28	14,100	.46	175,000	52.4	34.6	7.9	1.6	2.1	1.4
July 31	11,400	.19	58,500	43.5	35.7	10.7	3.2	4.6	2.3
Aug. 3	10,600	.17	48,700	45.0	37.2	11.2	2.1	3.1	1.4
Aug. 6	12,700	1.82	624,000	65.0	21.3	7.1	2.4	3.3	.9
Aug. 10	9,950	.46	124,000	59.9	30.0	4.7	1.8	3.1	.5
Aug. 14	8,720	1.11	261,000	70.9	23.0	4.3	.5	.7	.6
Aug. 17	9,680	.76	199,000	63.9	27.1	6.8	.8	.8	.6
Aug. 23	7,600	.48	98,500	62.3	31.1	4.6	.5	.9	.6
Aug. 25	7,380	.52	104,000	56.5	32.4	5.5	1.6	2.8	1.2
Aug. 26	9,640	4.81	1,250,000	49.3	25.7	18.5	3.9	2.0	.6
Aug. 28	10,600	2.74	784,000	63.4	21.4	9.9	2.9	1.9	.5
Aug. 31	8,240	2.14	476,000	64.5	27.1	6.4	.7	.7	.6
Sept. 4	12,300	5.02	1,670,000	53.0	22.9	17.0	3.8	2.7	.6
Sept. 7	7,670	2.00	414,000	67.5	23.8	6.0	1.0	1.2	.5
Sept. 11	6,270	.72	122,000	22.4	24.9	25.9	14.6	11.1	1.1
Sept. 14	6,490	.65	114,000	60.0	29.6	8.3	1.0	.8	.3
Sept. 18	6,370	.33	56,800	36.4	19.1	14.3	5.7	22.5	2.0
Sept. 21	5,480	.21	31,100	44.3	27.5	17.9	4.4	5.0	.9
Sept. 25	4,360	.12	14,100	61.1	27.8	7.7	1.1	1.5	.8
Sept. 27	7,420	.24	48,100	67.5	26.6	4.2	.7	.8	.2
Sept. 30, 8:50 a. m.	18,100	4.14	2,020,000	{ 69.2	25.4	3.9	.5	.5	.5
Sept. 30, 4:15 p. m.				55.2	34.2	6.6	1.7	1.6	.7
Oct. 1	15,800	5.09	2,170,000	60.3	29.5	5.9	1.4	1.5	1.4
Oct. 6	7,490	.88	178,000	47.0	43.9	5.5	1.3	1.4	.9
Oct. 9	6,550	.45	79,600	60.3	31.4	5.8	1.1	.8	.6
Oct. 12	5,820	.26	40,900	56.5	34.6	6.1	1.1	1.3	.4
Oct. 16	5,010	.14	18,900	54.2	33.2	9.7	1.0	1.2	.7
Oct. 19	4,660	.11	13,800	51.2	38.9	5.9	1.5	1.6	.9
Oct. 24	5,440	.12	17,600	50.6	41.4	5.5	.8	1.1	.6
Oct. 27	5,100	.16	22,000	55.4	32.7	10.4	.9	.3	.3
Nov. 2	5,230	.20	28,200	4.5	86.3	6.8	1.1	.7	.6
Nov. 7	5,360	.12	17,400	10.9	72.6	11.3	2.6	1.6	1.0
Nov. 10	5,680	.12	18,400	10.1	70.7	13.1	2.7	2.3	1.1
Nov. 13	5,560	.12	18,000	15.4	64.6	14.0	3.0	2.0	1.0
Nov. 16	6,020	.11	17,900	48.2	30.0	17.2	3.4	.8	.5
Nov. 20	5,610	.09	13,600	13.9	66.0	13.7	3.0	1.9	1.5
Nov. 23	5,790	.09	14,100	18.7	59.7	14.4	3.3	2.9	1.0
Nov. 27	5,900	.10	15,900	24.8	54.2	14.1	3.8	1.2	1.7
Nov. 30	5,650	.15	22,900	9.2	77.7	8.9	2.2	1.4	.7
Dec. 4	5,820	.10	15,700	19.3	61.1	14.0	2.8	1.9	.9
Dec. 7	6,230	.22	37,000	4.2	71.3	16.8	4.3	1.8	1.6
Dec. 11	4,970	.08	10,700	15.3	69.1	10.3	2.8	1.4	1.0
Dec. 14	5,010	.10	13,500	17.4	60.9	11.4	6.5	1.0	2.8
Dec. 17	4,790	.09	11,600	24.5	58.5	12.6	3.1	.9	.4
Dec. 21	4,600	.08	9,940	21.6	62.2	10.5	3.5	1.1	1.1
Dec. 25	3,280	.05	4,430	50.1	35.2	9.8	2.8	1.0	1.0
Dec. 29	3,560	.07	6,730	17.8	67.5	9.2	2.5	2.1	.9
<i>1936</i>									
Jan. 1	3,750	.08	8,100	28.7	56.5	9.8	2.6	1.3	1.0
Jan. 4	4,310	.06	6,980	39.8	42.3	12.4	2.2	1.8	1.5
Jan. 8	4,220	.07	7,980	36.0	44.8	13.6	2.9	1.7	1.0
Jan. 11	4,310	.05	5,820	45.7	35.8	13.2	2.8	1.2	1.3
Jan. 15	4,400	.06	7,130	37.4	41.0	16.0	2.5	2.1	1.0
Jan. 18	5,040	.06	8,160	30.8	40.2	22.3	3.4	2.0	1.3
Jan. 22	5,040	.07	9,530	28.3	48.7	17.6	5.2	3.4	1.5
Jan. 24	4,780	.05	6,450	29.9	55.4	10.2	1.7	1.3	1.5
Jan. 29	4,670	.06	7,570	31.7	47.2	13.8	2.8	2.6	1.9

TABLE 23.—*Mechanical analyses of suspended sediment in samples collected in the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 5, 1935, to Sept. 30, 1941—Continued*

Date of collection	Mean daily discharge (sec.-ft.)	Suspended sediment							
		Mean daily concentration (percent)	Tons per day	Percent in indicated size range					
				<0.005 mm.	0.005-0.020 mm.	0.020-0.050 mm.	0.050-0.074 mm.	0.074-0.149 mm.	>0.149 mm.
<i>1936</i>									
Feb. 1	5,390	0.08	11,600	36.8	32.0	22.6	5.4	1.8	1.4
Feb. 5	5,580	.17	25,600	14.6	58.3	19.7	4.4	2.0	1.0
Feb. 8	4,910	.17	22,500	11.6	70.8	13.0	2.6	1.0	1.0
Feb. 12	4,650	.10	12,600	15.0	47.6	25.8	9.0	1.7	.9
Feb. 15	4,970	.07	9,390	27.6	47.8	17.2	4.3	2.1	1.0
Feb. 19	6,510	.16	28,100	8.3	53.2	24.6	8.3	3.8	1.8
Feb. 22	6,480	.16	28,000	4.6	69.3	17.1	5.3	2.5	1.2
Feb. 26	6,730	.32	58,100	43.0	29.3	19.6	4.3	2.9	.9
Feb. 29	7,780	.35	73,500	6.5	65.6	18.4	5.7	2.9	.8
Mar. 4	5,970	.30	48,400	2.4	85.6	8.0	2.4	1.0	.6
Mar. 7	8,770	.42	99,500	1.8	59.6	21.6	13.0	3.2	.8
Mar. 11	8,270	1.10	246,000	56.4	28.3	9.5	3.4	1.9	.4
Mar. 14	9,140	.77	190,000	1.1	74.6	13.1	7.6	3.1	.5
Mar. 18	9,250	.62	155,000	4.6	61.6	15.3	12.2	4.4	1.8
Mar. 22	8,630	.45	105,000	3.3	76.7	12.0	5.6	1.9	1.0
Mar. 25	8,470	.34	77,800	6.6	64.1	11.8	9.2	5.5	2.7
Mar. 28	7,850	.37	78,400	6.3	66.1	13.0	9.0	4.7	.9
Apr. 1	6,740	.35	63,700	3.4	74.5	11.4	7.1	2.5	1.0
Apr. 4	7,840	.44	93,100	2.7	79.6	11.3	4.7	1.4	.3
Apr. 8	7,820	.38	80,200	4.1	67.4	12.0	10.0	5.3	1.2
Apr. 11	6,720	.26	47,200	6.3	62.8	14.3	11.2	4.5	.8
Apr. 15	11,500	1.09	338,000	1.1	21.9	9.3	11.2	36.0	20.5
Apr. 18	21,600	1.68	980,000	18.6	15.1	20.3	24.2	18.9	2.8
Apr. 22	35,400	1.57	1,500,000	31.0	24.1	17.1	20.0	6.8	1.0
Apr. 25	43,100	1.43	1,660,000	12.0	10.9	13.2	16.4	35.5	11.9
Apr. 29	51,100	1.32	1,820,000	14.4	13.1	13.6	13.8	33.5	11.6
May 2	51,100	1.01	1,390,000	12.8	11.0	12.7	12.1	37.1	14.4
May 6	45,900	.67	830,000	12.1	10.1	12.2	13.3	35.4	16.9
May 9	66,400	1.06	1,900,000	6.8	6.4	8.1	12.0	36.6	30.1
May 13	46,200	.54	674,000	10.7	10.9	12.9	13.6	30.5	21.3
May 16	44,000	.44	523,000	11.3	10.4	13.2	18.7	24.1	22.3
May 21	71,800	.59	1,140,000	8.7	9.0	12.5	15.5	33.0	21.2
May 24	75,100	.58	1,180,000	10.4	10.7	12.3	16.3	33.1	17.2
May 27	66,100	.54	964,000	6.1	5.5	7.7	13.9	33.4	33.4
May 30	65,400	.50	883,000	4.6	4.1	7.3	12.1	37.6	34.3
June 2	64,900	.54	946,000	5.4	4.7	8.5	13.5	32.2	35.7
June 6	60,300	.50	814,000	7.8	6.6	9.0	13.9	30.5	32.2
June 8	50,000	.40	540,000	8.6	7.4	9.3	12.1	31.0	31.6
June 12	47,200	.38	484,000	8.6	8.0	9.1	9.1	42.7	22.5
June 16	45,900	.33	409,000	6.5	5.5	8.4	12.6	28.0	39.0
June 20	40,900	.30	331,000	6.9	6.6	9.8	16.0	35.7	25.0
June 24	34,800	.28	263,000	6.3	6.3	11.5	12.5	43.3	20.1
June 27	30,100	.19	154,000	9.2	9.5	16.5	10.1	31.7	14.0
July 2	24,100	.17	111,000	17.3	14.0	18.3	18.7	21.4	10.3
July 4	22,400	.16	96,800	21.1	17.9	16.2	12.6	22.4	9.8
July 8	16,600	.12	53,800	19.2	28.6	15.9	12.9	13.7	9.6
July 11	15,500	.12	50,200	22.5	32.3	19.2	12.5	8.5	4.7
July 13	29,800	.82	660,000	21.3	19.7	29.6	16.6	7.7	5.1
July 14	29,200	4.72	3,720,000	5.4	59.9	17.1	9.3	5.9	2.4
July 17	16,900	3.62	1,650,000	17.8	66.6	10.7	2.7	1.3	.9
July 18	16,300	2.40	1,060,000	28.6	55.1	10.8	2.9	2.0	.6
July 22	15,200	.91	373,000	50.4	29.9	14.8	3.1	1.4	.4
July 25	12,900	.74	258,000	32.9	43.1	15.6	6.1	1.6	.7
July 29	11,400	1.24	382,000	26.0	53.1	13.7	5.4	1.3	.5
Aug. 1	9,800	1.13	299,000	45.7	43.4	8.6	1.5	0.7	0.3
Aug. 5	15,300	3.14	1,300,000	39.7	26.1	21.6	10.0	2.0	.6
Aug. 7	29,700	5.35	4,290,000	11.3	40.2	16.3	14.1	16.0	2.2
Aug. 10	27,200	3.99	2,930,000	26.6	36.3	14.2	10.8	10.1	1.9
Aug. 12	21,000	2.73	1,550,000	9.1	63.6	12.6	6.3	6.4	2.0
Aug. 15	15,200	2.22	911,000	23.6	49.9	15.3	6.7	3.6	.9
Aug. 18	12,800	1.15	397,000	51.5	27.9	10.1	5.0	4.3	1.1
Aug. 24	14,900	2.13	857,000	8.1	60.9	14.3	9.9	5.9	.8
Aug. 29	9,010	.98	238,000	29.1	56.7	7.8	2.8	2.6	.9

## QUANTITIES OF SUSPENDED SEDIMENT

153

TABLE 23.—*Mechanical analyses of suspended sediment in samples collected in the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 5, 1935, to Sept. 30, 1941—Continued*

Date of collection	Mean daily discharge (sec.-ft.)	Suspended sediment							
		Mean daily concentration (percent)	Tons per day	Percent in indicated size range					
				<0.005 mm.	0.005–0.020 mm.	0.020–0.050 mm.	0.050–0.074 mm.	0.074–0.149 mm.	
<i>1936</i>									
Sept. 3	21,500	7.74	4,490,000	4.7	51.1	15.6	13.5	12.8	2.3
Sept. 6	14,900	3.43	1,380,000	4.2	66.8	13.2	7.0	7.3	1.5
Sept. 9	10,800	2.40	700,000	5.6	74.9	10.0	4.5	4.3	.7
Sept. 12	8,830	1.38	329,000	11.6	74.7	8.1	3.9	.6	1.1
Sept. 16	8,600	1.49	346,000	8.7	73.4	9.2	4.7	3.4	.7
Sept. 19	7,870	.80	170,000	12.7	71.5	7.8	4.4	2.6	.9
Sept. 23	8,220	2.08	462,000	5.7	67.9	13.8	7.3	4.8	.5
Sept. 26	7,870	1.35	287,000	9.4	66.6	12.2	7.9	3.2	.6
Sept. 30	5,280	.91	130,000	10.2	76.7	6.6	3.6	2.1	.7
Oct. 2	5,300	.50	71,600	6.4	75.1	7.8	4.6	4.6	1.5
Oct. 8	5,580	.31	46,700	7.9	70.6	11.1	5.7	3.5	1.2
Oct. 10	5,520	.26	38,800	8.4	56.1	12.5	19.1	10.3	2.6
Oct. 13	5,740	.24	37,200	14.3	56.4	14.1	6.5	6.8	1.9
Oct. 17	5,650	.21	32,000	5.6	56.6	14.4	9.7	10.7	3.0
Oct. 21	5,870	.24	38,000	3.6	41.7	17.0	19.8	16.2	1.7
Oct. 24	6,520	.55	96,800	5.8	65.7	13.1	7.1	6.7	1.6
Oct. 28	6,980	.49	92,300	4.3	58.8	12.8	9.2	12.9	2.0
Oct. 31	6,830	.40	73,800	5.7	61.1	11.8	7.6	11.3	2.5
Nov. 4	9,670	1.91	499,000	48.4	25.6	11.1	6.5	7.7	.7
Nov. 7	8,710	.95	223,000	3.1	67.7	11.2	8.9	1.3	7.8
Nov. 10	7,570	.69	141,000	3.3	72.7	9.5	6.0	7.1	1.4
Nov. 14	7,510	.36	73,000	7.4	69.6	15.0	5.5	1.9	.6
Nov. 17	7,120	.33	63,400	2.6	47.9	15.2	11.0	19.3	4.0
Nov. 21	7,070	.19	36,300	4.4	62.1	20.5	10.2	2.4	.4
Nov. 24	7,180	.20	38,800	5.8	56.1	24.4	11.4	1.8	.5
Nov. 28	6,990	.16	30,200	6.5	53.9	23.1	12.0	3.9	.6
Dec. 1	6,600	.13	23,200	21.8	37.6	22.3	11.7	4.7	1.9
Dec. 5	5,960	.16	25,700	19.5	31.1	19.0	13.0	13.6	3.8
Dec. 8	5,560	.11	16,500	19.9	22.3	18.0	12.2	18.2	9.4
Dec. 12	4,880	.11	14,500	25.8	38.2	20.3	7.9	6.3	1.5
Dec. 15	4,210	.08	9,090	35.7	28.6	17.5	10.5	6.2	1.5
Dec. 19	4,580	.08	9,890	28.6	42.0	17.0	8.1	3.3	1.0
Dec. 22	5,700	.08	12,300	36.7	36.6	20.0	4.6	1.4	.7
Dec. 26	6,020	.12	19,500	22.1	28.8	26.3	12.1	9.2	1.5
Dec. 29	6,410	.11	19,000	21.3	24.6	27.9	15.4	9.1	1.7
<i>1937</i>									
Jan. 2, 5, 9, 12, 16, 19, 23, 27, 30	13,660	1.06	1,6,690	3.6	39.5	48.4	3.2	2.6	2.7
Feb. 2, 6	14,850	1.07	19,220	7.9	43.2	39.3	5.3	2.5	1.8
Feb. 9	10,000	.46	124,000	24.2	47.0	6.4	15.3	6.3	.8
Feb. 10	17,100	4.32	1,990,000	20.7	24.2	14.0	14.6	21.6	4.9
Feb. 13	8,720	.95	224,000	47.3	33.0	14.3	3.0	1.8	.6
Feb. 16	8,930	.44	106,000	31.6	42.7	17.8	5.2	2.3	.4
Feb. 17	18,200	2.34	1,150,000	21.4	16.4	26.2	20.8	14.0	1.2
Feb. 20	13,400	1.88	680,000	44.8	26.4	16.2	8.5	3.6	.5
Feb. 23	9,890	1.03	275,000	45.0	36.2	12.0	5.0	1.4	.4
Feb. 27	7,890	.45	95,900	48.3	32.2	10.4	6.4	2.2	.5
Mar. 2, 6, 9	18,200	1.49	1,109,000	47.8	25.8	14.2	6.9	4.0	1.3
Mar. 13	10,800	.95	277,000	42.5	22.8	17.5	12.2	4.1	.9
Mar. 16	14,600	1.75	690,000	35.6	20.7	14.7	13.5	11.8	3.7
Mar. 20	22,000	2.87	1,700,000	18.9	33.8	11.8	12.9	17.3	5.3
Mar. 23	20,100	2.26	1,230,000	19.2	16.5	16.3	16.8	22.0	9.2
Mar. 27	16,300	1.53	673,000	56.3	12.0	9.4	8.8	10.5	3.0
Mar. 30	13,100	.99	350,000	38.2	15.3	13.6	12.2	15.4	5.3
Apr. 3	10,800	.62	181,000	37.0	22.0	13.9	9.5	13.6	4.0
Apr. 6	15,300	1.45	599,000	26.2	15.8	14.2	13.8	21.1	8.9
Apr. 10	15,000	1.18	478,000	32.9	15.7	16.3	15.4	17.0	2.7
Apr. 13	19,200	1.80	933,000	23.5	14.0	20.0	19.4	14.9	8.2
Apr. 17, 19, 21–22, 25–26	140,400	1.24	1,560,000	15.8	11.8	18.3	16.1	26.2	11.8
Apr. 27	36,500	1.65	1,630,000	15.2	11.5	15.7	15.4	28.1	14.1
Apr. 28–30	132,600	1.40	1,230,000	15.6	11.8	15.7	14.6	25.0	17.3

1 Mean for days on which size samples were collected.

TABLE 23.—*Mechanical analyses of suspended sediment in samples collected in the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 5, 1935, to Sept. 30, 1941—Continued*

Date of collection	Mean daily discharge (sec.-ft.)	Mean daily concentration (percent)	Tons per day	Suspended sediment						
				Percent in indicated size range						
				<0.005 mm.	0.005-0.020 mm.	0.020-0.050 mm.	0.050-0.074 mm.	0.074-0.149 mm.	>0.149 mm.	
<i>1937</i>										
May 1	36,000	1.46	1,420,000	12.4	10.1	16.3	18.5	30.7	12.0	
May 2-3, 5	29,000	.89	701,000	13.8	10.2	14.3	18.9	26.1	16.7	
May 7	35,700	1.00	964,000	7.6	6.8	12.6	17.6	30.6	24.8	
May 9	43,600	1.28	1,510,000	7.2	6.1	12.1	17.1	32.2	25.3	
May 12	57,200	1.56	2,410,000	11.3	10.9	19.1	15.6	28.2	14.9	
May 13	65,400	1.92	3,390,000	9.6	10.1	19.4	17.5	29.9	13.5	
May 16, 18-20	177,900	1.21	2,540,000	11.2	11.0	17.4	13.6	28.3	18.5	
May 22-25, 27-30	164,100	1.82	1,460,000	7.1	6.7	13.1	13.7	26.3	33.1	
June 2-5, 7, 9-10	155,200	1.71	1,080,000	8.9	6.6	12.7	14.4	28.5	28.9	
June 11-12, 14, 17	135,800	1.44	1,430,000	9.4	7.8	13.0	15.7	25.7	28.4	
June 22, 27-29	132,100	1.45	1,390,000	12.2	10.7	14.7	16.0	24.7	21.7	
July 1	30,800	.40	333,000	13.8	12.8	12.5	23.4	27.0	10.5	
July 2	28,800	1.00	778,000	36.9	24.5	16.7	7.5	8.9	5.5	
July 9	18,700	.38	192,000	38.3	23.5	12.0	6.8	11.0	8.4	
July 10-11	19,000	1.19	609,000	46.8	27.1	15.6	4.0	4.9	1.6	
July 13	27,100	2.47	1,810,000	43.8	22.9	17.5	6.9	5.9	3.0	
July 14	27,200	2.52	1,850,000	41.8	22.9	18.4	8.1	6.0	2.8	
July 17	30,900	2.73	2,280,000	36.3	22.7	13.6	8.0	11.9	7.5	
July 20, 22	125,000	2.16	1,480,000	40.5	13.6	28.1	7.1	7.7	3.0	
July 24, 26	15,200	1.25	520,000	50.1	18.9	23.6	3.0	2.9	1.5	
July 28	11,300	.71	217,000	62.1	20.1	14.2	1.6	1.4	.6	
July 31	14,500	1.32	517,000	51.8	17.9	16.3	6.5	5.2	2.3	
Aug. 3	11,100	2.14	641,000	58.1	29.3	9.8	1.2	1.1	0.5	
Aug. 5	10,100	1.60	436,000	61.9	27.7	8.2	.9	.9	.4	
Aug. 7-8, 10, 12, 15-16	17,640	1.72	1,150,000	60.0	29.7	8.8	.7	.6	.2	
Aug. 18, 21, 23, 26, 28, 30	14,580	1.27	1,33,200	76.2	16.8	5.8	.2	.5	.5	
Sept. 1	9,760	2.49	656,000	64.5	23.5	9.0	.9	1.5	.6	
Sept. 3	14,700	4.77	1,890,000	48.1	22.3	17.9	7.5	3.2	1.0	
Sept. 4-6	13,900	2.96	1,110,000	48.3	23.3	15.1	3.7	2.9	.8	
Sept. 9, 11	8,130	2.56	1,564,000	66.1	23.8	8.1	1.0	.7	.3	
Sept. 14	7,340	1.41	279,000	62.4	29.3	6.9	.6	.6	.2	
Sept. 17, 19, 23	14,970	1.79	1,107,000	68.7	25.7	4.9	.2	.4	.1	
Sept. 26	4,370	.91	107,000	72.1	21.7	5.6	.1	.4	.1	
Sept. 29	4,220	.40	43,300	60.5	33.3	5.2	.3	.5	.2	
Sept. 30	10,400	1.13	233,000	38.2	32.1	21.9	5.4	2.0	.4	
Oct. 1	13,900	5.44	2,040,000	29.2	16.4	16.8	10.5	26.2	.9	
Oct. 2	23,100	5.38	3,360,000	25.9	14.4	19.6	21.5	17.1	1.5	
Oct. 4	10,500	7.54	2,140,000	62.2	12.0	17.1	4.1	3.5	1.1 A	
Oct. 7	5,960	2.73	439,000	77.2	14.7	6.4	.8	.6	.3	
Oct. 10	5,680	1.08	166,000	81.8	11.5	4.8	1.0	.7	.2	
Oct. 13	5,350	.51	73,700	60.5	28.3	8.7	1.4	.9	.2	
Oct. 16, 19	5,370	1.26	1,38,200	54.8	30.8	11.0	1.6	1.3	.5	
Oct. 22, 25, 27	7,790	1.76	1,150,000	52.7	24.1	15.6	3.4	3.5	.7	
Nov. 2	7,060	.53	101,000	47.4	32.2	12.3	4.7	2.6	.8	
Nov. 6, 9, 13, 17, 22, 26, 29	16,670	1.23	1,42,000	36.3	20.1	20.6	9.9	8.4	4.7	
Dec. 3, 7, 11	16,330	1.14	1,23,400	33.4	20.0	23.8	12.8	7.1	2.9	
Dec. 14	8,600	.75	174,000	7.7	9.0	42.0	29.0	11.3	1.0	
Dec. 18, 23	17,800	1.38	1,79,300	27.7	17.0	24.4	18.2	10.6	2.1	
Dec. 27	5,790	.25	39,100	37.5	34.6	12.1	8.6	5.2	2.0	
Dec. 31	5,130	.14	19,400	51.4	26.0	11.5	6.0	3.5	1.6	
<i>1938</i>										
Jan. 4, 8, 12, 16	15,070	1.10	1,13,800	41.7	23.5	16.6	8.4	7.9	1.9	
Jan. 20	5,910	.15	23,900	23.2	16.9	18.6	20.2	15.8	5.3	
Jan. 24	6,700	.23	41,600	28.7	19.3	22.6	15.2	11.3	2.9	
Jan. 28, 31	15,180	1.12	17,000	38.9	22.9	18.1	11.2	6.6	2.3	

<sup>1</sup> Mean for days on which size samples were collected.

TABLE 23.—*Mechanical analyses of suspended sediment in samples collected in the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 5, 1935, to Sept. 30, 1941—Continued*

Date of collection	Mean daily discharge (sec.-ft.)	Suspended sediment							
		Mean daily concentration (percent)	Tons per day	Percent in indicated size range					
				<0.005 mm.	0.005–0.020 mm.	0.020–0.050 mm.	0.050–0.074 mm.	0.074–0.149 mm.	>0.149 mm.
<i>1938</i>									
Feb. 3, 8, 12	5,880	1.16	1 25,500	25.4	17.4	21.0	20.4	13.3	2.5
Feb. 15	7,570	.42	85,800	7.3	13.3	27.0	40.9	8.8	2.7
Feb. 18	8,340	.69	155,000	37.0	9.1	19.7	23.7	9.5	1.0
Feb. 21	7,420	.45	90,200	35.2	14.6	16.7	22.3	9.5	1.7
Feb. 25	6,010	.23	37,300	14.1	44.5	13.6	14.1	10.4	3.3
Feb. 28	6,010	.20	32,500	39.2	22.5	14.1	15.2	7.6	1.4
Mar. 3	11,200	2.91	880,000	17.8	33.2	16.4	18.4	13.4	.8
Mar. 5	39,100	8.76	9,250,000	3.2	29.2	15.9	14.1	28.5	9.1
Mar. 8	20,700	2.88	1,610,000	7.8	39.9	18.7	10.3	20.2	3.1
Mar. 14, 18	1 11,800	1 1.12	1 354,000	34.6	29.5	13.9	10.2	9.8	2.0
Mar. 21, 25, 29	1 12,200	1 .77	1 256,000	21.0	17.7	14.2	17.1	26.1	3.9
Apr. 2	13,400	.90	326,000	6.1	36.8	17.0	19.6	18.9	1.6
Apr. 6, 9, 13	1 10,200	1 .51	1 140,000	28.3	14.6	13.4	15.3	22.9	5.5
Apr. 16	17,900	1.18	570,000	10.1	10.9	16.0	18.2	42.2	2.6
Apr. 21	23,400	1.72	1,090,000	3.2	23.3	16.6	18.6	34.8	3.5
Apr. 22	36,600	2.38	2,350,000	.8	24.0	14.8	19.5	30.7	10.2
Apr. 23	43,400	2.94	3,450,000	4.8	28.5	13.7	19.6	21.3	12.1
Apr. 26–27	1 59,200	1 2.69	1 4,300,000	6.7	23.5	14.1	16.1	27.6	12.0
Apr. 30	57,400	2.22	3,440,000	2.4	22.1	13.4	14.7	22.1	25.3
May 4–5, 7, 10	1 55,500	1 1.30	1 2,020,000	4.5	15.8	16.6	15.6	24.5	23.0
May 16–17	1 32,300	1 .66	1 592,000	.9	16.6	14.7	24.2	25.1	18.5
May 18–19	1 57,600	1 1.38	1 2,160,000	.7	9.2	9.5	16.4	28.6	35.6
May 24, 28, 30–31	1 65,600	1 .96	1 1,720,000	.9	15.0	11.3	13.9	27.8	31.1
June 1, 8, 11, 13, 15	1 84,800	1 .73	1 1,680,000	.7	8.8	5.3	9.9	35.1	40.2
June 18, 21, 23, 25, 29	1 65,700	1 .53	1 956,000	3.6	10.9	9.9	12.3	25.2	38.1
June 30	64,900	.73	1 280,000	2.7	42.7	15.5	10.0	14.4	14.7
July 2	60,200	.96	1 560,000	3.7	18.6	24.7	13.9	13.8	25.3
July 5–6	1 48,200	1 .44	1 580,000	3.7	29.3	19.0	17.0	3.3	27.7
July 9, 11, 13, 18, 20	1 26,500	1 .21	1 162,000	4.0	27.9	19.1	13.4	15.8	19.8
July 26, 30	1 13,300	1 .16	1 60,200	6.3	71.2	12.7	4.3	3.5	2.0
Aug. 1, 6, 9	1 10,600	1 .13	1 36,700	7.5	57.7	21.1	6.9	5.0	1.8
Aug. 10	10,200	1 .24	341,000	2.0	81.4	13.8	1.5	.9	.4
Aug. 12	9,030	.84	205,000	3.4	84.4	9.6	1.4	.9	.3
Aug. 14	12,200	.38	125,000	3.3	65.4	22.3	5.7	2.7	.6
Aug. 17	9,680	.81	212,000	1.7	90.2	6.5	.5	.8	.3
Aug. 20	9,510	1.92	493,000	3.8	86.6	8.3	.2	.8	.3
Aug. 23	7,070	.64	122,000	2.8	89.3	7.0	.2	.4	.3
Aug. 27	5,570	.34	51,100	2.6	91.5	5.1	.2	.4	.2
Aug. 30	5,050	.20	27,300	8.1	86.5	4.0	.2	.8	.4
Sept. 2	6,230	.14	23,500	15.7	74.8	6.1	1.4	1.4	.6
Sept. 3	8,400	.62	141,000	1.9	83.7	12.1	1.2	.7	.4
Sept. 5	19,300	3.04	1,580,000	1.9	74.4	13.4	7.5	2.4	.4
Sept. 9	21,300	2.65	1,520,000	3.2	79.4	11.1	3.5	2.2	.6
Sept. 12	22,500	3.01	1,830,000	1.1	80.9	7.0	5.8	4.2	1.0
Sept. 17	19,600	2.20	1,160,000	3.2	79.0	6.7	5.3	4.9	.9
Sept. 24, 27	1 10,400	1 .56	1 163,000	1.1	90.0	4.8	1.8	1.9	.4
Sept. 30	8,550	.20	46,200	4.5	75.7	13.3	3.1	2.2	1.2
Oct. 2, 6, 9, 12	1 8,470	1 .22	1 57,200	1.2	71.0	15.1	5.6	5.7	1.4
Oct. 17, 20	1 11,300	1 .69	1 212,000	1.8	79.6	10.9	3.1	3.5	1.1
Oct. 25	10,800	.48	140,000	3.6	78.5	11.6	3.8	1.7	.8
Oct. 28, 31	1 9,520	1 .33	1 84,700	2.0	77.4	11.7	4.3	2.7	1.9
Nov. 4, 8, 11, 14, 17	1 8,930	1 .14	1 33,800	1.4	69.7	16.4	6.1	4.5	1.9
Nov. 20, 23, 26, 29	1 7,600	1 .07	1 14,100	5.5	61.9	18.5	7.1	4.2	2.8
Dec. 4, 8, 11, 14, 17, 20, 23, 26, 29	1 7,250	1 .06	1 13,000	1.5	66.3	19.6	7.4	4.0	1.2

<sup>1</sup> Mean for days on which size samples were collected.

TABLE 23.—*Mechanical analyses of suspended sediment in samples collected in the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 5, 1935, to Sept. 30, 1941—Continued*

Date of collection	Mean daily discharge (sec.-ft.)	Suspended sediment							
		Mean daily concentration (percent)	Tons per day	Percent in indicated size range					
				<0.005 mm.	0.005-0.020 mm.	0.020-0.050 mm.	0.050-0.074 mm.	0.074-0.149 mm.	>0.149 mm.
1939									
Jan. 1, 4, 7, 10, 13, 16, 19, 22, 25, 28, 30	1 5,880	1 0.04	1 6,130	3.1	65.8	20.9	6.7	2.6	0.9
Feb. 2, 5, 8, 11, 14, 17, 20, 23	1 5,660	1 .04	1 5,020	14.1	38.1	36.9	7.3	2.4	1.2
Feb. 26	5,910	.08	12,800	11.3	75.7	7.0	3.7	1.4	.9
Mar. 1, 5, 8, 11, 14	1 6,350	1 .07	1 12,600	3.3	60.2	24.0	9.6	2.2	.7
Mar. 16	9,240	.28	69,900	3.5	51.5	25.9	12.9	4.6	1.6
Mar. 18	10,400	.54	152,000	1.7	61.8	18.0	13.2	4.6	.7
Mar. 21	11,200	.89	269,000	.9	70.8	10.8	12.1	4.6	.8
Mar. 23	21,100	1.82	1,040,000	.4	35.0	21.6	26.4	15.0	1.6
Mar. 24	27,400	1.84	1,360,000	.5	31.4	17.0	25.7	22.5	2.9
Mar. 26	28,500	2.06	1,590,000	1.2	35.9	16.3	19.1	23.7	3.8
Mar. 28	27,000	1.83	1,330,000	.6	56.6	12.4	11.3	15.7	3.4
Mar. 31	27,800	1.45	1,090,000	.4	45.9	10.1	10.6	25.5	7.5
Apr. 2	23,700	1.10	704,000	.8	51.2	13.2	11.8	17.7	5.3
Apr. 5	19,500	.88	463,000	.9	52.0	13.2	11.0	16.2	6.7
Apr. 8	25,400	1.36	935,000	.7	45.7	14.1	14.1	22.4	3.0
Apr. 11	22,600	.83	506,000	1.1	39.3	16.6	13.9	23.8	5.3
Apr. 14	21,500	.58	337,000	1.3	31.9	18.1	15.3	28.9	4.5
Apr. 20, 23, 26	1 16,400	1 .33	1 145,000	1.3	23.7	19.0	16.7	31.6	7.7
Apr. 29	21,000	.42	238,000	3.9	16.9	22.9	20.1	31.7	4.5
May 1	22,500	.53	322,000	3.7	25.9	24.2	20.5	22.5	3.2
May 3	29,600	.84	671,000	1.7	10.6	16.1	22.1	44.0	5.5
May 4	33,400	.94	848,000	1.7	14.5	22.1	21.4	31.8	8.5
May 7	40,600	1.12	1,230,000	6.6	13.0	17.1	16.4	34.5	12.4
May 9	45,300	1.17	1,430,000	2.2	13.6	16.7	17.0	34.8	15.7
May 13	40,100	.77	834,000	5.8	10.3	16.3	16.7	28.5	22.4
May 16, 18, 22	1 39,000	1 .65	1 686,000	.5	13.3	16.2	19.1	31.2	19.7
May 25, 28, 30	1 41,700	1 .61	1 699,000	1.1	7.5	18.6	19.3	32.8	20.7
June 1, 5, 8, 11, 13	1 36,300	1 .44	1 435,000	.5	14.8	16.3	21.1	27.4	19.9
June 15, 18, 20, 23, 26, 29	1 21,600	1 .20	1 127,000	.9	14.8	14.7	19.8	27.9	21.9
July 2, 5, 8, 11, 14	1 10,100	1 .04	1 12,200	4.0	41.6	22.1	15.8	10.7	5.8
July 17, 20, 23, 26	1 5,740	1 .02	1 3,100	28.5	41.4	19.0	6.4	3.1	1.6
July 29, Aug. 1, 4, 8	1 4,180	1 .01	1 1,120	29.9	43.1	15.6	2.8	6.3	2.3
Aug. 11, 15, 18, 21	1 4,520	1 .16	1 19,100	1.2	91.1	6.9	.3	.3	.2
Aug. 24, 27, 30, Sept. 2	1 3,100	1 .16	1 14,400	1.3	86.6	11.6	.2	.2	.1
Sept. 5	5,140	.68	94,400	1.6	88.1	9.4	.3	.4	.2
Sept. 7	8,540	1.65	380,000	.9	91.1	6.7	.6	.5	.2
Sept. 8	10,300	1.84	512,000	2.4	87.9	6.6	1.5	1.3	.3
Sept. 11	13,200	1.58	563,000	.8	77.9	13.8	3.6	2.7	1.2
Sept. 13	17,300	4.66	2,180,000	.4	86.3	9.2	2.0	1.5	.6
Sept. 14	25,200	6.37	4,330,000	1.0	61.0	17.7	12.4	6.8	1.1
Sept. 15	18,100	5.70	2,790,000	1.9	64.0	19.2	10.1	4.1	.7
Sept. 16	14,800	3.82	1,530,000	2.5	72.8	15.9	5.6	2.5	.7
Sept. 18	12,600	2.36	803,000	3.1	64.3	23.8	4.3	2.9	1.6
Sept. 21	9,970	1.58	425,000	3.8	70.7	21.3	2.4	1.5	.3
Sept. 24	7,720	.99	206,000	1.2	85.5	11.2	1.2	.7	.2
Sept. 27	6,300	.49	83,300	2.6	87.2	8.3	1.2	.5	.2
Sept. 29, Oct. 2, 5, 8, 11	1 6,350	1 .39	1 67,900	.7	94.6	2.8	.7	.9	.3
Oct. 14, 17, 20, 23, 26, 29	1 5,790	1 .16	1 24,500	.8	92.1	4.5	1.4	.9	.3
Nov. 1, 4, 7, 10, 13	1 5,460	1 .09	1 13,300	2.3	82.3	11.8	2.0	1.0	.6
Nov. 16, 19, 22, 25, 28	1 5,600	1 .08	1 16,000	2.9	73.5	17.7	3.4	1.7	.8
Dec. 1, 4, 7, 10, 13	1 5,270	1 .06	1 8,250	5.4	75.6	13.6	3.1	1.3	1.0
Dec. 16, 19, 22, 25, 28, 31	1 4,780	1 .07	1 9,110	4.4	72.8	17.1	2.9	1.9	.9

1 Mean for day on which size samples were collected.

TABLE 23.—*Mechanical analyses of suspended sediment in samples collected in the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 5, 1935, to Sept. 30, 1941—Continued*

Date of collection	Mean daily discharge (sec.-ft.)	Mean daily concentration (percent)	Tons per day	Suspended sediment						
				Percent in indicated size range						
				<0.005 mm.	0.005-0.020 mm.	0.020-0.050 mm.	0.050-0.074 mm.	0.074-0.149 mm.	>0.149 mm.	
<b>1940</b>										
Jan. 4, 7, 10, 13	1 4,730	1.07	1 9,320	5.5	72.2	15.7	3.1	2.3	1.2	
Jan. 15	7,170	.63	122,000	2.6	78.3	14.9	3.0	.8	.4	
Jan. 18	5,870	.21	33,300	5.4	77.9	13.4	1.8	.9	.6	
Jan. 21, 24, 27, 30, Feb. 2	1 4,030	1.07	1 8,280	5.1	76.2	13.9	3.1	1.3	.4	
Feb. 5	6,870	.18	33,400	10.0	65.0	18.0	4.8	1.5	.7	
Feb. 7	7,400	.57	114,000	1.3	85.4	9.8	2.1	1.0	.4	
Feb. 10	6,410	.34	58,800	3.6	80.5	12.5	1.9	1.1	.4	
Feb. 13, 16	1 5,460	1.17	1 25,200	3.4	83.2	9.4	2.8	.9	.3	
Feb. 19, 22, 25, 28	1 5,160	1.08	1 1,120	2.6	74.8	15.0	4.6	1.4	1.6	
Mar. 2	7,820	.24	50,700	5.2	53.7	23.6	13.8	3.0	.7	
Mar. 4	8,610	.95	221,000	.7	78.1	13.3	5.7	1.8	.4	
Mar. 7	6,990	.57	108,000	1.6	80.1	12.3	4.3	1.4	.3	
Mar. 9	9,000	.55	134,000	2.4	59.2	19.9	14.5	3.5	.5	
Mar. 12	8,520	.45	104,000	2.3	52.5	24.9	15.1	4.6	.6	
Mar. 15, 18, 21	1 7,250	1.25	1 50,600	1.5	69.0	14.9	10.0	3.5	1.1	
Mar. 24	6,500	.17	29,800	3.2	63.2	19.4	11.2	2.3	.7	
Mar. 27	6,940	.18	33,700	1.8	49.8	18.8	21.1	6.9	1.6	
Apr. 2, 9, 12, 21, 24	1 10,100	1.45	1 123,000	.2	41.3	14.3	25.4	16.1	2.7	
Apr. 25-26, 29	1 18,900	1 1.10	1 548,000	.4	28.4	20.5	31.5	18.0	1.2	
May 1-2, 5	1 22,000	1.89	1 536,000	.3	30.3	12.5	22.0	31.2	3.7	
May 10-11, 14, 17, 20	1 36,900	1 1.11	1 1,130,000	.3	21.0	11.7	14.9	37.4	14.7	
May 25	34,800	.64	601,000	.3	31.1	3.4	4.9	12.1	76.2	
May 28, 31	1 32,400	1.50	1 437,000	1.1	13.9	13.3	19.5	29.9	22.3	
June 3, 5, 8	1 38,500	1.63	1 661,000	.6	10.2	10.5	19.3	36.1	23.3	
June 10, 12	1 30,200	1.44	1 368,000	1.2	16.3	12.7	20.9	30.1	18.8	
June 15, 21, 25, 29	1 17,800	1.15	1 75,800	5.4	21.1	15.1	26.0	19.8	12.6	
July 2, 6	1 10,600	1.07	1 20,000	12.0	33.9	19.7	16.3	13.2	4.9	
July 9, 13, 17, 20, 23	1 6,180	1.10	1 19,800	2.0	81.3	12.4	2.6	1.3	.4	
July 27	4,660	.10	12,600	9.3	82.6	5.5	1.3	.7	.6	
July 29	5,740	2.93	454,000	1.1	87.0	10.7	.7	.3	.2	
July 31	5,340	1.24	179,000	1.4	86.4	11.2	.3	.4	.3	
Aug. 3	4,260	1.94	223,000	.7	96.6	2.3	.2	.1	.1	
Aug. 6	3,130	1.70	144,000	1.4	90.3	7.9	.2	.1	.1	
Aug. 14	2,350	.09	5,710	10.3	80.2	7.8	1.0	.3	.4	
Aug. 17	5,060	2.26	309,000	1.7	73.6	22.1	2.1	.3	.2	
Aug. 20	2,570	2.64	183,000	2.4	86.0	11.2	.2	.1	.1	
Aug. 24	4,940	4.93	658,000	1.0	57.8	11.2	.8	.1	29.1	
Aug. 29	7,130	4.65	895,000	1.8	83.4	10.0	3.4	1.2	.2	
Sept. 3	5,530	1.58	236,000	2.2	82.6	13.2	1.5	.4	.1	
Sept. 7	6,030	1.14	186,000	2.4	83.4	12.8	1.1	.2	.1	
Sept. 11	4,110	.60	66,600	2.2	78.0	18.0	1.3	.4	.1	
Sept. 14	7,270	.87	171,000	.8	86.9	10.1	1.8	.3	.1	
Sept. 15	8,980	4.83	1,170,000	1.5	74.2	13.5	8.0	2.4	.4	
Sept. 17	5,530	3.12	466,000	1.1	86.4	8.2	3.1	1.0	.2	
Sept. 19	11,300	4.97	1,520,000	.7	57.8	20.1	9.8	9.6	2.0	
Sept. 21	12,700	4.25	1,460,000	.7	68.4	10.8	11.2	8.4	.5	
Sept. 24	14,200	3.56	1,360,000	1.3	74.2	10.6	7.7	5.6	.6	
Sept. 26	11,200	3.28	992,000	1.0	78.3	10.3	5.6	4.3	.5	
Sept. 28	9,030	2.88	702,000	2.7	75.7	13.6	4.4	3.2	.4	
Oct. 1	22,300	8.06	4,850,000	2.2	49.0	15.6	16.1	15.5	1.6	
Oct. 3	19,200	4.61	2,390,000	2.9	52.8	21.8	11.5	9.3	1.7	
Oct. 5	16,900	2.86	1,300,000	3.3	71.4	13.6	7.1	3.9	.7	
Oct. 8	17,700	3.62	1,730,000	3.9	65.0	16.3	8.2	5.3	1.3	
Oct. 12	13,000	1.44	505,000	1.8	73.1	10.5	6.2	6.6	1.8	
Oct. 15	10,600	1.03	295,000	2.6	73.0	11.4	6.2	5.9	.9	
Oct. 19	8,520	.66	152,000	3.0	69.7	9.9	5.6	8.8	3.0	
Oct. 23	7,300	.34	67,000	3.2	25.0	57.4	6.1	6.0	2.3	
Oct. 29	7,070	.84	160,000	3.3	75.6	13.4	3.7	3.1	.9	

<sup>1</sup> Mean for days on which size samples were collected.

TABLE 23.—*Mechanical analyses of suspended sediment in samples collected in the Colorado River at gaging station near Grand Canyon, Ariz., Apr. 5, 1935, to Sept. 30, 1941—Continued*

Date of collection	Mean daily discharge (sec.-ft.)	Suspended sediment							
		Mean daily concentration (percent)	Tons per day	Percent in indicated size range					
				<0.005 mm.	0.005-0.020 mm.	0.020-0.050 mm.	0.050-0.074 mm.	0.074-0.149 mm.	>0.149 mm.
<i>1940</i>									
Nov. 9.....	6,760	.34	62,100	3.5	60.3	13.7	11.9	8.1	2.5
Nov. 12, 17, 19.....	1 6,450	1.20	1 34,700	4.8	54.4	14.1	9.9	12.3	4.5
Nov. 23.....	8,770	.99	234,000	2.2	62.5	9.4	9.6	14.0	2.3
Nov. 26.....	7,650	.76	157,000	2.8	65.8	8.4	8.7	11.2	3.1
Nov. 30.....	6,770	.31	56,700	5.3	63.0	9.4	7.7	10.5	4.1
Dec. 3, 7.....	1 6,140	1.21	1 34,800	4.2	41.2	10.2	13.0	24.5	6.9
Dec. 10, 14.....	1 6,990	1.24	1 46,400	3.9	28.0	16.8	17.1	22.5	11.7
Dec. 17.....	7,580	.62	127,000	2.5	42.2	10.5	14.0	22.5	8.3
Dec. 21.....	4,300	.24	27,900	7.9	74.4	10.8	2.7	3.0	1.2
Dec. 24.....	5,320	.50	71,800	3.6	86.3	2.7	3.8	2.6	1.0
Dec. 28.....	8,740	1.56	368,000	1.5	58.0	13.2	16.0	10.5	.8
Dec. 31.....	7,140	.84	162,000	2.3	73.5	7.9	8.4	6.5	1.4
<i>1941</i>									
Jan. 4.....	9,700	1.92	503,000	1.1	64.7	8.9	9.8	13.3	2.2
Jan. 14.....	7,590	3.44	705,000	1.1	68.6	11.0	8.0	10.0	1.3
Jan. 21.....	5,880	.52	82,600	1.5	65.9	5.5	7.6	13.0	6.5
Feb. 15.....	7,920	.89	190,000	.6	32.7	10.4	18.9	32.1	5.3
Feb. 25.....	16,100	2.17	943,000	.6	50.7	13.3	12.5	17.8	5.1
Mar. 1.....	13,600	1.58	580,000	1.5	63.0	12.1	11.1	11.2	1.1
Mar. 15.....	8,410	.48	109,000	1.6	56.2	9.4	12.7	16.7	3.4
Mar. 18.....	15,100	2.83	1,150,000	.7	60.9	9.8	10.4	15.0	3.2
Mar. 29.....	18,000	1.86	904,000	.7	39.1	13.6	15.0	21.4	10.2
Apr. 5.....	20,000	2.17	1,170,000	1.1	41.9	12.6	15.8	21.8	6.8
Apr. 26.....	20,500	.87	482,000	1.7	44.4	13.4	18.5	17.0	5.0
May 6.....	56,900	1.79	2,750,000	.8	29.6	15.4	17.5	24.7	12.0
May 26.....	83,100	1.28	2,870,000	1.2	41.0	14.3	16.1	18.6	8.8
June 5.....	69,000	.63	1,170,000	2.2	19.2	15.1	27.1	22.3	14.1
June 12.....	77,700	1.46	3,060,000	.9	33.8	11.9	13.0	22.7	17.7
June 28.....	70,100	.72	1,360,000	2.4	11.5	11.3	15.6	25.2	34.0
July 1, 7, 21.....	1 37,800	1.31	1 371,000	4.9	20.6	15.0	20.7	25.1	13.7
July 26.....	20,300	.49	269,000	2.5	68.2	12.8	8.2	6.1	2.2
July 30.....	15,600	.67	282,000	2.7	81.4	6.9	3.9	3.8	1.3
Aug. 2, 6, 9.....	1 11,100	1.15	1 49,200	3.6	76.9	11.7	4.6	2.4	.8
Aug. 12.....	23,500	2.89	1,830,000	1.2	65.6	15.0	10.8	6.4	1.0
Aug. 20.....	17,500	2.07	978,000	1.6	78.7	12.7	4.4	2.2	.4
Aug. 30.....	8,890	.82	197,000	2.8	86.1	9.0	.7	1.0	.4
Sept. 2.....	7,140	.86	166,000	2.1	90.9	6.3	.3	.2	.2
Sept. 13.....	5,350	.39	56,300	3.9	90.9	3.8	.7	.7	-----
Sept. 16.....	10,100	1.68	458,000	.6	87.1	9.0	2.2	1.1	-----
Sept. 24.....	13,600	1.80	661,000	1.3	68.1	13.8	8.3	7.7	.8
Sept. 27.....	19,300	2.71	1,410,000	1.4	67.3	14.5	10.4	5.8	.6
Sept. 30.....	21,200	1.88	1,080,000	.7	47.1	10.6	15.7	24.1	1.8

<sup>1</sup> Mean for days on which size samples were collected.

TABLE 24.—*Mechanical analyses of suspended sediment in samples collected in the Colorado River at gaging station near Willow Beach, Ariz., Apr. 2, 1935, to Sept. 27, 1936*

[Samples collected prior to May 4, 1936, dispersed with 1.5 percent sodium oxalate]

Date of collection	Mean daily discharge (sec.-ft.)	Mean daily concentration (percent)	Tons per day	Suspended sediment					
				Percent in indicated size range					
				<0.005 mm.	0.005-.020 mm.	0.020-.050 mm.	0.050-.074 mm.	0.074-.149 mm.	>0.149 mm.
1935									
Apr. 2	7,690	0.06	12,400	4.8	5.0	4.2	41.9	44.1	
Apr. 5	7,550	.07	14,300	4.9	7.4	9.3	50.9	27.5	
Apr. 9	7,320	.38	75,100	48.2	26.7	3.6	1.6	19.9	
Apr. 12	7,450	.70	141,000	56.1	36.6	3.4	.7	3.2	
Apr. 16	6,860	1.15	213,000	46.0	43.5	4.4	.7	2.9	2.5
Apr. 20	7,320	.24	47,400	3.3	78.5	5.5	12.7		
Apr. 22	7,520	.04	8,120				14.4	39.0	46.6
Apr. 23	7,380	.04	7,960				18.0	40.4	41.6
Apr. 26	7,420	.40	80,100	52.6	35.8	3.5	1.2	4.0	2.9
Apr. 30	7,280	.06	11,800				13.9	53.6	32.5
May 1	6,470	.04	6,990				14.2	33.6	52.2
May 3	7,350	.03	5,940				14.4	43.2	42.4
May 5	7,720	.03	6,260				12.4	56.6	31.0
May 7	7,350	.05	9,940				2.6	16.8	80.6
May 8	7,320	.04	7,910				34.8	55.1	10.1
May 10	7,120	.04	7,690				10.0	44.5	45.5
May 14	6,520	.10	17,600				2.3	17.8	79.9
May 15	6,610	.06	10,700				5.9	51.6	42.5
May 17	6,610	.06	10,700				12.6	40.1	47.3
May 21	6,930	.04	7,480				18.0	46.7	35.3
May 22, 26-28	13,100	1.08	129,300				15.7	51.2	33.1
May 29, 31	15,000	1.06	124,200				16.2	50.3	33.5
June 1	15,200	.06	24,600				44.1	32.9	23.0
June 5	15,800	.06	25,600				12.0	42.3	45.7
June 7	16,300	.05	22,000				14.9	58.6	26.5
June 9	16,200	.04	17,500				18.0	57.0	25.0
June 10	16,400	.06	26,600				12.6	38.6	48.8
June 11	16,800	.05	22,700				27.6	36.2	36.2
June 14	17,300	.04	18,700				7.3	28.5	64.2
June 21	18,600	.05	25,100				24.4	41.1	34.5
June 24	16,800	.04	18,100				8.1	28.0	63.9
June 25	14,400	.04	15,600				16.1	47.8	36.1
June 26	14,500	.05	19,600				17.6	31.1	51.3
June 28	14,700	.05	19,800				12.1	33.0	54.9
July 4	15,000	.07	28,300				8.5	37.1	54.4
July 10	10,000	.04	10,800				43.6	15.4	41.0
July 11	10,200	.04	11,000				17.4	19.5	63.1
July 14	10,000	.02	5,400				14.2	17.9	67.9
July 18	9,960	.01	2,000				15.2	28.4	56.4
July 21	10,000	.04	10,800				14.5	24.9	60.6
July 25	9,960	.03	8,080				16.0	19.5	64.5
July 28	10,000	.02	5,400				15.3	22.8	61.9
Aug. 1	10,100	.04	10,900				10.8	19.9	69.3
Aug. 4	10,000	.03	8,100				29.1	18.3	52.6
Aug. 8	10,200	.04	11,000				26.6	31.0	42.4
Aug. 11	10,100	.07	19,100				15.8	14.7	69.5
Aug. 15	10,300	.01	2,780				12.1	13.1	74.8
Aug. 18, 22, 25, 29	10,200	1.02	1,6760				2.1	7.0	90.9
Sept. 1	10,100	.03	8,180				16.9	24.2	58.9
Sept. 3	9,960	.86	231,000	34.2	62.0	1.6	2.2		
Sept. 6	10,100	.17	46,400	52.3	40.0	2.6	5.1		
Sept. 9	9,960	.70	188,000	28.0	68.6	2.3	1.1		
Sept. 12	10,100	1.37	374,000	46.8	48.9	2.5	1.8		
Sept. 15	10,100	.01	2,730				10.9	12.1	77.0
Sept. 19	10,000	.01	2,700				8.6	20.1	71.3
Sept. 22	9,960	.03	8,070				4.9	13.8	81.3
Sept. 26	10,100	.01	2,730				8.6	24.0	67.4
Sept. 29	9,920	.02	5,350				13.0	33.6	53.4

\* Mean for days on which size samples were collected.

TABLE 24.—*Mechanical analyses of suspended sediment in samples collected in the Colorado River at gaging station near Willow Beach, Ariz., Apr. 2, 1935, to Sept. 27, 1936—Continued*

[Samples collected prior to May 4, 1936, dispersed with 1.5 percent sodium oxalate]

Date of collection	Mean daily discharge (sec.-ft.)	Mean daily concentration (percent)	Tons per day	Suspended sediment					
				Percent in indicated size range					
				<0.005 mm.	0.005-0.020 mm.	0.020-0.050 mm.	0.050-0.074 mm.	0.074-0.149 mm.	>0.149 mm.
<i>1935</i>									
Oct. 3.....	10,000	.02	5,400	68.6	27.2	3.6	3.7	35.1	61.2
Oct. 6.....	9,740	1.57	413,000	68.6	27.2	3.6	.6	-----	-----
Oct. 10.....	9,680	2.16	565,000	74.5	21.8	2.6	1.1	-----	-----
Oct. 13.....	9,720	.34	89,200	73.9	4.8	2.2	19.1	-----	-----
Oct. 17.....	9,820	.01	2,380	-----	-----	-----	14.2	20.8	65.0
Oct. 20, 24, 27, 31.....	19,840	1.01	13,330	-----	-----	-----	13.9	23.7	62.4
Nov. 3, 7, 10, 14, 17.....	19,700	1.04	110,500	-----	-----	-----	1.4	5.2	93.4
Nov. 21, 24, 27, Dec. 1, 5, 9, 12, 16, 19, 23.....	16,340	1.02	13,480	-----	-----	-----	9.2	17.4	73.4
Dec. 26, 29.....	-----	-----	-----	-----	-----	-----	-----	-----	-----
<i>1936</i>									
Jan. 1-2, 5, 9, 12, 16, 19, 23, 26.....	14,840	1.01	11,030	-----	-----	-----	8.2	3.8	88.0
Jan. 30, Feb. 2, 6, 9, 13, 16, 20, 23, 27, Mar. 1.....	15,630	1.01	11,020	-----	-----	-----	6.1	1.2	92.7
Mar. 5-6, 9, 12, 16, 19, 22, 26, 29, Apr. 2.....	19,250	1.02	15,640	-----	-----	-----	8.3	17.7	74.0
Apr. 5, 9, 12, 16, 19.....	19,670	1.02	14,720	-----	-----	-----	8.0	12.0	80.0
Apr. 22.....	9,840	.21	55,800	58.1	14.6	2.3	1.9	4.7	18.4
Apr. 25.....	9,960	1.41	379,000	67.8	28.2	3.9	.1	-----	-----
Apr. 28.....	10,700	.74	214,000	13.0	81.6	2.4	3.0	-----	-----
May 1.....	9,460	.10	25,500	57.3	27.1	5.2	1.7	3.6	5.1
May 4, 7, 10, 14, 17, 21, 24, 28, 31.....	19,350	1.01	13,010	-----	-----	-----	16.0	23.2	60.8
June 4, 7, 11, 14, 18, 21, 25, 29.....	110,400	1.01	13,050	-----	-----	-----	6.7	16.6	76.7
July 2, 5, 9, 12, 16, 18, 23, 26, 30.....	111,300	1.01	12,720	-----	-----	-----	8.2	17.7	74.1
Aug. 2, 6, 9, 13, 16, 20, 23, 27, 30.....	19,980	1.01	12,050	-----	-----	-----	5.4	10.5	84.1
Sept. 6, 10-11, 13-14, 17-20, 24, 27.....	19,480	1.01	11,740	-----	-----	-----	8.0	14.1	77.9

<sup>1</sup> Mean for days on which size samples were collected.

## QUANTITIES OF SUSPENDED SEDIMENT

161

TABLE 25.—*Mechanical analyses of suspended sediment in samples collected in the San Juan River at gaging station near Bluff, Utah, May 3, 1935, to Sept. 30, 1936*

[Samples collected prior to May 4, 1936, dispersed with 1.5 percent sodium oxalate]

Date of collection	Mean daily discharge (sec.-ft.)	Tons per day	Suspended sediment						
			Mean daily concentration (percent)	Percent in indicated size range					
				<0.005 mm.	0.005-.020 mm.	0.020-.050 mm.	0.050-.074 mm.	0.074-.149 mm.	>0.149 mm.
<i>1935</i>									
May 3	4,230	1.02	116,000	8.3	5.4	10.9	21.8	37.2	16.4
May 5	3,660	.98	96,800	21.8	13.5	15.5	22.6	22.4	4.2
May 11	3,940	.86	91,500	9.2	10.5	21.1	26.1	26.6	6.5
May 14	6,120	1.32	218,000	12.2	8.0	16.0	28.5	25.1	10.2
May 18	5,960	1.83	295,000	15.4	8.9	17.6	27.0	22.9	8.2
May 19	6,460	1.81	316,000	7.8	4.8	11.4	18.1	32.6	25.3
May 21	7,140	1.25	241,000	14.9	7.2	13.2	21.5	27.8	15.4
May 22	11,300	2.51	766,000	11.2	18.4	15.0	16.6	21.8	17.0
May 23	8,590	1.99	462,000	26.8	19.7	16.6	2.1	24.4	10.4
May 25	6,970	1.16	218,000	11.4	9.1	16.6	21.7	31.2	10.0
May 27	8,590	1.17	271,000	14.7	9.6	16.5	23.8	27.7	7.7
May 28	9,160	1.35	334,000	14.1	10.1	15.8	23.0	27.0	10.0
May 29	9,160	1.08	267,000	10.1	10.4	10.2	25.5	28.0	15.8
June 1	8,780	1.01	239,000	8.4	7.5	13.2	20.9	33.7	16.3
June 3	6,800	.82	151,000	8.5	6.6	13.0	19.2	30.5	22.2
June 5	8,780	.94	223,000	8.9	11.4	22.1	30.3	23.3	4.0
June 6	10,100	.99	270,000	14.0	11.2	18.9	19.9	25.2	10.8
June 7	11,500	1.06	329,000	12.7	11.2	16.3	18.0	24.3	17.5
June 8	13,300	1.19	427,000	12.0	10.5	16.6	16.6	26.2	18.1
June 13	17,100	1.17	540,000	15.8	12.6	15.3	19.4	24.9	12.0
June 14	16,100	1.00	435,000	13.9	11.2	15.9	20.2	27.5	11.3
June 17	18,500	1.03	514,000	12.1	10.1	13.7	16.9	31.6	15.6
June 27	11,100	.72	216,000	9.8	7.5	11.9	22.0	32.9	15.9
June 29	10,100	.81	221,000	8.8	10.4	19.5	26.8	29.6	4.9
July 1	8,590	.87	202,000	6.2	4.3	6.5	15.6	37.0	30.4
July 3	7,860	.65	138,000	9.9	6.5	11.3	20.0	38.1	14.2
July 5	7,140	.70	135,000	9.4	6.9	11.2	20.1	39.9	12.7
July 7	6,290	.72	122,000	12.9	9.7	12.4	17.4	34.6	13.0
July 9	5,960	.69	111,000	10.2	6.8	9.4	18.1	41.8	13.7
July 11	5,640	.54	82,200	5.9	8.7	7.6	14.9	36.7	26.2
July 13	5,000	.46	62,100	9.1	5.8	8.3	13.8	31.9	31.1
July 15	4,680	.53	67,000	10.0	6.7	9.9	13.4	33.2	26.8
July 17	4,380	.78	92,200	35.6	14.6	5.6	9.1	19.8	15.1
July 19	5,800	2.71	424,000	26.8	14.4	13.1	11.6	21.3	12.8
July 20	3,940	1.17	124,000	39.2	19.4	9.0	7.3	14.7	10.4
July 24	3,660	.54	53,400	19.1	10.6	13.0	15.2	29.3	12.8
July 26	2,550	.52	35,800	18.7	9.7	10.8	18.3	32.1	10.4
July 29	1,820	1.28	62,900	6.3	2.7	1.7	5.2	43.2	40.9
July 31	2,730	1.77	19,800	5.8	2.6	1.4	3.4	14.7	72.1
Aug. 1	2,610	4.45	314,000	27.0	29.5	6.4	5.3	9.7	22.1
Aug. 5	2,140	2.48	143,000	15.0	5.6	1.9	1.8	12.4	63.3
Aug. 7	2,670	3.40	245,000	30.4	17.0	5.8	3.1	7.9	35.8
Aug. 9	2,800	4.13	312,000	28.9	14.0	9.0	4.1	9.6	34.4
Aug. 13	1,670	2.13	96,000	43.5	16.5	4.8	2.6	12.1	20.5
Aug. 15	1,720	1.70	78,900	21.6	10.4	6.4	3.7	17.8	40.1
Aug. 19	1,440	1.11	43,100	40.6	18.3	6.4	2.8	11.0	20.9
Aug. 22	964	.43	11,200	27.6	28.1	11.6	5.1	17.4	10.2
Aug. 25	2,140	2.63	152,000	35.5	31.3	15.3	5.7	8.4	3.8
Aug. 29	2,550	2.25	165,000	41.7	24.8	13.3	4.7	7.6	.8.0
Sept. 1	2,730	2.08	153,000	26.7	18.0	19.4	13.2	13.8	8.9
Sept. 3	1,770	4.67	223,000	29.5	16.4	12.5	15.4	23.6	2.6
Sept. 13	1,060	.95	27,200	35.5	15.1	9.4	5.9	23.3	10.8
Sept. 15	842	.57	13,000	27.4	13.4	10.6	13.5	26.5	8.6
Sept. 18	694	.31	5,800	29.7	14.4	11.8	8.5	30.6	5.0
Sept. 20	530	.27	3,860	15.3	25.7	9.8	11.6	32.7	4.9
Sept. 23	482	.38	4,640	5.8	32.2	10.9	12.9	31.5	6.7
Sept. 24	559	3.91	59,000	8.2	12.8	20.3	31.7	22.3	4.7
Sept. 25	3,940	5.95	633,000	11.8	33.8	13.3	6.4	16.9	17.8
Sept. 28	9,290	8.42	2,260,000	29.5	20.0	18.9	13.6	12.4	5.6

## SEDIMENT IN COLORADO RIVER, 1925-41

TABLE 25.—*Mechanical analyses of suspended sediment in samples collected in the San Juan River at gaging station near Bluff, Utah, May 3, 1935, to Sept. 30, 1936—Continued*

[Samples collected prior to May 4, 1936, dispersed with 1.5 percent sodium oxalate]

Date of collection	Mean daily discharge (sec.-ft.)	Mean daily concentration (percent)	Tons per day	Suspended sediment						
				Percent in indicated size range						
				<0.005 mm.	0.005-.020 mm.	0.020-.050 mm.	0.050-.074 mm.	0.074-.149 mm.	>0.149 mm.	
<i>1935</i>										
Oct. 7	1,260	.38	12,900	36.1	18.3	13.3	9.4	15.6	7.3	
Oct. 10	1,060	.36	10,300	23.4	13.7	9.8	8.5	22.8	21.8	
Oct. 14	872	.29	6,830	26.9	20.4	14.7	11.6	18.2	8.2	
Oct. 17	776	.24	5,020	33.0	17.2	16.3	10.0	18.4	5.1	
Oct. 19	720	.26	5,050	21.9	16.8	13.4	10.6	22.1	15.2	
Oct. 22	1,620	1.90	83,100	44.4	25.8	8.3	6.1	10.7	4.7	
Oct. 25	932	.99	24,900	17.9	41.7	6.6	4.2	13.2	16.4	
Oct. 28	910	.55	13,500	34.8	21.0	10.8	8.6	17.9	6.9	
Oct. 31	842	.40	9,100	36.7	17.9	12.6	8.8	16.6	7.4	
Nov. 3	762	.32	6,500	34.1	24.1	13.8	9.6	13.4	5.0	
Nov. 6	748	.29	5,860	13.8	31.9	13.1	13.8	20.6	6.8	
Nov. 8	688	.24	4,460	36.2	21.7	15.2	8.8	13.5	4.6	
Nov. 12	707	.25	4,780	25.8	16.7	15.2	10.7	17.8	13.8	
Nov. 15	643	.26	4,510	35.7	19.9	16.8	11.8	13.4	2.4	
Nov. 18	625	.22	3,730	23.8	15.0	14.8	12.3	24.4	9.7	
Nov. 21	655	.21	3,730	25.8	16.9	20.6	14.2	18.5	4.0	
Nov. 24	601	.26	4,210	18.7	14.5	16.0	13.5	22.9	14.4	
Nov. 27	707	.29	5,540	17.3	11.0	17.2	13.5	28.0	13.0	
Nov. 30	674	.24	4,370	18.3	21.5	14.8	14.6	21.4	9.4	
Dec. 3	565	.34	5,180	43.9	8.4	9.7	6.4	20.0	11.6	
Dec. 9	668	.24	4,320	34.3	12.5	17.5	13.3	17.9	4.5	
Dec. 10	655	.24	4,240	4.3	2.4	2.9	8.5	42.7	39.2	
Dec. 16	496	.23	3,080	17.0	9.6	8.4	8.7	27.9	28.4	
Dec. 20	312	.12	999	22.8	8.8	10.4	11.8	29.8	16.4	
Dec. 23	348	.14	1,320	13.0	7.8	7.3	9.2	28.5	34.2	
Dec. 26	518	.32	4,480	3.8	3.1	5.5	8.7	31.9	47.0	
Dec. 29	420	.29	3,290	5.6	5.0	9.1	14.4	39.0	26.9	
<i>1936</i>										
Jan. 1	559	0.23	3,480	2.9	3.7	9.0	16.5	45.2	22.7	
Jan. 4	474	.23	2,940	1.9	.9	2.4	5.1	20.7	69.0	
Jan. 7	518	.29	4,050	2.0	5.8	7.9	17.8	43.0	23.5	
Jan. 13	601	.38	6,160	8.0	3.1	3.7	10.4	30.4	44.4	
Jan. 16	694	.26	4,860	2.4	6.0	2.3	6.9	33.5	48.9	
Jan. 19	631	.24	4,080	3.3	14.8	4.5	10.8	43.4	23.2	
Jan. 22	452	.19	2,320	2.0	2.9	1.5	3.6	23.0	67.0	
Jan. 25	565	.19	2,890	3.8	8.0	2.9	5.3	25.4	54.6	
Jan. 28	880	.32	7,610	2.1	10.5	3.9	8.4	41.4	33.7	
Jan. 31	762	.31	6,370	16.9	8.9	5.1	8.3	41.0	19.8	
Feb. 3	918	.39	9,670	6.5	9.1	7.9	7.9	42.2	26.4	
Feb. 6	607	.24	3,940	5.3	7.8	5.2	8.3	41.5	31.9	
Feb. 9	452	.14	1,700	3.6	28.5	10.4	6.8	25.3	25.4	
Feb. 13	681	.25	4,590	20.1	11.3	13.3	11.9	32.6	10.8	
Feb. 16	1,220	.86	28,300	15.0	8.2	13.6	14.5	29.3	19.4	
Feb. 18	1,060	.66	18,900	47.4	15.6	8.7	7.8	13.6	6.9	
Feb. 21	902	.59	14,400	50.5	8.7	7.0	6.3	12.1	15.4	
Feb. 24	798	.48	10,300	38.1	8.4	7.1	7.2	21.7	17.5	
Feb. 27	1,670	2.29	103,000	46.8	27.9	6.3	5.1	6.7	7.2	
Mar. 1	734	.79	15,700	52.9	10.2	6.5	4.3	10.1	16.0	
Mar. 4	3,120	2.17	18,300	46.1	18.7	10.5	5.9	12.0	6.8	
Mar. 7	3,380	3.25	297,000	43.0	37.8	11.2	4.0	3.2	.8	
Mar. 10	3,120	1.82	153,000	37.2	18.7	9.9	24.0	7.0	3.2	
Mar. 13	2,430	1.53	100,000	44.1	22.0	13.8	7.6	8.8	3.7	
Mar. 16	2,670	1.23	88,700	33.3	19.6	16.9	13.9	12.5	3.8	
Mar. 19	2,140	1.00	57,800	36.7	20.0	18.3	11.6	9.6	3.8	
Mar. 22	1,820	.74	36,400	29.5	19.5	22.8	14.9	11.2	2.1	
Mar. 25	1,920	.64	33,200	25.5	14.9	20.5	16.2	16.7	6.2	
Mar. 28	1,260	.44	15,000	24.1	18.4	19.2	14.8	18.9	4.6	
Mar. 31	1,530	.56	23,100	29.4	20.9	21.4	14.4	10.7	3.2	

TABLE 25.—*Mechanical analyses of suspended sediment in samples collected in the San Juan River at gaging station near Bluff, Utah, May 3, 1935, to Sept. 30, 1936—Continued*

[Samples collected prior to May 4, 1936, dispersed with 1, 5 percent sodium ozalate]

Date of collection	Mean daily discharge (sec.-ft.)	Suspended sediment							
		Mean daily concentration (percent)	Tons per day	Percent in indicated size range					
				<0.005-mm.	0.005-0.020-mm.	0.020-0.050-mm.	0.050-0.074-mm.	0.074-0.149-mm.	
1936									
Apr. 3	1,980	.86	46,000	41.2	21.5	14.6	10.1	2.8	9.8
Apr. 6	1,770	.75	35,900	28.7	16.3	15.1	12.1	17.9	9.9
Apr. 9	1,580	.82	35,000	17.5	16.7	30.0	26.3	1.9	7.6
Apr. 12	4,230	.99	113,000	26.2	17.9	18.9	15.1	15.3	6.6
Apr. 14	6,800	1.74	319,000	21.2	17.5	26.1	18.4	12.2	4.6
Apr. 17	7,140	1.41	272,000	23.2	17.0	23.2	19.9	14.0	2.7
Apr. 20	7,680	1.18	245,000	15.7	15.4	24.4	24.8	16.4	3.3
Apr. 23	7,680	.96	199,000	17.0	10.4	19.2	27.5	21.7	4.2
Apr. 26	7,140	.83	160,000	14.0	9.0	20.8	27.7	22.1	6.4
Apr. 29	6,800	.92	169,000	9.9	6.4	9.2	30.0	27.0	17.5
May 2	5,480	.64	94,700	11.8	18.1	16.6	23.5	23.8	6.2
May 5	8,590	.88	204,000	15.8	11.5	20.8	22.7	22.8	6.4
May 8	10,300	1.33	370,000	11.3	7.8	15.1	22.5	31.0	12.3
May 11	4,840	.47	61,400	18.2	8.9	17.9	23.3	24.4	7.3
May 14	5,160	.53	73,800	10.7	6.0	10.2	20.7	37.1	15.3
May 17	6,460	.55	95,900	9.0	7.2	15.0	28.0	32.0	8.8
May 20	7,140	.80	154,000	6.7	3.9	10.2	18.7	41.9	18.6
May 23	7,320	.75	148,000	8.9	4.9	10.3	21.1	38.9	15.9
May 26	6,970	.64	120,000	14.4	9.2	15.6	30.6	26.3	3.9
May 29	6,630	.57	102,000	12.4	8.1	13.7	23.3	32.8	9.7
June 1	7,320	.80	158,000	4.2	4.2	6.7	14.4	31.3	39.2
June 4	5,000	.49	66,100	5.4	5.2	3.6	14.1	29.2	42.5
June 8	2,990	.35	28,200	9.2	5.5	9.3	22.0	37.5	16.5
June 11	4,230	.35	40,000	8.4	7.6	14.7	23.7	34.7	10.9
June 14	4,080	.34	37,400	5.3	3.2	5.4	11.2	29.6	45.3
June 17	3,120	.24	20,200	8.1	4.2	7.6	17.9	42.9	19.3
June 20	2,490	.23	15,500	7.4	3.7	7.1	18.7	42.4	20.7
June 23	1,720	.16	7,420	9.2	4.4	7.6	16.6	43.6	18.6
June 26	1,400	.17	6,430	14.6	6.7	6.1	15.3	39.6	17.7
June 28	1,220	.14	4,620	15.1	7.0	5.9	11.5	38.2	22.3
July 1	872	.18	4,240	42.5	11.7	3.9	8.7	24.7	8.5
July 4	769	.08	1,670	15.8	6.8	5.6	15.8	41.4	14.6
July 8	469	.06	756	5.5	3.1	2.7	8.7	45.6	34.4
July 11	430	.13	1,510	5.5	4.1	9.9	23.8	45.2	11.5
July 14	1,920	1.16	60,100	34.7	29.5	7.6	7.8	14.4	6.0
July 17	918	.33	8,180	40.6	15.6	4.8	7.8	23.5	7.7
July 20	583	.39	6,130	54.6	17.6	3.5	4.2	13.0	7.1
July 23	607	.60	9,830	56.8	25.5	3.8	2.7	6.0	5.2
July 26	480	.19	2,460	21.2	11.3	3.5	4.6	26.0	33.4
July 29	357	1.33	12,800	56.3	32.5	5.1	2.5	1.9	1.7
Aug. 1	326	.24	2,110	45.8	23.7	7.8	6.2	9.6	6.9
Aug. 4	915	2.25	55,600	42.5	32.5	12.5	5.3	4.9	2.3
Aug. 5	3,950	21.4	2,280,000	15.4	9.5	10.2	15.8	41.1	8.0
Aug. 6	7,140	8.81	1,700,000	43.5	26.0	12.3	7.1	7.0	4.1
Aug. 7	6,460	6.42	1,120,000	45.0	25.0	11.3	4.8	8.0	5.9
Aug. 10	3,250	1.79	157,000	47.9	21.5	12.1	6.0	7.9	4.6
Aug. 13	1,670	.74	33,400	38.5	22.5	12.7	7.7	13.5	5.1
Aug. 16	1,220	.43	14,200	46.8	16.9	11.0	7.4	13.5	4.4
Aug. 19	1,140	1.65	50,800	34.5	50.9	5.7	2.9	5.0	1.0
Aug. 22	4,530	5.03	615,000	42.6	28.4	11.3	5.6	6.7	5.4
Aug. 25	1,180	2.54	80,900	67.9	21.0	5.5	2.6	2.7	.3
Aug. 28	625	.65	11,000	54.9	28.3	8.6	4.6	3.1	.5
Aug. 30	5,440	6.56	964,000	32.7	28.2	15.7	6.9	9.2	7.3
Sept. 3	5,480	6.27	928,000	22.2	15.2	14.7	15.8	27.0	5.1
Sept. 6	3,520	1.95	185,000	28.4	29.0	18.0	11.0	9.2	4.4
Sept. 14	1,720	1.54	71,500	29.7	25.1	10.9	9.5	13.8	11.0
Sept. 17	1,100	.52	15,400	33.5	13.4	15.7	14.3	16.2	6.9
Sept. 20	1,260	.80	27,200	15.0	9.9	28.0	32.4	12.8	1.9
Sept. 22	1,620	8.12	355,000	27.7	23.1	18.6	14.0	12.5	4.1
Sept. 26	1,260	1.73	58,900	45.1	25.2	9.0	6.6	9.2	4.9
Sept. 30	1,140	1.98	60,900	29.0	32.2	10.0	8.2	14.2	6.4



## INDEX

	Page
Abstract.....	1
Arizona, suspended sediment of water in.....	10,
25-100, 141-160	
Bank deposits, description of.....	13
Bluff, Utah, San Juan River near.....	9,
10, 15, 110-143, 161-163	
Cisco, Utah, Colorado River near.....	8, 10, 15, 16-24
Colorado River, near Cisco, Utah.....	8, 10, 15, 16-24
near Grand Canyon, Ariz. ....	8, 10, 15, 28-82, 150, 158
near Lees Ferry, Ariz.....	8, 15, 25-27
near Topock, Ariz.....	9, 15, 87-100, 148-149
near Willow Beach, Ariz. ....	9, 15, 83-86, 159-160
near Yuma, Ariz.....	10
Colorado River sampler, use of.....	2; pl. 1
Grand Canyon, Ariz., Colorado River near.....	8,
10, 15, 28-82, 150-158	
Grand Falls, Little Colorado River at.....	15, 144-145
Green River, Ariz., Green River at.....	9,
10, 15, 101-109	
at Green River, Ariz.....	9, 10, 15, 101-109
Lees Ferry, Ariz., Colorado River near.....	8, 15, 25-27
Little Colorado River at Grand Falls, Ariz....	15,
144-145	
Particle size, collection of samples to determine.....	5
Reservoir deposits, description of.....	13-14
San Juan River, near Bluff, Utah.....	9,
10, 15, 110-143, 161-163	
Samples, frequency of collection of.....	5
individual, collection of.....	4
integrated, collection of.....	4
stations for collection.....	2, 3
Suspended sediment, computation of concentrations of.....	5-6
computation of loads of.....	6, 8-9
concentrations for daily samples of .....	7, 146-149
key to tables of information on.....	15
mean daily concentrations of .....	6-7, 16-140
mechanical analyses of .....	150-163
record of daily loads of .....	21-24, 35-53, 83-86, 92-100,
106-140, 144-145	
relation of depth to concentration of .....	146-149
relation of mean velocity to concentration of .....	146-149
relation of to runoff.....	10
weighing of samples of .....	5
Topock, Ariz., Colorado River near.....	9,
15, 87-100, 148-149	
Utah, suspended sediment of water in.....	10,
16-24, 101-143, 161-163	
Willow Beach, Ariz., Colorado River near.....	9,
15, 83-86, 159-160	
Yuma, Ariz., Colorado River near.....	10